Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Himmel

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Himmel Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Himmel Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
KP75-MB/2-M12K	Flat motor KP75-MB / 2 with angular gear 1: 1 Gear position position - pos. 11 like number P-693022/3 Weight: approx. 71.0 kg + packaging per piece Nomenclature number: 8501 5230 Motor and gear in protection class IP64 (based on ATEX class II 3D Ex tc IIIB T300 ° C Dc - IP64). There is no ATEX approval for the drive concept. Dimension sheet: 1NJ001659 K-model series / design series: KP75 Typ / type: KP75-MB / 2-M12K K-Maßblatt / dimension sheet: 1NJ001659 Color: RAL 7031 blue gray 2K / Blue gray 2K-PUR Design / mounting position: V5 K-Montageseiten / mounting sides: one-sided foot machining Protection class: IP64 K rating plate / name plate: Klebeschild 90x60 / adhesive label 90x60 Name plate logo / name plate logo: HIMMEL W. diameter / shaft diameter [mm]: 30 W.Länge / shaft-length [mm]: 156 (center foot bore to center gear) Shaft thread: M16-L.H. + M12-R.H. K flange washers Ø / external diameter flange [mm]: 140 K tool width [mm]: min. 2 / max. 5 K-Werkzeugtyp / tool type: Spiral bevel angular gear i = 1: 1 V140 K-Features 1 / specific feature 1: Angular gear i = 1: 1 KK version / Terminal box type: Aluminum-M25x1.5 / aluminum-M25x1.5 KK-Lage / Terminal box position: 2DK K-gear type / K-gear type: angle gear / angular gear V140 Transmission / Ratio [i]: 1.00 Gear position: Pos11 Oil quantity [l]: 0.30 Oil type: CLP PAO 68 Synth.oil Electrical design / Electrical design: CE Number of phases: 3 ~

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Nominal power / nominal power [kW]: 7.5 Motor speed nom / Motor speed nom. [1 / rpm]: 2880 Nominal frequency [Hz]: 50 Nominal voltage / nominal voltage [V]: 400 Nominal current In [A]: 15.2 CosPhi / CosPhi: 0.86 Circuit / Wiring: S102 (D) Operating mode / Duty type: S6-60% Winding protection / motor protector: PTC 160 ° C Insulation class: F Circuit diagram motor / Connection diagram motor: A0114000 Circuit diagram internals 1 / Con. diagram compon. 1: A01TP000 Brake type: M12K [12Nm] (L8) Brake supply voltage [V]: 400 Wiring / Connection: on the terminal board / on terminal block Circuit diagram brake 1 / Connection diagram brake 1: A01BA003
KF75-LP/2-M16K	Flat motor KF75-LP / 2 M20 Re + M16K like number P-656770/01 Weight: approx. 70.0 kg + packaging per piece Nomenclature number: 8501 5230 Dimension sheet: 1NJ200000000072 K model series / design series: KF75 Typ / type: KF75-LP / 2-M16K K-Maßblatt / dimension sheet: 1NJ200000000072 Color: RAL 7031 blue gray 2K / Blue gray 2K-PUR Design / mounting position: B3 Protection class: IP54 K rating plate / name plate: Klebeschild 29x53 / adhesive label 29x53 Name plate logo / name plate logo: HIMMEL W. diameter / shaft diameter [mm]: 40 W.Länge / shaft-length [mm]: 65 / [2.56 "] (free shaft end) Shaft thread: M20-R.H. KK version / Terminal box type: Terminal box / Terminal box KK material / Terminal box material: Kunststoff / plastic KK-Lage / Terminal box position: 3B KK screw connection / gland: (2x) -M25x1.5 Electrical design / Electrical design: CE Number of phases: 3 ~ Nominal power / nominal power [kW]: 11 Motor speed nom / Motor speed nom. [1 / rpm]: 2920 Nominal frequency [Hz]: 50 Nominal voltage / nominal voltage [V]: 380 Nominal current In [A]: 22.9 CosPhi / CosPhi: 0.85 Circuit / Wiring: S102 (D) Operating mode / duty type: S1 Winding protection / motor protector: PTC 160 ° C Insulation class: F

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Circuit diagram motor / Connection diagram motor: A0102000 Circuit diagram internals 1 / Con. diagram compon. 1: A01TP000 Brake type: M16K [16Nm] Brake supply voltage [V]: 380 Wiring / Connection: not on the terminal block / not on terminal block Circuit diagram brake 1 / Connection diagram brake 1: A01BA000
Flat motor KP75-MB / 2 with angular gear 1: 1	Gear position position - pos. 11 like number P-576362/2 Motor and gearbox in protection class IP64 (based on ATEX class II 3D Ex tc IIIB T300 ° C Dc - IP64). There is no ATEX approval for the drive concept. Dimension sheet: 1NJ001659 K-model series / design series: KP75 Typ / type: KP75-MB / 2-M12K K-Maßblatt / dimension sheet: 1NJ001659 Color: RAL 7031 blue gray 2K / Blue gray 2K-PUR Design / mounting position: V5 K-Montageseiten / mounting sides: one-sided foot machining Protection class: IP64
K62-L/2 M10 Li + M16K	
2140000277	HIMMEL® flat motor KP75-MB / 2 with angular gear 1: 1 like number P-71456/1 Weight: approx. 71.0 kg + packaging Motor and gear in protection class IP64 (based on ATEX class II 3D Ex tc IIIB T300 ° C Dc - IP64). An ATEX approval for the drive concept is not available. Dimension sheet: 1NJ001659 K-model series / design series: KP75 Typ / type: KP75-MB / 2-M12K K-Maßblatt / dimension sheet: 1NJ001659 Color: RAL 7031 blue gray 2K / Blue gray 2K-PUR Design / mounting position: V5 K-Montageseiten / mounting sides: one-sided foot machining Protection class: IP64 K rating plate / name plate: Klebeschild 90x60 / adhesive label 90x60 Name plate logo / name plate logo: HIMMEL Output variant: Spiral bevel right-angle gearbox i = 1: 1 V140 W. diameter / shaft diameter [mm]: 30 W.Länge / shaft-length [mm]: 156 (center foot bore to center gear / center foot hole to center gear) Shaft thread: M16-L.H. + M12-R.H. K flange washers Ø / external diameter flange [mm]: 140 K tool width [mm]: min. 2 / max. 5

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	K-Features 1 / specific feature 1: Angular gear i = 1: 1 KK version / Terminal box type: Aluminum-M25x1.5 / aluminum-M25x1.5 KK-Lage / Terminal box position: 2DK K-gear type / K-gear type: angle gear / angular gear V140 Transmission / Ratio [i]: 1.00 Gear position: Pos11 Oil quantity [l]: 0.30 Oil type: CLP PAO 68 Synth.oil Electrical design / Electrical design: CE Number of phases: 3 ~ Nominal power / nominal power [kW]: 7.5 Motor speed nom / Motor speed nom. [1 / rpm]: 2880 Nominal frequency [Hz]: 50 Nominal voltage / nominal voltage [V]: 400 Nominal current In [A]: 15.2 CosPhi / CosPhi: 0.86 Circuit / Wiring: S102 (D) Operating mode / Duty type: S6-60% Winding protection / motor protector: PTC 160 ° C Insulation class: F Circuit diagram motor / Connection diagram motor: A0114000 Circuit diagram internals 1 / Con. diagram compon. 1: A01TP000 Brake type: M12K [12Nm] (L8) Brake supply voltage [V]: 400 Wiring / Connection: on the clipboard / on terminal block Circuit diagram brake 1 / Connection diagram brake 1: A01BA003
MODEL : DR34	P1 MAX : 40 BAR P2 MAX : 0.5 - 16 BAR 3/4"
MODEL : DR22	P1 MAX : 25 BAR P2 MAX : 0.5 - 16 BAR 1/2"
511560 M12K Alu	Brake disc
2230064894	2230064894 HIMMEL® gear motor CF10-G56M4 As supplied under P-694335/1
KP75-XL/2-M12K M16-RH - ATEX	HIMMEL®-Flachmotor Do not brake the spring-loaded brake until < 3600 rpm Dimension sheet: 1NJ006553 K model series / design series: K75 Type: KP75-XL/2-M12K K-dimensional sheet / dimension sheet: 1NJ006553 Color / colour: RAL 6011 Reseda green 2K / Reseda green 2K-PUR

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Design / mounting position: B3 K-Befestigungsseiten / mounting sides: double-sided foot machining Degree of protection / protection class: IP64 K rating plate / name plate: adhesive label 90x60 /adhesive label 90x60 Rating plate logo / name plate logo: HIMMEL Flat motor according to ATEX / flat-motors acc. to ATEX: II 3D Ex tc IIIB T300°C Dc - IP64 max. drive speed/max. input speed [rpm;1/rpm]: 6000 max. radial force / max. radial forces / Fr [N]: 1200 Ambient temperature /Ta [°C]: -20/+40 Output variant: shaft with feather key/shaft with parallel key W.Diameter / shaft diameter [mm]: 40 W.Länge / shaft-length [mm]: 70 (free shaft end) Shaft thread: M16-R.H. Bearing AS / Bearing-AS (DE): double bearing [radially reinforced] / double bearing [radial reinforcement] Bearing BS / Bearing-BS (NDE): Single bearing / simple bearing KK version / terminal box type: terminal box / terminal box KK material / Terminal box material: aluminum / aluminium KK-Lage / Terminal box position: 2BK KK screw connection / gland: (4x)-M32x1.5 + (2x)-M16x1.5 Electrical design: CE Number of phases: 3~ Number of poles / poles: 2 Rated output / nominal power [kW]: 14.0//20.0 Motor speed nominal / Motor speed nom. [1/rpm]: 2920//5900 Nominal frequency [Hz]: 50//100 Nominal voltage / nominal voltage [V]: 230/400//400 Nominal current In [A]: 47.50/27.50//42.50 CosPhi / CosPhi: 0.84//0.84 Circuit / wiring: S100//S102 (D/Y//D) Duty type: S6-75% Supply type / power supply: FU operation / inverter duty Drive protection / motor protection (IEC60034-25): to be guaranteed by the person responsible for the system / to be guaranteed by system manager Winding protection / Motor protector: PTC 130°C Insulation class: F Circuit diagram motor / Connection diagram motor: A0100000 Circuit diagram internals 1 / Con. diagram compon. 1: A01TP000 Bremstyp / Brake type: M12K [12Nm] (L8) Bremssteuerspg / Brake supply voltage [V]: 360-440 Wiring / connection: separate / separate Circuit diagram brake 1 / Connection diagram brake 1: A01BA000
KP75-MB/2-M12K M16-RH-ATEX	wie Nummer P-720976 Dimension sheet: 1NJ000299

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	K model series / design series: K75 Type: KP75-MB/2-M12K K-dimensional sheet / dimension sheet: 1NJ000299 Color / colour: RAL 6011 Reseda green 2K / Reseda green 2K-PUR Design / mounting position: B3 K-Befestigungsseiten / mounting sides: double-sided foot machining Degree of protection / protection class: IP64 K rating plate / name plate: adhesive label 90x60 /adhesive label 90x60 Rating plate logo / name plate logo: HIMMEL Flat motor according to ATEX / flat-motors acc. to ATEX: II 3D Ex tc IIIB T300°C Dc - IP64 max. drive speed/max. input speed [rpm;1/rpm]: 6000 max. radial force / max. radial forces / Fr [N]: 1200 Ambient temperature /Ta [°C]: -20/+40 Output variant: Schnellspannsystem/quick change clamping system W.Diameter / shaft diameter [mm]: 30 W.Länge / shaft-length [mm]: 103 (middle of the foot hole to the beginning of the tool/center foot hole to beginning of tool) Shaft thread: M16-R.H. K flange discs Ø/ external diameter flange [mm]: 140 K tool width / tool width [mm]: 0 - 5 Tool carrier / tool lorry: 2 pins D=8 on LK=60 Bearing AS / Bearing-AS (DE): double bearing [radially reinforced] / double bearing [radial reinforcement] Bearing BS / Bearing-BS (NDE): Single bearing / simple bearing K-electr. connection type/elec. connection mode: terminal box KK material / Terminal box material: aluminum / aluminium KK-Lage / Terminal box position: 1BK/3BK KK screw connection / gland: (2x)-M25x1.5 Electrical design: CE Number of phases: 3~ Number of poles / poles: 2 Nominal power / nominal power [kW]: 6//8.5 Motor speed nominal / Motor speed nom. [1/rpm]: 2900//5800 Nominal frequency [Hz]: 50//100 Nominal voltage / nominal voltage [V]: 230/400//400 Nominal current In [A]: 20.90/12.10//17.60 CosPhi / CosPhi: 0.87//0.87 Circuit / wiring: S100//S102 (D/Y//D) Duty type: S6-75% Supply type / power supply: FU operation / inverter duty Drive protection / motor protection (IEC60034-25): to be guaranteed by the person responsible for the system / to be guaranteed by system manager Winding protection / Motor protector: PTC 130°C Insulation class: F Circuit diagram motor / Connection diagram motor: A0100000

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Circuit diagram internals 1 / Con. diagram compon. 1: A01TP000 Bremstyp / Brake type: M12K [12Nm] (L8) Bremssteuerspg / Brake supply voltage [V]: 360-440 Wiring / connection: separate / separate Circuit diagram brake 1 / Connection diagram brake 1: A01BA000
2150000367	K62-S/2-M7K M20-RH Dimension sheet: 1NJ100000000562 K model series / design series: K62 Type: K62-S/2 K-dimensional sheet / dimension sheet: 1NJ100000000562 Color / colour: RAL 6011 Reseda green 2K / Reseda green 2K-PUR Design / mounting position: B3 Degree of protection / protection class: IP54 K rating plate / name plate: aluminium W.Diameter / shaft diameter [mm]: 25.4 / [1"] W. Length / shaft length [mm]: 58 (middle of the foot hole to the beginning of the tool/center foot hole to beginning of tool) Shaft thread: M20-R.H. K flange discs Ø/ external diameter flange [mm]: 90 K tool width [mm]: max. 3 KK version / terminal box type: aluminum / aluminium KK-Lage / Terminal box position: 2B Electrical design: CE Nominal power / nominal power [kW]: 1.75 Motor speed nominal / Motor speed nom. [1/rpm]: 2700 Nominal frequency [Hz]: 50 Nominal voltage / nominal voltage [V]: 230/400 Nominal current In [A]: 7.1/4.1 Circuit / wiring: S100 (D/Y) Duty type: S6-40% Winding protection / motor protector: 2WT`s 160°C Insulation class: F Circuit diagram motor / Connection diagram motor: A2064 Bremstyp / Brake type: M7K [7Nm] Bremssteuerspg / Brake supply voltage [V]: 230 Wiring / connection: not on the terminal block / not on terminal block Circuit diagram brake 1 / Connection diagram brake 1: A2828
REDUCER EK 120-K4	
LDRP88	
DR 33-16	Pressure regulator G 1/2", 0.5 - 16 bar, Standard 3 series
2010001599	HIMMEL® worm gear motor SA01-G56M4 Dimension sheet: SA14

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Gearbox type: HIMMEL®-worm gear motor gear motor Gearbox type: SA01-G56M4 Dimension drawing / Dimension sheet: SA14 Output speed [rpm]: 18.00//21.50 Translation / Ratio [i]: 75.00 Color: RAL 7031 blue gray / blue gray Corrosivity category / corrosion protection: C1: iAa DIN EN ISO 12944-2 / HN716.21 Paint layer thickness [µm]: 60-80 Protection class: IP54 Design / mounting position: H-01-B Output torque [Nm]: 13.8//11.6 Direction of rotation: left / left [CCW] Output shaft [mm; inch]: H14x80 Gearbox bearing / Bearing: assigned bearings Oil type: CLP PG 460 Synth.oil Oil quantity [l]: 0.11 Shaft material: C45 Gearbox sealing / Sealing: Shaft seal ring (WDR) / shaft seal ring Marking/Approval|Identification/Certification: CE Number of poles: 4 Nominal frequency / Nominal frequency [Hz]: 50//60 Nominal voltage [V]: 200-240/380-420//220-277/380-480 Wiring: S100//S100 (D/Y//D/Y) Nominal power [kW]: 0.09//0.09 Nominal engine speed [rpm]: 1350/1610 Nominal current In [A]: 0.70/0.40//0.70/0.40 CosPhi / CosPhi: 0.68 KK location / Terminal box position: 2A KK version / Terminal box type: plastic Winding protection / Motor protector: WT 160°C Output shaft motor [mm; inch]: V11x24.5 Sealing motor: normal Isolation class / Insulation class: F Duty type: S1 Fan: plastic
DRI.55-N	P1:40 BAR P2:0-20 BAR
2140002410	HIMMEL® flat motor K75.01-LB/2 M27-LH Dimension sheet: 1NJ100000000186 K-series / design series: K75 Type: K75.01-LB/2 - - Painting - -: - Color: RAL 5015 Sky Blue 2K / Sky Blue 2K-PUR - - Mechanical data - -: - K dimension sheet: 1NJ100000000186 Mounting type / mounting position: B3

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	K-mounting sides: one-sided foot machining Bearing-DE: DL (Double bearing) Bearing-NDE: EL (simple bearing) Protection class: IP54 - - Output variant - -: - Output variant: Flange plate W.Diameter / shaft diameter [mm]: 30 W. Length / shaft length [mm]: 103.2 (start of tool to base bore) (surface to foot hole) Shaft thread: M27-LH K-flange discs Ø/ external diameter flange [mm]: 140 K-tool width [mm]: 0 - 5 Electrical data: - ... License plate/approval | Identification/Certification: CE Number of phases: 3 Rated power [kW]: 11.0 Operating mode / Duty type: S6-60% Number of poles: 2 Nominal engine speed [rpm]: 2880 Nominal voltage [V]: 400 Nominal frequency / Nominal frequency [Hz]: 50 Nominal current In [A]: 21 Circuit / Wiring: S102 (D) CosPhi / CosPhi: 0.89 Isolation class / Insulation class: F Winding protection / motor protector: WT 150°C Power supply type: Mains operation Motor wiring diagram / Connection diagram motor: A0102000 Circuit diagram component 1 / Circuit diagram component 1: A01TB000 - - Electrical connection - -: - K-electronic connection type/electronic connection mode: Terminal box KK material / Terminal box material: Aluminum / aluminium KK location / Terminal box position: 3A KK screw connection / gland: (2x)-M25x1.5 External grounding motor: Not present - - Ventilation - -: - Ventilation type: E - Self-ventilation - - - - Load, forces - - - -: - Ambient temperature /Ta [°C]: -20/+40 - - Nameplate - -: - K-performance sign / name plate: Adhesive label 90x60 Nameplate logo: HIMMEL - - Product Directory / Harmonised Codes - -: -
2150001847	Material cost surcharge MTZ 8.5% (FM)
HUA 5000	
Y-Sn4101-Ip	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Hgt10018a	ELECTRODE
42d12/2l	
2010000522	
169800 (Ex. 976292)	
701	SIGNAL COND
49722	
2030/6-2	TORQUEMETER HOLLOW FLANGE 600LB-IN RANGE
Siv420ipsc-A2	5/2-way solenoid valve, ISO 1, impulse valve, 230 V AC 001 SIV420IPSC-A2 1.5-10 bar Flow 1,600l / min.
Mcrt28002t52nfa	SHAFT
(Ka200)-G200l4-L260/240gh	
Mcrt3960x2-3nn4000	TORQUE TRANSMITTER 4000RPM 2000TORQUE RANGE
Mcrt-49001v(25-0)-N-F-N	TORQUEMETER DC OPERATED 25LB-IN 1500RPM FOOT MOUNT
Mcrt28061t14nnn	SERVO MOTOR
Mcrt28001t12nnn	TRANSDUCER
C102-G132s4-L80/25nb3-00-B D/Y	
Z38-G804m4(53d12/2ly112m)	
2230000755 (Ka200-G200l4-L260/240gh)	
Df40-A100li8/2r-D15/7.5nh	
Kl75.01-Sb/2 Li + M12k	
481 109 622	
Z38-A90lp12/2r(376413a2)	
Ka200-(G200-4)	
D40-A112m12/2r(53d12/2l100l)	
Mot.Red.Ca10-G56m4-H-03-A/	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
0,09kw-1350/12	
6.545.175.0+6.612.850.0	
2k16/19	
2010000132	
Caz61-A90sh4	
K75-M/2	
Ca10-M1b2-P5/2n	HELICAL WORM GEARED MOTOR SHAFT MOUNTED 220/240V
D40-A100lb12/2r(367190as)	
2010000297	
Mcrt48070p	METER
K75 D35	
Kl75.01-Sb/2 Re (1nj1-143) +m12k	
6208-Z	
Siv420ipsc-D4	5/2-way solenoid valve, ISO 1, pulse valve, 24 VDC SIV420IPSC-D4 1.5-10 bar Flow 1,600l / min.
K75 Sb/2-M12k Obsolete,Replaced By Kl75.01-Sb/2 Li + M12k	
Kf 75 M	
Z48-A90li4(376413a3)	
Saf06-M1c4	
Vtk1075	
Sa01-M1b4	
D121-A	
Kp75-Mb/2 M16 Re+m12k	
Din 625 6207 2z	
C81-A100li4-L32/18n	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.