Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Honigmann

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Honigmann Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Honigmann Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Digital Panel Meter Dpm 502	for direct, correct digits - LED 14 mm, red, 3 ½ digits - 0... ± 10 V input signal - Display value freely scalable - for 24 V DC supply - With integrated DC / DC converter for electrical isolation between supply voltage and measuring circuit
RFS® 150 100 N	Radial force measuring axis RFS® 150 Precision tensile force measurement - online - designed as a curling measuring system è uses the existing deflection point for direct tensile force measurement - Universally applicable, precise and robust RFSâ 150/0100/10/3 / O - Nominal measuring force: 100 N - Bearing pin Ø: 10 mm - Cable length: 3 m - Connection: open ends The measuring range of the sensors begins - independently from the nominal sensor measuring force - exactly at the force zero point.
RFS® 150 50N	Radial force measuring axis RFS® 150 Precision tensile force measurement - online - designed as a curling measuring system è uses the existing deflection point for direct tensile force measurement - Universally applicable, precise and robust RFSâ 150/0050/10/3 / O - Nominal measuring force: 50 N - Bearing pin Ø: 10 mm - Cable length: 3 m - Connection: open end
Honigmann	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Honigmann	
Honigmann	
Honigmann	
TENSIOTRON® TS 621	Electronic precision measuring amplifier for strain gauge-based sensors - 0 ... ±10 V output signal - 24Vdc power supply - with integrated DC/DC converter for galvanic isolation between supply and output signal - Compact module housing for DIN rail mounting
RFSâ 150/0200/BB/5/O	Radial force measuring axle RFS® BB for web tension measurement - precise and online - uses an existing reversing point for direct web tension measurement - especially designed for measurements in combination with web guiding rolls with interior bearings and without end-to-end axle - typically 2 RFSâ BB measuring axles are used per roll rated load: 200 N - cable length: 3 m - connection: open ends - incl. ball bearing compensating disc dimensions as per HG dwg. 64_255_919
Radial force measuring axis RFS® 150 SR	Standard Range Precision Tension Measurement - online - designed as a single-roll measuring system è uses existing deflection point for direct measurement of tensile force - universally applicable, precise and robust - SR: standard range RFSâ 150 SR/0200/12/3/O - Nominal measuring force : 200 N - Cable length: 3m - Connection: open ends The measuring range of the RFS sensors begins - independently from the nominal measuring force of the sensor - exactly at the zero point of the force. with the following OPTION RFS® 150: Special bearing journal Ø 12 mm - 2X - Length of the stub axle 22 mm - Bearing seat length 17.2 mm M6 x 10 threaded hole on front with circlip puncture - according to HG Zng. K640860

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
TRIENS® Tensile Force Sensor 136.3 S30	one sensor - three measuring ranges - for mobile and stationary tensile force measurement - Nominal measuring force: 300 N Standard version: - Length of the measuring section 350 mm - 3 aluminum V-groove pulleys with smooth-running bearing technology for material up to Ø 30 mm
TRITENS 136.3 S30:	3 steel rollers with V-groove - hardened steel, especially for measurements on highly abrasive materials, such as tire cord, hardened steel wire, fiberglass materials - excellent wear resistance - with anti-corrosion coating - Geometry according to the standard roles - instead of the standard aluminum wheels
DIGITENS® 485	Precision measuring amplifier with digital display - Correct display of the traction force - comfortable one-hand operation - with fast peak memory for recording short, rapid tensile force peaks - battery operated, mains independent - incl. sensor connection cable, 2 m long
RFS 150/0200/BB/5/O	Radial force measuring axle RFS® BB for web tension measurement - precise and online - uses an existing reversing point for direct web tension measurement - especially designed for measurements in combination with web guiding rolls with interior bearings and without end-to-end axle - typically 2 RFSâ BB measuring axles are used per roll - rated load: 200 N - cable length: 3 m - connection: open ends - incl. ball bearing compensating disc dimensions as per HG dwg. 64_255_919
RFS-BB 2NR 200N 1.0mV/V loadcell	
Radial force measuring axle RFS® BB	for web tension measurement - precise and online - uses an existing reversing point for direct web tension measurement - especially designed for measurements in combination with web guiding rolls with interior bearings and without end-to-end axle - typically 2 RFSâ BB measuring axles are used per roll

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	RFSâ 150/0200/BB/5/S - rated load: 200 N - cable length: 3 m - connection: connector - incl. ball bearing compensating disc dimensions as per HG dwg. 64_255_919
with the following OPTIONS RFS 150:	Connection cable, 5 m long - instead of the standard connection cable, 3 m long Additional price per sensor
Plug-version RFS 150:	end of sensor's connection cable with male connector - 6-pole, 270°, gold plated contacts
Accessories in addition to plug-version:	Connection cable RFS 150 with female cable connector / open ends suitable for plug-version of the sensor, - one end with female cable connector 6-pole, 270°, gold plated contacts - one end with open ends - cable length 3 m
RFS 150/0200/BB/5/S	Radial force measuring axle RFS® BB -uses an existing reversing point for direct web tension measurement - especially designed for measurements in combination with web guiding rolls with interior bearings and without end-to-end axle - typically 2 RFSâ BB measuring axles are used per roller - rated load: 200 N - cable length: 3 m - connection: open ends - incl. ball bearing compensating disc dimensions as per HG dwg. 64_255_919
Connection cable, 5 m long	- instead of the standard connection cable, 3 m long
Radial force measuring axle RFS® BB	for web tension measurement - precise and online - uses an existing reversing point for direct web tension measurement - especially designed for measurements in combination with web guiding rolls with interior bearings and without end-to-end axle - typically 2 RFSâ BB measuring axles are used per roller RFSâ 150/0200/BB/5/S - rated load: 200 N - cable length: 3 m - connection: open ends

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	- including roller screw-in base according to HG dwg no. 64_255_929 with integrated self-aligning ball bearing 1202 E smooth-running variant with special greasing mounted in pairs as a fixed- / floating bearing Overall design according to HG dwg no. 64_255_919
Connection cable, 5 m long	with the following OPTIONS RFSâ 150 BB: - instead of the standard connection cable, 3 m long Additional price per sensor
Plug-version RFSâ 150:	end of sensor’s connection cable with male connector - 6-pole, 270°, gold plated contacts
Connection cable RFSâ 150	with female cable connector / open ends suitable for plug-version of the sensor, - one end with female cable connector 6-pole, 270°, gold plated contacts - one end with open ends - cable length 3 m
Radial force measuring axle RFS® 150 SR	Precision Standard Range tension measurement - online - designed as a single-roller system è uses an existing reversing point for direct tension measurement - for a wide variety of applications - highly exact measuring results - easy to adapt and robust - SR: Standard Range RFSâ 150 SR/0060/12/3/O - rated load: 60 N - bearing journal Æ: 12 mm - cable length: 3 m - connection: open ends The measuring range of the RFS-sensor begins at the force's zero point - regardless of the rated load with following OPTION RFS® 150: Special bearing journal Ø 12 mm - 2X - total length of bearing journal 22 mm - length of bearing support 17,2 mm front side M6 x 10 threaded hole with lock ring groove - as per dwg. K 640860
Radial force measuring axle RFS® 150 SR-	based precision tensile force measurement in a process line - online Sensor in the same technical version as RFS® 150 - Serial No. 791409 Radial force measuring axle RFS® 150 SR Precision Standard Range tension measurement - online

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	- designed as a single roller system è uses an existing reversing point for direct tension measurement - for a wide variety of applications - highly accurate measuring results - easy to adapt and robust - SR: Standard Range RFSâ 150 SR/0400/12/3/O - rated load: 400 N - bearing journal Æ: 12 mm - cable length: 3 m - connection: open ends with following OPTION RFS® 150: Special bearing journal Ø 12 mm - 2X - total length of bearing journal 22 mm - length of bearing support 17.2 mm front side M6 x 10 threaded hole with lock ring groove - as per dwg. K 640860
Ts 621	
Rfs® 150/0020/8/3/S	
Kmv 04 Fm	
Tensiotron Ts 621	
Rfs 100 Lr	
Rfs-Bb 2, Nr:741471	
Rfs150 Hr/1000/10/3/O	
Rfsã174; 150e/0020/8/3/S/0-10	
Ip66 270° Mit Skala4.7 Kohm, 1 Turn	
Ts 621 - Ve02000000000000	
Tde Sw A2	
Longer Standard Connection Cable	OPTION RFS® 150: Price per additional meter
Rfs 150 Xy	
Rfsã174; 150/0020/8/3/S	
Dpm 502 Art. No 139918	
Rfs 150e/0400/10/3/O/0-10 Radialkraft-	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Messachse	
Rfs 150	
Rfs 200 Load Cell	
Digitens 485	
Rfs 150 Xy Force Sensor With 2 Measuring Axis	
485 Sh Precision Measuring Amplifier With Digital Display	
Fujikura 70s	
Rfsã174; 150e/0005/8/3/S/0-10	
Rfs150 Art No 600113	
Rfsã174; 150/0060/X/3/O	
Dpm 502 Digitalanzeige Fa	
Mit Der Option Zusätzlicher Ausgang Ts 621	
604642 Thermocouple Knife Assembly	
Rfs 200	
Sonderlagerzapfen 12mm	
Wts 2 25 A 1000 S	
Ip66 270; Mit Skala4.7 Kohm, 1 Turn	
Radialkraft-Messachse Rfs 150 E Rfs 150e/Xxxx/8/3o/0-10	
Rfs 100 Lr	
Rfs150 Art.No 139828	
Rfs® 150	Radial force measuring axis RFS® 150 Precision tension measurement - online - designed as a single roller measuring system è uses existing deflection point for direct tension measurement - universally applicable, precise and robust RFS 150/0400/10/3 / O - Nominal measuring force: 400 N

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	- Bearing Ø: 10 mm - Cable length: 3 m - Connection: open ends The measuring range of the sensors starts - independently from the nominal sensor force - exactly at zero force. https://honigmann.com/page.php?m_pro=64&lang=1
Rfs 150e/0400/10/3/O/0-10	
Kmv 04 Fm	
Swa1	
Rfs150-0040-10-4-0	
Rfs 150 Radialkraft-Messachse	
Dpm 502	
Rfs 150e Radialkraftsensor	
Wts Bg2	
604642	
Fujikura 70s	
A-100-02400-025001	
Tensiontron Ts 621	
Tensiotron Ts621 Art. No. 139690	
485 Sh	
Rfsã174; 150e/0100/8/3/S/0-10	
Mit Der Option Zusã196;Tzlicher Ausgang Ts 621	
Rfs 150 Sensor	
RFS® 150 SR	Radial force measuring axis RFS® 150 SR Standard Range Precision Tensile Force Measurement - online - designed as a roll-in measuring system Ë uses an existing deflection point for direct tensile force measurement - universally applicable, precise and robust - SR: Standard Range RFS® 150 SR/0100/12/3/O - Nominal measuring force: 100 N

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	- Bearing pin Ø: 12 mm - Cable length: 3 m - Connection: open ends with the OPTION RFS® 150: 1 piece special bearing pin Ø 12 mm - 2X - Length of axle stub 22 mm - Bearing seat length 17.2 mm M6 x 10 threaded hole on the front side with Seeger ring insertion - according to HG Zng. K640860
Dpm 502 Art. No 139918	
A-100-02400-025001	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.