

Hotset

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Hotset Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Hotset Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
6100950	
7832519	
MITG29009D	
MITI03001B	
MIUC10009E	
hotrod® 10x55 315W 230V	Item No. HT5030522 - hotrod® type HHP 10 mm (-0.02/-0.06 mm) x 55 mm (1/-1 mm) 315W (31.5/-31.5 W) 230V - Sheath material: 1.4541 - 40 mm lead-out pure nickel wires - Marking neutral Provide a press fit Diameter: 10.00mm Length: 55.00mm Power: 315.00 watts Voltage: 230.00 volts Connection length: 400 mm
hotrod® 10x50 315W 230V	Item No. MIWG25008D - hotrod® type HHP 10 mm (-0.02/-0.06 mm) x 50 mm (1/-1 mm) 315W (31.5/-31.5 W) 230V - Sheath material: 1.4541 - 1000 mm lead-out GLS-insulated Ni-cables (max. 320°C) Diameter: 10.00mm Length: 55.00mm Power: 315.00 watts Voltage: 230.00 volts Connection length: 1000 mm

Ürün	Açıklama
	This cartridge heater, designed according to your wishes, is an extreme design. The life expectancy of this heating element depends to a large extent on the Installation situation in your application. In the case of unfavorable installation conditions (e.g. too large a fit) and too high operating temperatures, the service life may be severely limited! We therefore strongly recommend that you carry out your own tests with regard to the service life and behavior of the perform heating cartridge. The following conditions must be met when using this heating element as intended at least be complied with: The surface temperature of this heating element must not exceed 700 °C. A press fit is to be provided. The controlled system should be short, i.e. an external temperature sensor must be close to the heating element are placed.
C296	
4031326	
Hotspring Messing 1,3x2,3	
4051035	
Typ Hhp 4052047	
Mikb11029a	
Typ Hhp T 10x65	
E09m 2325w 460v (1053815) Å216;16 X 260mm	
Hhp 8302152500	
Å216;20 X 90mm T + H Hlp 400v 600wá;	
B 04 M 230v 180 W 1003866 Ce	
Hhp 1600w 870mm	
Typ Hhp 8x40 100w 110v	
1069463d11m	

Ürün	Açıklama
Hhp 16x80 70w 230v	
Mod F12 600lg St37	
Hhp 8x40 100w 110v	