Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Hp Technik

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Hp Technik Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Hp Technik Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Drv 18 El For Light Oil 2 - 18 Bar	Pressure regulator valve m. Plunger u. Roll ^ Connection G 3/8 " Material: GGG 40 Flow range: 300 - 600 l / h Pressure level: 2 adjustable: 2 - 18 bar V.no. : # HS Code: 84811019 Origin: CE (DE) Net weight (kg): 1,500
Drv 18 El For Light Oil 6 - 25 Bar	DRV 18 EL for light oil Pressure regulator valve m. Plunger u. Roll ^ Connection G 3/8 " Material: GGG 40 Flow range: 300 - 600 l / h Pressure level: 3 adjustable: 6 - 25 bar V.no. : # HS Code: 84811019 Origin: CE (DE) Net weight (kg): 1,500
B-GHG-E/4	h p - Overflow valve threaded version Connection G 1 " Material: GGG 40 DIN tested: DIN 12514-2 Flow range: 300 - 6000 l / h Pressure level: 4 adjustable:: 15 - 40 bar V. no. : # HS Code: 84811019 Origin: CE (DE)
SMG 1552-I-2-10-H1	h p - motor pump group with industrial pump series VB and overflow valve tested according to: DIN / EN 12514-1 Pump type: VBHG M-I-2-10-H1 Flow rate: 4500 l / h

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Pressure level: 2 bar adjustable: 2 - 9 bar Medium: # Three-phase standard motor: B3 / B14 Motor power: 2.2 KW Speed: 1400 min-1 Voltage: 230 V / 400 V Frequency: 50 Hz Degree of protection: IP 55 Efficiency class: IE3 HS Code: 84136020 Origin: CE (DE)
MMG 1847-I-2-90-BH1	motor pump group with industrial pump Series VB Type : VBGG-I-2-90-m-BH1 Flow rate : 400 l/h Pressure level: 2 adjustable : 2 - 9 bar with magnetic clutch: for pinion 38 Media : # Standard three-phase motor : B35 Motor power : 0.37 kW Voltage : 230/400 V Frequency : 50Hz P. no. : # F. no. : # M. no. : # Type :
Oil,Pump,Exproof,2000L/hr, 070H1063,Clayt	OIL PUMP CAPACITY:2000 L/HR ROTATION:CLOCKWISE REFERENCE NO:070H1063 MODEL:KSN2000 R MANUFACTURER:HP TECHNIK Please find the label attached!
NVBHRM-D-4-15-BH1	4120041 hp - industrial pump Flow rate : 1000 l/h Pressure level: 4 adjustable : 15 - 40 bar at speed : 1400 min-1
FDR 25-E/2	2270003 h p - relief valve flange design Flange DN 25, PN 40 Material : GGG 40

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	DIN tested: DIN 12514-2 Flow range : 300 - 6000 l/h Pressure level: 2 adjustable : 2 - 9 bar
BIK 5211-FL	0520396 h p - double unit series BIK flanged version with integrated overflow valve 2 x pump type : VBHGRP-I-4-10 Flow rate : 2200 l/h Pressure level: 4 adjustable : 15 - 30 bar Connections : DN 32 Media : # Three-phase standard motor: B3 / B14 Engine power: 4.0 KW Speed : 1400 min-1 Voltage : 400/690 V Frequency : 50Hz Degree of protection: IP 55 Efficiency class : IE3 2 x filters : DN 32 Filter insert : 100µm Oil pan : 800x700x80mm Vacuum gauge : -1..+5 bar Pressure gauge : 0 - 40 bar P. no. : # F. no. : # M. no. : # Type : #
SMG 1631 VBHGRP	2200 lt /h 30 bar 4kw 1400 rpm
B-GHG-E/4	4210005 Connection G 1" Material : GGG 40 DIN tested: DIN 12514-2 Flow range : 300 - 6000 l/h Pressure level: 4 adjustable: : 15 - 40 bar
A X - Piston B-GHG 1"	900-6000 l/h
4380047	hp - Motor pump group SMG 1868-I-4-90 with industrial pump series VB Pump type : VBHP-I-4-90 Flow rate : 470 l/h Pressure level: 4 adjustable : 15 - 30 bar

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Media : # Three-phase standard motor: B3 / B14 Motor power : 1.5 kW Speed : 950 min-1 Voltage : 230/400 V Frequency : 50Hz Degree of protection : IP 55 Efficiency class : IE
3210005	hp overflow valve threaded version B-GHG-E/3-AX with heavy oil pistons connection G 1" Material: GGG 40 DIN tested: DIN 12514-2 Flow range: 300 - 6000 l/h Pressure level: 3 adjustable: : 6 - 25 bar
B-G-E/1	1210003 hp overflow valve threaded version ^ BGE/1 G 1/2" connection Material: GGG 40 DIN tested: DIN 12514-2 Flow rate range: 30 - 600 l/h Pressure level: 1 Adjustable: 1 - 4 bar V.-Nr. : #
B – Gh – E / 4 - V101532	
Uhe-A5-Gz-I-4-20	h p - I n d ustriepumpe Flow rate: 1050 l / h at 40 bar Pressure level: 4 adjustable: 15 - 40 bar at speed: 2800 min-1 P.-Nr. : # HS code: 84136020 Origin: CE (DE) Net weight (kg): 5.186
4110035	
L67776	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.