

Hw Group

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Hw Group Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Hw Group Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
Hw Group	
Hw Group	
Sensor, Motion PIR detector JS-20	600236 HW-group Sensor PIR Motion Detector, JS-20 Infrared Motion detector with potential-free contact for Poseidon, Damcoles and I/O Controller Series, external Power pack (600434) is required, detection angle / Sensitivity Radius: 120° / 12 m (with standard len)
Zubehör, Power strip DC	600434 HW-group accessories Power strip DC, distributor for DC Power pack, power supply for smoke, water, motion and gas sensors.
Sensor, Flood Detector 1W-UNI 3m	600579 HW group Sensor Flood Detector 1W-UNI, Water detector for the 1W-UNI bus for e.g. Poseidon2, Damcoles or ARES. Detects punctured water ingress and other electrically conductive liquids using four protruding pins on the sensor body. the sensor can be placed on the ground (on an electrically isolated surface), or on the ground or on a be attached to the wall. Detection: 1D water detection (at one point) Interface: 1-Wire UNI (RJ11) Cable length: 3m

	Connection to: Poseidon2 series, Ares 12/14 Power supply: via the 1-Wire UNI Bus (RJ11) Area of application: indoors and outdoors
Sensor, Door Contact MK4	600371 HW-group Sensor Door Contact MK4, safer MK4 Door contact with 3m cable for Poseidon, Damcoles and I/O Controller series, can be extended with a 4-wire line
Poseidon2 4002	600816 (formerly 600571) HW group Poseidon2 4002, 12 floating Input contacts, 4 DO (relay outputs), 6x RJ11 for up to 16 temperature or humidity sensors (1-Wire/1-Wire UNI). web interface with password protection, Data logger for more than 250,000 memory points, RS-485 for up to 24x industrial sensors, email, SMS to up to 5 numbers (optional GSM modem, HWg-SMS-GW) SNMP polling and traps, metal housing, Temperature range -30°C to +85°C, without power pack and Accessories, Free online portal for monitoring
Poseidon2 4002 Tset, inkl.	Temperatursensor 600594 HW group Poseidon2 4002, 12 floating input contacts, 4 DO (relay outputs), 6x RJ11 for up to 16 temperature or Humidity sensors (1-Wire/1-Wire UNI). web interface with password protection, Data logger for more than 250,000 Memory points, RS-485 for up to 24x Industrial sensors, email, SMS to up to 5 Phone number (optional GSM modem, HWg-SMS- GW) SNMP polling and traps, Metal housing, temperature range -30°C up to +85°C, incl. EU power supply unit, 1x Temp19" rack temperature sensor, 1 temperature sensor 3m, 1 door contact, 19" rack ears with
Rackmountkit 19" für Poseidon 2	600583 Rackmountkit 19" for Poseidon 2 4xxx and HWg SMS GW2 assembly in 19" rack.
Sensor, Temp-1Wire 3m IP67	600585 HW-group Sensor Temp-1Wire 3m, temperature sensor for Poseidon/ARES and STE series with 1-Wire-RJ-11 connector. IP67 waterproof version. probe with Coated stainless steel cover (17241). Temperature measurement in the range from -10°C to +80°C
Sensor, Humid-1Wire 3m	600488 HW-group Sensor Humid-1Wire 3m, humidity sensor for Poseidon/STE/ARES series with RJ-11 connector
See list	
930021	Poseidon2 3268 Tset, incl. Temperature sensor 600593 Remote sensor monitoring via LAN, 2xRJ11 for up to 8 Sensors (1-Wire UNI) 4 DI's and 2 relay output, stable metal housing, integrated web interface, Alert via email (or text message via HWgSMS-GW), internal log function, supports the following Protocols: HWg-Push, SNMP, WEB, XML, Modbus/TCP, SensDesk.com compatible, temperature range -35°C to +85°C, set including 3m temperature sensor, door contact, Power supply, manual and CD, free
930020	Poseidon2 3268 600814 Remote sensor monitoring via LAN, 2xRJ11 for up to 8 sensors (1-Wire UNI) 4 DI's and 2 relay output, stable Metal housing, integrated web interface, Alert via email (or text message via HWg-SMS-GW), internal log function, supports the following protocols: HWg-Push, SNMP, WEB, XML, Modbus/TCP, SensDesk.com compatible,

Temperature range -35°C to +85°C, without Accessories, free online portal for the Monitoring from any location	
Perseus Monitoring 150	
Temp-1wire Rack 19quot;	
Ac 1w-Uni	
12v Netzteil	
Power Strip Dc	
Temp-1wire-Flat 3m	
Perseus Monitoring 150 - 600845	Perseus 150 plain unit. Rack monitoring System: 16 DI, 4 DO (Relay), 8x RJ11 (8x60m, 1 port = 1 sensor), 1x WLD zone, RS485 Modbus-RTU, Meters API. LAN with PoE or external 48V DC. Power adapter or 19" Mounting kit NOT included
Pse325-14-Dp-T-M-O	
600381	
Fdr26	
600585	
Mount Plate E- 1u	
Ste2	