

## Igel Electric

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin **info@yursat.com.tr** e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.  
**Igel Electric** Markası, tedarik sresi iin ltfen bizimle iletiřime geiniz.

*Firmamız Igel Electric Trkiye Distribtr veya temsilcisi deęildir. Firmamız sipariř durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*



| rn                                                    | Aıklama |
|---------------------------------------------------------|----------|
| <a href="#">010100400100CV</a>                          |          |
| <a href="#">600062000001</a>                            |          |
| <a href="#">80001013</a>                                |          |
| <a href="#">990300001</a>                               |          |
| <a href="#">CMOD6523357</a>                             |          |
| <a href="#">EPT-RX 2.3-13.8KV</a>                       |          |
| <a href="#">ISA-HD 300-6300</a>                         |          |
| <a href="#">RESISTOR 60OHM/110W</a>                     |          |
| <a href="#">RIM-I 2 110/230VDC</a>                      |          |
| <a href="#">TRAF540964</a>                              |          |
| <a href="#">TRAF540965</a>                              |          |
| ISA-A 58-400 Technical data: Analogue soft starter with |          |

[ISA-A 58-400](#)

motor protection function and integrated bypass Rated motor voltage: 400V 50/60Hz Device rated current: 58 A Rated motor power: 30 kW Power unit: thyristors 3-phase control Degree of protection: IP00 Dimensions: 129 x 275 x 185 mm (WxHxD) Weight: 5.3kg Max starting current: 400% for 20s / 300% for 30s Starts per hour: 4 starts at maximum conditions Ambient temperature: 0°C - 40°C Maximum humidity: 95% non-condensing Maximum installation altitude: 1000m, power reduction at higher altitudes Benefits of ISA-A Integrated by-pass to bridge the thyristors after startup Extensive motor and starter protection package for current and voltage faults Current and torque limitation Maintenance-free design thanks to aluminum housing with natural cooling

[Isa-Dsm 590-400-230-3m-33\\_I](#)[010120400060](#)[Isa-B2p 44-400](#)[Isa-A 44-400](#)[478084 Softstarterthyristoren Fur Isa-Hd  
400-6000-230-230-1](#)[Isa-Ds 210-400-230-3m-5-8-I](#)[Imb 58-400](#)