



Ilc

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Ilc Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Ilc Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Part Number 39.Z05514.001	complete pump without motor
00.870.1	Type CME CE 230 V Reservoir 3.6 L WITHOUT TIMER
006430	
p/n 90.441.3	
60.822.2	
81.G2.CE.230	
part number 02.880.4	**the fittings are NOT included.
A72.079450	
81.G3.CE.230	CME SOFT-GREASE 3L WHITOUT TIMER 230 V AC 3L 230VAC 30 BAR
81.GR.CT.230	CME SOFT-GREASE 3L WITH TIMER 230 V AC
A91.111349	
A70.093687	
4.3I.12.06	
03.222.1.04	
TW.100504	
A72.079262	
00.648.6	
00.871.4	

SATAM ZC17 330 MECA	8" horizontal positive displacement flow meterMax flow rate up to 330 m ³ /h (5 500 l/mn), Accuracy class : 0,5 (OIML R117-1),on a flow rate range 1 to 10, typical repeatability 0.02%, linearity better than 0.1% Maximum working pressure 10 Bar, test pressure 15 Bar. Medium: diesel/ to be confirmed MA21 330 - 4 capsules design positive displacement flow meter, iron body cast, carbon vanes, aluminum rotor, cast Iron inner and outer covers and high Nitrile seals. Flow direction: left to right or right to left / to be confirmed 8" ductile iron standard manifold, inlet and outlet flanged 8 inch DIN ASA150 150lbs RF AB 21 mechanical stepless adjustment mechanism with VR Gear plate VR Gear plate + VR7887 mechanical indication meter register – decaliters, designed for delivery operations with resettable register and non resettable totalizer. The register totalizes and displays high-speed deliveries and transactions in large, easy-to-read figures. ATEX Marking : II 2 G c T4 (Mechanical version) / Ex IIA T4 Gb (Including electrical parts)Ambient temp. range (°C) : [-20°C?Tamb?+55°C]
MPT-100cc	
A53.106680	A53.106680 FOR LUBETOOL SYSTEM
A53.106680	
81.O2.CE.230 CME CE+PULS+PFL 230V	
A70.093165	
90.432.2	
00.224.6	
DPM-3	
00.871.4	
81.O3.CE.24V	
PAG-50 PL 2,5 KG 0.3-2cc	90.304.4
40.Z06289.001	ILC-MAX 2 24 V DC FIXED
PUMP TYPE: ILC-MAX	VOLTAGE : 24V DC CURRENT: 2.5A MAX PRESSURE: 250bar DELIVERY: 3,52 cc/min CO
The DPX divider complete of inlet	grease nipple and 6x outlet fittings
40.4.24DC.RST.G	MAX GREASE 24VDC 4KG ADJ
39.Z07588.001	MINI-MAX 24 V DC WITHOUT TIMER 1 pumping element
70.706.2	LL 2 + 2 WAYS CONVEYORS
A70.093165	LU COMPLETE PUMP BASE
PRA-15/3.6 OIL	00.224.6

CMV-15 N C.E. 2.2 L 230 V AC	90.440.5
81.02.CE.230	CME OIL 2 L EXT PFL 230 V AC
2.3I.03.M12	DPX-3 + INDUCTIVE SENSOR M12x1
A70.093463	LU COMPLETE PNEUMATIC PUMP NEW
A72.079450	PAG-50 RESERVOIR
40.2.24DC.RST.G	MAX GREASE 24VDC 2KG ADJ
00.879.2	CME-G CE+PULS+PFL 24V DC 3.6L
40.Z03285.003	
90.454.3	CMV-15 N C.E. 3.6 L 230 V AC
70.015.0.SL	LL MINIGF-EL-1/1.2 L-SL
ILC-MAX2	
ILC-MAX4	
3820 C	
A70.093463	
100.263/FC	Pump and motor as a unit
49.046.0.N	
3820-B	Pneumatic valve
A70.093463	MICRO LUBRICATION PUMP
90.980.5	
ILC MAX2 GREASE PUMP RESERVOIR	
Ilca70093230	
Ilc701510	
70.150.6	
90.311.5	
14.661.4	
Ilca70093181	
P/N:00.230.0	
60.822.2	
Part Number A72.079450	the new design for PAG reservoir is as included, and is perfectly interchangeable with the old design.
A52.090051	

Mpt-200	
40.2.24dc.Fct.G	
00.230.0 Obsolete	
A51.107046	
90.300.3	
49.081.0	
Dpm-3	
Ipr490500	
40.8.115ac.Rct.G	
608211	
46.650.0	
Ils Cmv-15n / 3 Liter	
017	MACHINE
00.870.1	
Part Number 00.870.3	
60.824.2	MPT-500/G Polypropylene Tank
I490810	
70.104.8	
14.663.0	
00.224.6	
90.304.1	
00.860.5	
14.660.1.R	
A72.079234	
A70.094037	
14.660.0	
90.441.5	
00.870.1 Lube Pump	
49.046.0	Pressure switch 10-65 bar
07.261.0	

[14.660.1](#)

[14.661.3](#)