

Intronic

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Intronic Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Intronic T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Adc1130	(PRICE/EA) ANALOG TO DIGITAL CONVERTER ADC, 14 BIT, MODULE, RESOLUTION (BITS):14BIT, SAMPLING RATE:-, SUPPLY VOLTAGE TYPE:-, SUPPLY VOLTAGE MIN:-, SUP
277j	IC, ISOLATION AMPLIFIER, 2.5KHZ, NO. OF AMPLIFIERS:1, INPUT OFFSET VOLTAGE:1.5MV, BANDWIDTH:2.5KHZ, ISOLATION VOLTAGE:3500VRMS, GAIN NON-LINEARITY MAX
Rti1260	COMPUTERS, DATA ACQUISITION INTERFACE CARDS, OPERATING TEMPERATURE RANGE:0 C TO +70 C
2b54a	IC, THERMOCOUPLE/MV CONDITIONER, 72-DIP, IC FUNCTION:FOUR-CHANNEL, ISOLATED THERMOCOUPLE / MV CONDITIONERS, SUPPLY VOLTAGE RANGE:12V TO 18V, OPERATING
Rti1225	COMPUTERS, DATA ACQUISITION INTERFACE CARDS
2b57a-1	(PRICE/EA) TEMPERATURE TRANSMITTER, SIGNAL CONDITIONER INPUT:RTD, SIGNAL CONDITIONER OUTPUT:CURRENT, NO. OF OUTPUT CHANNELS:2, ACCURACY %:-, NO. OF CH

Dac1146	IC, DAC, 18BIT, MODULE-32, RESOLUTION (BITS):18BIT, INPUT CHANNEL TYPE:PARALLEL, DATA INTERFACE:PARALLEL, SUPPLY CURRENT:-25MA, DIGITAL IC CASE STYLE:
Rti860	CONTROL CARD
Adc1140	IC, ADC, 16BIT, MODULE-32, RESOLUTION (BITS):16BIT, DATA INTERFACE:PARALLEL, SUPPLY CURRENT:150MA, DIGITAL IC CASE STYLE:MODULE, NO. OF PINS:32, OPERA
Rti1281	COMPUTERS, DATA ACQUISITION INTERFACE CARDS
Das1159	IC, ADC, 16BIT, 18KHZ, METAL CASE, RESOLUTION (BITS):16BIT, SAMPLING RATE:18KSPS, DATA INTERFACE:PARALLEL, SUPPLY CURRENT:15MA, DIGITAL IC CASE STYLE:
Dcw24/15d/400	(PRICE/EA) ANALOG IC
2b54b	IC, THERMOCOUPLE/MV CONDITIONER, 72-DIP, IC FUNCTION:FOUR-CHANNEL, ISOLATED THERMOCOUPLE / MV CONDITIONERS, SUPPLY VOLTAGE RANGE:12V TO 18V, OPERATING
Das1158	IC, ADC, 15BIT, 18KHZ, METAL CASE, RESOLUTION (BITS):15BIT, SAMPLING RATE:18KSPS, DATA INTERFACE:PARALLEL, SUPPLY CURRENT:15MA, DIGITAL IC CASE STYLE:
2b24b	SIGNAL CONDITIONING, ISOLATION AMPLIFIERS, SIGNAL CONDITIONER INPUT:TEMPERATURE, SIGNAL CONDITIONER OUTPUT:CURRENT, NO. OF OUTPUT CHANNELS:2, NO. OF C
277k	IC, ISOLATION AMPLIFIER, 2.5KHZ, NO. OF AMPLIFIERS:1, INPUT OFFSET VOLTAGE:1.5MV, BANDWIDTH:2.5KHZ, ISOLATION VOLTAGE:3500VRMS, GAIN NON-LINEARITY MAX
Adc1131k	IC, ADC, 14BIT, MODULE-72, RESOLUTION (BITS):14BIT, DATA INTERFACE:PARALLEL, SERIAL, SUPPLY CURRENT:250MA, DIGITAL IC CASE STYLE:MODULE, NO. OF PINS:7
Dac1136j	IC, DAC, 16BIT, MODULE-72, RESOLUTION (BITS):16BIT, INPUT CHANNEL TYPE:PARALLEL, DATA INTERFACE:PARALLEL, DIGITAL IC CASE STYLE:MODULE, NO. OF PINS:72
Dcw24/5/3000	(PRICE/EA) ANALOG IC
289l	(PRICE/EA) ISOLATION AMPLIFIER, 20KHZ, 0.14V/US, NO. OF AMPLIFIERS:1 AMPLIFIER, INPUT OFFSET VOLTAGE:5MV, ISOLATION VOLTAGE:2500VRMS, SUPPLY VOLTAGE R