

Intronics

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Intronics Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Intronics Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
2b34j	(PRICE/EA) STRAIN GAUGE/RTD CONDITIONER, 72-DIP, IC FUNCTION:RTD / STRAIN GAUGE CONDITIONER, SUPPLY VOLTAGE MIN:14.25V, SUPPLY VOLTAGE MAX:15.75V, IC
751n	IC
2b23j	IC ISOLATED VOLTAGE TO CURRENT CONVERTER, INPUT VOLTAGE:10V, NO. OF OUTPUTS:2, SUPPLY VOLTAGE RANGE: 14V TO 28V, NO. OF PINS:12, OPERATING TEMPERATURE
Rti1226	COMPUTERS, DATA ACQUISITION INTERFACE CARDS
Dac1136k	IC, DAC, 16BIT, MODULE-72, RESOLUTION (BITS):16BIT, INPUT CHANNEL TYPE:PARALLEL, DATA INTERFACE:PARALLEL, SUPPLY CURRENT:30MA, DIGITAL IC CASE STYLE:M
277a	IC, ISOLATION AMPLIFIER, 2.5KHZ, NO. OF AMPLIFIERS:1, INPUT OFFSET VOLTAGE:1.5MV, BANDWIDTH:2.5KHZ, ISOLATION VOLTAGE:3500VRMS, GAIN NON-LINEARITY MAX
Rti1262	COMPUTERS, DATA ACQUISITION INTERFACE CARDS, CONNECTOR TYPE:3M#3429,26PIN, OPERATING TEMPERATURE RANGE:0 C TO +70 C
Das1152	IC, ADC, 14BIT, 25KHZ, METAL CASE, RESOLUTION (BITS):14BIT, SAMPLING RATE:25KSPS, DATA INTERFACE:PARALLEL, SUPPLY CURRENT:80MA, DIGITAL IC CASE STYLE:
Rti1280	COMPUTERS, DATA ACQUISITION INTERFACE CARDS
Adc1131j	IC, ADC, 14BIT, MODULE-72, RESOLUTION (BITS):14BIT, DATA INTERFACE:PARALLEL, SERIAL, SUPPLY CURRENT:250MA, DIGITAL IC CASE STYLE:MODULE, NO. OF PINS:7
2b56a	SIGNAL CONDITIONING, SIGNAL CONDITIONER INPUT:THERMOCOUPLE, SIGNAL CONDITIONER OUTPUT:VOLTAGE, NO. OF OUTPUT CHANNELS:4, NO. OF CHANNELS:4, TYPE:DIGIT

Ürün	Açıklama
Das1153	IC, ADC, 15BIT, 20KHZ, METAL CASE, RESOLUTION (BITS):15BIT, SAMPLING RATE:20KSPS, DATA INTERFACE:PARALLEL, SUPPLY CURRENT:80MA, DIGITAL IC CASE STYLE:
2b55a	IC, THERMOCOUPLE/MV CONDITIONER, 72-DIP, IC FUNCTION:FOUR-CHANNEL, ISOLATED THERMOCOUPLE / MV CONDITIONERS, SUPPLY VOLTAGE RANGE:12V TO 18V, OPERATING
755n	(PRICE/EA) LOGARITHMIC AMPLIFIER, 400 UV, 100 US, NO. OF AMPLIFIERS:1 AMPLIFIER, DYNAMIC RANGE:6 DECADES, SCALE FACTOR:2V / DECADE, RESPONSE TIME:100
2b31l	(PRICE/EA) STRAIN GAUGE/RTD CONDITIONER, 29-DIP, IC FUNCTION:STRAIN GAUGE / RTD CONDITIONER, SUPPLY VOLTAGE MIN:12V, SUPPLY VOLTAGE MAX:18V, IC PACKAG
2b24a	SIGNAL CONDITIONING, ISOLATION AMPLIFIERS, SIGNAL CONDITIONER INPUT:TEMPERATURE, SIGNAL CONDITIONER OUTPUT:CURRENT, NO. OF OUTPUT CHANNELS:2, NO. OF C
451k	(PRICE/EA) F/V CONVERTER, 10KHZ, 0.015%, 9-DIP, FREQUENCY:20KHZ, FULL SCALE RANGE:0HZ TO 10KHZ, LINEARITY %:0.015%, SUPPLY VOLTAGE RANGE:12V TO 18V, D