

Ipf



Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Ipf** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Ipf Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

| rn | Aıklama |
|---|---|
| Ot140406 | Sensor Optisch, Taster, 27x14x12mm, Sn: 20-120, 10-30V DC, 2x PNP antivalent, Kabel 2m PUR (Pol... |
| Ot160400 (Alternativ) | Sensor Optisch, Taster, 35x35x12mm, Sn: 15-300, 10-30V DC, 2x PNP antivalent, Kabel 2m PVC, IP6... |
| IN180126 | Sensor inductive, M18x1 64long, non-flush, Sn: 20, 10-30V DC, PNP NO, M12 connector 3-pin, IP67 ... |
| OTQ40173 | Sensor optical, button, 45x6.2x4mm, Sn: 50, 11-30V DC, 1x PNP / NPN push-pull (push / pull), M8 cable ... We will be happy to supply you with the appropriate cable socket for the plug-in devices. kablo soketleri ayrı tekliflendirilmektedir, dahilindeyse ltfen bildiriniz |
| PS 13 00 70 SENDER M8 3P | |
| PE 13 01 70 EMPFANGER M8 3P | |
| SENSOR IN 99 11 97 230 °C | |
| VK 99 11 98 (30 METER SOCKET CABLE) | |
| 02351-93650 | |
| IN991070 | Sensor Inductive, M80x1.5 66long, non-flush, Sn: 50, 10-35V DC, -25-160°C, PNP NO, cable 2m silicone, IP67, VA |
| VK991198 | |
| IN991197 | |
| IB180151 | |
| IN991070 | Sensor inductive, M80x1.5 66long, not flush, Sn: 50, 10-35V DC, -25-160°C, PNP NO, cable 2m silicone, IP67, VA SPECIAL |

| | DEVICE |
|-----------------------------------|---|
| PROX IPF IB120123 | 24VDC PNP NO 12X60 S |
| IB98E245 CE | |
| IN080176 | Inductive sensor, M8x1 60 long, non-flush, Sn: 6, 10-30V DC, PNP NO, M8 connector 3-pin, IP67, brass chrome-plated |
| VK500071 | We are happy to offer you a cable socket suitable for the above device: Connection cable, 5m, M8 socket 3-pin angled, free Cable end 3-pole, 3x0.34mm ² , PUR (polyurethane), Ø4.3mm, 250V, -30-90°C, IP67, drag chain and torsion-resistant, oils and cooling lubricants, welding area, Silicone-free |
| MZR9F001 | Sensor Magnetic, Cylinder, 9mm Round, Ø9mm 20long, 10-30V DC, 1x PNP NO, M12 cable connector 4-pin 1m PUR (Polyurethane), IP67, VA, 2.8mT, Position of the sensor surface Device center |
| IB120155 | Sensor Inductive, M12x1 56long, flush, Sn: 3, 10-35V DC, 0-130°C, PNP NO, cable 2m silicone, IP65, VA |
| IN080176 | Inductive sensor, M8x1 60mm long, non-flush, Sn: 6, 10-30V DC, PNP NO, M8 connector 3-pin, IP67, brass chrome-plated |
| Os126020 | |
| Am000076 | |
| Ov580900 | |
| Mz070126 | |
| Mz070125 | |
| Ib090100 | sensor ind 8x40x8 10-30V DC,200mA,Sn:1,5/2m Kabel |
| Ib090170 | sensor ind 8x59x8 10-30V DC,200mA,Sn:1,5/M8-Stecker |
| Mzr40178 | |
| OE126020 | High-performance light barrier receiver, M12x1 55 long, Standard design, connection to amplifier, M12- Connectors, IP67, stainless steel + plastic SPECIAL DISCOUNT |
| M8x1 Inductive | -inductive -with sockets - as both include no and nc two contact sensor |
| Am000070 | |