

Italvalvole

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Italvalvole Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Italvalvole T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



| ¼r¼n | A¼ıklama |
|---|--|
| Ø160 X 13 X 23 Valve Cuff | |
| 5402 (G: 400 - P: 1.020) | SERVOCONTROL SPARE PARTS SBS D.360 |
| 11839 | |
| 12495 | |
| 12496 | |
| 12833 | |
| 12834 | |
| 17605 | |
| 17800 | |
| LOT2017000005225 | membrane rubber gasket |
| DN 15/25/40//50/80 | repair kit set |
| SBS B77 T360-STD 6-18 | DN20 GJL PN16 PK L C20 2VNC PN¼MATİK VALF DN20 |

| | |
|---|--|
| SBS B77 T360-STD 6-18 | DN25 GJL PN16 PK L C20 2VNC PNÖMATİK VALF DN25 |
| SBS B77 T360-STD 6-18 | DN50 GJL PN16 PK L C20 2VNC PNÖMATİK VALF DN50 |
| SBS B77 T360-STD 6-18 | DN65 GJL PN16 PK L C20 2VNC PNÖMATİK VALF DN65 |
| SBS B77 T360-STD 6-18 | DN80 GJL PN16 PK L C20 2VNC PNÖMATİK VALF DN80 |
| DN65 Proportional Burah Valve | |
| DN80 Proportional Steam Valve | |
| 19079 (G: 120 - P: 837) | SBS A63 H360-STD 03#15 DN050 GJL PN16 PK L S20 2WNC DN 50 Seat diameter [mm] 48 Actuator [mm] 360 Actuator Material Standard Signal [psi] 3÷15 Packing PTFE / PTFE-Gr Body GJL Rating PN16 Connections EN1092-2 PN16 Face-to-Face EN558-1 Series 1 Trim 316/304 Seal PEEK Leakage Class VI Characteristic Linear Kv [m3/h] 42,4 Max Dp [bar] 7,2 Max Temperature [°C]+200° Stroke [mm] 20 Function 2 way Normally Close/Open NC |
| DIAPHRAGM D.360 | 1714 (G: 584 - P: 40) |
| SERVOCONTROL SPARE PARTS SBS/10 D360 | 5402 (G: 400 - P: 1.020) |
| 13587/20 | SBS C77 T360-STD 06#30 DN065 GJL PN16 PK L S20 2WNO ♦ DN 65 Seat diameter [mm] 63 Actuator [mm] 360 Actuator Material Standard Signal [psi] 6÷30 Packing PTFE / PTFE-Gr Body GJL Rating PN16 Connections EN1092-1/2 PN16 Face-to-Face EN558-1 Series 1 Trim 316/304 Seal PEEK Leakage Class VI Characteristic Linear Kv [m3/h] 74,8 Max Dp [bar] 8,5 Max Temperature [°C]+200°C Stroke [mm] 20 Function 2 way Normally Close/Open NO |
| From the attached flanged on-off valves | DN20 3 pieces DN25 3 pieces DN32 3 pieces |
| 18813 (G: 072 - P: 7.400) | IVBV/D BALL V.3W-T DN020 316/316 PTFE 1-2-3:CL TS003DE ♦ CW -Integral Type 3 ways - T DN 20 Body AISI 316L Cap AISI 316L Ball AISI 316L Seal PTFE Stem AISI 316 Connections Clamp Rating PN64 Control Pneumatic Actuator DE Max Temperature [°C]+150° |
| 19129 (G: 072 - P: 8.050) | IVBV/D BALL V.3W-T DN020 316/316 PTFE 1-2-3:CL TS003DE ♦ CW -Integral -Sealed Type 3 ways - T DN 20 Body AISI 316L Cap AISI 316L Ball AISI 316L Seal PTFE Stem AISI 316 Connections Clamp Rating PN64 Control Pneumatic Actuator DE Max Temperature [°C]+150° |
| 19665 (G: 072 - P: 425) | IVBV/3P/I BALL V. 3P DN020 316/316 PTFE CL De50.5 ♦ TS003DE Type 3 pieces DN 20 Body AISI 316L Cap AISI 316L Ball AISI 316L Seal PTFE Stem AISI 316 Connections Clamp ISO Rating PN64 Control Pneumatic Actuator DE Max Temperature [°C]+160° |
| LOT 2024000000 | |
| 3580 Bottom valve dn015 filter | |

| | |
|---------------------------------|--|
| NST-20308030221 | DN80 PN16 NST proportional control valve PIK PEEK-Y |
| NST-20307030220 | DN65 PN16 NST proportional control valve PIK PEEK-Y |
| NST-20305030215 | DN40 PN16 NST proportional control valve PIK PEEK-Y |
| DN50 PN16 | PROPORTIONAL STEAM VALVE - OPERATING PRESSURE: 0.4...1.2 BAR |
| 16861 | VALF PNÖMATİK FFF/P DN15 D:63 EPDM 6-8BAR MATR:2016/24800 SVP CODICE:16861 |
| 16859 | VALF PNÖMATİK FFF/P DN50 D:80 EPDM 6-8BAR MATR:2016/24847 SVP CODICE:16859 |
| 16853 | VALF PNÖMATİK FFF/P DN32 D:80 EPDM 6-8BAR MATR:2016/24743 SVP CODICE:16853 |
| 12816 | SUITABLE AND THE PIPE DIAMETER MUST BE 1 1/4 Please look at the attachement |