

lwn

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

lwn Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız lwn Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
lwn	
lwn	
lwn	
0688-03	
181-040-003-0	pneum. 2/2-way valve - PMV-D 40/80-A-D Country of origin: Germany for CV 11/12 consisting of: Valve material - Brass housing - Spindle made of CK45 hard chrome-plated - Brass internal parts - Pressure spring made of 1.4310 - Spindle seal PTFE packing - Seat seal PTFE - Seals EPDM, Viton Drive material - Control head housing made of brass, bright nickel-plated - Cylinder base made of stainless steel - Brass internal parts - Pressure spring made of 1.4310 - Seals Viton, NBR Technical data: Connection size: G1 1/2, G1/4 Nominal width: 40 mm Temperature: max. +180°C Installation position: any Control pressure: 6 - 10 bar Pressure range: 0 - 6 bar Medium: Steam Medium above the seat With control cone, column design fully assembled and tested

Ürün	Açıklama
181-032-005-0	2/2-way angle seat valve - PMV-S 32/125-A-S-B Country of origin: Germany Connection G 1 1/4 Opens with control air Closes with spring force Control pressure: 2.5 bar Operating pressure: 0-6 bar Installation position: any Control head made of stainless steel With optical position indicator
181-032-005-0-	2/2-way angle seat valve - PMV-S 32/125-ASB Country of origin: Germany Connection G 1 1/4 opening under control air Spring force closing Control pressure: 2.5 bar Operating pressure: 0-6 bar Installation position: any Control head made of stainless steel with optical position indicator VALVE NO.:
PMV-D 32/80-A-D-S	181-032-002-0 pneumatically controlled 2/2-way valve - PMV-D 32/80-ADS Germany (Country of origin): Connection: G 1 1/4 Medium: Steam Pressure range: 0-10 bar Temperature: max. 180 degrees Control pressure: 6-10 bar Medium located under the seat with control cone Column design VALVE NO.: will be specified in the order
DHZ-100/100.5- Links	
5032.8250	LU SCHALTERBLOCK RE
0688-02-412	
094k024650	
909-000-064-0	