

## J-TEC

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**J-TEC** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız J-TEC T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">DAA0349-0003</a>	VF563AA-FLWMTR, IN-LINE, .375" 0-5VDC DAA0349-0003 Blow-by Meter. In-Line Style Gas Flow meter, 3/8", Anodized Aluminum, Flow Range: 0.14 to 5 ACFM (4.0 to 141.6 LPM) 0 - 5 VDC Output; Operating Temperature: 0 to 200 F (-18 to 93 C); Operating Pressure: -5 to 30 PSIG (-0.35 to 2.1 kg/cm <sup>2</sup> ); Accuracy: +/- 2% Full Scale; Actual measurements are recorded as is, estimation of uncertainty of measurement is not taken into account in determining a pass or fail decision. Repeatability: +/- 0.5% of reading; Electronics Temperature Limits: -40 to 150 F (-40 to 66 C); Response Time: 100 msec; Input Power: +12 to +24 VDC at 35 mA Mating electrical connector is included.
<a href="#">DAA0392-0003</a>	VF563J FLOWMETER, IN-LINE .75" W/0-5VDC DAA0392-0003 Blow-by Meter. In-Line Style Gas Flow meter, 3/4", Anodized Aluminum, Flow Range: .7 to 27 ACFM (20 to 765 LPM) 0 - 5 VDC Output; Operating Temperature: 0 to 200 F (-18 to 93 C); Operating Pressure: -5 to 30 PSIG (-0.35 to 2.1 kg/cm <sup>2</sup> ); Accuracy: +/- 2% Full Scale; Actual measurements are recorded as is, estimation of uncertainty of measurement is not taken into account in determining a or fail decision. Repeatability: +/- 0.5% of reading; Electronics Temperature

Limits: -20 to 150 F (-29 to 66 C); Response Time: 100 msec; Input Power: +12 to +24 VDC at 35 mA Mating electrical connector is included.

[DAA0393-0003](#)

VF563K FLOW METER, IN-LINE 1.0" W/0-5VDC DAA0393-0003 Blow-by Meter. In-Line Style Gas Flow meter, 1", Anodized Aluminum, Flow Range: 1 to 50 ACFM (28.3 to 1415.8 LPM) 0 - 5 VDC Output; Operating Temperature: 0 to 200 F (-18 to 93 C); Operating Pressure: -5 to 30 PSIG (-0.35 to 2.1 kg/cm<sup>2</sup>); Accuracy: +/- 2% Full Scale; Actual measurements are recorded as is, estimation of uncertainty of measurement is not taken into account in determining a pass or fail decision. Repeatability: +/- 0.5% of reading; Electronics Temperature Limits: -40 to 150 F (-40 to 66 C); Response Time: 100 msec; Input Power: +12 to +24 VDC at 35 mA Mating electrical connector is included.