Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Jaudt

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Jaudt Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Jaudt Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
REPAIR KIT OF 16-HV98071 (FSV 350 SLIDE GATE VALVE	DWG NO: 51-0483-6051 TYPE: 212-0686.10 VALVE SIZE: 14 IN # 150 lbs ATTACHED DATE SHEET AND MANUFACTURER CROSS SECTIONAL DRAWING
250/300, 0,37 kW, 28 upm_PN 6 Typ ZSFi GII rotary	
FSV 250 HR Manually operated bladed valve	(Slide Gate)
630107.3001	ZS Vario 200/350 KD article no. 15622 MB630107.3001 V JAUDT ROTARY WHEEL LOCK ZS Vario Inlet/outlet mm : 200 ø Height mm : 350 max. operating temp. °C : 60 Actuating pressure MPa : - Max. working pressure MPa : 0 Control voltage V : - Works certificate 2.2: according to DIN - EN 10204:2004 Housing : cast iron GG20 Flange drilling pattern according to DIN 2501 PN 6 according to MB630107.3001 End shields : cast iron GG20 External storage Stuffing seal adjustable Cell wheel : Welded construction mild steel With edge discs 10 pockets MRS + DL (3.3x overlap) 7.7L Sealing strips fabric rubber, replaceable Q2 = approx. 7.7 l/rev Drive: clutch bell and elastic. coupling Clutch bell mild steel, painted Motor : Three-phase spur gear motor >SEW< suitable for operation on the stat. converter

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Rated power [kW] 0.55 with mains operation 50 Hz Nominal voltage [V] 230/400 Frequency [Hz] 50 Frequency range [Hz] 8.7 - 50 - 87 Degree of protection IP 55 Type M 1 (flange) Heat class F Temperature sensor 3 x TF for heat class F (without release device) Rated current [A] 2.25 / 1.29 cosphi 0.75 Efficiency class IE3 Output speed [1/min] 17 (at 50 Hz) Flange [mm] 200 Shaft end [mm] ø 30 x 60 * WITHOUT converter Power : frequency 8.7 - 50 - 87 Hz Cell wheel speed 3.0 - 17 - 29.6 rpm theoretical Flow rate 1,367 - 7,854 - 13,665 dm^3/h at 100% filling Painting :* Housing, end shields RAL 2003 * Clutch bell RAL 2003 KH base and top coat each 30 µm Cell wheel primed 30 µm DIN parts according to manufacturer standard Drive according to manufacturer standard RAL 9005 Type plate (adhesive aluminum plate with protective film)
042507.20-40	sealing strip Textile rubber drive belt, 6 layers Drawing no.: 042507.20-40 366x109.5x8
212-0216.10	Repair kit set
612566.1002	FS100 ECO 400x400 H MB612566.1002 JAUDT FLAT SLIDE FS100 ECO H Grain size: 0.1-3.0 mm, pressure difference +/-0 da Pa, not dust/ gas tight passage and to the outside, for non-abrasive bulk materials, Emergency gate valve does not close against standing column of material Opening width mm: 400 x 400 Height mm: 100 Stroke direction in : 400 max.operating temp. °C: 80 Actuation pressure MPa : - max. operating pressure MPa: 0 Control voltage V : -

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Material: mild steel (Tmax 250°C) Frame: sheet metal edge welded construction Flange width 60 mm, sheet metal 6 mm unedited Product space: deflector strips welded on three sides Working area: *Top with cover plate, sheet metal 2 mm, screwed *Bottom with cover plate, sheet metal 2 mm, screwed Sealing: stuffing seal packing adjustable between product and work space Packing/pressure bar/cover mild steel (Tmax 2 Pack of glasses all around Packing material felt (Tmax 80°C) Slide plate: Mild steel, galvanized Sheet metal 8 mm Guide: on cylinder screws, replaceable Actuation: manual (spindle mild steel/spindle nut plastic) *with handwheel 200ø Manual operation (installation height) is provided by the customer ensure Accessories: Without Flange drilling : **according to old JAUDT dimension sheet Painting:* Structural steel painted according to JAUDT standard RAL 9002 * Cover plates for workspace RAL 9002 KH base coat and top coat 30 µm each Stainless steel according to JAUDT standard DIN parts according to manufacturer standards Type plate (adhesive aluminum plate with protective film) Weight: 65kg Device no. : 612566.1002 Version similar. 207-1907.40
611006.4002	FSV 150 P Alu MB611006.4002 V JAUDT VARIO-SCHIEBER FSV Opening width mm: 150 Height mm: 90 Max. operating temperature °C: 80 Actuating pressure MPa: 0.6 - 1.0 Max. operating pressure MPa: 0 Control voltage V: - Housing: cast aluminum (AlSi 10Mg) Pressure shock resistant up to 5 bar In the passage with coarse material baffle on the front Not dust-tight in the passage Flange drilling. : according to DIN 2501 PN 6 Sealing: slide plate lead-through to the outside with adjustable stuffing packing Packing material: ARAMID suitable up to 250°C Pressure piece made of cast aluminum

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Slide plate: stainless steel 1.4301 Slide plate guide: *eccentric rollers stainless steel 1.4305 Activation: pneumatic with cylinder ø 80 >JAUDT< double-acting treated, filtered compressed air Accessories: 5/2-way solenoid valve Mannesmann Rexroth 577 607 530 2 basic valve G1/4" without coil and plug Art. No. 013600.0017 1 limit switch make Schmersal IFL 20-400-11YPG for position - CLOSED - 10 - 60 V inductive Art. No. 005600.0030 Contact protection for work area Painting: stainless steel and aluminum parts, bare Steel parts galvanized, 10 µm Drive according to manufacturer standard Nameplate (aluminum adhesive plate with protective film)
FSZ ATEX 350 P	224-1014.10 Opening width mm: 350 Height mm: 75 Marking according to Directive 2014/34/EU: II 1D/3D Ex h IIIC T80°C...T95°C Da/Db Certificate No.: FSA 12 ATEX 1630 X Max. explosion pressure MPa: 1.0 Max. operating temperature °C: 80 Actuating pressure MPa: 0.6 - 1.0 Max. operating pressure MPa: 0.045
ATEX DN350 knife slide pneumatic double acting 220V valve	
115396	
207-1432-10	
D11-3435	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.