



Jm Concept

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Jm Concept Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Jm Concept Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
GK3000D1	DIGITAL CONVERTER Settable with keyboards on front plate (22.5 mm width) Display 99999 Counts 2 Process inputs 4-20mA 2 AON input isolated of process input 4-20mA and supply. 1 isolated analogue output 4-20mA Input/output insulation 2500V Power supply 20Vdc to 370Vdc and 80Vac to 256Vac Delivered WITHOUT wiring base
XALIS 9000UO	UNIVERSAL INDICATOR FRONT FACE OR PC PROGRAMMATION - Alphanumerical two-coloured display - Front face programmable with 4 buttons - 1 USB plug on rear face for easy PC programming AVAILABLE INPUT - Process Input mV/V/mA - RTD input (Pt100/Pt1000...) - Potentiometre input - Thermocouple input - Resistor input
BL09DRV	
EOLIS0030A2	
EOLIS0030A2 (Isolator 2-2)	
JK 3303	
JK0030A1-F	
JK3000A-2I	
JK3002	

Ürün	Açıklama
JK3002-AA1	
TELIS 9200U2	
TELIS9000U1	
TELIS9150U1	
XALIS 9200U1	UNIVERSAL INDICATOR 1 255.00 255.00 FRONT FACE OR PC PROGRAMMATION - Alphanumerical two-coloured display - Front face programmable with 4 buttons - 1 USB plug on rear face for easy PC programming AVAILABLE INPUT - Process Input mV/V/mA - RTD input (Pt100/Pt1000...) - Potentiometre input - Thermocouple input - Resistor input - Sensor power supply AVAILABLE OUTPUTS - 1 digital output RS485 MODBUS - 2 Relays 1 C/O - 1 Analogue output current or voltage OTHER CHARACTERISTICS - Input / Outputs / Power supply insulation - Universal power supply : 20Vdc/370Vdc & 80Vac/256Vac - Case 48 x 96 mm with unpluggable terminals
ULCOS 920D2 (Sans option)	Universal input digital Transmitter, 2 analog outputs, 2 relays, with display, DIN Rail Mounting Box
TELIS 9150U1	
JK9200N2	
XALIS 9200U1 (Without option)	Universal input indicator, 1 analog output, 2 relays, RS485/USB, DUALCOLOR LCD display and USB rear side
AK3200 N1	DEBI INDICATOR
Jk3000a-2i	
Jk20a2	
BI02alv	
Telis 9200u2	

Ürün	Açıklama
Telis9000u1	
Jk6010a1	
Jk3000a2	
Eolis6000p2-Aek	
Jmconcept3400p	
Xalis 9400u1	
Jk7000a1	
Gk3000d1	DIGITAL CONVERTER Settable with keyboards on front plate (22.5 mm width) Display 99999 Counts 2 Process inputs 4-20mA 2 AON input isolated of process input 4-20mA and supply. 1 isolated analogue output 4-20mA Input/output insulation 2500V Power supply 20Vdc to 370Vdc and 80Vac to 256Vac Delivered WITHOUT wiring base
9000u2	
Jk2001	
Jk3000a2i	
Telis 9400u1	
Ulc920d2	UNIVERSAL TRANSMITTER FRONT FACE PROGRAMMATION - LCD graphic display - Programmation joystick AVAILABLE INPUTS - 1 universal input and 1 sensor supply AVAILABLE OUTPUTS - 2 Analogue output current or voltage - 2 Relays outputs 1 C/O OTHER CHARACTERISTICS - Triple Isolation Input / Outputs / Auxiliary supply : 2500Vac - Universal auxiliary supply 20Vdc/370Vdc & 80Vac/256Vac - 17.5mm width DIN RAIL mounted case with unpluggable terminals

Ürün	Açıklama
Telis 9400u2	
Xalis3400p1	
Telis 9000u2	
Jk3000a1	
Xal3400p1	
Jk2002	
BI02alv Wiring Base	
Telis 9250t0	
B25655-A2507-A000	
Jk 9400n2 Obsolete, Replaced By Telis9400u2+ BI02alv	
Xalis 9000u1	
Jk 9400n1 Obsolete, Replaced By Telis 9400u1+ BI02alv	
Xg2714	
BI01alv For Telis9000u1	
Xalis 9000u0	UNIVERSAL INDICATOR FRONT FACE OR PC PROGRAMMATION - Alphanumerical two-coloured display - Front face programmable with 4 buttons - 1 USB plug on rear face for easy PC programming AVAILABLE INPUT - Process Input mV/V/mA - RTD input (Pt100/Pt1000...) - Potentiometre input - Thermocouple input - Resistor input AVAILABLE OUTPUTS - 1 digital output RS485 MODBUS OTHER CHARACTERISTICS - Input / Outputs / Power supply insulation - Universal power supply : 20Vdc/370Vdc & 80Vac/256Vac - Case 48 x 96 mm with unpluggable terminals
Wk6000tu-Ann	

Ürün	Açıklama
Xalis1000u1	
Wk6000tu	
Jk3000a21	
Xalis 9200u1	
Jk0030a-1	
Bl01alv	WIRING BASE FOR ONE TRANSMITTER 22,5mm
Ulc0600v1	
Jk 3002	Please see attached Photo
Telis6020u1 Is No More Manufactured It Can Be Replaced With Ulc0600v1	
9250t0	
Ulc062010	