

## Joviatlas

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Joviatlas** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Joviatlas T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



### ¼r¼n

### A¼ıklama

[100000011858](#)

JOVYTEC PE NT 1000 B3 JOVYTEC PE NT 1000 B3 ON-LINE UPS, class VFI-SS-111 Autonomy time at 1kVA (cos.φ 0.7) approx. 8 minutes UPS system for supplying power to nautical equipment. Approved according to DNV/GL/BV. Desktop device with LCD display, LED indicator and built-in batteries Static bypass with seamless switching Standards: EN 62040, ISO 9001 Not classified as dangerous goods according to IATA including adapter cable for the potential-free signals Entrance Input voltage: 1x 230V, N, PE Voltage tolerance: -20% to +13% at 100% load Frequency: 45 - 65 Hz Power factor: > 0.98 cos φ at the input Input connection: Terminals Exit Output voltage: 1x 230V, N, PE Frequency: 50/60 Hz Power: 1000 VA cos φ 0.9 Output connection: Terminals Efficiency: approx. 89% Noise level: <45 dB(A) Overload capacity in online mode: 120% for 30 seconds 150% for 10 seconds Overload capacity in battery operation: 115% for 10 seconds 150% for 3 seconds Ambient temperature: UPS 0 - 40°C Battery 20 - 25 °C Communication: RS 232, USB, slot for I/O cards Mechanical properties Dimensions (W x H x D): 152 x 237 x 420 mm Colour: RAL 9005 Protection class: IP20 Weight (with battery): 18 kg Battery system Design: AGM technology, maintenance-free,

sealed Quality: EUROBAT 10-12 years Practice lifespan:  
approx. 6-8 years Internally installed batteries: 3 x 9Ah