Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Karl Deutsch

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Karl Deutsch Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Karl Deutsch Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Bestellnummer 3846.001	UV LED large area light incl. Power supply + cable 2.5 m UV light with 365 nm wavelength Intensity approx. 40 W / m² or 4000 µW / cm² at a distance of 400 mm, switchable to white light with approx. 2500 lx at a distance of 400 mm
Leptoskop 2042.001	nur die Sonde (Prob)
Part No. 1076.001	Wall Thickness Gauge ECHOMETER 1076 Basic for measuring wall thickness or sound velocity - Measuring range 0,5 - 400 mm steel (depending on selected probe (probe is not included in delivery range of instrument), crystal structure, shape and surface of the measured item) - Measuring range for sound velocity measurement: 100 - 19.999 m/sec. - Automatic recognition of probes - Adjustment possible even in case of unknown sound velocity (range 300 - 19999 m/s) Convenient user-guidance in easy to understand clear text - Variable display modes for optimum adaptation to the measurement task: - Standard display - Commercially available batteries size AA - Long battery lifetime rubber holster with pop-up stand - Splash-proof housing according to IP 54 - Sturdy and durable: Shock absorbing protective - Display-background illumination - Limit value indication with alarm mode - Difference value - Minimum value

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	included in delivery range: - Transporting case with foam insert - Instruction manual 100 ml couplant ECHOTRACE
Part No. 1099.110	Standard access. set for ECHOMETER 1076 consisting of: - TR-probe DSE 10.4/6 PB 4 incl. 1 m-cable, Lemo 00-male Measuring range (uncoated material): 1,2 - 250 mm -Handling sleeve for DSE 10.4/6 PB 4 and DSE 8.3/15 PB 5 C incl. retaining ring - Protective foil set (10 ea.) for wear protection
Part No. 1465.671	TR Probe DSE 4.2/4 PB 10, incl. 1 m cable, Lemo 00 Miniature probe for ECHOMETER 1076/1076 TC/1077 Measuring range (uncoated material): 0,5-25 mm
Part No. 1934.251	Grip sleeve f. (D)SE 4.2/4 PBx incl. retaining ring for miniature probe
3846.001	UV LED Large Area Lamp incl. power supply + cable 2.5 m UV-A radiation at 365 nm wavelength Intensity at 400 mm distance: approx. 40 W/m² resp. 4000 µW/cm², switchable to white light with approx. 2500 lx at 400 mm distance
Part No. 1076.001	(Neues Model wenn verfügbar)A) without data storage: Wall Thickness Gauge ECHOMETER 1076 Basic for measuring wall thickness or sound velocity - Measuring range 0,5 - 400 mm steel (depending on selected probe (probe is not included in delivery range of instrument), crystal structure, shape and surface of the measured item) - Measuring range for sound velocity measurement: - 100 - 19.999 m/sec. - Automatic recognition of probes - Adjustment possible even in case of unknown sound velocity (range 300 - 19999 m/s) - Convenient user-guidance in easy to understand clear text - Variable display modes for optimum adaptation to the measurement task: - Standard display - Difference value - Minimum value - Display-background illumination

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	- Limit value indication with alarm mode - Adaptation of sensitivity to the sound damping of different materials - Units switchable mm/inch, resolution can be switched (0,1 resp. 0,01) - Sturdy and durable: Shock absorbing protective rubber holster with pop-up stand - Splash-proof housing according to IP 54 - Commercially available batteries size AA - Long battery lifetime included in delivery range: - Transporting case with foam insert - Instruction manual - 100 ml couplant ECHOTRACE
Part No. 1076.002	B) Alternatively with data storage: Wall Thickness Gauge ECHOMETER 1076 Data for measuring wall thickness or sound velocity Measuring range 0,5 - 400 mm steel (depending on selected probe (probe is not included in delivery range of instrument), crystal structure, shape and surface of the item measured) - Automatic recognition of probes - Adjustment possible even in case of unknown sound velocity (range 300 - 19999 m/s) - Convenient user-guidance in easy to understand clear text - Variable display modes for optimum adaptation to the measurement task: - Standard display - Difference values - Minimum value - Limit value indication with alarm mode - Display-background illumination - Windows-like storage of readings with convenient file management: Folders and files with alpha-numeric designation - Individual memorization of calibration in the associated files - Facilities of storage: up to 9999 results, organized in result files with up to 999 results each - Graphic representation of the course of readings and quick navigation through the individual readings - Data output to printer and/or PC - Adaptation of sensitivity to the sound damping of different materials - Units switchable mm/inch, resolution can be switched (0,1 resp. 0,01)

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	- Sturdy and durable: Shock absorbing protective rubber holster with pop-up stand - Splash-proof housing according to IP 54 - Batteries in standard size AA - Long battery lifetime included in delivery range: - Transport case with foam insert - Instruction manual - 100 ml couplant ECHOTRACE
Part No. 1099.110 (Probe alternatives)	Standard access. set for ECHOMETER 1076 consisting of: - TR-probe DSE 10.4/6 PB 4 incl. 1 m-cable, Lemo 00-male Measuring range (uncoated material): 1,2 - 250 mm - Handling sleeve for DSE 10.4/6 PB 4 and DSE 8.3/15 PB 5 C incl. retaining ring - Protective foil set (10 ea.) for wear protection
Part No. 1465.671	TR Probe DSE 4.2/4 PB 10, incl. 1 m cable, Lemo 00 Miniature probe for ECHOMETER 1076/1076 TC/1077 Measuring range (uncoated material): 0,5-25 mm
Part No. 1465.361	TR Probe DSE 18/25 PB 2, incl. 1 m cable, Lemo 00 Low frequency probe for ECHOMETER 1075/1076/ 1076 TC Measuring range (uncoated material): 5 - 400 mm
Part No. 1934.201	Grip sleeve f. DSE 18/25 PBx for use w/ protective foils for low frequency probe incl. retaining ring
Part No. 1930.004	Set of protective foils, 10 pcs. for DSE 18/25 PB x Options for ECHOMETER 1076 Data:
Part No. 1657.308	PC and printer cable for ECHOMETER
Part No. 2906.001	PC software "iCom" f. data admin. Win XP/7/8/8.1/10 System Software: Windows 2000/XP (from SP3 on) Windows Vista, Windows 7, Windows 8/8.1/10 (Operation also possible with 64-Bit-version)
Part No. 2905.001	EasyExport, PC Software for Windows XP/2000/Vista/7/8.1/10 (32/64) Possibly necessary accessories for instruments with data cable and software in case the PC has no serial input:

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Part No. 2691.001	Adapter USB (PC) -> RS232 including driver CD
Part No. 1077.020	Wall Thickness Gauge A-Scan ECHOMETER 1077 Data for ultrasonic high precision wall thickness measurement - Measuring range of the instrument 0,25 - 400 mm steel. Range varies depends upon connected probe (probe is not included in delivery range of instrument), measuring mode (evaluation of transmitter pulse - back wall, back wall - back wall) and material properties. - Function for automatic adjustment of parameters depending upon the connected probe, after which it is ready to measure. - High resolution colour display with 320 x 240 Px - Automatic Gain Control (AGC) - Automatic Time Corrected Gain (Auto-TCG) - Variable display modes for optimum adaption to the testing task. Value display with or without A-Scan - Three function keys, depending upon the display mode free programmable or assigned to fixed parameters - Five different measuring units selectable (mm, inch, m/s, inch/µs, µs) - Variable resolutions selectable (e.g. 0,1mm / 0,01mm / 0,001mm) - Measuring range for sound velocity measurement: 100 - 19.999 m/s - Five different display modes for the measured value: direct value, mean value, minimum, difference, relative - Different possibilities for echo evaluation are selectable: polarity, TP-BE, BE-BE - Convenient user-guidance in easily to understand clear text, several languages - Storage of 20 different configurations - Configuration for standard applications undeletable stored - Storage capacity: 5 files, each for up to 999 measured values - Data transfer of single measurement values or values out of data files by means of the special software EasyExport (must be ordered separately) - Robust and durable: shock absorbing protective rubber holster with pop-up stand - Splash-proof housing according to IP 54 - Batteries in standard size AA included in the scope of delivery: - Transport case with foam insert - Instruction manual

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	- 100 ml couplant ECHOTRACE
Part No. 1422.701	Contact probe DS6 PB4-14 incl. 10 mm delay line, Microdot ceramic transducer diameter: 6 mm frequency range: 4 - 14 MHz Recommended measuring range: approx. 1,0 mm up to 20 mm in SI-RE mode for ECHOMETER 1077 Recommended measuring range: approx. 0,25 mm up to 10 mm in RE-RE mode for ECHOMETER 1077
Part No. 1422.703	Contact probe, S 12 PB 1-7, 25 mm delay line, Lemo 00 Broad band probe with exchangeable delay line length of delay line: 25 mm ceramic transducer diameter: 12 mm frequency range: 1 - 7 MHz Recommended measuring range: approx. 1,5 mm up to 50 mm in SI-RE mode for ECHOMETER 1077 Recommended measuring range: approx. 1,0 mm up to 25 mm in RE-RE mode for ECHOMETER 1077
Part No. 1432.701	Contact probe DS 6 HB 4-12 Microdot with wear-resistant protective layer ceramic transducer diameter: 6 mm frequency range: 4 - 12 MHz Recommended measuring range: approx. 1,0 mm up to 450 mm in SI-RE mode for ECHOMETER 1077 Recommended measuring range: approx. 1,0 mm up to 100 mm in RE-RE mode for ECHOMETER 1077
Part No. 1433.705	Contact probe DS 12 HB 2-7 Microdot with wear-resistant protective layer Ceramic transducer diameter: 12 mm Frequency range: 2 - 7 MHz Recommended measuring range: approx. 2,0 mm up to 450 mm in SI-RE mode for ECHOMETER 1077 Recommended measuring range: approx. 2,0 mm up to 225 mm in RE-RE mode for ECHOMETER 1077
Part No. 1616.010	Probe cable, length 1 m, Lemo 00 / Lemo 00
Part No. 1618.010	Probe cable, length 1 m, Lemo 00 / Microdot
Part No. 1657.314	PC cable for ECHOMETER 1077 -> USB (incl. drivers CD)

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Part No. 2905.001	EasyExport, PC Software for Windows XP/2000/Vista/7/8.1/10 (32/64)
Part No. 1713.003	Stepped ref. block 4-7-15 mm (steel), can not be certified
Pocket-LEPTOSKOP 2021 Fe	Part No. 2021.901 package consisting of: Pocket-LEPTOSKOP 2021 Fe, Measuring range: 0-3.000 µm/ 120 mil Test block Fe Calibration foil (2 pcs.)
Pocket-LEPTOSKOP 2026 Fe/NFe	Part No. 2026.901 package consisting of: Pocket-LEPTOSKOP 2026 Fe, Measuring range: 0-3.000 µm/ 120 mil Pocket-LEPTOSKOP 2026 NFe, Measuring range: 0-1.200 µm/48 mil Test block Fe Test block NFe Calibration foil (2 pcs.)
ECHOMETER 1077.080-A	
1076.001	Wall Thickness Gauge ECHOMETER 1076 Basic Wall Thickness Gauge ECHOMETER 1076 Basic for measuring wall thickness or sound velocity - Measuring range 0,5 - 400 mm steel (depending on selected probe (probe is not included in delivery range of instrument), crystal structure, shape and surface of the measured item) - Measuring range for sound velocity measurement: - 100 - 19.999 m/sec. - Automatic recognition of probes - Adjustment possible even in case of unknown sound velocity (range 300 - 19999 m/s) - Convenient user-guidance in easy to understand clear text - Variable display modes for optimum adaptation to the measurement task: - Standard display - Difference value - Minimum value - Display-background illumination - Limit value indication with alarm mode - Adaptation of sensitivity to the sound damping of different materials

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	- Units switchable mm/inch, resolution can be switched (0,1 resp. 0,01) - Sturdy and durable: Shock absorbing protective rubber holster with pop-up stand - Splash-proof housing according to IP 54 - Commercially available batteries size AA - Long battery lifetime included in delivery range: - Transporting case with foam insert - Instruction manual - 100 ml couplant ECHOTRACE
2042.902	LEPTOSKOP 2042 NFe basic package, consisting of: LEPTOSCOPE 2042 Probe NFe 0° measuring range: 0-1,000 µm control body NFe calibration foil set
1076.902	Wall thickness gauge ECHOMETER 1076 data package consisting of: Wall thickness gauge ECHOMETER 1076 for measuring the wall thickness or the Speed of sound - Measuring range 0.5 - 400 mm steel (depending on selected test head (test head not in Included in delivery of the device), structure, shape and surface of the measurement object) - Automatic test head detection - Adjustment even if unknown Speed of sound (range 300-19999 m/s) - Convenient user guidance in an understandable way Plain text - Variable display modes for optimal adjustment the measurement task - Standard display - Difference value - Minimum value - Limit display with alarm mode - Display backlight - Storage of measured values with uncomplicated File management like under Windows Directories and files with alphanumeric designation - Individual storage of the calibration in the individual files - Storage options: up to 9999 measured values, Can be organized into measurement files with up to each to 999 readings - Graphical representation of the measured value progression and quick navigation within

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	the individual measured values - Data output to printer and/or PC - Sensitivity adjustment to sound attenuation different materials - Unit switchable mm/inch, resolution switchable (0.1 or 0.01) - Robust and durable: more shock-absorbing Rubber protective frame with stand bracket
1099.110	Standard accessory set for ECHOMETER 1076 consisting of: - SE test head DSE 10.4/6 PB4 Includes 1 m cable, Lemo 00 plug Measuring range (uncoated material): 1.2 - 250mm - Grip sleeve for DSE 10.4/6 PB 4 and DSE 8.3/15 PB 5 C including retaining ring - Protective film set (10 pieces) as wear protection
1465.671	SE test head DSE 4.2/4 PB 10, incl. 1 m cable, Lemo 00 Miniature test head for ECHOMETER 1076/1076 TC/1077 Measuring range (uncoated material): 0.5-25mm
2091.001	LEPTO-Pen (measurement range: 10-500 µm)
A) without data storage:	Order number 1076.001 wall thickness gauge ECHOMETER 1076 Basic for measuring the wall thickness or the speed of sound - Measuring range 0.5 - 400 mm steel (depending on selected probe (probe not in the included in the scope of delivery of the device), of structure, shape and surface of the measuring object) - Measuring range for sound speed measurement: - 100 - 19,999 m/sec. - Automatic probe recognition - Adjustment even with unknown speed of sound (range 300 - 19999 m/s) - Comfortable user guidance in understandable plain text - Variable display modes for optimal adaptation to the measurement task - Standard display - difference value - minimum value - Display backlight - Limit value display with alarm mode - Sensitivity adjustment to the Sound attenuation of different materials - Unit switchable mm/inch, resolution

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	switchable (0.1 or 0.01) - Robust and durable: shock-absorbing rubber protective frame with stand - Splash-proof housing according to IP 54 - Long battery life included in delivery: - Transport case with foam molding - Operating instructions - 100 ml couplant ECHOTRACE
B) Alternative with data storage:	Order number 1076.902 Wall thickness gauge ECHOMETER 1076 Data package consisting of: wall thickness gauge ECHOMETER 1076 for measuring the wall thickness or the speed of sound - Measuring range 0.5 - 400 mm steel (depending on selected probe (probe not in the included in the scope of delivery of the device), of structure, shape and surface of the measuring object) - Automatic probe recognition - Adjustment even with unknown
1099.110-	probe alternatives Standard accessory kit for ECHOMETER 1076 consisting of: - SE test head DSE 10.4/6 PB4 including 1 m cable, Lemo 00 connector Measuring range (uncoated material): 1.2 - 250 mm - Handle sleeve for DSE 10.4/6 PB 4 and DSE 8.3/15 PB 5 C including retaining ring - Protective film set (10 pieces) as wear protection
Echometer 1076 UT	
ECHOMETER 1076 K Data package	Order number 1076.912 consisting of: ECHOMETER 1076K (1076.012) RS232 interface for measured value output PC and printer cable 1657.308 Probe for concentration measurement (1498.023) AA batteries, 2 pieces CD with PC utility program (1994.001) for documentation (under Windows) (to install 2000/XP/Windows 7) Temperature measuring device "Checktemp" (6025.001) ml distilled water for basic adjustment 100 ml beakers ‡ Operating instructions
3821.002	Remaining field indicator

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	with quality test certificate
1657.308 Pc- U Druckerkabel Für Echometer Mit Rs232	
4418 001	
760500 350	
4416.001	
6015.001	
1095.020 Echograph 1095 Basic	
610.201,Mobile Thermal Printer	
1090 Obsolete, Replacement 1095 Echograph	
1465.361 Se-Prüfkopf Dse 18/25 Pb 2, Inkl 1 M Kabel, Lemo 00	
4015.003	
1075 005	
4417.001	
Griffhulse Fur Dse 10.4/6 Pb 4 Und Dse 8.3/15 Pb 5 C	
3865.004 Magnetpulver-Prufset	
6016.001	
1076.002	
9903.1	
760500 300	
1099.110 (1465.762) Normalzubehörsatz Für Echometer 1076, Standard-Prüfkopf Dse 104/6 P	
49-6800-2026	
2026.01	
1095.030 Echograph 1095 Dac/Tcg/Aws	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
1090.201	
496800 2026	
1099.109	
1075.005	
2042.300,Fe Probe With Cable	
1076.001	
2042.924,2042 Leptoskop Combined Fe / Nfe Data Set	
2042	
1095.040 Echograph 1095 Dgs/Dac/Tcg	
Bestellnummer 1465.761	SE test head DSE 10.4 / 6 PB 4, incl. 1 m cable, Lemo 00 Measuring range: 1.2 - 250 mm for ECHOMETER 1073/1074/1075
1075b	
Dpp-04	
4825.001	
4015 003	
4498.010	
Echometer 1076	
4720.002	
Check Sd-1 9903-14	
2806.001	
Ts12wb6	
1465.751 / Dse 10.4/6 Pb 4	
Piastrina 46.8	
4815.001	
ECHOMETER 1076 Data	Order number 1076.002 Wall Thickness Gauge ECHOMETER 1076 Data

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	for measuring the wall thickness or the speed of sound - Measuring range 0.5 - 400 mm steel (depending on selected probe (probe not in included in the scope of delivery of the device), of structure, shape and surface of the measuring object) - Automatic probe recognition - Adjustment also with unknown Speed of Sound (Range 300-19999 m/s) - Comfortable user guidance in understandable plain text - Variable display modes for optimal adaptation to the measurement task - Standard display - difference value - Minimum value - Limit value display with alarm mode - Display backlight - Measured value storage with uncomplicated File management like under Windows Directories and files with alphanumeric designation - Individual storage of the calibration in the individual files - Storage options: up to 9999 readings, can be organized in measured value files each with up to to 999 readings - Graphic display of the course of measured values and quick navigation within of the individual readings - Data output to printer and/or PC - Sensitivity adjustment to the sound attenuation different materials - Unit switchable mm/inch, resolution switchable (0.1 or 0.01) - Sturdy and Durable: More shock absorbing Rubber protective frame with stand - Splash-proof housing according to IP 54 - Commercially available batteries and rechargeable batteries - Long battery life included: - Transport case with molded foam part - Operating manual - 100 ml of ECHOTRACE couplant Probe alternatives:
3873.901	DEUTROMETER set for field strength measurement, consisting of - Field strength meter DEUTROMETER 3873 including batteries and carrying case ‡ For connecting field strength probes to Measurement of magnetic alternating and

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Equal fields ‡ Automatic detection of alternating fields and Equipotential field ‡ Unit of measurement switchable: mT, A/cm, kA/m, Gauss ‡ Measuring range 0 ± kA/m or 0 ± Gauss or 0 ± mT ‡ Measurement display in large digits with additional maximum value memory ‡ User-friendly menu navigation in an easy-to-understand format plain text ‡ Visual and audible threshold alarm ‡ Battery-saving display lighting ‡ Fluorescent lettering under UV light ‡ Splash-proof housing (IP 54) Order No. 3873.001 - Field strength probe for DEUTROMETER 3873 angled 90° including connection cable Order No. 3873.101 also available as a straight probe - Reference magnet for DEUTROMETER field strength probes Order No. 3872.601
Check Pr-2 9907-14	
4420.001	
1095.050 Echograph 1095 Dgs/Dac/Tcg/ Aws/Jis	
1465.671	
2042.310,Nfe Probe With Cable	
4498 010	
Order Number 2026.901	Pocket LEPTOSKOP 2026 Fe / NFe Package consisting of: Pocket LEPTOSCOPE 2026 Fe measuring range: 0-3,000 µm / 120 mil NFe measuring range 0-1,200 µm / 48 mil Control body Fe Control body NFe Calibration foils (2 pieces)
1076.002 Wanddickenmessgerät Echometer 1076 Data	
4815.002	
4820.001	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
1076.912	
1099 109	
Ts 6 Wb 4	
Adapter Usb (Pc) -Gt; Rs232 Inkl. Treiber-Cd	
1465.751	
610.202,Paper Roll	
4816.001	
1095	
10143 Sheet Thickness Measuring Device	
4418.001	
S12hb1-8	
Echometer 1075 Basic	
2042 Leptoskop	
1465.671 Se-Prüfkopf Dse 42/4 Pb 10, Inkl 1 M Kabel, Lemo 00	
1657.704 Usb-Cable For Echograph 1095	
Dpp 04	
Check Rdp-1 9901-14	
V1076.902	ECHOMETER 1076 Wall Thickness Gauge Data Package Set "ECHOMETER 1076 Wall Thickness Gauge for measuring wall thickness or sound velocity - Measuring range 0.5 - 400 mm steel (depending on the selected probe (probe not included in the device's scope of delivery), microstructure, shape, and surface of the object being measured) - Automatic probe detection - Adjustment even with unknown sound velocity (range 300-19999 m/s) - User-friendly interface with clear

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	plain text - Variable display modes for optimal adaptation to the measurement task - Standard display - Differential value - Minimum value - Limit value display with alarm mode - Display backlight - Data storage with straightforward file management similar to Windows directories and files with alphanumeric naming - Individual saving of calibration in each file - Storage capacity: up to 9999 data points, organizable in measurement files with up to 999 measurements each - Graphical display of the measurement trend and quick navigation within individual measurements - Data output to printer and/or PC - Sensitivity adjustment to the sound attenuation of different materials - Unit switchable mm/inch, resolution switchable (0.1 or 0.01) - Robust and durable: Shock-absorbing rubber protective frame with stand - Splash-proof housing according to IP 54 - Standard batteries and rechargeable batteries - Long battery life Included in delivery: - Carrying case with molded foam insert - Operating instructions - 100 ml couplant ECHOTRACE PC cable for ECHOMETER 1076 ->USB (incl. driver CD) PC software "iCom"" for data management Win XP/7/8/8.1/10/11
V1465.762	SE probe DSE 10.4/6 PB 4, incl. 1 m cable, Lemo 00
A1934.151	Handle sleeve for DSE 10.4/6 PB 4 and DSE 8.3/15 PB 5 C
A1930.006	Protective film set (10 pieces) for DSE10, S12W, SE10/, SE8/
A1465.671	SE probe DSE 4.2/4 PB 10 incl. 1 m cable, Lemo 00

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Miniature probe for ECHOMETER 1076/1076 TC/1077 SE probe with 10 MHz test frequency Measuring range (uncoated material): 0.5-25 mm steel
A1934.251	Handle sleeve for (D)SE 4.2/4 PBx
A1465.361	SE probe DSE 18/25 PB 2 incl. 1 m cable, Lemo 00 Low-frequency probe for ECHOMETER1075/1076/1076 TC SE probe with 2 MHz test frequency Measuring range (uncoated material): 5 - 400 mm steel
A1934.201	Handle sleeve for DSE 18/25 PBx for use with protective films for low-frequency probe incl. retaining ring
A1930.004	Protective film set (10 pieces) for DSE 18/25 PB x diameter 32 mm

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.