

Karl Georg

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin **info@yursat.com.tr** e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.
Karl Georg Markası, tedarik sresi iin ltfen bizimle iletiřime geiniz.

Firmamız Karl Georg Trkiye Distribtr veya temsilcisi deęildir. Firmamız sipariř durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
2110.0078	
2320.0024	
2320.0025	
2320.0028	
2320.0029	
4662.0000	
6401.0000	
6401.0001	
6401.0003	
640101	
640131	
6402.0000	

6413.0000	
6201.0002	Wheel block RBA 160 x 60, driveable Size RB 160 Drive type can be driven Shaft-hub connection cone Tread diameter [mm] 160 Track width [mm] 60 Form 1 - wheel flange on both sides Impeller width [mm] 87 Wheel flange diameter [mm] 190 Bearing type spherical roller bearing 222 10 Type of seal: double-sided sealing washers made of POM Grease Multifak EP2 (Texaco) Temperature range [°C] -30 to +90 Impeller material EN-GJS-700-2 Painting the impeller side surfaces, inside and outside surfaces of the housing red-brown Primed paint (standard) Preservation processed surfaces preserved with Tectyl
6201.0003	Wheel block RBA 160 x 87, driveable Size RB 160 Drive type can be driven Shaft-hub connection cone Tread diameter [mm] 160 Track width [mm] 87 Form 4 - without wheel flanges Impeller width [mm] 87 Bearing type spherical roller bearing 222 10 Type of seal: double-sided sealing washers made of POM Grease Multifak EP2 (Texaco) Temperature range [°C] -30 to +90 Impeller material EN-GJS-700-2 Painting the impeller side surfaces, inside and outside surfaces of the housing red-brown primed (standard) Preservation processed surfaces preserved with Tectyl
6202.0002	Wheel block RBN 160 x 60, not drivable Size RB 160 Drive type cannot be driven Tread diameter [mm] 160 Track width [mm] 60 Form 1 - wheel flange on both sides Impeller width [mm] 87 Wheel flange diameter [mm] 190 Bearing type spherical roller bearing 222 10 Type of seal: double-sided sealing washers made of POM Grease Multifak EP2 (Texaco) Temperature range [°C] -30 to +90 Impeller material EN-GJS-700-2 Painting the impeller side surfaces, inside and outside surfaces of the housing red-brown primed (standard) Preservation processed surfaces preserved with Tectyl
6202.0003	Wheel block RBN 160 x 87, not driveable Size RB 160 Drive type cannot be driven Tread diameter [mm] 160 Track width [mm] 87 Form 4 - without wheel flanges Impeller width [mm] 87 Bearing type spherical roller bearing 222 10 Type of seal: double-sided sealing washers made of POM Grease Multifak EP2 (Texaco) Temperature range [°C] -30 to +90 Impeller material EN-GJS-700-2 Painting the impeller side surfaces, inside and outside surfaces of the housing red-brown primed (standard) Preservation processed surfaces preserved with Tectyl