

Karl Georg

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Karl Georg Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Karl Georg Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
2110.0078	
2320.0024	
2320.0025	
2320.0028	
2320.0029	
4662.0000	
6401.0000	
6401.0001	
6401.0003	
640101	
640131	
6402.0000	
6413.0000	
6201.0002	Wheel block RBA 160 x 60, driveable Size RB 160 Drive type can be driven Shaft-hub connection cone Tread diameter [mm] 160 Track width [mm] 60 Form 1 - wheel flange on both sides Impeller width [mm] 87 Wheel flange diameter [mm] 190 Bearing type spherical roller bearing 222 10 Type of seal: double-sided sealing washers made of POM

Ürün	Açıklama
	Grease Multifak EP2 (Texaco) Temperature range [°C] -30 to +90 Impeller material EN-GJS-700-2 Painting the impeller side surfaces, inside and outside surfaces of the housing red-brown Primed paint (standard) Preservation processed surfaces preserved with Tectyl
6201.0003	Wheel block RBA 160 x 87, driveable Size RB 160 Drive type can be driven Shaft-hub connection cone Tread diameter [mm] 160 Track width [mm] 87 Form 4 - without wheel flanges Impeller width [mm] 87 Bearing type spherical roller bearing 222 10 Type of seal: double-sided sealing washers made of POM Grease Multifak EP2 (Texaco) Temperature range [°C] -30 to +90 Impeller material EN-GJS-700-2 Painting the impeller side surfaces, inside and outside surfaces of the housing red-brown primed (standard) Preservation processed surfaces preserved with Tectyl
6202.0002	Wheel block RBN 160 x 60, not drivable Size RB 160 Drive type cannot be driven Tread diameter [mm] 160 Track width [mm] 60 Form 1 - wheel flange on both sides Impeller width [mm] 87 Wheel flange diameter [mm] 190 Bearing type spherical roller bearing 222 10 Type of seal: double-sided sealing washers made of POM Grease Multifak EP2 (Texaco) Temperature range [°C] -30 to +90 Impeller material EN-GJS-700-2 Painting the impeller side surfaces, inside and outside surfaces of the housing red-brown primed (standard) Preservation processed surfaces preserved with Tectyl
6202.0003	Wheel block RBN 160 x 87, not driveable Size RB 160 Drive type cannot be driven Tread diameter [mm] 160

Ürün	Açıklama
	Track width [mm] 87 Form 4 - without wheel flanges Impeller width [mm] 87 Bearing type spherical roller bearing 222 10 Type of seal: double-sided sealing washers made of POM Grease Multifak EP2 (Texaco) Temperature range [°C] -30 to +90 Impeller material EN-GJS-700-2 Painting the impeller side surfaces, inside and outside surfaces of the housing red-brown primed (standard) Preservation processed surfaces preserved with Tectyl