Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Kbr

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Kbr Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Kbr Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Kbr	
Kbr	
Kbr	
Kbr	
2-LED-ESMS-2RO1DO-US5	multimess F144 Panel mount power meter, LED display Version: 2-LED-ESMS-2RO1DO-US5 Dimensions: HxWxD 144mm x 144mm x 60mm Power supply Us: 22.5-64 V +/-10% AC/DC, 50/60 Hz, 15 VA Measuring voltage Um: 3 x 5...600 V AC, measuring current Im: 4 x 0.01...6 A AC Interface(s): KBR eBus RS485, Modbus RS485 Load profile storage for 366 days 1 synchronous, 1 tariff switching input 2 signaling relays, 1 work pulse output S0 Degree of protection: front IP 40 / insulation class I Software requirement for integration into "visual energy 4" is the SW version 4.7 Release 1
23426	multimess F96 Mains measuring instrument for panel mounting, TFT display Colors can be freely adjusted by the user Version: 2-TFT-ESMS-2RO1DO-US1 Dimensions: HxWxD 96 mm x 96 mm x 67 mm Power supply Us: 100-240 V +/-10% AC/DC, 50/60 Hz, 8 VA Measuring voltage Um: 3 x 5...600 V AC, measuring current Im: 3 x 0.01...6 A AC Interface(s): KBR eBus RS485, Modbus RS485 Load profile storage for 366 days 2 signal relays, 1 working pulse output S0 Protection class: Front IP 40 / SK I Software requirement for integration into “visual energy” is SW version 4.7 Release 1

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
UHPC-33.4-480-3P	10371 multicond-premium Three-phase power capacitor in SF6-free dry technology Capacitor rated voltage: 480 V Capacitor nominal frequency: 50/60 Hz Power: 23.2 kvar at 400 V / 50 Hz Power: 33.4 kvar at 480 V / 50 Hz Capacity: 3 x 153.82 µF Current carrying capacity: 2.0 x In Protection class: IP 20 with discharge resistor Dimensions: H x D 246.5 mm x 136 mm plus grounding bolt M12. l=16.5 mm Life expectancy at temperature class: D (-40/55 °C) > 250,000 h
10368	multicond premium UHPC-25.0-480-3P Three-phase power capacitor in SF6-free dry technology Capacitor rated voltage: 480 V Capacitor rated frequency: 50/60 Hz Power: 17.4 kvar at 400 V / 50 Hz Power: 25.0 kvar at 480 V / 50 Hz Capacity: 3 x 115.1 µF Current carrying capacity: 2.0 x In Protection class: IP 20 with discharge resistor Dimensions: H x D 246.5 mm x 116 mm plus grounding bolt M12. l=16.5 mm Life expectancy at temperature class: D (-40/55 °C) > 250,000 h
21425	multicond premium UHPC-20.8-480-3P Three-phase power capacitor in SF6-free dry technology Capacitor rated voltage: 480 V Capacitor rated frequency: 50/60 Hz Power: 14.4 kvar at 400 V / 50 Hz Power: 20.8 kvar at 480 V / 50 Hz Capacity: 3 x 95.8 µF Current carrying capacity: 2.0 x In Protection class: IP 20 with discharge resistor Dimensions: H x D 246.5 mm x 116 mm plus grounding bolt M12. l=16.5 mm Life expectancy at temperature class: D (-40/55 °C) > 250,000 h
10365	multicond premium UHPC-16.7-480-3P Three-phase power capacitor in SF6-free dry technology Capacitor rated voltage: 480 V Capacitor rated frequency: 50/60 Hz Power: 11.6 kvar at 400 V / 50 Hz Power: 16.7 kvar at 480 V / 50 Hz Capacity: 3 x 76.9 µF Current carrying capacity: 2.0 x In Protection class: IP 20

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	with discharge resistor Dimensions: H x D 246.5 mm x 116 mm plus grounding bolt M12. l=16.5 mm Life expectancy at temperature class: D (-40/55 °C) > 250,000 h
14181	
D2-4ai	
14193	
Multimess F144	23657 Network instrument for panel mounting, LED display Version: 2-LED-ESMSDP-2RO1DO-US1 Dimensions: HxWxD 144 mm x 144 mm x 60 mm Power supply Us: 100-240 V +/- 10% AC / DC, 50/60 Hz, 18 VA Measuring voltage Um: 3 x 5 ... 600 V AC, measuring current Im: 4 x 0.01 ... 6 A AC Interface (s): KBR eBus RS485, Modbus RS485, Profibus DP Load profile storage for 366 days 1 synchronous, 1 tariff switching input 2 signaling relays, 1 working impulse output S0 Type of protection: Front IP 51 / SK I Customs tariff number: 90303200 Country of origin: Germany Total weight: 0.7 kg
4401006	
14206	
Uhpc-25-525-3p	
4f144-1-Led-Esms-Us1/-Us5	
Thyroswitch 2ph-400-50-115	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.