Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Kimo

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Kimo Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Kimo Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
LEKTROMIK 11S2-27	including I2 option 11/15 kW, 110-500 V, 26/40 A, - / B Soft starter and stop device with adjustable voltage ramp Art.-No .: 8083.321 / 27
Option 4.7MF	Capacitor 4.7 µF Ramp extension Item no .: 8360.001
OPTION Z	Einbau der Optionen Art.-Nr.: 8360.000
MPR 10000 MODELL DRUCKMODUL FÜR MP210 GERÄT	
MT 40 MMH2O	Inclined tube manometer Measuring range: 0 - 40 mmH2O including measuring liquid, blue (density = 1.86) Case and 1 m hose Item no .: 56-10549
GP 500-1	KIMO pressure calibrator for mobile calibration of pressure sensors Pressure range: -2500 ... +2500 Pa with pressure sensor for pos. and negative pressure Very high accuracy with PC interface and evaluation software Included in the delivery are... - 2 x 1m silicone hose - Cable for power supply - USB cable and evaluation software - Operating instructions (English) - Calibration certificate Item No.: 56-24485
C 310-BO mit Display	Multifunction transmitter Art.-Nr.: 56-24410

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	which adapts to your measurement requirements. Optional are several measurements simultaneously with the correspond to probes and modules such as e.g. differential pressure, air velocity, volume flow, rel. Humidity, dew point, temperature, CO2, CO and (barometric air pressure) possible. Likewise, the pressure signal with the SQR/3 function (optional) the air speed, the flow rate is shown on the display and as analogue signal can be further processed. Technical specifications: Voltage supply: 24 V AC / DC Analog outputs: 2 x 0/4-20 mA or 2 x 0/5-10V (Optional: 4 x 0/4-20 mA or 4 x 0/5-10V) Relay outputs: 4 x changeover contacts 5A / 230V (optional) interchangeable Pressure modules including temperature input (+/- 100Pa, 500Pa, 1000Pa, 10,000Pa optional) Optional: Interface for RS485 Modbus-RTU protocol and Ethernet networks. Please note when ordering the Ethernet interface cannot be retrofitted. Housing: IP 65 ABS housing with stainless steel front incl. 4 x 2 colored LEDs and acoustic alarm Operating temperature: -10..to + 50°C All transmitter settings can be carried out using the keypad on the device or (optionally) via the parameterization software LCC-S quickly and easily from your laptop. Delivery: with wall bracket and adjustment certificate
SPI2-100	Replaceable differential pressure module including temperature input for C310 transmitter Art.-Nr.: 56-24414 The module has a separate temperature input (type K) (Temperature compensation possible) No zero point drift thanks to automatic zero point adjustment, that ensures good long-term stability. Measuring ranges: Pressure: +/- 100 Pa (other measuring ranges available) Resolution: 1 Pa High resolution option with 0.1 Pa Type: HRP Accuracy: ± 0.2% Temperature: -200 ... 1300°C (depending on the probe)
Flow function / SQR/3 unlock code	for differential pressure transmitters of the 210 / 310 series This function allows the measured Pressure signal as volume flow and air speed is shown in the display.

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	In addition, the analog output signals / relay functions, are used for this function. Item no.: 56-24105
TPL-06-800-T	Pitot tube, stainless steel To measure: pressure, air velocity, volume flow, temperature heat-resistant up to +600°C (optional up to 1000°C) with integrated Thermocouple for simultaneous Temperature measurement (compensation) type K Diameter: 6 mm / NL: 800 mm Delivery incl. 1.5 m cable for thermocouple (suitable hose 5mm inside)
CP112-AN	differential pressure transmitter Type: CP112-AN without display Measuring range: -1000...+1000 Pa (intermediate ranges adjustable) Power supply: 24 VAC/DC active output: 0 - 10 V and 4 - 20 mA (3-4 wire) Accuracy: ± 1.5% of meas. ± 3 Pa Interface: USB mini DIN cable Housing: ABS, IP 65 (Optional: parameterisation software LCC-S) Weight: about 150g Item no.: 56-23907
CP212-BO-R	Differential pressure transmitter Type: CP212-BO-R with display Pressure measuring range: -1000 / +1000 Pa (Optionally, the measured pressure signal can also be as air velocity and/or as volume flow be output with the SQR/3 function) Temperature input: Pt100 from -100 to +400°C Autozero: By key or autom. with solenoid valve Accuracy: +/- 0.5% of reading Power supply: 24V AC/DC 2 analogue outputs: 0-10 V or 4-20 mA / 0-20 mA 2 relay outputs PC interface: USB mini DIN Housing: ABS, IP 65 Weight: about 340g Country of origin: France Part.-Nr.: 56-25636
CP112-AO	Measuring range: -1000...+1000 Pa (Intermediate ranges adjustable) Power supply: 24 VAC/DC

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Active output: 0-10 V and 4-20 mA (3-4 wire) Accuracy: ± 1.5% of reading, ± 3 Pa Interface: USB-mini DIN cable Housing: ABS, IP 65 Optional: LCC-S parameterization software (it can) Any desired measuring range can be set. Weight: approx. 150 g
Temperature and humidity transmitter	Model: TH210-BODI/150-R with display remote stainless steel probe, Sensor length: 150mm / diameter 13mm Cable length 1.9 m (other lengths available) (Optional sensor mounting clamps Duct Mount: BF13 or BFP-13 Wall mount: RBE-13) Humidity: 5...95% RH Temperature: -40...+180 °C More functions: Absolute humidity, dew point, enthalpy which is also available as an analog output signal can be used. Supply: 24 VDC/AC 2 x analogue outputs: 4...20 mA or 0...10 V 2 relay outputs / changeover (3A / 230V) Housing/degree of protection: ABS, IP 65
temperature calibration	temperature probe 2 calibration points The calibration is based on DAkkS guidelines carried out including calibration certificate (traceable to national standards) Item No.: 99-KT-EM-2 ++++++++++++++++ Examinee(s): - TH210-BODI-150-R ++++++++++++++++
Anemometer / Thermo-Hygrometer	incl. 100 mm vane probe Type: VT 210 L - set / graphic display up to 6 measurements simultaneously 2 external probe inputs 1 slot for modules Outputs for PC and IR printer radio probe option automatic probe detection Features: air velocity, volume flow, Measuring funnel function, temperature, humidity, speed, climate module Log function (1000 data records with 20,000 measurement points)

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Included: VT210 - Anemometer / Thermo-Hygrometer Vane probe SH-100 (100 mm diameter) Air speed: 0.3....35 m/s Flow rate: 0...99999 m³/h Temperature: -20...+80 °C Handle with multifunction control button - CSM probe cable - Li-Ion battery block (up to 40 hours continuous operation) - USB adapter cable and power supply - Transport case - Calibration certificate Weight: about 500g
TH210-BNSP-R without display	Temperature and humidity transmitter ATTENTION: Parameterization only possible with the LCC-S software The sensor probe is firmly attached to the housing. polycarbonate probe, Sensor length: 100 mm Humidity: 5...95% r.h. Temperature: -20...+80 °C More functions: Absolute humidity, dew point, enthalpy which also as an analog output signal can be used. Power supply: 24 VDC/AC 2 x analogue outputs: 4...20 mA or 0...10 V 2 relay outputs / changeover contact (3A / 230V) Housing/protection class: ABS, IP 65 Art.-No.: 56-2564
LCC-S configuration software	for all stationary devices of the 110 / 210 / 310 series With this software you have a quick and very easy option, transmitter, switch or Adjust display devices and change parameters. This saves time and costs.... The parameterization of the setpoints for each individual Switching and analogue outputs, alarm functions as well as the settings for the units and measuring ranges etc. that should be shown on the display easy and quick for everyone you want area can be adjusted. (With this software transmitters/switches All of them are equipped with dip switches Intermediate areas can be set that would otherwise would not be possible) For info: A graphical and tabular representation the measurement is also possible with this software Real time possible. The test function with which the analog outputs

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	and the Relay functions can be tested. Would you like to record the measured values, trend curves create, our data loggers offer you one simple and suitable solution. DANGER: This software is used for transmitters without a display absolutely necessary to set up the devices. Delivery: Software USB stick incl. KIMO USB mini DIN cable Country of origin: France
C 310-BO with display	Optionally, several measurements can be carried out at the same time correspond to probes and modules such as Pressure, Differential pressure, air speed, volume flow, rel. Humidity, dew point, temperature, CO2, CO and (barom. air pressure) possible. You can also use the pressure signal the SQR/3 function (optional) the air speed, the volume flow is shown on the display and as analog signal can be further processed. Technical data: Power supply: 24V AC/DC Analogue outputs: 2 x 0/4-20 mA or 2 x 0/5-10V (Optional: 4 x 0/4-20 mA or 4 x 0/5-10V) Relay outputs: 4 x changeover contacts 5A / 230V (optional) exchangeb. Pressure modules including temperature input (+/- 100Pa, 500Pa, 1000Pa, 10,000Pa optional) Optional: Interface for RS485 Modbus-RTU protocol and Ethernet networks. Please note when ordering, the Ethernet interface cannot be retrofitted. Housing: IP 65 ABS housing with stainless steel front including 4 x 2 colored LEDs and acoustic alarm Operating temperature: -10..to + 50°C All transmitter settings can be carried out using the keypad on the device or (optionally) via the parameterization software LCC-S quickly and easily from your laptop. Included in delivery: bracket / adjustment certificate DANGER: We would like to point out that probes, modules etc. are not included.
Extension of the C310 multifunctional transmitter	by 2 additional analog output channels. Type: O2S For the following output signals: 0-20mA, 4-20mA, 0-5V, 0-10V
Replaceable differential pressure module	including temperature input for C310 transmitter Type: SPI2-100

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	The module has one separate temperature input (Type-K) (Temperature compensation possible) No zero point drift thanks to automatic zero point adjustment, which ensures good long-term stability. Measuring ranges: Pressure: +/- 100 Pa (other measuring ranges available) Resolution: 1 Pa High resolution option with 0.1 Pa Type: HRP Accuracy: ±0.2% Temperature: -200 ... 1300°C (depending on the probe)
Interchangeable temperature/humidity probe	for class 310 transmitter Type: SHDI-150 Stainless steel probe with stainless steel filter for relative humidity and temperature. Measuring range: 5 ... 95%RH and -40 ... +180°C Cable: white silicone cable, approx. 2 m long (Cable extensions available 5 and 10 m) Measuring probe: Ø 13 mm Probe length: 150mm Various filter caps available (optional) Sensor attachment / cable extension (optional) Calibration certificate (optional)
Multifunctional transmitter	that adapts to your measurement requirements. Type: C 310-BO with display Optionally, several measurements can be carried out at the same time correspond to probes and modules such as Pressure, Differential pressure, air speed, volume flow, rel. Humidity, dew point, temperature, CO2, CO and (barom. air pressure) possible. You can also use the pressure signal the SQR/3 function (optional) the air speed, the volume flow is shown on the display and as analog signal can be further processed. Technical data: Power supply: 24V AC/DC Analogue outputs: 2 x 0/4-20 mA or 2 x 0/5-10V (Optional: 4 x 0/4-20 mA or 4 x 0/5-10V) Relay outputs: 4 x changeover contacts 5A / 230V (optional) exchangeb. Pressure modules including temperature input (+/- 100Pa, 500Pa, 1000Pa, 10,000Pa optional) Optional: Interface for RS485 Modbus-RTU protocol and Ethernet networks. Please note when ordering, the Ethernet interface cannot be retrofitted. Housing: IP 65 ABS housing with stainless steel front including 4 x 2 colored LEDs and acoustic alarm Operating temperature: -10..to + 50°C All transmitter settings

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	can be carried out using the keypad on the device or (optionally) via the parameterization software LCC-S quickly and easily from your laptop. Included in delivery: bracket / adjustment certificate DANGER: We would like to point out that probes, modules etc. are not included.
Multifunctional handheld measuring device including device case	that meets your measurement requirements through adapts its unique modular system. The operation of the device is also so simple which for most applications the manual is superfluous. Type: AMI 310 with large color display - Incl. enclosed 8 GB / SD card for unlimited Recording of measurements - up to 8 modules for measuring function extension - simply replace the measuring module and off you go. - measure up to 6 temperatures simultaneously - only one cable for all hand probes, thus No more tangled cables in the suitcase - wireless communication possible - Smart-plus system automatic detection of probes - Rubber protective housing including strong holding magnets - (optional data processing software) Function: Air speed, volume flow, pressure, Air pressure, climate, humidity, temperature, Measured value storage, averaging, air quality, Co, Co2, U-value, speed, Comfort measurement, Wet Bulb Globe (WBGT) IR printer (optional) Included in delivery: - AMI 310 handheld measuring device including holding magnets - 8 GB SD memory card - Powerful battery pack with USB port - 230V plug / USB output including USB cable - high-quality ABS measuring device case - Adjustment certificate Language: English, French, German DANGER: Probes and modules are not included included, these must be ordered separately
Immersion temperature sensor	Type: SIK 500 HT Inconel sensor tube 6.0 x 500 mm Handle with spiral cable and mini TE connector Thermocouple Type K (Class 1) Temperature range: -40 ... +1000 °C
Humidity / temperature probe (stainless	with handle and multifunction button

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
steel)	Very robust probe which is also suitable for very high Temperatures suitable up to + 180°C The probe features the latest automatic smart probe detection system Type: SHR-300 Measuring range: Relative humidity: 3 ... 98% RH Temperature: -40 ...to + 180°C Probe length: 300 mm Probe diameter: 13 mm Incl. adjustment certificate (test certificate)
TH210-BODI/150-R	with display remote stainless steel probe, Sensor length: 150 mm / diameter 13 mm Cable length 1.9 m (other lengths available) (Optional sensor mounting clamps Duct mounting: BF13 or BFP-13 Wall mounting: RBE-13) Humidity: 5...95% RH Temperature: -40...+180 °C Additional features: Absolute humidity, dew point, enthalpy which is also known as analog output signal can be used. Power supply: 24 VDC/AC 2 x analog outputs: 4...20 mA or 0...10 V 2 relay outputs / changeover contact (3A / 230V) Housing/protection class: ABS, IP 65 Customs tariff number: 9025 8040 Country of origin: France Weight: approx. 320 g
SIK 500 HT	Length: 500 mm
SHR 300	Type: Cable probe (not wireless)
AMI310	
KH-120	KISTOCK USB data logger for relative humidity and temperature Integrated USB connector for direct connection to the PC. Recorded measured values are automatically generated in PDF format. It is used for the standard Setting and data download no special software required. Adjustment certificate also saved as a PDF. Housing material compatible for food industry Type: KH-120 with display For temperature and humidity Data storage: 50,000 measurement points Measuring ranges:

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Temperature: -20.. to +70°C Relative humidity: 5 to 95% RH 2 adjustable alarm limits per channel Power supply: CR 2450 battery can be replaced by yourself With magnetic holder Housing type: IP 20 The full version KIC3-N is available as an option This allows, for example, the start/stop function on the device be activated etc.
CAL 3 PT TEMP STD	Calibration / Temperature Type: CAL 3 PT TEMP STD (M) 3-point calibration at standard temperature by comparing a complete measuring chain. Possible measuring range from -100 to +1100 °C. Calibration points defined at: -20 / 50 / 100 °C. Supplied with calibration certificate and proof of conformity.
CAL 3 PT RH% STD (M)	Calibration / Humidity Type: CAL 3 PT RH% STD (M) Calibration in hygrometry at room temperature with temperature control any type of hygrometer. Possible measuring range from 5 to 98 %RH. 3 x calibration points: defined at: 11 / 44 / 85 %RH. Delivery: Calibration certificate and proof of conformity
TH210-BODI/300-R mit Display	Temperature and humidity transmitter Model: TH210-BODI/300-R with display offset stainless steel probe, Sensor length: 300 mm / Diameter: 13 mm Cable length approx. 2 m (other lengths available) Humidity: 5...95% RH Temperature: -40...+180 °C Other features: Absolute humidity, dew point, enthalpy which also serves as an analog output signal can be used. Power supply: 24 VDC/AC 2 x analog outputs: 4...20 mA or 0...10 V 2 relay outputs / changeover contacts (3A / 230V) (Optional sensor mounting clamps) Channel mounting: BF13 or BFP-13 Wall mounting: RBE-13) Housing/Protection class: ABS, IP 65 Weight: 320 g
TPL-06-800	Pitot tube, stainless steel TPL-06-800

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Diameter: 6 mm / NL: 800 mm For measuring: Pressure, air velocity, volume flow Heat resistant up to +600°C (optionally up to 1000°C) (suitable hose 5mm inner diameter) Complies with the standard according to: ISO 3966
TPL-06-300	Pitot tube, stainless steel TPL-06-300 Diameter: 6 mm / NL: 300 mm For measuring: Pressure, air velocity, volume flow Heat resistant up to +600°C (optionally up to 1000°C) (suitable hose 5mm inner diameter) Complies with the standard according to: ISO 3966
Cp 202-Bo Obsolete,Replaced By Cp212-Bo	
Aq 100 S	
56-24072	
Svs	
Hd 100 E	
Mp 101 S	
56-25269	
56-21791, Lx 200	
Fg100s	
Typ: Tpl-06-500-T	Pitot tube, stainless steel Type: TPL-06-500-T For measuring: Pressure, air velocity, volume flow, temperature heat resistant up to + 600 ° C (optional up to 1000 ° C) with integr. Thermocouple for simultaneous Temperature measurement (compensation) type K Incl. 1.5m connection cable with plug Diameter: 6 mm / NL: 500 mm Delivery incl. 1.5 m cable for thermocouple
56-17071	
Cp213-Ho	
Ds 200	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
R310-5	
Cp212-Bo,56-24029	
2k1-14, 07201.312/16	
56-17077	
Type: C 310-Bo With Display	Multifunction transducer which adapts to their measuring requirements. Optional are the following measurements with the corresponding modules / probes such as. Differential pressure, air velocity, volume flow, rel. Humidity, dew point, temperature, CO2, CO and air pressure (barometric pressure) possible. Likewise, over the pressure signal with the SQR / 3 function (optional) the air velocity, the flow rate is shown on the display and as analog signal to be processed further. Technical specifications: Power supply: 24 V AC / DC Analog outputs: 2 x 0 / 4-20 mA or 2 x 0 / 5-10V (Optional: 4 x 0 / 4-20 mA or 4 x 0 / 5-10V) Relay outputs: 4 x change-over contacts 5A / 230V (optional) REPL. Print modules incl. Temperature input (+/- 100 Pa, 500 Pa, 1000 Pa, 10,000 Pa optional) Optional: Interface for RS485 Modbus protocol and Ethernet networks. Please note when ordering, the Ethernet interface can not be retrofitted. Housing: IP 65 ABS housing with stainless steel fron
Ctv110-Vna300/Ohne Display	
Cq 15	
56-16544	
56-20823-Tbji-6-900	
56-15089, Sb-47-25	
56 24629 Typ Ct 100e C	
Shdi-150	
Hd 100 S	
Typ: Spi2-500	Replaceable differential pressure module incl. temperature input for class 310

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	For measuring differential pressure and temperature. Thermocouple input type-K. (Temperature compensation possible) The printing module has an autom. self-calibration of the zero point This ensures excellent long-term stability. Measuring ranges: Pressure: + / - 500 Pa (other measuring ranges available) Resolution: 1 Pa Accuracy: +/- 0.2% of reading Temperature: -200 ... 1300 ° C (depending on the probe) Tariff No .: 9026 2020 Art.-No .: 56-24415
56-17073	
Typ: Mpr-10000	Diff. Pressure module incl. Temperature input The module has the latest Autom. recognition system With this module, the differential pressure, temperature Air velocity and the volume flow be determined. Type: MPR-10000 Measuring range: - 10,000 to .. + 10,000 Pa (Conversion to other units possible) Resolution: 1 Pa Accuracy: +/- 0.2% v. reading Temperature measuring range: -200 ... to + 1300 ° C (for thermocouple type-K, J, or T) Delivery incl. 2 x 1 m silicone hose Incl. Adjustment certificate (test certificate) Country of origin: France Customs fee number. 9026 9000 Art.-No .: 56-24784
CP113-AO	CP113-AO with display Differential pressure transmitter Measuring range: -10,000...+10,000 Pa (Intermediate ranges adjustable) Power supply: 24 VAC/DC Active output: 0-10 V and 4-20 mA (3-4 wire) Accuracy: ± 1.5% of reading, ±30 Pa Interface: USB-mini DIN cable Housing: ABS, IP 65 Optional: LCC-S parameterization software (it can) Any desired measuring range can be set. Weight: approx. 150 g Customs tariff number: 9026 2020 Country of origin: France Item No.: 56-23910

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Ctv110-Voa300/Mit Display	
SHDI-300	interchangeable humidity probe for class 310 Stainless steel probe with stainless steel filter for relative humidity and Temperature. Suitable for all KIMO transmitters of the class 310 Measuring range: 5 ... 95%RH and -40 ... +180°C Cable: white silicone cable, 2 m length Measuring probe: Ø 13 mm, 300 mm length different filter caps available (optional) delivered with adjustment certificate Calibration certificate (optional)
56-16537	
56-16493	
Mp 200 M	
56-16495, Ami 300 Std	
Ce 300	
56-21631	
56-24049	
Lgv 1000 Hc2	
O2s	
Sqr/3	
56-25248	
Ami 310 Pro With Large Color Display	Multifunction hand-held device incl. Equipment case that meets your measurement requirements its unique modular system adapts. Likewise, the operation of the device is so easy that for the vast majority of applications the manual is redundant. Type: AMI 310 PRO with large color display - Recording the measurements on SD card - (optional data processing software) - up to 8 modules for measuring function expansion - simply replace the measuring module and you're off. - Measure up to 6 temperatures simultaneously - wireless communication "wireless" possible - Smart-plus system autom. Detection of the probes - Rubber protection housing incl. Strong magnets

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	features: Air velocity, volume flow, pressure, Air pressure, climate, humidity, temperature, Measured value memory, averaging, air quality, Co, Co2,, U-value, speed, Comfort Measurement, Wet Bulb Globe (WBGT) IR printer (optional) Complete set, consisting of: - AMI 310 hand-held measuring device incl. Holding magne
Mp 100 S	
56-22593	
56-25244	
Mod.Pst-2	
Spi2-10.000	
56-24422	
C310-Ho	
56-20810	
Th210-Hodi/150-R	
Lcc- S, (56-24106)	
Cp50 - Obsolete (Replaced By Cp113-Ao)	
Lv 110 S	
Sqr/3 (56-24105)	
56-24412+56-24435	
Mp 120 S	
56-16702	
Calculation Function Sqr / 3	Calculation function SQR / 3 for differential pressure transmitters of the series 210/310 This feature allows the measured Pressure signal as volume flow and air velocity displayed and as an analogue output signal can be processed further. Tariff No .: 9025 9000 Country of origin: France Art.-No .: 56-24105

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Tx 50	
56-25255	
56-17114	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.