



Kistler

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Kistler Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Kistler Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
5073A111	18004735 ICAM - Programmable, industrial course 1-channel, BNC input connector - Measuring range: $\pm 100 \dots 1\,000\,000$ pC - Number of channels: 1 - Charge input: BNC neg. - Output signal: -10 ... 10 V - Interface: RS-232C
9257B	Piezo multicomponent dynamometer Measuring range Fz - 5 ... 10 kN - Measuring range Fx, y: -5 ... 5 kN - Measuring range Fz: -5 ... 10 kN - Dimensions cover plate LxW: 100x170 mm - Connection: Fischer flange 9-pin neg.
TYPE 8330B3 ServoK-Beam Accelerometer -	- Force Feedback Capacitive Accelerometer
2151B60154002	NC joining module NCFH with hollow shaft motor and compact design Integrated piezoelectric force sensor including charge amplifier and Absolute displacement encoder Measuring direction pressure / tension Measuring range 1: 60 kN Measuring range 2: 15 kN Stroke: 400mm Path repeatability: 0.01 mm Max. travel speed: 300 mm/s With holding brake Wall and flange mounting
Type:9211	
18000522	

Ürün	Açıklama
PAAE618699	
ISS-20-30-1-A	Inductive analog sensor Type: ISS-A series with integrated amplifier Circuit type: analog output 0 - 10 V Linearity range: 0.5 - 2 mm Measurement distance (Se ST 37): 1.25 mm Dimensions: 30 x 20 x 8mm Connector: M8 3-pin.
PSI-40-40/3-P	Single-beam infrared fork light barrier Type: PSI 8mm series with integrated amplifier Circuit type: PNP constant light trigger Switching function: light / dark switching Fork width: 40 mm Fork depth: 40mm Connector: M8 3-pin.
4501A	
9129AA	Piezo multi-component dynamometer Measuring range - 10 ... 10 kN - Measuring range Fx,y: -10 ... 10 kN - Measuring range Fz: -10 ... 10 kN - Dimensions cover plate LxW: 90x105 mm - Connection: Fischer flange 9-pin neg.
Application advice	Depending on the application, approx. 4 days on site plus travel expenses
INSTRUMENT TYPE:5038A2YO463	CONSISTING OF 5038A2 WITH 4PG9 THREAD HOLDES INPUT RESISTOR 15 MOHM 5.730.419 FOR ALL CHANNELS.4 COUPLING TYPE1900A 3 MOUNTED AND CONNECT TO AMPLI FI ER(2BY2) 1 CHASSI SOCKET 1500A59 MOUNTED ACCESORY 1 PLUG 1500A57 LABELIN ON TOP PLATE CHANNEL1=RANGE 1000N ADJUSTED TO MEAN SENSITIVITY OF TYPE 9341SN../SN.. CHANNEL 2=RANGE 500N ADJUSTED TO MEAN
9257B	18007542 Piezo multi-component dynamometer Measuring range Fz - 5 ... 10 kN - Measuring range Fx,y: -5 ... 5 kN - Measuring range Fz: -5 ... 10 kN

Ürün	Açıklama
	Dimensions cover plate LxW: 100x170 mm - Connection: Fischer flange 9-pin neg.
LOADCELL JUNCTION BOX PCB 63-1135-01/03	
application advice	90000011
TYPE 7513A	
ISS 20-30-1	
4097Q02-SN4520683,	
6157C Quartz Pressure Sensor	
6192B K-type Thermocouple	
Ascenix ADCR	
ADCR ATL4-0lot	
6157CAUMRKF	1,0
6192BGSP2,0	k-type 4mm ,2m S102 2-pin
5074B211	dICA - digital industrial LV with Industrial Ethernet - Measuring range: $\pm 20 \dots 1\,000\,000$ pC - Number of channels: 2 - Charge input: KIAG 10-32 neg. - Interface: EtherCat
18005972	6215 Quartz crystal high pressure sensor, M10 x 1 For ballistic applications Nominal pressure range 6 000 bar Front sealing Incl. 1063, 10x 1100
18000528	1631C5 High temperature connection cable, KIAG 10-32 pos. - BNC pos., l = 5 m
18029231	2180ANCFN0300SB Servo amplifier for NCFN 300 kN IndraDrive 100 A Interface: Sercos III Integrated Safety Technology S4 (up to PL e) Functions: SMES, SMST2, SMM1

Ürün	Açıklama
	safety zone box Mains filter and choke: HNK01.1A-A075-E0080-A-500 Braking resistor: HLR01.1N-0470-N11R7-A-007 Firmware MPB-18
18025912	2151B10052001 NC joining module NCFH with hollow shaft motor and compact design Integrated piezoelectric force sensor including charge amplifier and absolute position encoder measuring direction compression / tension Measuring range 1: 10 kN Measuring range 2: 5 kN stroke: 200 mm Path repeatability: 0.01 mm Max. travel speed: 300 mm/s With holding brake wall and flange mounting
18032002	5847B0 maXYmos NC for monitoring and control of NC joining modules - 128 independent programs with up to 10 evaluation elements through various types with online and offline evaluations - Integrated sequence control for highest flexibility - Real-time behavior through Sercos III control of the servo amplifier - 5000 curve memories, 8 000 measured value memories - Statistics and logging of measurement results (Q-DAS®, CSV, PDF, XML, IPM 5.0, QDA9) Consisting of: Measurement and Evaluation Module (MEM) connection options - Channel-Y: Piezo, DMS, Active ±10 V - Channel-X: Servo, Incremental, SSI, Potentiometer, ±10 V, inductive - Fieldbus: PROFIBUS DP, PROFINET, EtherNet/IP, EtherCAT - Network: Ethernet (TCP/IP) - USB
18025908	2151B05012001 NC joining module NCFH with hollow shaft motor and compact design Integrated piezoelectric force sensor including charge amplifier and absolute position encoder

Ürün	Açıklama
	measuring direction compression / tension Measuring range 1: 5 kN Measuring range 2: 1 kN stroke: 200 mm Path repeatability: 0.01 mm Max. travel speed: 300 mm/s With holding brake wall and flange mounting
18032002- 5847B0	5847B0 maXYmos NC for monitoring and control of NC joining modules - 128 independent programs with up to 10 evaluation elements through various types with online and offline evaluations - Integrated sequence control for highest flexibility - Real-time behavior through Sercos III control of the servo amplifier - 5000 curve memories, 8 000 measured value memories - Statistics and logging of measurement results (Q-DAS®, CSV, PDF, XML, IPM 5.0, QDA9) Consisting of: Measurement and Evaluation Module (MEM) connection options - Channel-Y: Piezo, DMS, Active ± 10 V - Channel-X: Servo, Incremental, SSI, Potentiometer, ± 10 V, inductive - Fieldbus: PROFIBUS DP, PROFINET, EtherNet/IP, EtherCAT - Network: Ethernet (TCP/IP) - USB
5847B0	
1631C5	
FORCE SENSOR M10X1 9217A	
3.220.139	
KIAG 10-32 5M 1641B5	
6021A	
5181A	
6613CG118013192	6613CG1 M10 cylinder pressure sensor, 250 bar, Viton cable 1 m, 10s, 4 ... 20 mA galvanically isolated

Ürün	Açıklama
6115CF-4AQ06S4-3	In-cylinder Pressure Sensor
1300A19	Mounting Wrench
5165A	
5015A	
Ksm036448	
18006740	
4740awy2x0b4	
18000582	
5037b3211	
1603bz	
5038a1	
1939a1	
Ksm301660-5	
18025926	
1939a3	
18001539 2516b10	
9215a	
1635cspo.5	
00052101	
18025985	
1603b2	
5125c1	
5995a	
44000178	
4740aey2x0b4	
18025989	

Ürün	Açıklama
1700a111a2	
9101a	
4740aey1x0b4	
1633csp16m	
18028885	
45326	
18007651 9313aa2	
18008983	
18007841 9500a01	
18026095	
1700a111a2 Replaces Type 1500b15	
18029223	
18007542 9257b	
Ida 354-5c-S78b	
9333a	
Ksm313720-5	
18009072	
18010639 5134b1(E)	
1500a57	
88102-1000hz	
Ksm036457-5	
18005348	
1609b2	
5027a12j-500n/Fs	
Transmitter For 6652ci39a1q01	
18008896	

Ürün	Açıklama
516157ba6457	
1635c	
18007197, 9124b1011	
Kig 10-32 Neg 1307 24 1631c5	
6457	
1500as7	
1651c5	
1900a3	
Integrated Cable With Sensor For 6652ci39a1q01	
18000590	
18029160	
2516b11	
1687b5	
Art. Nr. 18007552 , Type 9272	
10 U	
5039a221	
18005236	
4734awdy2x400s1	
1411a	
5073a111	
5027a2(500m)	
18005274	
18005753	
2p10a10ka	
18004872, 5223b1	

Ürün	Açıklama
1943a2	
Cat1401	
1662asp015	
18004711 5070a11100	
18004871, 5221b2	
18025915	
Tp6157a	
18028884	
5027a12	
18000617 1677a5	
5361a	
18029580	
5867b0000	
1633c1	
Cat6157	
18026545	
1631c3	
18009139	
18010953 8688a50	
Ksm036438	
Model: 9125a	
18004238	
1667b2	
Cat6457	
18007552 9272	
2112a27	

Ürün	Açıklama
18029161	
28820/A400	
18009065	
18009088	
18004220	
7613ca	
18007353, 9165	