

Kleev

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Kleev Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Kleev Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
I.60.2.4NM.0-10BAR	KAI.60.2.4NM.0-10BAR.5A.DG.ST.CN.CC.SS.SM.MT.EZ
I.60.2.4NM.0-150BA	KAI.60.2.4NM.0-150BAR.5A.DG.ST.CN.CC.SS.SM.MT.EZ
.60.2.4NM.0-25BAR	KAI.60.2.4NM.0-25BAR.5A.DG.ST.CN.CC.SS.SM.MT.EZ
60.2.4 NM.0-2BAR	KAI.60.2.4NM.0-2BAR.5A.DG.ST.CN.CC.SS.SM.MT.EZ
60.2.4NM.0-300BAR	KAI.60.2.4NM.0-300BAR.5A.DG.ST.CN.CC.SS.SM.MT.EZ
AI.60.2.4NM.0-400	KAI.60.2.4NM.0-400BAR.5A.DG.ST.CN.CC.SS.SM.MT.EZ
AI.60.2.4NM.0-6BAR	KAI.60.2.4NM.0-6BAR.5A.DG.ST.CN.CC.SS.SM.MT.EZ
GAUGE ,6",0-10B,KLEEV,KAI. 60.2.4NM	KAI.60.2.4NM.0-10BAR.5A.DG.ST.CN.CC.SS.SM.MT. EZ"
PRESS GAUGE,6",0-25B,KLEEV,KAI. 60.2.4NM	KAI.60.2.4NM.0-25BAR.5A.DG.ST.CN.CC.SS.SM.MT. EZ"
PRESS GAUGE,6",0-160B,KLEEV,KAI . 60.2.4NM	"Pressure gauge , 6 "dial ,Range-0 -160Barg ,Type :Bourdon,Mounting: Directbottom entry,Gauge connection:1/2"" NPT(M) , Scale: bar/psi (Dual Scale) , Accuracy: ±0.5 %of FSD , Ambient temp: -25°c to60°c , Max temp: 300°c , Liquidfilled: Glycerine, Case & Bezel:SS316 , Movement: SS 316 ,Socket: SS 316L, Bourdon: SS316L , Dial: Aluminium blackgraduations on white background, Protection: IP66 ,Window: Safety Glass (Solid Front type) , Manufacturer Name: Kleev, USA , Model No: KAI.

Ürün	Açıklama
	60.2.4NM.0- 160BAR.5A.DG.ST.CN.CC.SS.SM.MT.EZ"
PRESS GAUGE,6",0-350B,KLEEV,KAI . 60.2.4NM	"Pressure gauge , 6 "dial ,Range-0-350Barg ,Type :Bourdon,Mounting: Directbottom entry,Gauge connection:1/2"" NPT(M) , Scale: bar/psi (Dual Scale) , Accuracy: ±0.5 %of FSD , Ambient temp: -25°c to60°c , Max temp: 300°c , Liquidfilled: Glycerine, Case & Bezel:SS316 , Movement: SS 316 ,Socket: SS 316L, Bourdon: SS316L , Dial: Aluminium blackgraduations on white background ,Protection: IP66 ,Window: Safety Glass (Solid Front type) , Manufacturer Name: KleeV, USA , Model No: KAI. 60.2.4NM.0- 350BAR.5A.DG.ST.CN.CC.SS.SM.MT.EZ
PRESS GAUGE,6",0-450B,KLEEV,KAI . 60.2.4NM	Pressure gauge , 6 "dial ,Range-0-450Barg ,Type :Bourdon,Mounting: Directbottom entry,Gauge connection:1/2"" NPT(M) , Scale: bar/psi(Dual Scale) , Accuracy: ±0.5 %of FSD , Ambient temp: -25°c to60°c , Max temp: 300°c , Liquidfilled: Glycerine, Case & Bezel:SS316 , Movement: SS 316 ,Socket: SS 316L, Bourdon: SS316L , Dial: Aluminium blackgraduations on white background, Protection: IP66 ,Window: Safety Glass (Solid Front type) , Manufacturer Name: KleeV, USA , Model No: KAI. 60.2.4NM.0- 450BAR.5A.DG.ST.CN.CC.SS.SM.MT.EZ"