



Kromschrder

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Kromschrder Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Kromschrder Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
84444400	Pressure switch for air For monitoring air and flue gas pressures, for positive pressure, negative pressure and differential pressure, EC type-tested and certified Adjusting range: 0.2-3 mbar, can be used as "special-design pressure 90262080
Ifs 110im-5/1/1t	Automatic burner control New construction stage. Function and terminal assignment remain the same. *** Only for replacement *** Ignites and controls gas burners, for intermittent operation, with ionization or UV control, single-electrode operation possible, multi-flame control possible, EC type-tested and certified For grounded mains Fault lock-out in the event of flame failure Safety time on start-up: 5 s Safety time during operation for V2: 1 s Safety time during operation for V1: 1 s Mains voltage: 220/240 V AC, 50/60 Hz Stat. Warennummer 90268020 Ursprungsland: DE
Bcu 460-10/1lw3gbd2s3	Burner control, 400 series On-site housing, for control, ignition and monitoring from impulse-controlled, modulating or stage-controlled Gas burners. For Continuous operation with ionization monitoring or UV monitoring with UV probe UVD. Intermittent operation with UV probe UVS. Display of the Program status, device parameters and Flame signal. Manual mode. Diagnosis and adjustment of the Device parameters over optical interface and PC software BCSoft. EU certified, AGA, FM, EAC and CSA approved, certified for systems up to SIL 3 (corresponds to PL e). Standard version Safety time start-up tSA: 10 s Safety time operation tSB: 1 s Air valve control Mains voltage: 230 V ~, 50/60 Hz Ignition transformer TZI 7.5-12 / 100 Stat. Product number 85371098 Country of origin: DE
	BCU 460-10/1LW3GBD2S3 Burner control, 400 series On-site housing, for control, ignition and monitoring from impulse-controlled, modulating or stage-controlled Gas burners. For Continuous operation with ionization monitoring or UV monitoring with UV probe UVD. Intermittent operation

88610183	with UV probe UVS. Display of the Program status, device parameters and Flame signal. Manual mode. Diagnosis and adjustment of the Device parameters over optical interface and PC software BCSoft. EU certified, AGA, FM, EAC and CSA approved, certified for systems up to SIL 3 (corresponds to PL e). Standard version Safety time start-up tSA: 10 s Safety time operation tSB: 1 s Air valve control Mains voltage: 230 V ~, 50/60 Hz Ignition transformer TZI 7.5-12 / 100 Stat. Product number 85371098 Country of origin: DE
84326116	
CG 30R03VW5CWZZ	Compact unit Dreizler version With sieve, two safety valves and Servo pressure regulator to secure and Rules of atmospheric burners, Forced draft burners, Fan-assisted boilers, EC type tested and certified Size 30 Special variant Stat. Product number 84814090 Country of origin: DE
elektrod ZMI 25L700	
DG50U-3	,2.5-50 MBAR,1/2,0-250V AC,COG GAS Pressure Switch
BCU 370WFEU0D3B1	88600953
IFD 244-5/1WI	Automatic burner control replaces mat.no. 84620046 + 84620056 + 84620059, compatible Ignites and monitors gas burners, for continuous operation, Ad for Program status and flame signal strength, IP 54, EC type tested and certified, FM and CSA approved 200 series Ionization monitoring Restart after flame failure Start-up safety time: 5 s Safety time operation: 1 s Mains voltage 230 V ~, 50/60 Hz Integrated electronic ignition Stat. Lot number 90268020
VK 80F10T5A93D	85311060 Gas engine valve For automatic shut-off, normally closed, slowly opening, fast closing, for natural gas, town gas, liquid gas and Air, too suitable for biogas and landfill gas, class A according to EN 161, EC type tested and certified DN 80 Flange according to ISO 7005 pu max. 1 bar Mains voltage 220/240 V ~, 50 Hz Valve housing AISi Metal junction box with terminals, IP 54 Screw plugs in the entrance and exit Amount adjustment Stat. Product number 84814090 Country of origin: DE
FMS 080-16	48115105 Flange mounting kit Nominal width: DN 80 / PN 16 according to DIN 30690-1 and DVGW Information G19 consisting of: 1 pc Refalit gas seal, incl. WAZ HTB approval according to VP 401 HTB approved up to 5 bar incl. labeling 8 hexagon bolts, M16 nuts 14 U-washers, hardened, hardness class 200 HV and 2 serrated lock washers, DIN 6798, incl. recommendation of tightening torques calculated according to DIN 30690-1 Stat. Lot number: 90329000
IC 50-60W30TR10	For outputting rotary movements (0-90 °), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, Protection class IP 65 Series 50, with increased torque Running time 60 s / 90 ° Mains voltage 230 V ~, 50/60 Hz Torque 30 Nm Three-point step control Feedback potentiometer 1000 Ohm Stat. Product number 85011010 Country of origin: DE
IFD 258-5/1W	gas burner control replaces mat. no. 84620630, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC type tested and certified, FM and CSA approved 200 series Ionization or UV monitoring Immediate lockout or restart after flame failure, switchable Safety time start-up: 5 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
BIO 140HB-100/35-(26)E	Burner for gas, for installation in burner quarl Burner size 140 Longer flame shape For natural gas 100 mm length of the steel tube from the furnace flange 35 mm distance between the furnace flange and the front edge of the burner head Code number of the burner head 26 Construction status E Stat. Lot number 84162080 Country of origin: DE
BIO 125HB-100/35-(2)E	Burner for gas, for installation in burner quarl Burner size 125 Longer flame shape For natural gas 100 mm length of the steel tube from the furnace flange 35 mm distance between the furnace flange and the front edge of the burner head Code number of the burner head 2 Construction status E

TZI 5-15/100W	Ignition transformer new order no. for 34331381 For high-voltage ignition of gas and oil burners High voltage 5 kV Output current 15 mA at 50 Hz Duty cycle 100% Mains voltage 230 V ~
IFD 258-3/1W	Automatic burner control replaces mat. no. 84620610 IFS 258-3 / 1W, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC type tested and certified, FM and CSA approved 200 series Ionization or UV monitoring Immediate lockout or restart after Flame failure, switchable Start-up safety time: 3 s Safety time operation: 1 s Mains voltage 230 V ~, 50/60 Hz
UVS 10D0G1	UV probe For monitoring gas burners in intermittent Business, EC type tested and certified in conjunction with magpie Kromschrder automatic burner control units Series 10 Quartz glass thermal protection Rp 1/2 internal thread M20 screw connection Stat. Lot number 90275000
TZI 5-15/20W	
IFD244-5/1 WI	
GIK 25R02-5	
IFD 258-10/1Q	Automatic burner control unit replaces Mat.No. 84620450, compatible Ignites and monitors gas burners, for continuous operation with ionization control, adjustable cut-off point, display for indicating program status and flame signal intensity, IP 54, EC type-tested and certified, FM and CSA approved Series 200 Ionization or UV control Immediate fault lock-out or restart in the event of flame failure, switchable Safety time on start-up: 10 s Safety time during operation: 1 s Mains voltage: 120 V AC, 50/60 Hz
ZKIH 150/100R	Pilot burner For the safe ignition of gas burners, with forced Air supply 150 mm length An additional 100 mm Rp internal thread
GRS 25R	To prevent creeping and sudden movements Backstep, for Gas, air and oxygen, DVGW tested and registered DN 25 G female thread pu max. 25 bar
DG 6U-3	84447250 DG 6U-3 Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as " pressure monitor special Bauart ", EU certified Setting range: 0.4-6 mbar Function: Switches when the overpressure increases (gas / air), negative pressure (Air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP 54
BCU 580WC0F3U0D0K2-E	Burner control Control cabinet installation housing, for control, ignition and Monitoring of pulse-controlled, modulating or step-controlled Gas burners. For Continuous operation with ionization monitoring or UV monitoring with UV probe UVD. Intermittent operation with UV probe UVS. Height Lifetime thanks to exchangeable power module for failsafe Outputs. Display of the program status, the Device parameters and des Flame signal. Manual operating mode. Diagnosis and Setting the Device parameters via optical interface and BCSoft PC software. Series: Version for pilot and main burners Market: EU certified, certified for systems up to SIL 3 (is equivalent to PL e) Mains voltage: 230 V ~, 50/60 Hz Valve proving system: No. Power control: air valve control Flame monitoring: With ionization or UV signal Stat. Lot number 90268020
OCU 500-1	Control unit For connection to a control unit (FCU 500 or BCU 500). depiction the device status in plain text, language switchable, Reading from Process values, statistics and parameter values, Control and Setting of connected throttle valves in Manual operation, for Fastening in a control cabinet door, protection class IP 65, suitable for 22 mm mounting grid, connection with the Control unit via 4-pin Control cable, cable length up to 10 m, suitable Connector parts in Scope of delivery of the OCU. 500 series German, English, French, Dutch, Italian, Spanish Stat. Lot number 90268020 Country of origin: DE
TGI 7-25/20W	Ignition transformer in the housing For high-voltage ignition of gas and oil burners High voltage 7 kV Output current 25 mA at 50 Hz Duty cycle 20%

	Mains voltage 230 V ~ Stat. Lot number 90268020 Country of origin: DE
DG 50U-3	Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as " pressure monitor special Bauart ", EU certified Setting range: 2.5-50 mbar Function: Switches when the overpressure (gas / air) increases, negative pressure (Air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP 54 Stat. Lot number 90262080 Country of origin: DE
CG340R01 VT2WFIZ	
DG 6U-3	84447250 Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as " pressure monitor special Bauart ", EU certified Setting range: 0.4-6 mbar Function: Switches when the overpressure increases (gas / air), vacuum (Air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP 54
DG 50U-3	Gas pressure switch 84447350 For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as " pressure monitor special Bauart ", EU certified Setting range: 2.5-50 mbar Function: Switches when the overpressure increases (gas / air), vacuum (Air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP 54
DG 50B-3	Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as " pressure monitor special Bauart ", EU certified Setting range: 2.5-50 mbar Function: Switches when the overpressure increases Electrical connection: With screw terminals and M16 cable gland, IP 54
DG 6U-5	Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for setting the switching point, can be used as a " pressure monitor special Bauart ", EU certified Setting range: 0.4-6 mbar Function: Switches when the overpressure increases (gas / air), vacuum (Air), differential pressure (air-air) Electrical connection: With 4-pin plug, without socket Stat. Lot number 90262080
QA 400Z100-160-	Flow meter For non-calibration Gas quantity metering, display of consumed Quantity, with pulse generators E1 and E200 Nominal flow rate: 400 m3/h Measuring range 32-650 m3/h(b) Intermediate flange DN 100, E1: 1 Imp/m3, E200: 187.5 Imp/m3 pu max. 16 bar QA400Z100-160 Flow meter For metering gas where no calibration is required, display of the quantity consumed, with E1 and E200 pulse generators Nominal flow rate: 400 m3/h, measuring range: 32-650 m3/h(b) Intermediate flange DN 100, E1: 1 pulse/m3, E200: 187.5 pulses/m3 pu max. 16 bar
QA 40R25-40	Flow meter For metering gas where no calibration is required, display of the quantity consumed, with E1 and E200 pulse generators Nominal flow rate: 40 m3/h, measuring range: 3.3-65 m3/h(b), Rp internal thread, DN 25, E1: 10 pulses/m3, E200: 500 pulses/m3 pu max. 4 bar, for gas and air Stat. Warennummer 90281000 Ursprungsland: SK
TC 218 RO5T	TC 218R05T K 220/240VAC 10VA IP54 Pmax 500 mbar
VAS 115R/NW	gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Outlet: DN 15 (1/2") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Quantity setting: With quantity setting Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 screw plugs Accessories on the left: 2 locking screws Stat. Lot number 84818099 Country of origin: DE
VAH 115R/NWBE	Flow rate controller with solenoid valve For securing and regulating the gas pressure, pressure regulator Class A according to EN 88, class A solenoid valve according to EN 161, for gas and air, also for Biogas, pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Outlet: DN 15 (1/2") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Mains voltage: 230 V~, 50/60 Hz Valve seat: Reduced Connection set for air control pressure psa: 1 Compression fitting, 2 Test nozzles pd and psa

	Accessories on the right: 2 screw plugs Accessories on the left: 2 locking screws
DG 10U-3T	gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 1-10 mbar Function: Switches with increasing overpressure (gas/air), vacuum (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54 Feedback: Blue control lamp for 230 V~ Stat. Commodity number 90262080
VAS 125R/NW	gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 25 (1") Outlet: DN 25 (1") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Quantity setting: With quantity setting Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 screw plugs Accessories on the left: 2 locking screws Stat. Lot number 84818099
VAH 125R/NWAE	Flow rate controller with solenoid valve For securing and regulating the gas pressure, pressure regulator Class A according to EN 88, class A solenoid valve according to EN 161, for gas and air, also for Biogas, pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 25 (1") Outlet: DN 25 (1") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: plug with socket Mounted on the left side of the junction box: connector for Valve (3 pole) Valve Seat: Normal Connection set for air control pressure psa: 1 Compression fitting, 2 Stat. Lot number 84818059
DG 50B-3	gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 2.5-50 mbar Function: Switches when overpressure increases Electrical connection: With screw terminals and M16 cable gland, IP54 Stat. Commodity number 90262080 Country of origin: DE
IC 20-60W3E	88300077 actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 60 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: Continuous control Stat. Commodity number 85011010 Country of origin: DE
IC 20-30W3E	actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 30 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: Continuous control
74921672	Adaptersatz IC20/IC40 auf DKG/DKL /B
74921671	Mounting kit IC20/IC40 single application /B accesories
IC 40A2A	actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 40, parameterizable via optical interface Running time: Adjustable from 4.5 to max. 75 s Mains voltage: 120-230 V~, 50/60 Hz Torque: 2Nm Control: analogue input 4-20 mA and digital inputs Parameter set: 68001, operating mode 06, 3-stage operation with one or two digital inputs, running time: 6 s Stat. Commodity number 85011010 Country of origin: DE
88202695	VAS 665F05LW3B/PP/PP gas solenoid valve For automatic shut-off, normally closed, for Natural gas, LPG and air, class A according to EN 161, with blue control lamp, IP 65, FM approved, EU certified Size: 6 Nominal width: DN 65 Pipe connection: Flange according to ISO 7005 Inlet pressure: pu max. 500 mbar Opening behavior: slowly opening, fast closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Mounted on the left side of the junction box: M20 screw connection Lateral processing: Basic Accessories on the right, input: screw plug Accessories on the right, exit: screw plug Accessories on the left,

	input: screw plug Stat. Lot number 84818079 Country of origin: DE
DG 150B-3	84447400 gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 30-150 mbar Function: Switches when overpressure increases Electrical connection: With screw terminals and M16 cable gland, IP54 Stat. Commodity number 90262080 Country of origin: DE
ZMI 16B800R	ionization ignition burner With an ignition and monitoring electrode to be on the safe side ignition of Gas burners, with forced air supply 16mm burner size For natural gas 800mm length Rp internal thread Stat. Commodity number 84162080 Country of origin: DE
ZMI 16B800R	
DL 3A-3	air pressure switch For monitoring air and flue gas pressures, for overpressure, Vacuum and differential pressure, EU certified Setting range: 0.2-3 mbar, can be used as a "pressure switch". special Type" Housing: With threaded connection Rp 1/4 and Hose connection with handwheel Electrical connection: With screw terminals Stat. Commodity number 90262080 Country of origin: DE
IFC 120/20R05-20MMP/20-60W3TR10	Linear actuator with actuator To control continuously regulated combustion processes, linear Relationship between input signal and flow rate, Turndown ratio 25:1, for Gas and air, EU certified Size: 1 Inlet: DN 20 (3/4") Outlet: DN 20 (3/4") Pipe connection: Rp internal thread Inlet pressure: pu max. 500 mbar (7 psig) Cylinder: 20 Accessories on the right: 2 test sockets Accessories on the left: 2 locking screws Actuator: IC 20 Running time: 60 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Stat. Commodity number 85011010 Country of origin: DE
DG 150U-3	gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 30-150 mbar Function: Switches with increasing overpressure (gas/air), negative pressure (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54
IFD 258-10/1W	gas burner control replaces mat. no. 84620650, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC type tested and certified, FM and CSA approved 200 series Ionization or UV monitoring Immediate lockout or restart after flame failure, switchable Safety time start-up: 10 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
TC 2R05W/W	tightness control To check two safety valves upstream and/or after burner run, with adjustable measuring time (5-30 s) to adapt to different test volume, leak rates and inlet pressures, EU certified For fast opening individual valves Rp internal thread PU max. 500 mbar Mains voltage: 230 V~, 50/60 Hz Control voltage 230 V~, 50/60 Hz Stat. Commodity number 90262020 Country of origin: DE
IFD 258-10/1W	84621650 A.1520-008838 FW01AF CE-0063BT1310
ZAI K 84228010	Atmospheric ionization pilot burner For safe ignition of gas burners, power approx. 3 kW Tapered ring screw connection for 8 mm pipe, supplied loose Stat. Commodity number 84162080 Country of origin: DE
IFD 258-5/1W	
TC 410-1T 84765810	tightness control Within the scope of European directives, this product only used for substitute purposes. For checking two safety valves, with adjustable test duration for adapting to different test volumes, leak rates and inlet pressures, for fast opening valves, EC type tested and certified In the plug-in housing Check before or after burner run External pressure switch Test duration: 10-60 s Mains voltage 220/240 V~, 50/60 Hz
TSC 100B065-300/35-Si-1500	Ceramic tube set for BIC burners Made of silicon carbide, with seal Burner size 100 Conical shape Outlet diameter 65 mm Length 300mm 35 mm

	distance between the furnace flange and the front edge of the burner disc SiC infiltrated with silicon Up to 1500 °C (melting point silicon 1380 °C)
BIC 100HB-0/35-(37)E	Gas burner with connection for ceramic tube Burner size 100 Longer flame shape For natural gas 0 mm length of the steel pipe from the furnace flange 35 mm distance between the furnace flange and the front edge of the burner head Burner head identification number 37 Construction status E
BCU 460W3P2C0D0000K1E1-/LM400WF00E1-	burner control On-site housing, for controlling, firing and monitoring from pulse-controlled, modulating or stage-controlled gas burners. For Continuous operation with ionization monitoring or UV monitoring with UV probe UVD. Intermittent operation with UV sensor UVS. display of program status, the device parameters and the flame signal. manual operation mode. Diagnosis and adjustment of device parameters above optical interface and BCSoft PC software. EU certified, FM and EAC approved, certified for systems up to SIL 3 (corresponds to PL e). Series: standard version Mains voltage: 230 V~, 50/60 Hz Ignition transformer: 8 kV, 12 mA, ED 100% Flange plate: M32 Valve monitoring system: None High Temperature Operation: None Input function: None
ZE 14-12 A1 35mm	spark plug Thread M 14 x 1.25, thread length 12 mm Total length of wire from end of thread 35 mm Central electrode Kanthal A1, D= 3.5 mm Beru - No. 0009.340.040
Connex L.Spannst. L4X40 1.4568 annealed	Connex L.Spannst.
UV photo cell (P 578) for UVS	Accesories new order no. for 04065304
UVS 10D0G1	UV probe For monitoring gas burners in intermittent Operation, EC type tested and certified in connection with magpie Kromschröder automatic gas burners Series 10 Thermal protection made of quartz glass Rp 1/2 internal thread M20 screw connection
BR 140 L35	Elektr.Stab
TGI 5-15/100R	Ignition transformer in the housing For high-voltage ignition of gas and oil burners High voltage 5kV Output current 15 mA at 50 Hz Duty cycle 100% Mains voltage 115 V~
ARP GAS REGULATOR VALVE GIK 65F02-6	KROMSCHRODER GIK 65F02-6 AIR/GAS RATIO CONTROL DN65, PU MAX 200 MBAR
ARP GAS REGULATOR VALVE GIK 15R02-5	GIK 15R02-5 AIR/GAS RATIO VALVE, RP THREAD, 200 MBAR
48115104	FMS 065-16 flange mounting kit Nominal width: DN 65 /PN 16 according to DIN 30690-1 and DVGW Information G19 consisting of: 1 piece Refalit - gas seal, incl. WAZ HTB approval according to VP 401 up to 5 bar HTB approved including marking 4 hexagonal screws, nuts M16, 6 washers, hardened hardness class 200 HV and 2 serrated lock washers, DIN 6798, incl. recommended tightening torques calculated according to DIN 30690_1
ZKIH 300/100R	pilot burner For the safe ignition of gas burners, with forced air supply 300 mm length An additional 100 mm Rp internal thread ZKIH 300/100R Pilot burner For safely igniting gas burners, with forced air supply Length: 300 mm Plus 100 mm RP internal thread
BIO 125HB-500/435-(2)E	Burner for gas, for installation in burner quarl Burner size 125 Longer flame shape For natural gas 500 mm length of the steel pipe from the furnace flange 435 mm distance between the furnace flange and the front edge of the burner head Identification number of burner head 2 Construction status E
sealing block assembly VPS8/05LKG	
TZI 7,5-12/100W	ignition transformer new order no. for 34331383 For high-voltage ignition of gas and oil burners High voltage 7.5kV Output current 12 mA at 50 Hz Duty cycle 100% Mains voltage 230 V~ Stat. Commodity number 85043200 Country of origin: DE
UVS 10D0G1 843 15200	

74960445 UV TUBE FOR UVS 10)	
74960611	
DG10U-3 84447300)	
TC318R05T (84765710) 220/240VAC	
DG50U-3 84447350)	
DG150U-3 84447500)	
GT 50-30 T 20 E (16302441)	
DG10U-5 84447306)	
DG150U-5 84447506)	
BCU460-3/1W3 GBU)	
DG6U-6 84447251)	
IC40A2A 74105751 100-230V 8.4VA	
TC410-10/230V50Hz 100 BIS 600SEC	
IFD 258-5/1W	84621630 gas burner control replaces mat. no. 84620630, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC type tested and certified, FM and CSA approved 200 series Ionization or UV monitoring Immediate lockout or restart after flame failure, switchable Safety time start-up: 5 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz Stat. Item number 90268020 Country of origin: DE
TZI 5-15/100W 230V 50-60Hz 5KV 15mA	
IFS 110IM-3/1/1T	gas burner control New construction status. Function and pin assignment are stayed the same. Within the scope of European directives, this product only used for substitute purposes. Ignites and monitors gas burners, for intermittent operation, Ionization or UV monitoring, single-electrode operation possible, multi-flame monitoring possible, EC type tested and certified For grounded networks Lockout after flame failure Safety time start-up: 3 s Safety time operation for V2: 1 s Safety time operation for V1: 1 s Mains voltage 220/240 V~, 50/60 Hz Stat. Item number 90268020 Country of origin: DE
IC 40A2A	actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 40, parameterizable via optical interface Running time: Adjustable from 4.5 to max. 75 s Mains voltage: 120-230 V~, 50/60 Hz Torque: 2Nm Control: analogue input 4-20 mA and digital inputs Parameter set: 68001, operating mode 06, 3-stage operation with one or two digital inputs, running time: 6 s Stat. Commodity number 85011010 Country of origin: DE
74918602	Test connection G1/4 Ms+AFM /B Gauge connection made of MS with seal Stat. Commodity number 90329000 Country of origin: DE
03175467	Socket EN 10242-M2-1/2-Zn-A sleeve Stat. Commodity number 90329000 Country of origin: QU
61006050	Alternative high pressure welding sleeve A-G 1/2"x 35 mm PN 100 Material C22.8N (P250GH)
61006051	Alternativ Screw for high-pressure welding sleeve G 1/2", galvanized steel with copper sealing ring
TZI 5-15/100W	ignition transformer new order no. for 34331381 For high-voltage ignition of gas and oil burners High voltage 5kV Output current 15 mA at 50 Hz Duty cycle 100% Mains voltage 230 V~ Stat. Commodity number 85043200 Country of origin: DE

VGBF 50..40	74922193 Spare parts pack consisting of membranes, O-rings and Insert-k. Stat. Commodity number 90329000 Country of origin: SK
VAS 115R/LW	gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Outlet: DN 15 (1/2") Pipe connection: Rp internal thread Opening behaviour: Slow opening, fast closing Quantity setting: With quantity setting Mains voltage: 230 V~, 50/60 Hz Electrical connection: plug with socket Accessories on the right: 2 test points pu and pd Accessories left: 2 test points pu and pd
BIO 50HB-300/235-(37)D	Burner for gas, for installation in burner quarl Burner size 50 Longer flame shape For natural gas 300 mm length of the steel pipe from the furnace flange 235 mm distance between the furnace flange and the front edge of the burner head Burner head identification number 37 Construction status D
BIO 65HB-300/235-(34)E	Burner for gas, for installation in burner quarl Burner size 65 Longer flame shape For natural gas 300 mm length of the steel pipe from the furnace flange 235 mm distance between the furnace flange and the front edge of the burner head Identification number of the burner head 34 Construction status E
IFD 258-3/1W	gas burner control replaces mat. no. 84620610 IFS 258-3/1W, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC type tested and certified, FM and CSA approved 200 series Ionization or UV monitoring Immediate lockout or restart after flame failure, switchable Safety time start-up: 3 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
IBA 125Z05/40A2A	Throttle valve for air with actuator For continuous or stepped control of a volume flow Nominal diameter: DN 125 Pipe connection: Installation between two DIN flanges Inlet pressure: pu max. 500 mbar (200" WC) Type: Penetrating Actuator: IC 40 Running time: Adjustable from 4.5 to max. 75 s Mains voltage: 120-230 V~, 50/60 Hz Torque: 2Nm Control: analogue input 4-20 mA and digital inputs Parameter set: 68026, operating mode 21, 2-point operation, Running time: 7.5s Consisting of: 88300104 88300087 Stat. Commodity number 85011010 Country of origin: DE
IC 20-30W3E	88300076 actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 30 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: Continuous control Stat. Commodity number 85011010 Country of origin: DE
VK 100F10T5A93D	85311070 gas engine valve For automatic shut-off, normally closed, slowly opening, fast closing, for natural gas, town gas, liquid gas and air, too suitable for biogas and landfill gas, class A according to EN 161, EC type tested and certified DN100 Flange according to ISO 7005 PU max. 1 bar Mains voltage 220/240 V~, 50 Hz Valve housing AISI Metal junction box with terminals, IP 54 Locking screws in the input and output quantity setting
VFC 125/25R05-20MMP	linear actuator To control continuously regulated combustion processes, linear relationship between input signal and flow rate, Turndown ratio 25:1, for Gas and air, EU certified Size: 1 Inlet: DN 25 (1") Outlet: DN 25 (1") Pipe connection: Rp internal thread Inlet pressure: pu max. 500 mbar (7 psig) Cylinder: 20 Accessories on the right: 2 test sockets Accessories on the left: 2 locking screws Stat. Commodity number 85011010 Country of origin: DE
85092220-	GIK65F02-6 Air-conditioning regulator To maintain a constant Pressure ratio 1:1 DN65 Flange according to ISO 7005 pu max. 200 mbar Measuring nozzles in the inlet and outlet For gas, EC type tested and certified GIK65F02-6 Ratio control To maintain a constant pressure ratio of 1:1 DN65 Flange to ISO 7005 pu max. 200 mbar Pressure test point at the inlet and outlet For gas, EC type-tested and certified
	flange mounting kit Nominal width: DN 65 /PN 16 according to DIN 30690-

FMS 065-16	1 and DVGW Information G19 consisting of: 1 piece Refalit - gas seal, incl. WAZ HTB approval according to VP 401 up to 5 bar HTB approved including marking 4 hexagonal screws, nuts M16, 6 washers, hardened hardness class 200 HV and 2 serrated lock washers, DIN 6798, incl. recommended tightening torques calculated according to DIN 30690_1 Stat. Commodity number: 9032900
DG 60VC5-5W	gas pressure switch For monitoring gas and air pressures, also for Biogas, factory set switching point, EC type tested and certified Setting range 10-60 mbar Switching point adjustable via hand wheel Compact design Rp 1/4 internal thread El. Connection with 4-pin plug, without socket changeover contact Stat. Commodity number 90262080 Country of origin: DE
DG 500VC5-5W	gas pressure switch For monitoring gas and air pressures, also for Biogas, factory set switching point, EC type tested and certified Setting range 150-500 mbar Switching point adjustable via hand wheel Compact design Rp 1/4 internal thread El. Connection with 4-pin plug, without socket changeover contact
UVS 10D4G1	UV probe 84315204 ur monitoring of gas burners in intermittent Operation, EC type tested and certified in connection with magpie Kromschröder automatic gas burners Series 10 Thermal protection made of quartz glass UVS 1 adapter (28 mm (1.1")) M20 screw connection Stat. Commodity number 90275000 Country of origin: SK
86414 SET Membrane	Ersatz C50 + C52 / SET Diaphragm replacement C50 + C52
GFK 50R10-6	With filter mat made of random fiber fleece (polypropylene), for clean from gas (natural gas, town gas, liquid gas, biogas) and air, EC type tested and certified DN 50 Rp internal thread PU max. 1 bar Test sockets in the input and output
IFS 110IM-10/1/1T	gas burner control New construction status. Function and pin assignment are stayed the same. Within the scope of European directives, this product only used for substitute purposes. Ignites and monitors gas burners, for intermittent Operation, Ionization or UV monitoring, single-electrode operation possible, Multi-flame monitoring possible, EC type tested and certified For grounded networks Lockout after flame failure Safety time start-up: 10 s Safety time operation for V2: 1 s Safety time operation for V1: 1 s Mains voltage 220/240 V~, 50/60 Hz
IFS 110IM-10/1/1N	gas burner control New construction status. Function and pin assignment are stayed the same. Within the scope of European directives, this product only used for substitute purposes. Ignites and monitors gas burners, for intermittent Operation, Ionization or UV monitoring, single-electrode operation possible, Multi-flame monitoring possible, EC type tested and certified For grounded networks Lockout after flame failure Safety time start-up: 10 s Safety time operation for V2: 1 s Safety time operation for V1: 1 s Mains voltage 110/120 V~, 50/60 Hz
PRESSURE SPANNER KROMSCHRODER DG6U-3	
BCU480-3/10/1LW1GB	88610728
DG 50 U-3 2,5-50mbar	
DG 60VC5-5W	84448230 gas pressure switch For monitoring gas and air pressures, also for Biogas, factory set switching point, EC type tested and certified Setting range 10-60 mbar Switching point adjustable via hand wheel Compact design Rp 1/4 internal thread El. Connection with 4-pin plug, without socket changeover contact
UVS 10D0G1	UV probe For monitoring gas burners in intermittent Operation, EC type tested and certified in connection with magpie Kromschröder automatic gas burners Series 10 Thermal protection made of quartz glass Rp 1/2 internal thread M20 screw connection
VGBF 80F40-3	gas pressure regulator Spring-loaded, with pre-pressure compensation membrane and zero degree, for Keeping the adjustable pressure constant DN 80 Flange according to ISO 7005 PU max. 4 bar Locking screw in the input and output For gas, EC type tested and certified Set to 20 mbar (range 10-30 mbar)

VP57/05NW3	ventil
DMG S2610	Electronic pressure gauge Art: 03352142 -1000 to +1000 mbar. For measuring pressure, negative pressure and differential pressure of air and gaseous non-aggressive gases, digital display, switchable pressure units, hold function for current measured value, display of smallest and largest measured value, Soft plastic protective case with holding magnet Measuring range: ±1000 mbar, accuracy: ± 1.0% of Measured value, resolution: 0 .01 (to 199.9); 0.1 (from 200) mbar, max. overpressure: 3 bar
IC 50-60W30E	actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable position indicator, Degree of protection IP 65 Series 50, with increased torque Running time 60 s/90° Mains voltage 230 V~, 50/60 Hz Torque 30 Nm Steady control
TZI 7,5-12/100W	84331383 ignition transformer new order no. for 34331383 For high-voltage ignition of gas and oil burners High voltage 7.5kV Output current 12 mA at 50 Hz Duty cycle 100% Mains voltage 230 V~
GIK 25R02-5	03155134 equal pressure regulator To keep a constant pressure ratio of 1:1 DN 25 Rp internal thread PU max. 200 mbar Test point in the outlet For gas, EC type tested and certified
DG 150U-3	84447500 gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 30-150 mbar Function: Switches with increasing overpressure (gas/air), vacuum (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54
DG 50U-3	84447350 gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 2.5-50 mbar Function: Switches with increasing overpressure (gas/air), vacuum (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54
VK 80F10T5A93D	85311060 Gas Motorventil For automatic shut-off, normally closed, slowly opening, fast closing, for natural gas, town gas, liquid gas and air, too suitable for biogas and landfill gas, class A according to EN 161, EC type tested and certified DN 80 Flange according to ISO 7005 PU max. 1 bar Mains voltage 220/240 V~, 50 Hz Valve housing AISi Metal junction box with terminals, IP 54 Locking screws in the input and output quantity setting
FMS 080-16 flange mounting kit (optional)	48115105 Nominal width: DN 80 /PN 16 according to DIN 30690-1 and DVGW Information G19 consisting of: 1 piece Refalit - gas seal, incl. WAZ HTB approval according to VP 401 up to 5 bar HTB approved including marking 8 hexagonal screws, nuts M16 14 washers, hardened hardness class 200 HV and 2 serrated lock washers, DIN 6798, incl. recommended tightening torques calculated according to DIN 30690-1
DKR 50Z03H450D	72701260 Ring damper for air and flue gas For continuous control of a volume flow DN 50 Installation between two DIN flanges PU max. 300 mbar With manual adjustment Temperature range 450°C resounding
FDU 510W1T2/1O1-0K1	84368012 Flame Warden For flame signalling, EU certified Series: For intermittent operation Mains voltage: 230 V~, 50/60 Hz Flame control: ionization Switch-off threshold: 2 micro A Response time after flame failure: 1 s Flame signal: 1 NC, 1 NO contact Flame Signal Strength: No output Connection plug: With screw terminals
TC 410-10T	84765820 tightness control External pressure switch Test duration: 100-600 s Mains voltage 220/240 V~, 50/60 Hz Within the scope of European directives, this product may only be used for replacement purposes. For checking two safety valves, with an adjustable test duration to adapt to different test volumes, leak rates and inlet pressures, for quick-opening valves, EC type tested and certified. In the plug-in housing Check before or after burner run

UVS 10D0G1	84315200 UV probe For monitoring gas burners in intermittent Operation, EC type tested and certified in connection with magpie Kromschröder automatic gas burners Series 10 Thermal protection made of quartz glass Rp 1/2 internal thread M20 screw connection
VAG 2-/40R/NWAE	Balanced pressure regulator with solenoid valve For securing and regulating the gas pressure, pressure regulator Class A according to EN 88, class A solenoid valve according to EN 161, for gas and air, also for Biogas, pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 2 Certification: EU certified Inlet: Without inlet flange Outlet: DN 40 (1 1/2") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Valve Seat: Normal Connection set for air control pressure psa: 1 Compression fitting, 2 Test nozzles pd and psa Accessories on the right: 2 screw plugs
VA62-/40R/NWAE	
IC 20-60W3TR10	actuator 88300069 For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 60 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: Three-point step control Feedback potentiometer: 1000 ohms
BIO 140RB-50/35-(47)E	Article number: 84008018 Electric rod BR 140 L35 74330411
Electric rod BR 140 L35	
IFD 258-10/1W	gas burner control replaces mat. no. 84620650, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC type tested and certified, FM and CSA approved 200 series Ionization or UV monitoring Immediate lockout or restart after flame failure, switchable Safety time start-up: 10 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
VGBF 40R40-3	Gas pressure regulator Spring, with a form compensation membrane and Zero degree, to Constant keeping of the adjustable pressure DN 40 RP inside thread PU max. 4 bar Closure screw in the entrance and output Checked and certified for gas, EC patterns Set to 20 mbar (range 10-30 mbar)
MHP32/7417	
QA 400Z100-160	flow meter For non-calibratable gas metering, display of consumed quantity, with pulse generators E1 and E200 Nominal flow: 400 m3/h Measuring range 32-650 m3/h(b) intermediate flange DN 100, E1: 1 pulse/m3, E200: 187.5 pulse/m3 PU max. 16 bar QA 400Z100-160 Flow meters For metering gas where no calibration is required, display of the quantity consumed, with E1 and E200 pulse generators Nominal flow rate: 400 m3/h, measuring range: 32-650 m3/h(b) Intermediate flange DN 100, E1: 1 pulse/m3, E200: 187.5 pulses/m3 PU max. 16 bar
IC 50-60W30E	actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable position indicator, Degree of protection IP 65 Series 50, with increased torque Running time 60 s/90° Mains voltage 230 V~, 50/60 Hz Torque 30 Nm Steady control
REFALIT flange seal DN 100 - HTB PN 10/16	DIN 2690, without bores, 115 x 162 x 2.0 mm, code. according to DIN 30690-1: date of manufacture, material, 2.2 certificate and torque calculation for screws 5.6 for flange connections according to DIN 30690-1 and DVGW Information Gas No. 19
VAS 120R/NW	gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 20 (3/4") Outlet: DN 20 (3/4") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Quantity setting: With quantity setting Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 screw plugs Accessories on the left: 2 locking screws
	74215213 Actuator To submit rotating movements (0-90 °), for activity

IC 50-15W15TR10	From gas and Air flaps, position feedback via external readable Position indicator, Protection class IP 65 50 series 50, with increased torque Duration 15 S/90 ° Network voltage 230 V ~, 50/60 Hz Torque 15 Nm Three-point-step control Corpus potentiometer 1000-ohms
MC202-D00/MC202-F10	
DG 150U-3	84447500 Gas pressure To monitor gas and air pressing, also for Biogas, with a handwheel for switching point setting, can be used as " print monitor special Bauart ", EU certified Setting range: 30-150 mbar Function: switches with increasing overpressure (gas/air), negative pressure (Air), differential pressure (air air) Electrical connection: with screw terminals and M16 cable screw connection, IP 54
IC 20-30W3TR10	88300068 actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 30 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: Three-point step control Feedback potentiometer: 1000 ohms
DG 50U-6	84447351 gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 2.5-50 mbar Function: Switches with increasing overpressure (gas/air), negative pressure (air), differential pressure (air-air) Electrical connection: With 4-pin plug, with socket
IC 20-30W3E	88300076 actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 30 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: Continuous control Stat. Commodity number 85011010900 Country of origin: DE
VG40R02	
QA 25R25-40	47102525 Flow meter For metering gas where no calibration is required, display of the quantity consumed, with E1 and E200 pulse generators Nominal flow rate: 25 m3/h, measuring range: 2.5-40 m3/h(b) Rp internal thread DN 25, E1: 10 pulses/m3, E200: 500 pulses/m3 pu max. 4 bar, for gas and air
GIK 25R02-5	03155134 equal pressure regulator To keep a constant pressure ratio of 1:1 DN 25 Rp internal thread PU max. 200 mbar Test point in the outlet For gas, EC type tested and certified
GFK 25/32	Spare parts pack, consisting of 10 filter mats and 10 O-rings
TC 410-1T	tightness control 84765810 Within the scope of European directives, this product only used for substitute purposes. For checking two safety valves, with adjustable test duration for adapting to different test volumes, leak rates and inlet pressures, for fast opening valves, EC type tested and certified In the plug-in housing Check before or after burner run External pressure switch Test duration: 10-60 s Mains voltage 220/240 V~, 50/60 Hz
74960445 UV photo cell (P 578) for UVS accessories	new order no. for 04065304
DM25R25-40	
VAS 125R/NW	gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 25 (1") Outlet: DN 25 (1") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Quantity setting: With quantity setting Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 screw plugs Accessories on the left: 2 locking screws
GIK 50R02-5	equal pressure regulator To keep a constant pressure ratio of 1:1 DN 50 Rp internal thread PU max. 200 mbar Test point in the outlet For gas, EC type tested and certified

BVA 100Z05	Drosselklappe für Luft Zur stetigen oder stufigen Regelung eines Volumenstroms Nennweite: DN 100 Rohranschluss: Einbau zwischen zwei DIN-Flansche Eingangsdruck: pu max.
IC 20-15W3E	actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 15 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: Continuous control
UVS 10D0G1	UV probe For monitoring gas burners in intermittent Operation, EC type tested and certified in connection with magpie Kromschröder automatic gas burners Series 10 Thermal protection made of quartz glass Rp 1/2 internal thread M20 screw connection
IC 50-60W30TR10	actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable position indicator, Degree of protection IP 65 Series 50, with increased torque Running time 60 s/90° Mains voltage 230 V~, 50/60 Hz Torque 30 Nm Three-point step control Feedback potentiometer 1000 Ohm
IC 50-60W30TR10	actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable position indicator, Degree of protection IP 65 Series 50, with increased torque Running time 60 s/90° Mains voltage 230 V~, 50/60 Hz Torque 30 Nm Three-point step control Feedback potentiometer 1000 Ohm
BCU 370.....I1	
GT50-60T20 (16302311)	
IFD 454-10/1/1T	
TZI 8-12/100WE	Ignition transformer For high-voltage ignition of gas and oil burners High voltage 8 kV Output current 12 mA at 50 Hz Duty cycle 100% Mains voltage 230 V~ EU certified
VAG 125R/NWAE	Air/gas ratio control with solenoid valve For safeguarding and control of the gas pressure, Class A pressure regulator to EN 88, Class A solenoid valve to EN 161, for gas, air and biologically produced methane, pu max. 500 mbar (7 psig), with pilot lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 25 (1") Outlet: DN 25 (1") Pipe connection: Rp internal thread Opening properties: Quick opening, quick closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 cable gland Valve seat: Normal Connection kit for air control pressure psa: 1 compression fitting, 2 pressure test points pd and psa Accessories, right: 2 screw plugs Accessories, left: 2 screw plugs
75421971	Spring 10-30 mbar, red Spring (red) for GBF 40, VGBF 25-40 (10-30 mbar) and VAR 25-40 (10-25 mbar) for outlet pressure changes for GBF 40, VGBF 25 and VGBF 40, Outlet pressure range 10 - 30 mbar for VAR 25 and VAR 40, Outlet pressure range 10 - 25 mbar
75421980	Spring 25-45 mbar, yellow Spring (yellow) for GBF 40, VGBF 25-40 (25-45 mbar) and VAR 25-40 (26-40 mbar) for outlet pressure changes: for GBF 40, VGBF 25 and VGBF 40, Outlet pressure range 25 - 45 mbar for VAR 25 and VAR 40, Outlet pressure range 26 - 40 mbar
75421990	Spring 40-60 mbar, green Spring (green) for GBF 40, VGBF 25-40 (40-60 mbar) and VAR 25-40 (41-55 mbar) for outlet pressure changes: for GBF 40, VGBF 25 and VGBF 40, Outlet pressure range 40 - 60 mbar for VAR 25 and VAR 40, Outlet pressure range 41 - 55 mbar
75422000	Feder 55-75 mbar, blau Feder (blau) für GBF 40, VGBF 25-40 (55-75 mbar) and VAR 25-40 (56-70 mbar) für Ausgangsdruck-Umstellungen: für GBF 40, VGBF 25 und VGBF 40, Ausgangsdruckbereich 55 - 75 mbar für VAR 25 und VAR 40, Ausgangsdruckbereich 56 - 70 mbar
75422010	Spring 70-90 mbar, black Spring (black) for GBF 40, VGBF 25-40 (70-90 mbar) and VAR 25-40 (71-86 mbar) for outlet pressure changes: for GBF 40, VGBF 25 and VGBF 40, Outlet pressure range 70 - 90 mbar for VAR 25

	and VAR 40, Outlet pressure range 71 - 85 mbar
VAS 120R/LW	gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 20 (3/4") Outlet: DN 20 (3/4") Pipe connection: Rp internal thread Opening behaviour: Slow opening, fast closing Quantity setting: With quantity setting Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 screw plugs Accessories on the left: 2 locking screws
GRSF 25R	03150674 Non-return gas safety device, flameproof at combustion with air To prevent creeping and sudden Gas withdrawal, for Gas, air and oxygen, DVGW tested and registered DN 25 G internal thread Flameproof up to pu max. 5 bar natural gas, LPG pu max. 1.5 bar city gas, hydrogen
Spring 85-105 mbar, white	Spring (white) for GBF 40, VGBF 25-40 (85-105 mbar) and VAR 25-40 (86- 100 mbar) for outlet pressure changes: for GBF 40, VGBF 25 and VGBF 40, Outlet pressure range 85 - 105 mbar for VAR 25 and VAR 40, Outlet pressure range 86 - 100 mbar
VGP 20R01W6	gas solenoid valve For automatic shut-off, normally closed, fast opening, fast closing, for natural gas, town gas, liquid gas, biogas and air, Class A according to EN 161, EC type tested and certified DN 20 Rp internal thread PU max. 150 mbar Mains voltage 230 V~, 50/60 Hz Connection with rectifier adapter and standard socket
QA 65Z50-40	DurchfluŐmengen zähler Zur nichteichpflichtigen Gasmengenzählung, Anzeige der verbrauchten Menge, mit Impulsgebern E1 und E200 Nenndurchfluss: 65 m3/h Messbereich 6-100 m3/h(b) Zwischenflansch DN 50, E1: 1 Imp/m3, E200: 250 Imp/m3 pu max. 4 bar, für Gas und Luft QA 65Z50-40 Flow meter For metering gas where no calibration is required, display of the quantity consumed, with E1 and E200 pulse generators Nominal flow rate: 65 m3/h, measuring range: 6-100 m3/h(b) Intermediate flange DN 50, E1: 1 pulse/m3, E200: 250 pulses/m3 pu max. 4 bar, for gas and air
BCU480-5/3/1 LW3G	
UVS 10D0G1	84315200 UV probe For monitoring gas burners in intermittent Operation, EC type tested and certified in connection with magpie Kromschröder automatic gas burners Series 10 Thermal protection made of quartz glass Rp 1/2 internal thread M20 screw connection
REFALIT flange seal DN 50 - HTB PN 10/16	DIN 2690, without bores, 61 x 107 x 2.0 mm, code. according to DIN 30690-1: date of manufacture, material, 2.2 certificate and torque calculation for screws 5.6 for flange connections according to DIN 30690-1 and DVGW Information Gas No. 19
Length compensation GRSF 25R	gas non-return device For use with GRSF 25R (03150674) for exchange GRSF 25R50 (03150645) Overall length 174 mm DN 25 G male/female thread PU max. 5 bar
QAe 250Z100-40	Flow meter with electronic counter header For non-calibratable gas metering, display of consumed quantity, key date value, key date, instantaneous flow and High resolution of the amount consumed, with a pulser E200 Nominal flow: 250 m3/h Measuring range 20-400 m3/h(b) intermediate flange DN 100, E200: 187.5 imp/m3 pu max. 4 bar, for gas and air Interface for M-Bus QAE 250Z100-40 Flow meter with electronic counter head For metering gas where no calibration is required, display of the quantity consumed, key date value, key date, current flow guess and high resolution of the quantity consumed, with E200 pulse generator Nominal flow rate: 250 m3/h, measuring range: 20-400 m3/h(b) Intermediate flange DN 100, E200: 187.5 pulses/m3 pu max. 4 bar, for gas and air M-Bus interface
UVS 10D0G1	UV probe For monitoring gas burners in intermittent Operation, EC type tested and certified in connection with magpie Kromschröder automatic gas burners Series 10 Thermal protection made of quartz glass Rp 1/2 internal thread M20 screw connection
UVS.10D0G1	
74921998	Find VA2 /B

DG 150B-3 84447400	gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 30-150 mbar Function: Switches when overpressure increases Electrical connection: With screw terminals and M16 cable gland, IP54 Stat. Commodity number 90262080 Country of origin: DE
DG 500B 84447450	gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 100-500 mbar Function: Switches when overpressure increases Electrical connection: With screw terminals and M16 cable gland, IP54 Stat. Commodity number 90262080 Country of origin: DE
DG 50U-3 84447350	gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 2.5-50 mbar Function: Switches with increasing overpressure (gas/air), negative pressure (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54
BIO 125HB 35	
BIO 125HB 35 / repair kit set	
DL 3A-3	air pressure switch For monitoring air and flue gas pressures, for overpressure, Vacuum and differential pressure, EU certified Setting range: 0.2-3 mbar, can be used as a "pressure switch". special Design type" Housing: With threaded connection Rp 1/4 and Hose connection with handwheel Electrical connection: With screw terminals
VAS 115R/NQ	gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Outlet: DN 15 (1/2") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Quantity setting: With quantity setting Mains voltage: 120 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 screw plugs Accessories on the left: 2 locking screws
VAA 240R/NQ	Air Solenoid Valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 2 Certification: EU certified Inlet: DN 40 (1 1/2") Outlet: DN 40 (1 1/2") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Mains voltage: 120 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 screw plugs Accessories on the left: 2 locking screws
TC 3R05W/W	tightness control To check two safety valves upstream and/or after burner run, with adjustable measuring time (5-30 s) to adapt to different test volume, leak rates and inlet pressures, EU certified For fast or slow opening individual valves Rp internal thread PU max. 500 mbar Mains voltage: 230 V~, 50/60 Hz Control voltage 230 V~, 50/60 Hz
UVC 1D1G1A	UV flame detector For continuous operation to monitor gas burners in connection with Kromschr¼der burner controls BCU or PFU..U. series 1 Thermal protection made of quartz glass Rp 1/2 internal thread and cooling air connection M20 screw connection Mains voltage 100-230 V~, 50/60 Hz
PFF 704T/N	Flame Warden Within the scope of European directives, this product only used for substitute purposes. For flame signaling or for Multi-flame control with PFS/PFD Series 700 For intermittent operation, ionization or UV monitoring With 4 independent flame monitors Switchable from 220/240 V~ to 110/120 V~, 50/60 Hz, for grounded or floating networks
GFK 65F10-6	gas filter With filter mat made of random fiber fleece (polypropylene), for clean from gas (natural gas, town gas, liquid gas, biogas) and air, EC type tested and certified DN 65 Flange according to ISO 7005 PU max. 1 bar Test sockets in the input and output
Spare parts pack GRP 65	Spare parts pack, consisting of 1 filter mat and 1 O-ring
TZI 7,5-20/33W	IGNITION TRANSFORMER new order no. for 34326116 For high-voltage ignition of gas and oil burners High voltage 7.5kV Output current 20 mA at

	50 Hz Duty cycle 33%, mains voltage 230 V~
VALF VAS125-R/NW+VAH1-/NWAE+VMV1-/25R05I	VAS125/-R/NW VAH1-/NWAE VMV1-/25R05I REQUIRED AS COMBINED, ASSEMBLED. INPUT - OUTPUT THREAD WILL BE ON DN25 CONNECTION FLANES. IMAGES ARE ATTACHED
VG 15/12R18NT31	gas solenoid valve For automatic shut-off, normally closed, for Natural gas, town gas, liquid gas and air, class A according to EN 161, EC type tested and certified DN 15/15 Rp internal thread PU max. 1.8 bar Quick opening, quick closing 220/240V~, 50/60Hz Junction box with terminals, IP 54 Locking screw in the entrance Stat. Commodity number 84814090 Country of origin: SK
UV photo cell (P 578) for UVS accessories	74960445
VAG 240R/NWAE	Balanced pressure regulator with solenoid valve For securing and regulating the gas pressure, pressure regulator Class A according to EN 88, class A solenoid valve according to EN 161, for gas and air, also for Biogas, pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 2 Certification: EU certified Inlet: DN 40 (1 1/2") Outlet: DN 40 (1 1/2") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Valve Seat: Normal Connection set for air control pressure psa: 1 Compression fitting, 2 Test nozzles pd and psa Accessories on the right: 2 screw plugs
VK 100F10T5A93D	85311070 gas engine valve For automatic shut-off, normally closed, slowly opening, fast closing, for natural gas, town gas, liquid gas and air, too suitable for biogas and landfill gas, class A according to EN 161, EC type tested and certified DN100 Flange according to ISO 7005 PU max. 1 bar Mains voltage 220/240 V~, 50 Hz Valve housing AISi Metal junction box with terminals, IP 54 Locking screws in the input and output quantity setting Stat. Commodity number 84814090 Country of origin: DE
VGBF 80F05-3	86050220 gas pressure regulator Spring-loaded, with pre-pressure compensation membrane and zero degree, for Keeping the adjustable pressure constant DN 80 Flange according to ISO 7005 PU max. 0.5 bar Locking screw in the input and output For gas, EC type tested and certified Set to 20 mbar (range 10-30 mbar)
spring 5-12.5 mbar, -	75426230 Spring for GBF 80 and VGBF 80 for outlet pressure changes for GBF 80 and VGBF 80, packed in a bag, with Additional plate for changed outlet pressure, Outlet pressure range 5 - 12.5 mbar
IFD 244-3/1W	art nr 84621025 gas burner control replaces mat. no. 84620025 + 84620035, compatible Ignites and monitors gas burners, for continuous operation, ad for Program status and flame signal strength, IP 54, EC type tested and certified, FM and CSA approved 200 series ionization monitoring Restart after flame failure Safety time start-up: 3 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz Stat. Item number 90268020 Country of origin: DE
VGBF 50F40-3	gas pressure regulator Spring-loaded, with pre-pressure compensation membrane and zero degree, for Keeping the adjustable pressure constant DN 50 Flange according to ISO 7005 PU max. 4 bar Locking screw in the input and output For gas, EC type tested and certified Set to 20 mbar (range 10-30 mbar)
Spring 220-350 mbar, black/green	Spring (black/green) for VGBF 50 (220- 350 mbar) and VAR (221-340 mbar) for outlet pressure changes: for VGBF 50, Outlet pressure range 220 - 350 mbar for VAR 50, Outlet pressure range 221 - 340 mbar
VAG 115R/NWBE	Balanced pressure regulator with solenoid valve For securing and regulating the gas pressure, pressure regulator Class A according to EN 88, class A solenoid valve according to EN 161, for gas and air, also for Biogas, pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Outlet: DN 15 (1/2") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: plug with socket Valve seat: Reduced Connection set for air control pressure psa: 1 Compression fitting, 2 Test nozzles pd and psa Accessories on the right: 2

	screw plugs Stat. Lot number 84818059 Country of origin: DE
VMV 115R05P	fine adjustment valve To supplement valVario routes or as a single product Size: 1 Inlet: DN 15 (1/2") Outlet: DN 15 (1/2") Pipe connection: Rp internal thread Inlet pressure: pu max. 500 mbar (7 psig) Housing type: Basic (no accessories possible) Accessories above: screw plugs
VAG115R/NWBE 8	
IFS 110IM-3/1/1T	gas burner control New construction status. Function and pin assignment are stayed the same. Within the scope of European directives, this product only used for substitute purposes. Ignites and monitors gas burners, for intermittent Operation, Ionization or UV monitoring, single-electrode operation possible, Multi-flame monitoring possible, EC type tested and certified For grounded networks Lockout after flame failure Safety time start-up: 3 s Safety time operation for V2: 1 s Safety time operation for V1: 1 s Mains voltage 220/240 V~, 50/60 Hz
G650 Elster	turbine type EK220 in combination with gas meter box
VAS 125R/NQ	gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 25 (1") Outlet: DN 25 (1") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Quantity setting: With quantity setting Mains voltage: 120 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 screw plugs Accessories on the left: 2 locking screws
VGBF 80F40-3Z *Price + FertNote*	gas pressure regulator Outlet pressure adjusted on customer request If pressure is missing, set to standard 20 mbar Spring-loaded, with pre-pressure compensation membrane and zero degree, for Keeping the adjustable pressure constant DN 80 Flange according to ISO 7005 PU max. 4 bar Locking screw in the input and output For gas, EC type tested and certified Special outlet pressure range Wh:150-230mbar pe:4bar Pas:160
JSAV 80F40-0 shut off	
DG 50U-3	Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 2.5-50 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54
GDJ 50R04-4	03155040 Pressure regulator Spring-loaded, with pre-pressure compensation membrane and Zero degree, none Blow-out line required to keep the air constant adjustable pressure DN 50 Rp internal thread pu max. 400 mbar Measuring nozzle in the entrance For gas, EC type tested and certified Set to 20 mbar Stat. Commodity number 90322000900 Country of origin: SK
03089206	Spare parts pack GDJ/GIK 50 (EXISTING A MEMBR. AND SEAL) Stat. Commodity number 90329000900
VGBF 80F40-3	Gas pressure regulator Spring-loaded, with pre-pressure compensation membrane and Zero termination, for Keeping the adjustable pressure constant DN 80 Flange according to ISO 7005 pu max. 4 bar Closing screw in the entrance and exit For gas, EC type tested and certified Set to 20 mbar (range 10-30 mbar)
DG 6UG-3	84447270 Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 0.4-6 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) With gold-plated contacts: Yes Electrical connection: With screw terminals and M16 cable gland, IP54
IFD 258-10/1W	84621650 Gas burner control unit replaces mat. no. 84620650, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC model tested and certified, FM and CSA approved Series 200 Ionization or UV monitoring Immediate shutdown or restart after flame failure, switchable Safety time start-up: 10 s Safety

	time operation: 1 s Mains voltage 230 V~, 50/60 Hz
IFD 258-5/1W	Gas burner control unit Replaces mat. no. 84620630, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC model tested and certified, FM and CSA approved Series 200 Ionization or UV monitoring Immediate shutdown or restart after flame failure, switchable Safety time start-up: 5 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
DG 50U-3	Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 2.5-50 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54
DG6U-3	84447250 DG 6U-3 Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 0.4-6 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54
DG 10UG-4	Gas pressure switch IP65 / Kapsto cone plug in the lower part, Gold contacts 24/250V For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 1-10 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) With gold-plated contacts: Yes Electrical connection: With screw terminals and M16 cable gland, IP65
UVC 1D0G1A	84320305 UV flame detector For continuous operation to monitor gas burners in connection with Kromschröder burner controls BCU or PFU..U. Series 1 Thermal protection made of quartz glass Rp 1/2 internal thread M20 screw connection Mains voltage 100-230 V~, 50/60 Hz
DG 50U-5	Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 2.5-50 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) Electrical connection: With 4-pin plug, without Power outlet
BIC 50-65-100	SURVEILLANCE FITTING 24 MM, 6 CORNER, Ø 16 GLASS ORDER NO:50.62.110
BR.Eins.k BR 165RB 35 (17)	74970431
VG 40/33R10NT33	Gas solenoid valve For automatic locking, closed without power, for Natural gas, Town gas, liquid gas and air, class A according to EN 161, EC model tested and certified DN 40/33 Rp internal thread pu max. 1 bar Quick opening, quick closing 220/240V~, 50/60Hz Connection box with terminals, IP 54 Closing screw in the inlet and outlet
TC 1C05W/W	Leak check 84765552 To check two safety valves before and/or after burner run, with adjustable measuring time (5-30 s) for adjustment different Test volume, leak rates and inlet pressures, EU certified For cultivation on CG pu max. 500 mbar Mains voltage: 230 V~, 50/60 Hz Control voltage 230 V~, 50/60 Hz
VAD 115R/NW-25B	Pressure regulator with solenoid valve To secure and regulate the gas pressure, pressure regulator Class A according to EN 88, solenoid valve class A according to EN 161, for gas and air, also for Biogas, pu max. 500 mbar (7 psig), with control lamp, IP 65, FM and CSA approved Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Output: DN 15 (1/2") Pipe connection: Rp female thread Opening behavior: Quick opening, quick closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: plug with socket Mounted on the right side of the connection box: plug for Valve (3 pole) Output pressure range: 2.5-25 mbar

VK 50F10T5A93D	Gas engine valve 85311040 For automatic locking, closed without power, opening slowly, quick closing, for natural gas, town gas, liquid gas and Air, too Suitable for biogas and landfill gas, class A according to EN 161, EC model tested and certified DN 50 Flange according to ISO 7005 pu max. 1 bar Mains voltage 220/240 V~, 50 Hz Valve housing AISi Metal connection box with terminals, IP 54 Closing screws in the entrance and exit Quantity setting
TC 410-10T	Leak check This is permitted within the scope of European directives product only be used for replacement purposes. For checking two safety valves, with adjustable Test duration to adapt to different test volumes and leak rates and Inlet pressures, for quick opening valves, EC type tested and certified In the plug-in housing Test before or after the burner runs External pressure switch Test duration: 100-600 s Mains voltage 220/240 V~, 50/60 Hz
GDJ 25R04-0L	Pressure regulator 03155033 Spring-loaded, with pre-pressure compensation membrane and Zero degree, none Blow-out line required to keep the air constant adjustable pressure DN 25 Rp internal thread pu max. 400 mbar Without measuring point Just for air Set to 20 mbar
TC 410-10T	Leak check 84765820 This is permitted within the scope of European directives product only be used for replacement purposes. For checking two safety valves, with adjustable Test duration to adapt to different test volumes and leak rates and Inlet pressures, for quick opening valves, EC type tested and certified In the plug-in housing Test before or after the burner runs External pressure switch Test duration: 100-600 s Mains voltage 220/240 V~, 50/60 Hz
VGBF 40R40-3	Gas pressure regulator Spring-loaded, with pre-pressure compensation membrane and Zero termination, for Keeping the adjustable pressure constant DN 40 Rp internal thread pu max. 4 bar Closing screw in the entrance and exit For gas, EC type tested and certified Set to 20 mbar (range 10-30 mbar) Stat. Commodity number 90322000 Country of origin: SK
VAS 120R/NW	Gas solenoid valve 88000004 pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 20 (3/4") Output: DN 20 (3/4") Pipe connection: Rp female thread Opening behavior: Quick opening, quick closing Quantity adjustment: With quantity adjustment Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 locking screws Accessories on the left: 2 locking screws
IC 20-30W3TR10	88300068 Actuator For emitting rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 30 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: three-point step control Feedback potentiometer: 1000 ohms
BVA 50Z05	88300100 Throttle valve for air For continuous or step control of a volume flow Nominal diameter: DN 50 Pipe connection: Installation between two DIN flanges Inlet pressure: pu max. 500 mbar (200 "WC) Design: Penetrating
DG 50UG-6K2	Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 2.5-50 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) With gold-plated contacts: Yes Electrical connection: With 4-pin plug, with socket Feedback: Red/green control LED for 24 V~/=
DG 500U-3	Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 100-500 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54
	Gas pressure switch For monitoring gas and air pressures, also for Biogas,

DG 150UG-3K2	with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 30-150 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) With gold-plated contacts: Yes Electrical connection: With screw terminals and M16 cable gland, IP54 Feedback: Red/green control LED for 24 V~/-
SWİTCH DG 150U-6	
SWİTCH DG6U-6 (84447251) 0.5-6.5 MBAR	
GIK 20R02-5	Constant pressure regulator To maintain a constant pressure ratio of 1:1 DN 20 Rp internal thread pu max. 200 mbar Measuring nozzle in the outlet For gas, EC type tested and certified Stat. Commodity number 90322000
84768505	CG 25R03VW5CWZZ
75438978	Spring 100-160 mbar, black/red Spring (black/red) for VGBF 25-40 (100-160 mbar) and VAR 25-40 (101-150 mbar) for output pressure changes: for VGBF 25 and VGBF 40, Output pressure range 100 - 160 mbar for VAR 25 and VAR 40, Output pressure range 101 - 150 mbar
7542197	Spring 10-30 mbar, red Spring (red) for GBF 40, VGBF 25-40 (10-30 mbar) and VAR 25-40 (10-25 mbar) for output pressure changes for GBF 40, VGBF 25 and VGBF 40, Output pressure range 10 - 30 mbar for VAR 25 and VAR 40, Output pressure range 10 - 25 mbar
75421980	Spring 25-45 mbar, yellow Spring (yellow) for GBF 40, VGBF 25-40 (25-45 mbar) and VAR 25-40 (26-40 mbar) for output pressure changes: for GBF 40, VGBF 25 and VGBF 40, Output pressure range 25 - 45 mbar for VAR 25 and VAR 40, Output pressure range 26 - 40 mbar
75421990	Spring 40-60 mbar, green Spring (green) for GBF 40, VGBF 25-40 (40-60 mbar) and VAR 25-40 (41-55 mbar) for output pressure changes: for GBF 40, VGBF 25 and VGBF 40, Output pressure range 40 - 60 mbar for VAR 25 and VAR 40, Output pressure range 41 - 55 mbar
75422000	Spring 55-75 mbar, blue Spring (blue) for GBF 40, VGBF 25-40 (55-75 mbar) and VAR 25-40 (56-70 mbar) for output pressure changes: for GBF 40, VGBF 25 and VGBF 40, Output pressure range 55 - 75 mbar for VAR 25 and VAR 40, Output pressure range 56 - 70 mbar
75422010	Spring 70-90 mbar, black Spring (black) for GBF 40, VGBF 25-40 (70-90 mbar) and VAR 25-40 (71-86 mbar) for output pressure changes: for GBF 40, VGBF 25 and VGBF 40, Output pressure range 70 - 90 mbar for VAR 25 and VAR 40, Output pressure range 71 - 85 mbar
75422020	Spring 85-105 mbar, white Spring (white) for GBF 40, VGBF 25-40 (85-105 mbar) and VAR 25-40 (86-100 mbar) for output pressure changes: for GBF 40, VGBF 25 and VGBF 40, Output pressure range 85 - 105 mbar for VAR 25 and VAR 40, Output pressure range 86 - 100 mbar
75438979	Spring 150-230 mbar, black/yellow Spring (black/yellow) for VGBF 25-40 (150-230 mbar) and VAR 25-40 (151-220 mbar) for output pressure changes: for VGBF 25 and VGBF 40, Output pressure range 150 - 230 mbar for VAR 25 and VAR 40, Output pressure range 151 - 220 mbar
75438980	Spring 220-350 mbar, black/green Spring (black/green) for VGBF 25-40 (220-350 mbar) and VAR 25-40 (221-340 mbar) for output pressure changes: for VGBF 25 and VGBF 40, Output pressure range 220 - 350 mbar for VAR 25 and VAR 40, Output pressure range 221 - 340 mbar
VAS 125R/NQ	Gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 25 (1") Output: DN 25 (1") Pipe connection: Rp female thread Opening behavior: Quick opening, quick closing Quantity adjustment: With quantity adjustment Mains voltage: 120 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 locking screws Accessories on the left: 2 locking screws
	Gas burner control unit 84621650 Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54,

IFD 258-10/1W	EC model tested and certified, FM and CSA approved Series 200 Ionization or UV monitoring Immediate shutdown or restart after flame failure, switchable Safety time start-up: 10 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
VAS 1-/25R/NWSL	Gas solenoid valve 88006295 pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Input: Without input flange Output: DN 25 (1") Pipe connection: Rp female thread Opening behavior: Quick opening, quick closing Quantity adjustment: With quantity adjustment Mains voltage: 230 V~, 50/60 Hz Feedback: signaling switches and optical Position indicator, left-hand side Electrical connection: M20 screw connection Accessories on the right: Reserved for right in the direction of flow Bypass valve VAS 1 Accessories on the left: 2 locking screws
JSAV 100F50/1-0	Safety shut-off valve 03151136 Switch-off pressure set to 120 mbar New version: inlet pressure up to 5 bar Breathing line connection required To secure all fittings associated with a gas pressure regulator downstream are EC type tested and certified DN 100 Flange according to ISO 7005 pu max. 5 bar Upper response pressure pdo Without measuring point pdo set to 120 mbar
RFM 16RB100	Bourdon tube pressure gauge For displaying pressures, overpressure-proof, with Zero point correction, for gas and air Measuring range 0-16 bar R external thread Overpressure 100mm visible scale diameter
RFM 6RB100	Bourdon tube pressure gauge For displaying pressures, overpressure-proof, with Zero point correction, for gas and air Measuring range 0-6 bar R external thread Overpressure 100mm visible scale diameter
IC 20-30W3E	Actuator For emitting rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 30 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: Continuous control
IFD 244-3/1W	Gas burner control unit Ignites and monitors gas burners, for continuous operation, Ad for Program status and flame signal strength, IP 54, EC type tested and certified, FM and CSA approved Series 200 Ionization monitoring Restart after flameout Safety time start-up: 3 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
IFD 258-5/1W	Gas burner control unit Replaces mat. no. 84620630, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC model tested and certified, FM and CSA approved Series 200 Ionization or UV monitoring Immediate shutdown or restart after flame failure, switchable Safety time start-up: 5 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
CG 10R70-D2W5BW	Compact unit With dirt trap, pressure regulator, two solenoid valves and Quantity setting for securing and regulating atmospheric burners, Fan burners, fan-assisted boilers up to 50 kW, EC model tested and certified Size 10 Rp internal thread pu max. 70 mbar Pressure regulator with starting gas level pd max. 40 mbar Mains voltage 230 V~, 50/60 Hz Electrical connection with rectifier adapter without Power outlet Valve class B Pressure switch DG 35C
CGS71	
VAS 125R/NW	
VAS 115R/NW	Gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Output: DN 15 (1/2") Pipe connection: Rp female thread Opening behavior: Quick opening, quick closing Quantity adjustment: With quantity adjustment Mains voltage: 230 V~, 50/60 Hz Electrical connection: plug with socket Mounted on the right side of the connection box: plug for Valve (3 pole) Accessories on the right: 2 locking screws Accessories on the left: 2 locking screws
VAS 240R/NW	

IC 20-15Q3E	Actuator For emitting rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 15 s/90° Mains voltage: 120 V~, 50/60 Hz Torque: 3Nm Control: Continuous control
VMO 1-/25R05M10	Measuring aperture 88015987 To supplement valVario routes or as Single product Size: 1 Input: Without input flange Output: DN 25 (1") Pipe connection: Rp female thread Inlet pressure: pu max. 500 mbar (7 psig) Housing type: Basic (no accessories possible) Accessories above: measuring nozzle Aperture diameter: 10 mm
VCH 1E25R/25R05NHEVWR3/PPPP/PPPP	Volume flow controller with two solenoid valves 88100240 For gas and air, also for biogas, with control lamp, IP 65, complete assembled and checked for leaks Size: 1 Certification: EU certified Inlet: DN 25 (1") Pipe connection inlet: Rp internal thread Output: DN 25 (1") Pipe connection output: Rp internal thread Inlet pressure: pu max. 500 mbar (7 psig) Module 1: 1. Valve opens quickly, closes quickly Module 2: 2nd valve with volume flow controller, connection for Air control pressure: compression fitting Module 3: Fine adjustment valve Mains voltage: 230 V~, 50/60 Hz Flow direction: From left to right
VMO 365R05M50	Measuring aperture 88033176 To supplement valVario routes or as Single product Size: 3 Inlet: DN 65 (2 1/2") Output: DN 65 (2 1/2") Pipe connection: Rp female thread Inlet pressure: pu max. 500 mbar (7 psig) Housing type: Basic (no accessories possible) Accessories above: measuring nozzle Aperture diameter: 50 mm
IFD 258-5/1W	84621630 Gas burner control unit Replaces mat. no. 84620630, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC model tested and certified, FM and CSA approved Series 200 Ionization or UV monitoring Immediate shutdown or restart after flame failure, switchable Safety time start-up: 5 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
DG 500B-3 32Z	Gas pressure switch Bottom housing part rotated For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 100-500 mbar Function: Switches when the overpressure increases Electrical connection: With screw terminals and M16 cable gland, IP54 Packaging: Pack of 32
DG500B-3 32Z	
DG500B-3 32Z	
IFD258-5/1W	
DKR 200Z03F350D	Ring throttle valve for air and flue gas For constant control of a volume flow DN 200 Installation between two DIN flanges pu max. 300 mbar With free shaft end Temperature range 350°C
GDJ 15R04-4	Pressure regulator Spring-loaded, with pre-pressure compensation membrane and Zero degree, none Blow-out line required to keep the air constant adjustable pressure DN 15 Rp internal thread pu max. 400 mbar Measuring nozzle in the entrance For gas, EC type tested and certified Set to 20 mbar
DG 6UG-5	Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 0.4-6 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) With gold-plated contacts: Yes Electrical connection: With 4-pin plug, without Power outlet
VAS 780F05NW 3B/PP/PP	Gas solenoid valve For automatic locking, closed without power, for Natural gas, Liquefied gas and air, class A according to EN 161, with blue control lamp, IP 65, FM approved, EU certified Size: 7 Nominal diameter: DN 80 Pipe connection: Flange according to ISO 7005 Inlet pressure: pu max. 500 mbar Opening behavior: Quick opening, quick closing Mains

	<p>voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Mounted on the left side of the junction box: M20 screw connection Lateral processing: Basic Accessories on the right, input: screw plug Accessories on the right, output: screw plug Accessories on the left, input: screw plug</p>
VAS 780F05NW3B/PP/PP	<p>Gas solenoid valve For automatic locking, closed without power, for Natural gas, Liquefied gas and air, class A according to EN 161, with blue control lamp, IP 65, FM approved, EU certified Size: 7 Nominal diameter: DN 80 Pipe connection: Flange according to ISO 7005 Inlet pressure: pu max. 500 mbar Opening behavior: Quick opening, quick closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Mounted on the right side of the junction box: M20 screw connection Lateral processing: Basic Accessories on the right, input: screw plug Accessories on the right, output: screw plug Accessories on the left, input: screw plug</p>
FDU 510W0T2/1O1-0K1	<p>Flame detector For flame detection, EU certified Series: For intermittent operation Mains voltage: 230 V~, 50/60 Hz Flame control: Ionization Switch-off threshold: 2 micro A Reaction time in the event of flame failure: 1 s Flame report: 1 NC, 1 NO contact Flame signal intensity: No output Connection plugs: With screw terminals</p>
FDU 520W1T2/1O1-0K1	<p>Voltage 230 V 84368000 Flame guard For flame signaling, EU certified Series: For continuous operation Mains voltage: 230 V~, 50/60 Hz Flame monitoring: ionization Switch-off threshold: 2 micro A Response time after flame failure: 1 s Flame detection: 1 normally closed, 1 normally open contact Flame signal strength: No output Connection plug: With screw terminals</p>
BCU460W3P2C0D1000K1E0-/LM400WF3O0E0	BURNER CONTROL UNIT
IC 20-30W3E	<p>Actuator For emitting rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 30 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: Continuous control</p>
MH 15	<p>Pressure gauge shut-off valve Please send certificates to: m.systemtechnik@honeywell.com To protect a pressure gauge from pressure surges, for gas and air, DVGW tested and certified DN 15, Rp/R internal/external thread, pu max. 100 bar Set including; 03110621 4 piece Flat gasket 1/2" for pressure gauges CU version 99920281 2 piece Pressure gauge connection accessories for pressure gauge tap MH.. consisting of union nut G 1/2" and pressure gauge flat nipple 12 mm 99900135 2 piece Straight screw connection, type GERK On the one hand, cutting ring screw connection RVS 12 on the other hand, external pipe thread G 1/2" L series</p>
03110621	Flat gasket 1/2" for pressure gauges CU version
99920281	Pressure gauge connection accessories for pressure gauge tap MH.. consisting of union nut G 1/2" and pressure gauge flat nipple 12 mm
99900135	Straight screw connection, type GERK On the one hand, cutting ring screw connection RVS 12 on the other hand, external pipe thread G 1/2" L series
48136000	DH 15R50 Push button faucet To protect a pressure gauge from pressure surges, for gas and air, EC type tested and certified DN 15 Rp internal thread pu max. 5 bar Set including 1 piece 03110615 Pressure gauge seal 1/2" - Cu Profile seal with internal centering G 1/2", copper
03110615	Pressure gauge seal 1/2" - Cu Profile seal with internal centering G 1/2", copper
61004415	KH 15R50B Ball valve Yellow lever handle For manual shut-off, for natural gas, town gas, Liquefied gas, air, water and heating oil, EC type tested and certified DN 15 Rp internal thread pu max. 5 bar (HTB up to 0.1 bar) Housing: brass, ambient temperature: -20 to +60 °C
61004425	KH 25R50B Ball valve Yellow lever handle For manual shut-off, for natural gas, town gas, Liquefied gas, air, water and heating oil, EC type tested and certified DN 25 Rp internal thread pu max. 5 bar (HTB up to 0.1 bar) Housing: brass, ambient temperature: -20 to +60 °C

61004440	KH 40R50B Ball valve Yellow lever handle For manual shut-off, for natural gas, town gas, Liquefied gas, air, water and heating oil, EC type tested and certified DN 40 Rp internal thread pu max. 5 bar (HTB up to 0.1 bar) Housing: brass, ambient temperature: -20 to +60 °C
61004450	KH50R50B Ball valve Yellow lever handle For manual shut-off, for natural gas, town gas, Liquefied gas, air, water and heating oil, EC type tested and certified DN 50 Rp internal thread pu max. 5 bar (HTB up to 0.1 bar) Housing: brass, ambient temperature: -20 to +60 °C
34331381	84331381 Ignition transformer For high-voltage ignition of gas and oil burners High voltage 5 kV Output current 15 mA at 50 Hz Duty cycle 100% Mains voltage 230 V~
DG 50U-3	84447350 Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 2.5-50 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54
DG 6U-3	84447250 Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 0.4-6 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54
UVS 10D0G1	84315200 UV probe For monitoring gas burners in intermittent mode Operation, EC type tested and certified in conjunction with magpie Kromschröder gas burner controls Series 10 Thermal protection made of quartz glass Rp 1/2 internal thread M20 screw connection
IFD 258-5/1W	84621630 Gas burner control unit Replaces mat. no. 84620630, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC model tested and certified, FM and CSA approved Series 200 Ionization or UV monitoring Immediate shutdown or restart after flame failure, switchable Safety time start-up: 5 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
VAG 115R/NWBE	88000141 Constant pressure regulator with solenoid valve To secure and regulate the gas pressure, pressure regulator Class A according to EN 88, solenoid valve class A according to EN 161, for gas and air, also for Biogas, pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Output: DN 15 (1/2") Pipe connection: Rp female thread Opening behavior: Quick opening, quick closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Valve seat: Reduced in size Connection set for air control pressure psa: 1 Clamping ring screw connection, 2 Measuring nozzles pd and psa Accessories on the right: 2 locking screws
VAS 115R/NW	88000003 Gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Output: DN 15 (1/2") Pipe connection: Rp female thread Opening behavior: Quick opening, quick closing Quantity adjustment: With quantity adjustment Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 locking screws Accessories on the left: 2 locking screws
GDJ 40R04-0L	03155034 Pressure regulator Spring-loaded, with pre-pressure compensation membrane and zero termination, none Blow-out line required to keep the adjustable pressure constant DN 40 Rp internal thread pu max. 400 mbar Without measuring point Just for air Set to 20 mbar
BCU480-5/3/1LW3GB	
	Control valve with solenoid valve For controlling continuously regulated combustion processes, linear Relationship between input signal and

RVS 50/LF03W60S1-3	volume flow, Control ratio 100:1, for Gas and air, EU certified DN 50 Valve seat L Flange according to ISO 7005 pu max. 360 mbar Mains voltage 230 V~, 50/60 Hz 60 s running time Three-point step control Solenoid valve connection box with terminals
VAS 115R/NO	Gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Output: DN 15 (1/2") Pipe connection: Rp female thread Opening behavior: Quick opening, quick closing Quantity adjustment: With quantity adjustment Mains voltage: 120 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 locking screws Accessories on the left: 2 locking screws
GRSF 15R	03150672 Gas non-return valve, flameproof combustion with air To prevent gradual and sudden Gas return, for Gas, air and oxygen, DVGW tested and registered DN 15 G internal thread Flame transmission resistant up to pu max. 5 bar natural gas, LPG pu max. 1.5 bar town gas, hydrogen
ZAI K	Atmospheric ionization ignition burner For safely igniting gas burners, power approx. 3 kW Conical ring screw connection for 8 mm pipe, enclosed loosely
BR 65HB(34) BIO 65HB 35(34)	
BR65 BIO 65HB 35(34)	
IFD 258-5/1W	Gas burner control unit Replaces mat. no. 84620630, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC model tested and certified, FM and CSA approved Series 200 Ionization or UV monitoring Immediate shutdown or restart after flame failure, switchable Safety time start-up: 5 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
74330421	BR 65HB(34) BIO 65HB 35(34) BRUİLDER HEAD
74923436	BR65 BIO 65HB 35(34) GAS FLOW REGULATOR SET
DG 150U-6	Gas pressure switch For monitoring gas and air pressures, also for biogas, with handwheel for setting the switching point, can be used as a "pressure switch of a special design", EU-certified Setting range: 30-150 mbar Function: Switches when excess pressure (gas/air), negative pressure (air), differential pressure (air-air) increases Electrical connection: With 4-pin plug, with socket
DG 50U-5	Gas pressure switch For monitoring gas and air pressures, also for biogas, with handwheel for setting the switching point, can be used as a "pressure switch of a special design", EU-certified Setting range: 2.5-50 mbar Function: Switches when excess pressure (gas/air), negative pressure (air), differential pressure (air-air) increases Electrical connection: With 4-pin plug, without socket
DG 6UG-6K2	Gas pressure switch For monitoring gas and air pressures, also for biogas, with handwheel for setting the switching point, can be used as a "pressure switch of a special design", EU-certified Setting range: 0.4-6 mbar Function: Switches when excess pressure (gas/air), negative pressure (air), differential pressure (air-air) increases With gold-plated contacts: Yes Electrical connection: With 4-pin plug, with socket Feedback: Red/green control LED for 24 V~/=
GRSF 15R	Gas non-return valve, flame-proof when combusting with air To prevent gradual and sudden gas backflow, for gas, air and oxygen, DVGW tested and registered DN 15 G internal thread Flame-proof up to pu max. 5 bar natural gas, LPG pu max. 1.5 bar town gas, hydrogen
IC 20-15W3E	Actuator For emitting rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 15 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: Continuous control
MPT 700	

BIC 100HB-100/135-(37)E	Burner for gas, with connection for ceramic tube Burner size 100 Longer flame shape For natural gas 100 mm length of steel tube from furnace flange 135 mm distance from furnace flange to front edge of burner head Burner head code 37 Construction status E
BVH 80Z01A	Throttle valve for air and flue gas up to 450 °C For continuous or step-by-step control of a volume flow Nominal diameter: DN 80 Pipe connection: Installation between two DIN flanges Inlet pressure: pu max. 150 mbar (60 "WC) Design: With stop bar
IC 40A2A	Actuator For delivering rotary movements (0-90°), for operating gas and air flaps, position feedback via externally readable position indicator, protection class IP 65 Series: 40, parameterizable via optical interface Running time: Adjustable from 4.5 to max. 75 s Mains voltage: 120-230 V~, 50/60 Hz Torque: 2 Nm Control: Analog input 4-20 mA and digital inputs Parameter set: 68026, operating mode 21, 2-point operation, Running time: 7.5 s
BVA 80Z05	Throttle valve for air For continuous or step-by-step control of a volume flow Nominal diameter: DN 80 Pipe connection: Installation between two DIN flanges Inlet pressure: pu max. 500 mbar (200 "WC) Design: Through-flow
BCU460-5/1W1GB	230VAC 50Hz E.1149-009067 FW 15AA, IP54, -20/+60C
VAS 115R/LW+VBY 8IW	
BIO 65HB-300/235-(34)E	Burner for gas, for installation in burner block Burner size 65 Longer flame shape For natural gas 300 mm length of steel pipe from furnace flange 235 mm distance from furnace flange to front edge of burner head Burner head code number 34 Construction status E
VGP 15R02W6Z	Gas solenoid valve with Pg 9 plug For automatic shut-off, closed without current, quick opening, quick closing, for natural gas, town gas, liquid gas, biogas and air, Class A according to EN 161, EC type tested and certified DN 15 Rp internal thread pu max. 200 mbar Mains voltage 230 V~, 50/60 Hz Connection with rectifier adapter and standard socket
BIO 65HB-300/235-(34A)E	Burner for gas, for installation in burner block Burner size 65 Longer flame shape For natural gas 300 mm length of steel pipe from furnace flange 235 mm distance from furnace flange to front edge of burner head Burner head code 34 Burner head: heat-resistant Construction status E
BIO 65HB-300/235-(34A)EB	Burner for gas with attachment pipe, only for cold air Burner size 65 Longer flame shape For natural gas 300 mm length of the steel pipe from the furnace flange 235 mm distance from the furnace flange to the front edge of the burner head Burner head code number 34 Burner head: heat-resistant Construction status E With purge air holes
84228010	ZAI K Atmospheric ionization ignition burner For the safe ignition of gas burners, output approx. 3 kW Conical ring screw connection for 8 mm pipe, enclosed loose
84359020	IFW 15-T Flame monitor 'When replacing IFW 15-T 84359010; (without transformer)' please follow the conversion instructions. In the scope of European directives, this product may only be used for replacement purposes. For multi-flame monitoring with IFS 110/111IM, for intermittent operation Ionization or UV monitoring Mains voltage 220/240 V~, 50/60 Hz, for earthed or earth-free networks
84391150	TZI 5-15/100WE Ignition transformer For high-voltage ignition of gas and oil burners High voltage 5 kV Output current 15 mA at 50 Hz Duty cycle 100% Mains voltage 230 V~ EU certified
VAS 120R/NWGR	Gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU-certified Inlet: DN 20 (3/4") Outlet: DN 20 (3/4") Pipe connection: Rp internal thread Opening behavior: Quick opening, quick closing Quantity setting: With quantity setting Mains voltage: 230 V~, 50/60 Hz Feedback: Signal switch for 24 V and optical position indicator, right-hand side Electrical connection: Plug with socket Mounted on the left side of the connection box: Plug for valve (3-pin) Mounted on

	the right side of the connection box: Plug for
IFD 258 - 10/1W	
VFC 125/25R05-20PPPP	Linear actuator For controlling continuously regulated combustion processes, linear relationship between input signal and volume flow, control ratio 25:1, for gas and air, EU-certified Size: 1 Input: DN 25 (1") Output: DN 25 (1") Pipe connection: Rp internal thread Input pressure: pu max. 500 mbar (7 psig) Cylinder: 20 Accessories on the right: 2 locking screws Accessories on the left: 2 locking screws
IC 20-30W3E	Actuator For delivering rotary movements (0-90°), for operating gas and air flaps, position feedback via externally readable position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 30 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3 Nm Control: Continuous control
VFC 125/25R05-20PPPP	Linear actuator For controlling continuously regulated combustion processes, linear relationship between input signal and volume flow, control ratio 25:1, for gas and air, EU-certified Size: 1 Input: DN 25 (1") Output: DN 25 (1") Pipe connection: Rp internal thread Input pressure: pu max. 500 mbar (7 psig) Cylinder: 20 Accessories on the right: 2 locking screws Accessories on the left: 2 locking screws
DKR 100	BUTTERFLY VALVE 2 1/2" PN16 , W , TE
BCU370WI1FEU0D1	88601642 Burner control, series 300 On-site housing for controlling, igniting and monitoring modulating fan burners. For continuous operation with ionization monitoring or UV monitoring with UVD UV probe. Intermittent operation with UVS UV probe. Display of the program status, the device parameters and the flame signal. Manual operation mode. Diagnosis and setting of the device parameters via optical interface and PC software BCSoft. EU-certified. AGA approved. Market: European market, EU-certified Mains voltage: 230 V~, 50/60 Hz Electronic ignition: Single-pole Fan control: Relay 3 A Flap control: Three-point step Flame monitoring: Ionic (continuous operation/intermittent) or UV
VCS 2E40R/40R05FNNWR3/PPPP/PPPP	88101234 Double solenoid valve For gas and air, also for biogas, with control lamp, IP 65, fully assembled and tested for leaks Size: 2 Certification: EU-certified Input: DN 40 (1 1/2") Pipe connection input: Rp internal thread Output: DN 40 (1 1/2") Pipe connection output: Rp internal thread Input pressure: pu max. 500 mbar (7 psig) Module 0: Filter module Module 1: 1st valve quick opening, quick closing Module 2: 2nd valve quick opening, quick closing Mains voltage: 230 V~, 50/60 Hz Flow direction: From left to right Electrical connection: M20 screw connection
DKR 100Z03H100D	Ring throttle valve for air and flue gas For continuous control of a volume flow DN 100 Installation between two DIN flanges pu max. 300 mbar With manual adjustment Temperature range 100 °C Permeable
DG 50B-3	Gas pressure switch For monitoring gas and air pressures, also for biogas, with handwheel for setting the switching point, can be used as a "pressure switch of a special design", EU-certified Setting range: 2.5-50 mbar Function: Switches when excess pressure increases Electrical connection: With screw terminals and M16 cable gland, IP 54
VBY 8IW6L-RBD	Bypass valve For securing bypass sections on valVario, EC type tested and certified DN 8 Internal bypass Mains voltage 230 V~, 50/60 Hz Connection box with plug and socket with LED Mounting side of the main valve: right Included (sold individually) Quantity setting
VAS 115R/LW	Gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU-certified Inlet: DN 15 (1/2") Outlet: DN 15 (1/2") Pipe connection: Rp internal thread Opening behavior: Slow opening, quick closing Quantity setting: With quantity setting Mains voltage: 230 V~, 50/60 Hz Electrical connection: Plug with socket Accessories on the right: 2 measuring nozzles pu and pd Accessories on the left: 2 measuring nozzles pu and pd
VBY 8IW6L-RBD	Bypass valve For securing bypass sections on valVario, EC type tested and certified DN 8 Internal bypass Mains voltage 230 V~, 50/60 Hz Connection box with plug and socket with LED Mounting side of the main valve: right

	Included (sold individually) Quantity setting
VAA 350R/RW	
VAS 120R/LW+VBY	
VAA 240R/RW	Air solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 2 Certification: EU-certified Inlet: DN 40 (1 1/2") Outlet: DN 40 (1 1/2") Pipe connection: Rp internal thread Opening behavior: Slow opening, slow closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 locking screws Accessories on the left: 2 locking screws
VAS 120R/LW	Gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU-certified Inlet: DN 20 (3/4") Outlet: DN 20 (3/4") Pipe connection: Rp internal thread Opening behavior: Slow opening, quick closing Quantity setting: With quantity setting Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: Bypass valve, DN 8, 230 V~, socket, Quantity setting Accessories on the left: 2 locking screws
VAA 350R/RW	Air solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 3 Certification: EU-certified Inlet: DN 50 (2") Outlet: DN 50 (2") Pipe connection: Rp internal thread Opening behavior: Slow opening, slow closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 locking screws Accessories on the left: 2 locking screws
VAA 240R/RW	Air solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 2 Certification: EU-certified Inlet: DN 40 (1 1/2") Outlet: DN 40 (1 1/2") Pipe connection: Rp internal thread Opening behavior: Slow opening, slow closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 locking screws Accessories on the left: 2 locking screws
UVS 10D0G1	UV probe For monitoring gas burners in intermittent operation, EC type tested and certified in conjunction with Elster Kromschöder gas burner controls Series 10 Thermal protection made of quartz glass Rp 1/2 internal thread M20 screw connection
PCO 200 USB IR-ADAPTER inkl.CD-ROM	PCO 200 (USB IR-ADAPTER) incl. CD-ROM For diagnosis and parameterization of BCU, PFU, FCU and IC40. Adapter with magnetic holder for connection to device interface. USB connector type A, USB 1.1 interface; cable length 3.0 m. Software: From Windows 98, overview of process values, setting and documentation of device parameters, reading of statistical data, line recorder function
BCU 480W3P2C0D0000K1E0-/LM400WF300E0-	Burner control On-site housing for controlling, igniting and monitoring pulse-controlled, modulating or step-controlled gas burners. For continuous operation with ionization monitoring or UV monitoring with UVD UV probe. Intermittent operation with UV probe UVS. Display of the program status, the device parameters and the flame signal. Manual operation mode. Diagnosis and setting of the device parameters via optical interface and PC software BCSof. EU-certified, FM and EAC approved, certified for systems up to SIL 3 (corresponds to PL e). Series: Version for ignition and main burners Mains voltage: 230 V~, 50/60 Hz Ignition transformer: 8 kV, 12 mA, ED 100% Flange plate: M32 Valve monitoring system: Without High temperature operation: Without Input function: Without Pressure switch: Without Connection plug: With screw terminals Packaging: Individual packaging Power supply: Via safety chain Power module: Power module Series: 400 Mains voltage: 230 V~, 50/60 Hz Air actuator: With air valve control Optional output: Without Power supply: Via safety chain I004 Flame monitoring: Ionization I050 Function contact 80, 81/82: Fault message I051 Function contact 90, 91/92: Ready message I052 Function contact 95/96: Burner 1 operating message I053 Function contact 95/97: Burner 2 operating message I054 Function contact 85/86, 87: Air message I061 Function terminal 1: Start 1 I062 Function terminal 2: Reset I063 Function terminal 3: Purge I064 Function terminal 4: Air I065 Function terminal 5: Start 2 I068 Function terminal 35: Safety chain A001 Burner 1 shutdown threshold: 2 micro A A002 Burner 2 shutdown threshold: 2 micro A A003 External light test: In standby A007

	<p>Burner 1 start-up attempts: 1 A008 Burner 2 start-up attempts: 1 A093 Pre-ignition time tVZ: 0 s A094 1st start-up safety time: 5 s A095 Flame stabilization time 1 tFS1: 0 s A096 2nd safety time start-up: 3 s A097 Flame stabilization time 2 tFS2: 0 s A078 Burner application: Burner 1 and burner 2 A079 Ignition burner: Externally controlled A009 Restart: No A074 Combustion operating mode: Flame operation A043 Run-on: Off A039 Run- on duration: 0 s A048 Air actuator control: Opens when externally controlled A129 Active cooling outputs: Air actuator A041 Run time selection: On, for moving to the positions for minimum/maximum power A042 Run time: 1 s A049 Air actuator when starting up: Cannot be controlled externally A050 Air actuator in the event of a fault: Can be controlled externally</p>
85311323	<p>VK 150F10T5HA93S2V Gas motor valve For automatic shut-off, closed without power, slow opening, quick closing, for natural gas, town gas, liquid gas and air, also suitable for biogas and landfill gas, class A according to EN 161, EC type-tested and certified DN 150 Flange according to ISO 7005 pu max. 1 bar Mains voltage 220/240 V~, 50 Hz Reinforced drive Valve housing AISi Metal connection box with terminals, IP 54 Closing screws in the inlet and outlet 2 signal switches Viton sealing elements</p>
Spare parts pack GDJ/GIK 50	(CONSISTING OF MEMBRANE AND SEAL)
TZI 5-15/100WE	<p>Ignition transformer For high-voltage ignition of gas and oil burners High voltage 5 kV Output current 15 mA at 50 Hz Duty cycle 100% Mains voltage 230 V~ EU certified</p>
DL 3E-1	<p>Air pressure switch For monitoring air and flue gas pressures, for overpressure, underpressure and differential pressure, EC type tested and certified Setting range 0.3-3 mbar, can be used as a "pressure switch of a special design" Flat plug, hose connection and adjustment screw Electrical connection with AMP plugs (UR-approved)</p>
QA 250Z100-40	<p>flow meter For non-calibration gas quantity measurement, display of consumed quantity, with pulse generators E1 and E200 Nominal flow rate: 250 m3/h measuring range 20-400 m3/h(b) intermediate flange DN 100, E1: 1 Imp/m3, E200: 187.5 Imp/m3 pu max. 4 bar, for gas and air QA 250Z100-40 flow meter For metering gas where no calibration is required, display of the quantity consumed, with E1 and E200 pulse generators Nominal flow rate: 250 m3/h, measuring range: 20-400 m3/h(b) Intermediate flange DN 100, E1: 1 pulse/m3, E200: 187.5 pulses/m3 pu max. 4 bar, for gas and air</p>
48115426	<p>REFALIT flange seal DN 100 - HTB PN 10/16 DIN 2690, without holes, 115 x 162 x 2.0 mm, code according to DIN 30690-1: Date of manufacture, material, 2.2 certificate and torque calculation for screws 5.6 for flange connections according to DIN 30690-1 and DVGW Information Gas No. 19</p>
48127010	<p>IC-M1D pulse storage module remote meter display and M-Bus converter Operation without power supply, power supply from M-Bus • Integrated battery to bridge bus failures • Full counting function even with battery operation (bus failure) • Complete data retention in the event of a power failure • Connection of potential-free pulse generators (reed contact, optocouplers) • Connection of pulse generators with electronic S0 interface (open collector) according to DIN 43864 • Counter reading, pulse value and unit can be adjusted • A freely programmable deadline and 12 previous month's end values • Wall mounting • Connection cable for pulse signals max. length 30 cm If you wish, we can adjust the ICM. Please specify meter type or CP value when ordering and if required Specify primary address MBUS.</p>
99999019	<p>Programming the IC-M1D M-Bus pulse storage module according to customer requirements</p>
VAA 350F/NQ	<p>88035850 air solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 3 Certification: EU-certified Inlet: DN 50 (2") Outlet: DN 50 (2") Pipe connection: Flange according to ISO 7005 Opening behavior: Fast opening, fast closing Mains voltage: 120 V~, 50/60 Hz Electrical connection: plug with socket Mounted on the right side of the junction box: plug for valve (3-pole) Accessory right: Variable bypass Accessory left: 2 locking screws</p>

DG500U-3 84447550	
gfk 15R40-4	
DKR 80Z03H100D	ring throttle valve for air and flue gas For continuous control of a volume flow DN 80 Installation between two DIN flanges pu max. 300 mbar With manual adjustment temperature range 100 °C Resounding
DKR 80Z03H450D	ring throttle valve for air and flue gas For continuous control of a volume flow DN 80 Installation between two DIN flanges pu max. 300 mbar With manual adjustment temperature range 450 °C Resounding
VR 50F01NQ6L3D3,0Z	BYPASS BOREHOLE 3 MM. 120VAC,50/60HZ
842214030	
84447520 DG 150UG-3	gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as "Pressure switch special type", EU-certified Setting range: 30-150 mbar Function: Switches when overpressure increases (gas/air), negative pressure (air), differential pressure (air-air) With gold-plated contacts: Yes Electrical connection: With screw terminals and M16 cable gland, IP 54
84315201 UVS 10L0G1	UV probe For monitoring gas burners in intermittent operation, EC type tested and certified in connection with magpie Kromschröder gas burner controls series 10 Thermal protection made of quartz glass in lens form Rp 1/2 internal thread M20 screw connection
84765716 TC 3R05W/W	leak test To check two safety valves before and/or after burner run, with adjustable measuring time (5-30 s) to adapt to different test volumes, leak rates and inlet pressures, EU-certified For fast or slow opening single valves Rp internal thread pu max. 500 mbar Mains voltage: 230 V~, 50/60 Hz Control voltage 230 V~, 50/60 Hz
84621650 IFD 258-10/1W	gas burner control unit replaces Mat.No. 84620650, compatible Ignites and monitors gas burners, for continuous operation with ionization monitoring, shutdown sensitivity adjustable, display for program status and flame signal strength, IP 54, EC type tested and certified, FM and CSA approved 200 series ionization or UV monitoring Immediate shutdown or restart after flameout, switchable Safety time start-up: 10 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
84621610 IFD 258-3/1W	gas burner control unit replaces Mat.No. 84620610 IFS 258-3/1W, compatible Ignites and monitors gas burners, for continuous operation with ionization monitoring, shutdown sensitivity adjustable, display for program status and flame signal strength, IP 54, EC type tested and certified, FM and CSA approved 200 series ionization or UV monitoring Immediate shutdown or restart after flameout, switchable Safety time start-up: 3 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
88300059 IC 20-15W 3T	actuator For the delivery of rotary movements (0-90°), for Operation of gas and Air flaps, position feedback via outside readable position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 15 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3 Nm Control: Three-point step control
88300075 IC 20-15W 3E	actuator For the delivery of rotary movements (0-90°), for Operation of gas and Air flaps, position feedback via outside readable position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 15 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3 Nm Control: Continuous control
85234510 VG 15/10R01T6G	gas solenoid valve For automatic shut-off, without power closed, quick opening, quick closing, for natural gas, town gas, LPG and air, class A according to EN 161, EC type tested and certified DN 15/10 Rp internal thread pu max. 100 mbar Mains voltage 220/240 V~, 50/60 Hz Connection with standard 3-pin plug and socket Low noise
TZI 5-15 /100 W 84331381	
	pressure regulator Spring loaded, with pre-pressure compensation

GDJ 25TN04-0	membrane and zero balance, to Maintaining the adjustable pressure of the gas or air supply to gas burners and gas appliances DN 25 NPT internal thread pu max. 5 psig (350 mbar) Without measuring point For gas
88000029	
85092220	GIK 65F02-6 constant pressure regulator To maintain a constant pressure ratio of 1:1 DN 65 flange according to ISO 7005 pu max. 200 mbar measuring nozzles in the inlet and outlet For gas, EC type tested and certified
DG 110VC1-6WG /B	For monitoring gas and air pressures, also for biogas, factory-made set switching point, EC type tested and certified setting range 30-110 mbar Switching point adjustable via handwheel Compact design Bottom connection for valVario, pressure recording at the connector side El. connection with 4-pin plug, with socket changeover contact With gold-plated contacts In the package
VG 20R02LQ6L1DZ	DN20-,PN16
IC 20-60W3T	actuator For the delivery of rotary movements (0-90°), for operation of gas and air flaps, Position feedback via externally readable position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 60 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3 Nm Control: Three-point step control
84230020	ZMI 16B200R pilot burner With an ignition and monitoring electrode for safe ignition of gas burners, with forced air supply 16 mm burner size For natural gas 200 mm length Rp internal thread
VAS1 - 25R/LW 88003481	220 Volt
VAD125/88003466	220 volt
VAS1-O/NW 88000112	220 Volt
84320305	
GFK 25R40-4	
DKR 80Z03F100D	Ring throttle valve for air and flue gas For continuous control of a Volume flow DN80 Installation between two DIN flanges pu max. 300 mbar With free shaft end Temperature range 100 °C Resounding DKR 80Z03F100D Butterfly valve for air and flue gas For continuous control of flow rates DN80 For fitting between two DIN flanges pu max. 300 mbar With free shaft end Temperature range: 100°C With disc clearance
UVS 10D0G1 84315200 UV	DETECTOR
DKR 80Z03F450D	Ring throttle valve for air and flue gas For continuous control of a Volume flow DN80 Installation between two DIN flanges pu max. 300 mbar With free shaft end Temperature range 450 °C Resounding DKR 80Z03F450D Butterfly valve for air and flue gas For continuous control of flow rates DN80 For fitting between two DIN flanges pu max. 300 mbar With free shaft end Temperature range: 450°C With disc clearance
VAH 115R/NWBE-	Volume flow controller with solenoid valve To secure and regulate the gas pressure, Pressure regulator class A according to EN 88, Solenoid valve Class A according to EN 161, for Gas and air, also for biogas, pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Outlet: DN 15 (1/2") Pipe connection: Rp internal thread Opening behavior: Quick opening, quick closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Valve seat: Reduced Connection set for air control pressure psa: 1 Clamp ring screw connection, 2 measuring nozzles pd and psa Accessory right: 2 locking screws Accessory left: 2 locking screws VAH 115R/NWBE Flow rate regulator with solenoid valve For safeguarding and control of the gas pressure, Class A pressure regulator to EN 88, Class A solenoid valve to EN 161, for gas, air and biologically produced methane, pu max. 500 mbar (7 psig), with pilot lamp, IP65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Outlet: DN 15 (1/2") Pipe connection: Rp internal thread Opening properties: Quick opening, quick closing Mains voltage: 230 V~,

	50/60 Hz Electrical connection: M20 cable gland Valve seat: Reduced Connection kit for air control pressure psa: 1 compression fitting, 2 pressure test points pd and psa Accessories, right: 2 screw plugs Accessories, left: 2 screw plugs
IFD 258	
DG6B-3 84447100	
GIK 25R02-5-	Air-conditioning regulator To maintain a constant Pressure ratio 1:1 DN25 Rp internal thread pu max. 200 mbar Measuring nozzle in the outlet For gas, EC type tested and certified GIK 25R02-5 Ratio control To maintain a constant pressure ratio of 1:1 DN25 Rp internal thread pu max. 200 mbar Pressure test point at the outlet For gas, EC type-tested and certified
RV 2/ZML10W60S1	control valve For controlling continuously regulated Burning processes, linear relationship between input signal and Volume flow, control ratio 100:1, for Gas and air, EU-certified Size 2 Valve seat Z MODULINE system pu max. 1000 mbar Mains voltage 230 V~, 50/60 Hz 60 s running time Three-point step control RV 2/ZML10W60S1 Control valve For controlling continuously regulated burner processes, linear ratio between input signal and flow rate, control ratio 100:1, for gas and air, EU certified Size 2 Valve seat Z MODULINE system pu max. 1000 mbar Mains voltage: 230 V AC, 50/60 Hz 60 s running time Three-point step control
DG60VC5-5W	
DG50VC5-5W	
DM 400Z100-160	
84447083	DG 12IG-6 Gas pressure switch Low pressure monitor For monitoring gas and Air suppression, also for biogas, with Handwheel for switching point adjustment, EU-certified Setting range: +7 - +1 mbar and -1 - -12 mbar Gas type: negative pressure for gas With gold-plated contacts: Yes Electrical connection: With 4-pin plug, with socket, IP 54 DG 12IG-6 Pressure switch for gas For monitoring negative gas and air pressures, also for biologically produced methane, with hand wheel for switching point adjustment, EU certified Adjusting range: +7 ? +1 mbar and -1 ? -12 mbar Gas type: Negative pressure for gas With gold-plated contacts: Yes Electrical connection: Via 4-pin plug, with socket, IP 54
ZKIH 400/100R	pilot burner For safe ignition of gas burners, with forced air supply 400 mm length Additional 100 mm Rp internal thread ZKIH 400/100R Pilot burner For safely igniting gas burners, with forced air supply Length: 400 mm Plus 100 mm Rp internal thread
ZKIH 600/100R	pilot burner For safe ignition of gas burners, with forced air supply 600 mm length Additional 100 mm Rp internal thread ZKIH 600/100R Pilot burner For safely igniting gas burners, with forced air supply Length: 600 mm Plus 100 mm Rp internal thread
UVS 10D4G1-	UV probe For monitoring gas burners in intermittent operation, EC type tested and certified in Connection with Elster Kromschr¼der gas burner controls Series 10 Thermal insulation made of quartz glass UVS 1 adapter (28 mm (1.1")) M20 screw connection UVS 10D4G1 UV sensor For monitoring gas burners in intermittent operation, EC type-tested and certified in conjunction with Elster Kromschr¼der automatic burner control units Series 10 Quartz glass heat guard UVS 1 adapter (28 mm (1.1")) M20 cable gland
KS8422801084228010 ZAI K	Atmospheric ionization ignition burner For safe ignition of gas burners, Power approx. 3 kW Conical ring screw connection for pipe 8 mm, enclosed loose ZAI K Atmospheric ionization pilot burner For safely igniting gas burners, capacity: approx. 3 kW Double-cone olive for 8 mm tube loosely enclosed
	Gas solenoid valve pu max. 500 mbar (7 psig), with Control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 25 (1") Outlet: DN 25 (1") Pipe connection: Rp internal thread Opening behavior: Quick opening, quick closing Quantity setting: With quantity setting Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessory right: 2

88000005 VAS 125R/NW	locking screws Accessories left: 2 locking screws VAS 125R/NW Gas solenoid valve pu max. 500 mbar (7 psig), with pilot lamp, IP65 Size: 1 Certification: EU certified Inlet: DN 25 (1") Outlet: DN 25 (1") Pipe connection: Rp internal thread Opening properties: Quick opening, quick closing Flow adjustment: With flow adjustment Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 cable gland Accessories, right: 2 screw plugs Accessories, left: 2 screw plugs
KS84359020	
KS84367440	
84444470	DL 5A-31
84444480	(DL 10A-31
47010225	BK-G2.5 MT V1.2 DN25 Single-nozzle diaphragm gas meter Brand Elster, measuring range 0.025 - 4 m³/h Connection DN 25 Pmax 0.1 bar HTB incl. calibration fee approved according to DIN EN 1359 Pulse magnet for I=0.01 m³/Imp Gas temperature -10°C to + 40°C
72910109	Low-frequency pulse pickup IN-Z61 including plug and 2 m cable Retrofit kit for all diaphragm gas meters BK-G2.5 to BK-G100
Optional 48200027	Ball valve for single-pipe meter Through-type with wall bracket DN 25, bds 22 mm press connection Input press fitting 22, Outlet press fitting 22, Pressure measuring point G 1/8", MOP5, -20°C to +60°C, HTB 650° for 30 min. (DIN 3331 B0.1)
84391170 TZI 8-12/100WE	ignition transformer For high-voltage ignition of gas and Oil burners High voltage: 8 kV Output current: 12 mA at 50 Hz Duty cycle: 100% Mains voltage: 230 V~ Market: EU-certified TZI 8-12/100WE Ignition transformer For high-voltage spark ignition of gas or oil burners High voltage: 8 kV Output current: 12 mA at 50 Hz Duty cycle: 100% Mains voltage: 230 V~ Market: EU certified
81943190 GFK 80F10-6	Gas filter With filter mat made of random fiber fleece (polypropylene), for cleaning Gas (natural gas, town gas, liquefied petroleum gas, biogas) and air, EC type tested and certified DN80 Flange according to ISO 7005 pu max. 1 bar Measuring nozzles in the inlet and outlet GRP 80F10-6 Gas filter With (polypropylene) fleece filter pads, for cleaning gas (natural gas, town gas, LPG, biologically produced methane) and air, EC type-tested and certified DN80 Flange to ISO 7005 pu max. 1 bar Pressure test point at the inlet and outlet
85092220 GIK 65F02-6	Air-conditioning regulator To maintain a constant Pressure ratio 1:1 DN65 Flange according to ISO 7005 pu max. 200 mbar Measuring nozzles in the inlet and outlet For gas, EC type tested and certified GIK65F02-6 Ratio control To maintain a constant pressure ratio of 1:1 DN65 Flange to ISO 7005 pu max. 200 mbar Pressure test point at the inlet and outlet For gas, EC type-tested and certified
84391140 TZI 8-20/33QE	ignition transformer For high-voltage ignition of gas and Oil burners High voltage: 8 kV Output current: 20 mA at 50 Hz Duty cycle: 33% Mains voltage: 120 V~ Market: EU-certified TZI 8-20/33QE Ignition transformer For high-voltage spark ignition of gas or oil burners High voltage: 8 kV Output current: 20 mA at 50 Hz Duty cycle: 33% Mains voltage: 120 V~ Market: EU certified
03200124 KFM 160RB100	Capsule pressure gauge For displaying pressures, overpressure resistant, with zero point correction, for gas and air Measuring range 0-160 mbar R-external thread Overpressure 100 mm visible scale diameter KFM 160RB100 Pressure gauge with capsule element For pressure display, positive pressure proof, with zero point correction, for gas and air Measuring range: 0-160 mbar R external thread Positive pressure 100 mm visible scale diameter
TZI 8-20/33QE	
KFM 160RB100	
DG 150U-3-	

<p>84368012 FDU 510W0T2/1O1-0K1</p>	<p>Flame monitor For flame signaling, EU-certified Series: For intermittent operation Mains voltage: 230 V~, 50/60 Hz Flame monitoring: Ionization Switch-off threshold: 2 micro A Reaction time after flame failure: 1 s Flame detection: 1 normally closed, 1 normally open contact Flame signal strength: No output Connection plug: With screw terminals FDU 510W0T2/1O1-0K1 Flame detector For flame detection, EU certified Series: For intermittent operation Mains voltage: 230 V~, 50/60 Hz Flame control: Ionization Switch-off threshold: 2 micro A Reaction time in the event of flame failure: 1 s Flame report: 1 NC, 1 NO contact Flame signal intensity: No output Connection plugs: With screw terminals</p>
<p>Alternatively 84368013 FDU 510W1T5/1O1-0K1</p>	<p>Flame monitor For flame signaling, EU-certified Series: For intermittent operation Mains voltage: 230 V~, 50/60 Hz Flame monitoring: UV probe UVS Switch-off threshold: 5 micro A Reaction time after flame failure: 1 s Flame detection: 1 normally closed, 1 normally open contact Flame signal strength: No output Connection plug: With screw terminals FDU 510W1T5/1O1-0K1 Flame detector For flame detection, EU certified Series: For intermittent operation Mains voltage: 230 V~, 50/60 Hz Flame control: UV sensor UVS Switch-off threshold: 5 micro A Reaction time in the event of flame failure: 1 s Flame report: 1 NC, 1 NO contact Flame signal intensity: No output Connection plugs: With screw terminals</p>
<p>84367440 IFS 110IM-W-10/1/1T *Inaktivteil*</p>	<p>Gas burner control unit New construction status. Function and Connection assignments have remained the same. Within the scope of European Directives, this product may only be used for replacement purposes. Ignites and monitors gas burners, for intermittent surgery, Ionization or UV monitoring, Single electrode operation possible, Multi-flame monitoring possible, EC type tested and certified For grounded networks Restart after flame failure Safety time start-up: 10 s Safety time operation for V2: 1 s Safety time operation for V1: 1 s Mains voltage 220/240 V~, 50/60 Hz IFS 110IM-W-10/1/1T *Inactive part* Automatic burner control unit New stage construction. Function and pin assignment have remained the same. Within the scope of European directives, This product may only be used for replacement purposes. Ignites and controls gas burners, for intermittent operation, with ionization or UV control, single electrode operation possible, multi-flame control possible, EC type tested and certified For grounded mains Restart in the event of flame failure Safety time on start-up: 10 s Safety time during operation for V2: 1 s Safety time during operation for V1: 1 s Mains voltage: 220/240V AC, 50/60Hz</p>
<p>84448230 DG 60VC5-5W</p>	<p>Gas pressure switch For monitoring gas and Air pressures, also for biogas, factory set switching point, EC type tested and certified Setting range 10-60 mbar Switching point adjustable via handwheel Compact design Rp 1/4 internal thread Electrical connection with 4-pin plug, without Power outlet Changeover contact DG 60VC5-5W Pressure switch for gas For monitoring gas and air pressures, also for biologically produced methane, switching point set at factory, EC type-tested and certified Adjusting range: 10-60 mbar Switching point adjustable on hand wheel Compact design Rp 1/4 internal thread Electrical connection via 4-pin plug, without socket Changeover contact</p>
<p>Alternatively 84368013 FDU 510W1T5/1O1-0K1-</p>	<p>Flame monitor For flame signaling, EU-certified Series: For intermittent operation Mains voltage: 230 V~, 50/60 Hz Flame monitoring: UV probe UVS Switch-off threshold: 5 micro A Reaction time after flame failure: 1 s Flame detection: 1 normally closed, 1 Normally open contact Flame signal strength: No output Connection plug: With screw terminals FDU 510W1T5/1O1-0K1 Flame detector For flame detection, EU certified Series: For intermittent operation Mains voltage: 230 V~, 50/60 Hz Flame control: UV sensor UVS Switch-off threshold: 5 micro A Reaction time in the event of flame failure: 1 s Flame report: 1 NC, 1 NO contact Flame signal intensity: No output Connection plugs: With screw terminals</p>
<p>GFK 25 R 40-4</p>	
	<p>Inactive part* Gas burner control unit New construction status. Function and Connection assignments have remained the same. Within the scope of European Directives, this product may only be used for replacement purposes. Ignites and monitors gas burners, for intermittent operation, Ionization or UV monitoring, Single electrode operation possible, Multi-flame monitoring possible, EC type tested and certified For earthed networks Lockout after flame failure Safety time start-up: 5 s Safety time</p>

<p>IFS 110IM-5/1/1T</p>	<p>operation for V2: 1 s Safety time operation for V1: 1 s Mains voltage 220/240 V~, 50/60 Hz IFS 110IM-5/1/1T *Inactive part* Automatic burner control unit New stage construction. Function and pin assignment have remained the same. Within the scope of European directives, this product may only be used for replacement purposes. Ignites and controls gas burners, for intermittent operation, with ionization or UV control, single electrode operation possible, multi-flame control possible, EC type tested and certified For grounded mains Fault lock out in the event of flame failure Safety time on start-up: 5 s Safety time during operation for V2: 1 s Safety time during operation for V1: 1 s Mains voltage: 220/240V AC, 50/60Hz</p>
<p>84621650</p>	<p>IFD 258-10/1W Gas burner control unit replaces Mat.No. 84620650, compatible Ignites and monitors gas burners, for Continuous operation with Ionization monitoring, Switch-off sensitivity adjustable, display for program status and Flame signal strength, IP 54, EC type tested and certified, FM and CSA approved Series 200 Ionization or UV monitoring Immediate shutdown or Restart after flame failure, switchable Safety time start-up: 10 s Safety time during operation: 1 s Mains voltage 230 V~, 50/60 Hz IFD 258-10/1W Automatic burner control unit replaces Mat.No. 84620650, compatible Ignites and monitors gas burners, for continuous operation with ionization control, adjustable cut-off point, display for indicating program status and flame signal intensity, IP 54, EC type-tested and certified, FM and CSA approved Series 200 Ionization or UV control Immediate fault lock-out or restart in the event of flame failure, switchable Safety time on start-up: 10 s Safety time during operation: 1 s Mains voltage: 230 V AC, 50/60 Hz</p>
<p>IFW 15-T Flame Dedector</p>	
<p>84368013</p>	<p>FDU 510W1T5/1O1-0K1 Flammenwachter Zur Flammensignalisierung, EU-zertifiziert Baureihe: F¼r intermittierenden Betrieb Netzspannung: 230 V~, 50/60 Hz Flammen¼berwachung: UV-Sonde UVS Abschaltsschwelle: 5 mikro A Reaktionszeit nach Flammenausfall: 1 s Flammenmeldung: 1 ¼ffner-, 1 Schlieerkontakt Flammensignalstrke: Kein Ausgang Anschluss-Stecker: Mit Schraubklemmen FDU 510W1T5/1O1-0K1 Flame detector For flame detection, EU certified Series: For intermittent operation Mains voltage: 230 V~, 50/60 Hz Flame control: UV sensor UVS Switch-off threshold: 5 micro A Reaction time in the event of flame failure: 1 s Flame report: 1 NC, 1 NO contact Flame signal intensity: No output Connection plugs: With screw terminals</p>
<p>BCU 460W3P2C0D0000K1E0-/LM400WF00E1</p>	<p>Burner control unit Housing for on-site mounting, for controlling, igniting and monitoring impulse-controlled, modulating or stage-controlled gas burners. For continuous operation with ionization control or UV control using UV sensor UVD. Intermittent operation with UV sensor UVS. Display of the program status, unit parameters and flame signal. Manual operating mode. Diagnosis and adjustment of unit parameters via optical interface using PC software BCSoft. EC-type tested and certified, FM and EAC approved, certified for systems up to SIL 3 (compliant with PL e). Series: Standard version Mains voltage: 230 V AC, 50/60 Hz Ignition transformer: 8 kV, 12 mA, ED 100 % Flange plate: M32 Valve proving system: None High temperature operation: None Input function: None Pressure switch: None Connection plugs: With screw terminals Packaging: Individual packaging Energy supply: Via safety interlocks Power module: Power module Series: 400 Mains voltage: 230 V AC, 50/60 Hz Air actuator: None Optional output: None Energy supply: Via L1</p>
<p>VG40/32R02LT31DZ2</p>	
<p>GFK 25R40-6</p>	<p>Gas filter With filter mat made of random fiber fleece (Polypropylene), for cleaning Gas (natural gas, town gas, liquefied petroleum gas, biogas) and air, EC type approval tested and certified DN 25 Rp internal thread PU max. 4 bar Measuring ports at the inlet and outlet GFK 25R40-6 Gas filter With (polypropylene) fleece filter pads, for cleaning gas (natural gas, town gas, LPG, biologically produced methane) and air, EC type-tested and certified DN 25 RP internal thread PU max. 4 bar Pressure test point at the inlet and outlet</p>
	<p>21802326 recuperative burner for gas for heating furnace systems Burner size: 3, rated output 100 kW Recuperator: With cast steel ribbed</p>

ECOMAX 3M545-SB/R-(34)B-	recuperator Recuperator length: 545 mm Use: With staged combustion Gas type: For natural gas Heating type: For radiant tube heating without ejector Burner head identification number: (34) Construction status: B-ECOMAX 3M545-SB/R-(34)B- Self recuperative burner for gas For heating of furnace systems Burner size: 3, rated capacity: 100 kW Recuperator: With cast steel ribbed tube recuperator Recuperator length: 545 mm Use: With staged combustion Gas type: For natural gas Type of heating: For radiant tube heating without eductor Burner head identifier: (34) Construction stage: B-
ECOMAX 2M545-SB/R-(33)B-	21802401 recuperative burner for gas for heating furnace systems Burner size: 2, rated output 60 kW Recuperator: With cast steel ribbed recuperator Recuperator length: 545 mm Use: With staged combustion Gas type: For natural gas Heating type: For radiant tube heating without ejector Burner head identification number: (33) Construction status: B-ECOMAX 2M545-SB/R-(33)B- Self recuperative burner for gas For heating of furnace systems Burner size: 2, rated capacity: 60 kW Recuperator: With cast steel ribbed tube recuperator Recuperator length: 545 mm Use: With staged combustion Gas type: For natural gas Type of heating: For radiant tube heating without eductor Burner head identifier: (33) Construction stage: B-
TZI 8/12	
DG 500B-3	Gas pressure monitor For monitoring gas and Air pressure, also for biogas, with handwheel for switching point adjustment, usable as "Special pressure switch" Design, EU-certified Adjustment range: 100-500 mbar Function: Switches on as the temperature rises Overpressure Electrical connection: With screw terminals and M16 cable gland IP 54 DG 500B-3 Pressure switch for gas For monitoring gas and air pressures, also for biologically produced methane, with hand wheel for switching point adjustment, can be used as "special-design pressure switch", EU certified Adjustment range: 100-500 mbar Function: Switches with rising positive pressure Electrical connection: Via screw terminals and M16 cable gland, IP 54
DG 500U	
Eco 3 Ø 33/Ø 41,5-MT-SiSiC	combustion chamber for Ecomax 3 - gas insert Variant for mixing funnel (MT) Com. chamber Eco 3 Ø 33/Ø 41.5-MT-SiSiC for Ecomax 3 - Gas insert variant for mixed hopper (MT)
Eco 2 Ø 28/Ø 38,8-MT-SiSiC	combustion chamber for Ecomax 2 - gas insert Variant for mixing funnel Com. chamber Eco 2 Ø 28/Ø 38.8-MT-SiSiC for Ecomax 2 - Gas insert variant for mixing hopper
3M Eco Sealing Kit	For Ecomax 3M Seal for: Gas unit, LFR unit, recuperation unit, Exhaust gas, burner/oven 3M Eco Gasket Set for ECOMAX 3M Gaskets for: Gas insert, AGT unit, Recu unit, Flue gas, Burner/Furnace
Sealing set Eco 1M/2M	for Ecomax 1M/2M Seals for: Gas unit, LFR unit, recuperation unit, Exhaust gas, burner/oven Gasket Set Eco 1M/2M for Ecomax 1M/2M Gaskets for: Gas insert, AGT unit, Recu unit, Flue gas, Burner/Furnace
ITC 200	
7421976	Drive VA2,3..W (VA3 from week 39, 2009) /B Replacement drive for VA 3 from week 39/09 (Serial number 224311)
88004706	VAV 125R/NWAK Ratio pressure regulator with solenoid valve To secure and regulate gas pressure, Pressure regulator class A according to EN 88, Class A solenoid valve according to EN 161, for Gas and air, also for biogas, pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU-certified Inlet: DN 25 (1") Outlet: DN 25 (1") Pipe connection: Rp internal thread Opening behavior: Quick opening, fast in conclusion Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Valve seat: Normal Connection set for PSA and PSC: 2 Fittings for plastic hose Accessories on the right: 2 locking screws Accessories on the left: 2 locking screws Nozzle diameter, air control pressure (PSA): 0.5 mm Nozzle diameter, combustion chamber pressure (psc): 0.5 mm

47111080	QA 100Z80-160 Flow meter For metering gas where no calibration is required, display of the quantity consumed, with E1 and E200 pulse generators Nominal flow rate: 100 m3/h, measuring range: 10-160 m3/h(b) Intermediate flange DN 80, E1: 1 pulse/m3, E200: 187.5 pulses/m3 pu max. 16 bar
IFD 258-10/1W, 84621650	
Vav 125r/Nqak	
Vg 8r03q6g	
Bvh 100z01a	
Vgbf 40f40-3	
Rv 65/Nf02t60e	EINSTELLVENTIL
Bvgf 100/80z05	
Vg40 R02-Nt33	
75440163	
Dg 110vc8d-5w	
84391045	
Gik 20r02-5	
Rvs 3/Hml03w60e-3	
Vas 350f/Lq	
Vas 8100f051w3b/Pp/Pp	
Dkr 150z03h100d	
Ic 50-60w30e	Actuator For Transmitting rotary movements (0-90 °), for Actuation of gas and air valves, position feedback via externally readable position indicator, enclosure IP 65 Series 50, with higher torque Running time: 60 s / 90 ° Mains voltage: 230 V AC, 50/60 Hz Torque: 30 Nm Continuous control
Tsc 100b065-300/35-Si-1500	
84765850	TC 410-1K leak test Within the scope of European directives, this product only be used for replacement purposes. For checking two safety valves, with adjustable test duration to adapt to different test volumes, leak rates and inlet pressures, for quick opening valves, EC type-tested and certified In the plug housing Test before or after burner run External pressure switch Test duration: 10-60 s mains voltage 24 V= TC 410-1K *Inactive part* Tightness Control Within the scope of European directives, this product
Vfc 365/65r05-25pppp	
Gik 40r02-5	
Akt 150f50tas	
Vk 200f10t5hg93	
Vk 50f10w5xa43d	
Vg 6r05t6	
Gfk 80f10-6	
Gik 15r02-5	
Vg 40/33f10nq33	

85205036	
Gik 50r02-5l	
Zkih 150/100r	pilot burner For the safe ignition of gas burners, with forced air supply 150 mm length An additional 100 mm Rp internal thread ZKIH 150 / 100R Pilot burner For safely igniting gas burners, with forced air supply Length: 150 mm Plus 100 mm Rp internal thread Stat. Product number 84162080 Country of origin: DE
Vg15r02/Nd31	
03150677	
Var 40f05-1	
Vk 65r10t5a93d	
Bio 50kb-40/35-(34)d	
84331381	
Vg 15/12r18nq31	
84447500	
Vas 232r/Nq	
81937190	
Bvh 50z01a	
Bica 65hb-0/35-(34)d	
74921343	
Bic 65mb-0/35-(104)e	
Ifc 125/25r05-15pppp/20-60q3t	
88000107	
Jsav 40r40/2-3	
85317121	
74214547	
Uvs 10d0g1	UVS 10D0G1 UV-sensor For monitoring gas burners in intermittent operation, EC type-tested and certified in conjunction with Elster Kromschröder automatic burner control units Series 10 Quartz glass heat guard Rp 1/2 internal thread M20 cable gland
Vg 25/15r18nq31	
Bic 100hb-0/35-(37)e	
Vas 340r/Nq	
Van 240r/Nw	
Uvs6	
Gfk 40r10-6	
Bvg 125/100z05	
3109016	
Bio 80kb-50/35-(8)e	
Bic-65	

Vk 250f05t5ha93	
Ifc 365/65r05-32pppp/20-60w3t	
Gfk 150f10-3	
Var 80f05-1	
93 3421309	
Tsc 80m075-300/35-Si-1500	
Bic 140mb-0/35-(75)e	
Dg 300vc8d-5w	
Vas 115r/Nw	Gas solenoid valve For gas, air and biologically produced methane, pu max. 500 mbar (7psig), with pilot lamp, IP 65, FM and CSA approved Size 1 EU certified Inlet: DN 15 (1/2") Outlet: DN 15 (1/2") Rp internal thread Quick opening, quick closing With flow adjustment Mains voltage: 230 V AC, 50/60 Hz Electrical connection: M20 cable gland Accessories, right: 2 screw plugs Accessories, left: 2 screw plugs Stat. Warennummer 84814090 Ursprungsland: DE
Bic 100mb-0/35-(118)e	
Rsg 100/65-0	
Tsc 80b040-250/35-Si-1500	
Vad 125r/Nq-100a	
Gfk 125f10-3	
85265010	
Vah 120r/Nqae	
Dg 300/300vc4-6w	
DI 40k-3	
Vg 6r05q6	
Vk 50r10t5a93d	
3352510	
Vas 110r/Lq	
Tc410-10t	DICHTUNGSREGLER
85206072	
DI 3,5k-3	
3109017	
35440829	
Vav 120r/Nwak	
Tgi 7,5-12/100w	Z¼ndtransformator
Rvs 3/ImI02w60e-3	
Vk 40r10t5a93d	
7 193 5010	
Dg500b-3	100-500 Mbar PRESOSTAT
Bvaf 150/125z05	

Tsc 140b070-300/35-Si-1500	
VAS 115R/LW	Gas solenoid valve pu max. 500 mbar (7 psig), with pilot lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Outlet: DN 15 (1/2") Pipe connection: Rp internal thread Opening properties: Slow opening, quick closing Flow adjustment: With flow adjustment Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 cable gland Accessories, right: 2 screw plugs Accessories, left: 2 screw plugs
74921976	
Vgbf 50f05-3	
Vas 250r/Lq	
Ic 20-30w3e	actuator To deliver rotary movements (0-90 °), for Operation of gas and Air dampers, position feedback via the outside read Position indicator, protection class IP 65 Series 20, with floating limit switches Running time 30 s / 90 ° Mains voltage 230 V ~, 50/60 Hz Torque 3 Nm Constant control Stat. Product number 85011010 Country of origin: DE
Rsg 200/140-0	
03089125	
Vg 20r03nq31dmvz	
Zio 200rb-50/35-(20)d	
84099840	
Zic 165rbl-0/35-(20)d	
Vad 350r/Nq-100a	
Vgbf 50f10-3	
03155023	
Vas 240r/Nq	
Gdj 15r04-0l	
Vav 350r/Nwak	
Vk 50r10w5xa43d	
Bio 80hbl-100/35-(34)f	
74482442	
72702070	
Vas 340r/Lq	
Bvgf 150/125z05	
Vg 6k03q6g	
Var 50f05-2	
Vas 240f/Lw	
Bio 50rb-50/35-(39)d	
Ic20-30w3e	
Bic 125hbl-0/35-(9)e	
Vg 65f02nq33dmvz	
Gik 50r02-5	

84583011
Ic 40a2ar10
Bva 150z05
Vg 50f03nt33dmvz
Vk 50f40w5xg43d
Fpt Br 65-100/950/500/50
88005614
84391080z
Vas 780f05lq3b/Pp/Pp
Vas 9125f05na3e/Pp/Pp
86044010
Bic 80rb-0/35-(11)e
Bic 65rb-0/35-(37)e
Tc 2r05w/K
Vgp 15r02q6
3150634
Bvaf 40/25z05
84447379
Ifc 125/25r05-20pppp/20-60q3t
DI 5ag-31
Vas 125r/Nw
Jsav 25r40/2-0
Bic 100rb-150/185-(109)fr
Akt 32f50tas
Vg 10r01t6
Vg 8r05q6
Vg 8r18q6
Bio 50hb-100/35-(37)d
Akt 40f50tas
Vad 240r/Nq-100a
Akt 50r50tas
Bvaf 150z05
Bic 140rb-0/35-(47)e
Vag 350r/Nqae
Fpt Br 140-220/1150
Tzi 7,5/100
Vas 232r/Lw

Vg 15r03nt31dmvz	
84447253	
Bvg 80/65z05	
60dj Z	
74920589	
Vas 8100f05lw3e/Pp/Pp	
72701540	
Zic 200rbl-0/35-(25)d	
Dkr 400z03f450d	
Vgp 15r02w6	
Var 25r05-2	
3109431	
Vah 125r/Nqae	
Bic 140hb-0/35-(26)e	
84230090	
DI 150ag-32	
Bvg 150/100z05	
Bic 65/50hbr-100/235-(108)er	
74 489310	
Ifc 110/10r05-08pppp/20-60w3t	
74918152	
Vg 40r03lq33dmvz	
84447256	
Dkr 125z03f450d	
88000141	
Tc 3r05q/Q	
Ifc 365/65r05-25pppp/20-60q3t	
Var 100f05-2	
Uvc 101g1a	FOTOSEL
DI 4,5kg-3	
03352504	
Vas 8100f05nq3e/Pp/Pp	
84214030	
Bvaf 150/100z05	
Bic 125mb-0/35-(26)e	
Vgbf 100f05-3	

8_193_5200	
Akt 125f50tas	
Akt 32r50tas	
88020010	
Akt 40r50tas	
Zic 165rb-0/35-(17)d	
84315204	UVS 10D4G1
Ziow 200	
Msvs	
DI 40kg-3	
Vav 240r/Nwak	
Vk 40r10w5xa43d	
Vgp 20r01w6	
24_0854802	
Bio 140hb-100/35-(26)e	
Van 120r/Nq	
Vg 25r03nt31dmvz	
Ifc 120/20r05-08pppp/20-60w3t	
Vg 15r03nq31dmvz	
Vas 110r/Nq	
M 264983	
Vas 120r/Lw	
Vfc 350/50r05-32pppp	
Vgbf 40f10-3	
Pfp 700t/N	
Tsc 140a120-300/35-Si-1500	
Gfk 32r10-6	
74336310	
Var 40r05-1	
Tsc 80b033-250/35-Si-1500	
Dkr 400z03h450d	
Tc 410-1n	
Vas 120r/Nq	
Bio 140kbl-50/35-(67)e	
Akt 15r10tas	
Vas 350r/Nq	
Vas 250r/Nq	

84315010
Vas 225r/Nq
Tc 2r05q/K
03110012
Dkr 500z03f100d
Gfk 40r40-6
Gik 150f02-6l
Fpt Br 80-125/1300/700/50
Vg 20r03lq31dmvz
Dkr 150z03h450d
Vgbf 15 R40-1
88002297
85231710
Rvs 40/Kf05w60e-3
Bvg65/40zo5
Vas 250r/Lw
Van 120r/Nw
Vah 115r/Nqbe
Bio 80hb-100/35-(16)f
Vas 232r/Nw
74105751
Dkr 450z03h100d
84347010
Vg 15/10r01q6
85231010
Zio 165hbl-100/35-(24)d
88012146
Bvg 150/125z05
Gik 20r02-5l
Vk50f
Gik 25r02-5
Tc410-1t
Vad 120r/Nq-100a
Van 250r/Nw
3 416 0010
Gfk 100f60-6
Dg 110vc5-5w

Bio 80rb-50/35-(6)e
Vk 50f80t5hg93d
Bic 50rb-0/35-(39)d
85256860
Dkr 100z03f450d
Gik 65f02-6l
Var 65f05-1
Gdj 40r04-0l
Zio 165hb-100/35-(18)d
Vgbf 40f05-3
Vg 15r03lq31dmvz
Vg 40/32r02lq31dmvz
Bioa 65rb-50/35-(37)d
Vgbf 100f40-3
Vg 40/32r02lt31dmvz
Tc 1c05q/K
Gik 100f02-6l
Vad 125r/Nw-100a
Vgbf 50f05-3v
Dg 500vc4-5w
Uvs 10d4g1
Bio 65kb-50/35-(46)e
Gfk 65f60-6
85231012
Gdj 15r04-0
Vas 110r/Lw
88611509
Vk 65r31t5a93d
Kfm 160 R B 100
Vg8r05t6
Vas 225r/Lw
Bvhs 50z01a
Ic 40sa3ar10
Vg 6k05q6
Gdj-25 R04-Zr1
Fpt Br 100-150/700

Tsc 50b028-300/135-Si-1500 Z	
Vk 40f10t5a93d	
74918682	
Vas 665f05lq3b/Pp/Pp	
Akt 25r10tas	
Van 240r/Nqsr	
Tsc 100m180-300/35-Si-1500	
Bio 140kb-50/35-(66)e	
Gdj 50r04-0l	
Van 115r/Nwsr	
Zic 165hb-0/35-(18)d	
Vas 665f05nwsr3b/Pp/Pp	MAGNETISCHES VENTIL
72700560	
Vfc 120/20r05-15pppp	
84447520	
71937010	
Gik 20r02-5b	
Van 250r/Nq	
Rvs 65/Mf02w60e-3	
Ziow 165	
84447020	
Gik 50r02-5lb	
Vgp 25r01q6	
Vas 240f/Lq	
75422071	
84234040	
74921345	
3152149	
Fpt Br 65-100/500	
Din3384	
Bio 140rb-50/35-(47)e	
Vas 9125f05na3b/Pp/Pp	
8 604 6010	
Vg 50/39r10nt33	
Gik 40r02-5b	
39 0539311	
Van 120r/Nwsr	

75448580
Var 100f05-1
84214040
Rvs 2/Aml10w60s1-3
Vgp 25r01w6
Ifs 135b-3/1/1t
Tc 3r05k/K
Tsc 125m260-300/35-Si-1500
Vk 50r40t5a93d
Bic 140rbl-0/35-(54)e
Gik 25r02-5lb
74923041
Ifc 365/65r05-40pppp/20-60q3e
85256863
Bic 125rb-0/35-(15)e
DI 11kg-3
74330414
Van 240r/Nq
Vas 340r/Nw
Vg 50/39r10nq33
Var 40f05-2
Vad 120r/Nw-100a
Dg 150/300vc4-6w
Vas 8100f05nw3e/Pp/Pp
Dg 250c8d-5s
Vg 50f03lt33dmvz
Dg 300vc5-5w
Gfk 50f10-6
Vas 115r/Lq
Akt 10 R 50
Ifc 365/65r05-40pppp/20-60w3t
Dkr 20z03f100d
DI 5ag-32
Bio 100hb-100/35-(37)e
Vk 65f10w5xa43d
GFK 15R40-6
gas filter With filter mat made of random fiber fleece (polypropylene), for cleaning Gas (natural gas, town gas, liquefied petroleum gas, biogas) and

	air, EC type tested and certified DN 15 Rp internal thread pu max. 4 bar measuring nozzles in the inlet and outlet
Dkr 200z03f100d	
72703710	
Gdj 25r04-0l	
J78r 1	
Dl 3a-3tz	Air-pressure switch Switch housing drilled out (Rp1 / 8 connection) For monitoring of air and flue gas pressures, for overpressure, negative pressure and differential pressure, EC type tested and certified Adjustment range 0.2-3 mbar, can be used as "pressure monitor of special design" ' Housing with screw terminals, threaded connection Rp 1/4 and hose connection with handwheel Electrical connection with screw terminals Blue Control Lamp for 220/240 V ~ DL 3A-3TZ Pressure switch for air switch housing on-drilled (Rp1 / 8 connection) For monitoring air and flue gas pressures, for positive Pressure, negative pressure and differential pressure, EC type-tested and certified Adjusting range: 0.2-3 mbar, can be used as " special-design pressure switch " Housing with screw terminals, Rp 1/4 threaded connection and tube connection with hand wheel Electrical connection via screw terminals Blue pilot lamp for 220/240 V AC Stat. Lot number 90262080 Country of origin: DE
86046010	
J78r 1-L	
Akt 100f50tas	
Bvaf 40z05	
Vg 50r03lt33dmvz	
Vas 8100f05lq3e/Pp/Pp	
Dg 50u-3	
Ic 20-15w3t	
Bvaf 40/32z05	
Gdj 25r04-0	
Bvhr 100z01a	
Jsav 40f40/1-3	
Vr 25r01rt31d 220 V	
Van 120r/Nqsr	
Fpt Br 100-150/1300/900/100	
Bic 100rbl-0/35-(111)e	
Bic 80rb-0/35-(6)e	
Zio 200kbl-50/35-(38)d	
VAS 240R/LW	gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 2 Certification: EU-certified Inlet: DN 40 (1 1/2") Outlet: DN 40 (1 1/2") Pipe connection: Rp internal thread Opening behavior: Slow opening, fast closing Quantity setting: With quantity setting Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessory right: 2 locking screws Accessory left: 2 locking screws
Bic 140lb-0/35-(60)e	
Bio 100kb-50/35-(41)e	

843 674 40
Ifc 115/15r05-20pppp/20-60w3t
85315316
Gik 50r02-5b
Bva150z05
Tc 3r05q/K
Pfu 760 Ltk1
Vas 780f05lw3e/Pp/Pp
Tc 1c05w/K
Gfk 65r10-6
Rvs 2/Bml10w60e-3
Gik 15r02-5b
74918138
Vgbf 150 F 05-3
74960352
Dkr 500z03h100d
Vgbf 100f10-3
Gik 40r02-5l
Vgp 10r02w6
Vg 20r03nt31dmvz
88012154
84583010
Tc 410-1t
Tc 410-10t
Gfk 20r40-6
Vag 125r/Nqae
Vk 150f04w5xg43
Jsav 40f40/2-3
Dg 150u-3
SWITCH
Bio 125rb-50/35-(15)e
Dg 150vc8d-5w
Gfk 100f10-6
Gvrh 350ml02f1t6
88000148
Tsc 100b040-300/105-Si-1500
Tsc 140b055-300/35-Si-1500
Vas 120r/Nw

35441256
Akt 25f50tas
Tc 410-10n
Bic 50hb-0/135-(37)d
Vg 50r03nt33dmvz
Vas 665f05lw3e/Pp/Pp
74922222
3089123
03200111
Bvaf 80z05
Ic 20-07q2tr10
3262045
Vas 240f/Nw
Gfk 65f10-6
Vas 240r/Lq
Vg 6k05t6
8 444 7350
Vas120r/Nwsr
34160010
03200124
60dj Lz
Ifc 350/50r05-25pppp/20-60q3e
Gdj 20r04-0l
Bic 140rbl-250/285-(54)er
88012860
74960023
88000146
Bva 40/25z05
Bio 100kbl-50/35-(52)e
Vag 350r/Nwae
Vas 780f05nw3e/Pp/Pp
Gik 15r02-5lb
Bic 65hb-0/35-(34)e
Gik 40r02-5lb
Bio 80rbl-50/35-(11)e
Vk 200f02w5xg43
Vas 365r/Lw

Vgbf 150f10-3
Vg 15/10r01t6
Vgbf 80f05-3v
Vg 25r03lt31dmvz
8 423 0100
Vk 40r40t5a93d
Vg 40r03nt33dmvz
Tsc 100b050-300/35-Si-1500
Kfm Mb: 0-250
Vas 225r/Lq
DI 5a-32
Vg 50f03nq33dmvz
8429 9748
74921823
3262067
Ic 20-60w3e
Bva 100/65z05
Vav 120r/Nqak
03152276
Ic 40sa3dr10
Bic 80mb-0/35-(57)e
Tc 2r05k/K
Ic 40sa3a
Vmv115r05m
84367030
8 520 612 0
Dg 60/300vc4-6w
DI 24kg-3
03152348
Dkr 500z03h450d
Vad 350r/Nw-100a
Vas232r/Nwsr
Jsav 80f50/1-0
Van 115r/Nw
DG 50U-6

Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as " pressure monitor special Bauart ", EC type-tested and certified Setting range 2.5-50 mbar Overpressure (gas / air), underpressure (air), differential pressure

(Air-air) El. Connection with 4-pin plug, with socket Stat. Lot number 90262080 Country of origin: DE
Rvs 65/Mf02w60s1-3
Tsc 50b020-300/135-Si-1500 Z
88004435
Gfk 200f10-3
Tsc 200a180-300/35-Si-1500
88300159
Ifc 365/65r05-25pppp/20-60w3t
Bvg 125z05
DI 150a-32
VAS 110R/NW gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU-certified Inlet: DN 10 (3/8") Outlet: DN 10 (3/8") Pipe connection: Rp internal thread Opening behavior: Fast opening, fast closing Quantity setting: With quantity setting Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessory right: 2 locking screws Accessory left: 2 locking screws
Vk 65 F 10 T5 A 93 Ds
88202653
Zio 200hb-100/35-(21)d
Vag 115r/Nwbe
85313126
Var 80f05-2
Bio 140hbl-100/35-(44)e
Vas125r/Nwsr
Tc 3r05w/W
Bvg 50z05
Rvs 65/Lf03w60s1-3
Bvg 125/80z05
Zio 200hbl-100/35-(23)d
Vas 120r/Nwsr MAGNETISCHER VENTIL POSITIONSSCHALTER
71939010
Vav 350r/Nqak
Dkr 65z03h100d
Bio 125hb-100/35-(2)e
Vg 25r03lq31dmvz
Zio 165kb-50/35-(25)d
Bic 80hb-0/35-(16)f
Bio 100hbl-100/35-(49)e
Vg 10r01q6

Vgbf 80f40-3	
88001019	
Bvaf 125/80z05	
Tc 3r05w/K	
Vah 120r/Nwae	
Vas 780f05nq3e/Pp/Pp	
Bg 80/100	
Jsav 25r40/1-0	
DI 150ag-31	
Dkr 450z03f450d	
84447350	
Van 250r/Nqsr	
74920293	
Vas 665f05nw3e/Pp/Pp	
Tc 1c05k/K	
Vsbv 25r40-4	
35440784	
Tsc100b065-300	
Dkr 450z03h450d	
Ifs 135b-5/1/1t	Gas burner control *** only for replacement *** Ignits and monitors gas burners, for intermittent operation, Ionisation or UV monitoring, EC type tested and certified Lockout after flame failure Safety time start-up: 5 s Safety time Operation for V2: 1 s Safety time operation for V1: 1 s Mains voltage 220/240 V ~, 50/60 Hz, for grounded nets IFS 135B-5/1 / 1T Automatic burner control unit *** Only for replacement *** Ignites and controls gas burners, for intermittent operation, with Ionization or UV control, EC type-tested and certified Fault lock-out in the event of flame failure Safety time on start-up: 5 s Safety time during operation for V2: 1 s Safety time during operation for V1: 1 s Mains voltage: 220/240 V AC, 50/60 Hz, for grounded mains Stat. Lot number 90268020 Country of origin: DE Technical documentation can be found at: http://docuthek.kromschroeder.com/doclib/main.php?language=1&folderid=206030
74919901	
74105996	
Ic 20-07w2e	
Gfk 125f40-3	
Jsav 40r40/1-3	
Vag 120r/Nqae	
Doos3oo8	
Vag 240r/Nwae	
717893	
75448312	

Fpt Br 50-100/500
03352506
03200159
Zic 200rb-0/35-(20)d
88650057
85257863
Zio 200kb-50/35-(34)d
84447355
Bio 125rbl-50/35-(17)e
Zic 200hb-0/35-(21)d
85249151
Dkr 350z03f100d
Dg 110c8d-5s
Dg 300vc4-5w
35448584
DI 50ag-32
Vgbf25r40-1
Vas 225r/Nw
Van 115r/Nqsr
Vg 25r03nq31dmvz
Ic 20-60q3e
75440160
Vg15r03nt31d
Vgbf 150f05-3
Vas 240r/Nw
Biow 80
Vas 350r/Lq
Bva 65/40z05
Tsc 140m360-300/35-Si-1500
Var 50f05-1
Tc 2r05w/W
74919312
Gik 150f02-6
Vg 65f02lt33dmvz
Vas 780f05nq3b/Pp/Pp
Bic 100lb-0/35-(123)h

Gfk 4071939010	
Vg 40/32r02nt31dmvz	
Gdj 50r04-0	
Vfc 125/25r05-08pppp	
Vag 120r/Nwae	
Bva 150/100z05	
Vas 8100f05lq3b/Pp/Pp	
Bva 100/80z05	
Ifc 125/25r05-08pppp/20-60q3t	
Fpt Br 80-125/600	
88012160	
DI 50a-31	
Dg 40vc4-5w	
Vg 65f02nt33dmvz	
8 444 4400	
DI 3a-3	Pressure switch for air For monitoring air and flue gas pressures, for positive pressure, negative pressure and differential pressure, EC type-tested and certified Adjusting range: 0.2-3 mbar, can be used as "special-design pressureswitch" Housing with screw terminals, Rp 1/4 threaded connection and tube connection with hand wheel Electrical connection via screw terminals Stat. Warennummer 90262080 Ursprungsland: DE
Dg 150u-6t	Pressure switch for gas For monitoring gas and air pressures, also for biologically produced methane, with hand wheel for switching point adjustment, can be used as "special-design pressure switch", EC type-tested and certified Adjusting range: 30-150 mbar Positive pressure (gas/air), negative pressure (air), differential pressure (air-air) Electrical connection via 4-pin plug, with socket Blue pilot lamp for 220/240 V AC Stat. Warennummer 90262080 Ursprungsland: DE
84230050	
Vas 125r/Lw	
Fpt Br 140-220/1650/1100/100	
81941103	
Vg 50r03nq33dmvz	
Gfk 80f60-6	
Vad 240r/Nw-100a	
Vav 240r/Nqak	
Tsc 65m035-300/35-Si-1500	
Bic 50hb-0/35-(37)d	
84367520	
Bvhr 50z01a	
Vg 50f03lq33dmvz	
Vas 780f05lq3e/Pp/Pp	

Vas 115r/Nq
3109018
03352385
Dkr 65z03h450d
3109003
Bio 125hbl-100/35-(9)e
03200110
Bic 80lb-0/35-(59)f
Vgbf 150f05-3v
8434 4920
Gfk 32r40-6
Bvhs 100z01a
88003876
Vgp 20r01q6
Vav 115r/Nqbk
Gfk 150f40-3
Bvgf 150z05
74923271
Bvgf 100z05
Van 115r/Nq
Vas 240f/Nq
R30-85205030
74923285
Ifc 365/65r05-40pppp/20-60w3e
Vas 120r/Lq
Bica 65rb-0/35-(37)d
Gfk 40f10-6
Vas 125r/Lq
Ifc 115/15r05-15pppp/20-60w3t
Vas 250r/Nw
Zic 200hbl-0/35-(23)d
88610003
14541
8 421 4050
IC 20-30W3T actuator For the transmission of rotary movements (0-90°), for operating gas and air flaps, External position feedback Readable position indicator, IP protection class 65 Series: 20, with potential-free Limit switches Duration: 30 s/90° Mains voltage: 230 V~, 50/60 Hz

88300060	Torque: 3 Nm Control: Three-point step control IC 20-30W3T Actuator For transmitting rotary movements (0-90°), for actuation of gas and air valves, position feedback via externally readable position indicator, enclosure IP 65 Series: 20, with voltage-free limit switches Running time: 30 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3 Nm Control: Three-point step control
Vk125av	
Bvg65/40z05	
8 439 510 1	
Gfk 50r40-6	
Bvgf 150/100z05	
Bic 100rbl-150/185-(111)fr	
03200109	
Bio 100rbl-50/35-(111)e	
Fpt Br 125-195/950	
Biow 140	
74959774	
Vgbf 40f05-3v	
Vg 20r03lt31dmvz	
16010081	
Akt 50f50tas	
Fpt Br 125-195/1350/1000/100	
Rsg 140/100-0	
85234510	
Zio 165rbl-50/35-(20)d	
Tc 410-10k	
Rvs 50/Mf02w60e-3	
Gik 80f02-6	
Bio 65rb-50/35-(37)e	
Gik 25r02-5l	
Bva 65z05	
Vg 15r03lt31dmvz	
84.398.164	
Bio 125kbl-50/35-(21)e	
Bva 150/125z05	
Gdj15r04-4lz	
15100111	
Dg 60vc8d-5w	
Vas 665f05nq3e/Pp/Pp	
Bio 65hb-100/35-(34)e	

Fpt Br 50-100/500/300/50	
Vg 40/33r10nq33	
GFK 25R40-6	Gas filter With filter mat made of random fiber fleece (polypropylene), for cleaning Gas (natural gas, town gas, liquefied petroleum gas, biogas) and air, EC type tested and certified DN25 Rp internal thread pu max. 4 bar Measuring nozzles in the inlet and outlet GRP 25R40-6 Gas filter With (polypropylene) fleece filter pads, for cleaning gas (natural gas, town gas, LPG, biologically produced methane) and air, EC type-tested and certified DN25 Rp internal thread pu max. 4 bar Pressure test point at the inlet and outlet
Dg 500vc8d-5w	
Bic 140rb-250/285-(47)er	
Vgbf 80f10-3	
Vg 25/15r18nt31	
84447573	
Var 40r05-2	
Vas 8100f05nq3b/Pp/Pp	
Vg 50/39f10nq33	
Vg8r05t6/220v	
Vgbf 65f05-3	
Van 240r/Nwsr	
Vad 115r/Nq-100b	
Vg 40/33r10nt33	
Vah 115r/Nwbe	
Dkr 300z03f450d	
Dg6u-5	
84099543	
Bvaf 100/80z05	
Akt 20r10tas	
Vah 240r/Nqae	
Vah 350r/Nwae	
81937200	
88300161	
88205351	
Bcu460-5/1 Lw3ds2b1/1	
03200379	
Tc 2r05q/Q	
Vk 150f04w5xa43	
Bvg 150z05	
	Pressure switch for gas For monitoring gas and air pressures, also for

DG 50B-3	biologically produced methane, with hand wheel for switching point adjustment, can be used as "special-design pressure switch", EU certified Adjusting range: 2.5-50 mbar Function: Switches with rising positive pressure Electrical connection: Via screw terminals and M16 cable gland, IP 54
74919356	
Dkr 350z03h100d	
Biow 65	
3109434	
84444880	
84230080	
Vfc 120/20r05-20pppp	
Bio 125kb-50/35-(20)e	
Vav 115r/Nwbk	
Akt 80f50tas	
Kfm 60 R B 100	
84315200	
Dg 500vc5-5w	
Bg 50/65	
Vas 232r/Lq	
Ecomax 2 Mb 695	
88012148	
Bio 140rbl-50/35-(54)e	
Ifc 350/50r05-32pppp/20-60q3e	
74951926	
Vg 8r05t6	
Jsav 50f50/1-0	
Vas 350f/Lw	
Bioa 65hb-100/35-(34)d	
Geh 20 R 10	
Vg 50/39f10nt33	
Bva 40z05	
88301151	
85312165	
Bic 100hbl-0/35-(49)e	
Vas 365r/Nq	
Gik 80f02-6l	
Zic 165hbl-0/35-(24)d	

Vas_665f05lw3b/Pp/Pp
88000570
Vag_115r/Nqbe
Vg_8r03t6g
Gfk_25r10-6
88012166
Akt_65f50tas
74911637
Vas115r/Nwsl
Vas_350r/Lw
Tsc_200b107-300/35-Si-1500
Vg_40r03lt33dmvz
75448582
74923284
Vg_15/12r18nt31
Vg_8r18t6
Gik_65f02-6
71935010
Gfk_25-1
Tc_1c05q/Q
Dg_40vc5-5w
81943190
Zio_165rb-50/35-(17)d
Var_25r05-1
3109436
Bvaf_65/40z05
75442048
Bic_80hbl-0/35-(34)f
Gik_20r02-5lb
Vgp_10r02q6
Gfk40/50
Van_250r/Nwsr
Vg_40/33f10nt33
Dkr_15z03f100d
Tsc_140b085-300/35-Si-1500
84765528
7491-1637

Dkr 300z03h450d
Vg 6k03t6g
Vgbf 100f05-3v
Zio 200rbl-50/35-(25)d
Dkr 500z03f450d
74923085
Jsav 100f50/1-0
Gfk 40f60-6
Vg 65f02lq33dmvz
Vas 340r/Lw
Van 125r/Nw
Tsc 100b050-250/35-Si-1500
Bva 50/40z05
Vg 15/10r01t6g
Vk 40f10w5xa43d
842 210 23
03200108
Vk 65r10w5xa43d
Vk 200/100f40t5hg93
Van 125r/Nwsr
Vfc 365/65r05-40pppp
Rvs 3/Iml02w60s1-3
Vad 115r/Nw-100b
Vk 80f10t5a93ds
13110238
88650068
Vas 365r/Lq
Bcu460-3/1w3gcb1/1
Gfk 50r10-6
Gdj 20r04-0
Biow 125
Ic 20-15w3tr10
Gfk 20r10-6
84444453
Gfk40r10-7
Gdj 40r04-0
Tsc 100a082-300/35-Si-1500

Vgbf 65f05-3v
Bio 100rb-50/35-(109)e
Vas 665f05lq3e/Pp/Pp
75421951
Bic 125rbl-0/35-(17)e
Vas 780f05lw3b/Pp/Pp
86049222
Bic 100rb-0/35-(109)e
Vg 40/32r02nq31dmvz
Vah 350r/Nqae
Dg 60vc4-5w
74924633
74918692
84447505
Gfk 15r10-6
3150674
Vg 50r03lq33dmvz
Vag 125r/Nwae
Rvs 3/Gml05w60s1-3
74921144
Dkr 100z03f100d
Gfk 250f10-3
Vav 125r/Nwak
84765710
Vas 350r/Nw
60djz
Vgbf 50f40-3
Vag 240r/Nqae
Vas 350f/Nw
Vg 40r03nq33dmvz
Bg 125/140
Van 125r/Nqsr
Vah 125r/Nwae
DI 3,3kg-3
Van 125r/Nq
Bic 140hbl-0/35-(44)e

[DI 11k 3](#)
[88300076](#)

[72700760](#)

[Gik 15r02-5l](#)

[Vas 115r/Lw](#)

[Vas 350f/Nq](#)