

Kyowa

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Kyowa Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Kyowa Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
19b05164	min. order?
AC200V 50/60 HZ MR-Q3-42-314-8AAAA - 18F11322	
AC380V 50/60HZ MR-Q3-57-285-8AFBA-18F20177	
DTH-A-100	Displacement transducer Measuring range: 100mm 350 Ohm bridge output, supply voltage max. 6V AC or DC Including 2m cable and two assembly straps.
DTH-A-10	Displacement transducer Measuring range: 10mm 350 Ohm bridge output, supply voltage max. 6V AC or DC incl. 2m cable and mounting tape.
04F01121?	
CC-33A-5	
EDX-200A	
EDX-200A-4H	
KLPC-100FR	
KSP-6-350-E4	
LC-20TV	
LC-5TSHR-7Z5	
LCTB-A-10KN	
LUK-A-10KN	

Ürün	Açıklama
LUK-A-20KN	
LUK-A-50KN	
MR-A3-42-288-4YAAA	
PAL-500KB	
PAV-250KC-M28 (SERIAL NO: YV6841)	
S32-7	
WGA-100B-1 0	
PCD-400A	Four channel USB 2.0 sensor interface. Expandable to 16 channels. 24-bit ADC with a maximum sampling rate of 10 kHz. Measuring ranges: 200, 500, 1000, 2000, 5000, 10000, 20000µm/m LP filter switchable: 10, 30, 100Hz & Flat Bandwidth: 200Hz Working temperature range: 0°C ... 40 °C Dimensions [mm]: 210x35x157.5 Incl. DCS 100A control software and USB cable.
LMB-A-2KN	Low Profile Compression Load Cell Messbereich: 2000N, Spring rate: 41 kN/mm, Cable: 2m Long
CFM-16B	Mounting plate for LMB-A-500N up to 2KN
PCD-400A	3 cm strain guage
Manuel Hydro Pressure Test Pump	
LMB-A-2KN	Low Profile Compression Load Cell Messbereich: 2000N, Spring rate: 41 kN/mm, Cable: 2m Long
DTS-A-100	Strain type Displacement Transducer for tension and compression 100mm Rated Capacity Fast response (DC to 50 Hz, when the head is fixed, displacement: 30 mm) Safe temperature range -10 to 70 °C(Noncondensing) 4-conductor(0.08 mm ²) vinyl shielded cable, 3.2 mm diameter by 1 m long, terminated with connector plug. Incl. Probe: X-1-DT , 1 PC and Mounting band (FXBP-100A) 2 PCs.
S32-7	NDIS Kupplung (Female) (PRC03-32A10-7F10.5) Passend zu den Kyowa Sensoren.
PR TD 50 1191 45zmgf motorized angle	

Ürün	Açıklama
roller	
PR TD 50 1191 45zmgf dimensions to be idle	
PR-AD-50-578-25ZMGT	
Phc-B-2mp	
Dlt-5bs	
Mr-Q3-57-700-25afba	
Pav-300kh M76	
Kfc-10-C1-11, Replaced By Kfgs-10-120-C1-11	
Sc-18-00a	
Ksp-6-350-E4(4 Pcs/1 Bag)	
Ber-A-2mp79s	
Lcn-A-20kn	LOAD CELL
Kfg-1-350-C1-11(10 Pcs/1 Bag)	
Pav 300ku	
Pcd430a	INTERFACE
Lmc-A-5 Kn	
Edx-200a	
Cable For The Charge Cell Of F340a	
Das200a	SOFTWARE
Dtj-A-200	
Sc01r100a	
Sp-20-88ax915l	
Wga-100b-00	
Kfrs-02-120-C1-13n10c3	
Lcr-S-160kns19c	

Ürün	Açıklama
Lc-10tv	
Lcna20knp	LOAD CELL
Kfgs-10-120-C1-11 (Pack Of 10)	
Phf-S-5mpsa2	
Kfg(S)*-5-120-C1-11	Single-axis slides DMS Executed with 25mm ready applied solder flags Nominal resistance: 120 Ω Grid in mm: 5 x 1.4 Carrier in mm: 9.4 x 2.8 Thermally adjusted to 11ppm / degree Kelvin Package content 10 pieces
Pav-H-300-K	
Dts-A-100	
Pcd400a	INTERFACE
Kmp-3-4c114-508-20	
Phl-A-50mp-A	
Wds-180a	
Kfg-6-120-C1-16(10 Pcs/1 Bag)	
Wga-800c-20ac-M253	
Kmp3-114-520-20	
Pav-350kh M76	
Lma-A-20n	
Pav-250kc-M28 (Serial No: Yv6841)	
Id/Dlt-5bs	
Kfg-5-120-C1-11	Single-axis slides DMS Executed with 25mm ready applied solder flags Nominal resistance: 120 Ω Grid in mm: 5 x 1.4 Carrier in mm: 9.4 x 2.8 Thermally adjusted to 11ppm / degree Kelvin Package content 10 pieces
Bpr-A-50kps	

Ürün	Açıklama
Kfg-30-120-C1-11 L1m3r	
Ksp-1-350-E4(4 Pcs/1 Bag)	
Lck5ta	LOAD CELL
Wga-800b-20ac-M253	
Dth-A-30	
S21-7 Prc03-21a10-7f	
Yeni Model	