

Kytola



Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin

info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Kytola Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Kytola T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
SR6-2,5-MD33-S	Oval gear meter max. 2.5 l / min, oil, coil sensor, Service valve
SR4-6-MD33-S	Oval gear meter max. 6 l / min., oil, coil sensor, Service valve (block of 4),
SR120-BH51	Oval gear meter max. 120 l / min, oil, coil sensor (replaces SR100-BH51)
SR60-BH51	Oval gear meter max. 60 l / min, oil, connections on the back, coil sensor
SR4-2,5-MD33-S	Oval gear meter max. 2.5 l / min., oil, coil sensor, Service valve (block of 4),
SR6-6-MD33-S	Oval gear meter max. 6 l / min., oil, coil sensor, Service valve (block of 6)
SR8-6-MD33-S	Oval gear meter max. 6 l / min., oil, coil sensor, Service valve (block of 8)
SR20-8850	Oval gear meter 2-20 l / min., Oil, connections on the back, Coil sensor
KERAIN	Andersen cascade impactor 6-stage for sampling in Inner space, Stage d50, particle size [µm] 1 - 7.0 2 - 4.7 3 - 3.3 4 - 2.1 5 - 1.1 6 - 0.65
ZLET-KERAIN	1.8 m hose with 2 Quick couplings (9 mm)
EK-5ER-E	Alternative position Flow meter 7.5 - 47.5 l / min, air, valve in output
ZLET-KERAIN	Alternative position 1.8 m hose with 2 Quick couplings (9 mm) (f. exit Flow meter)

PNELIRUR1/4	Alternative position Impactor connection incl. poetry PNETIR 1/4 (Input + output Flow meter EK)
KLH-4DA-D	Flowmeter 10-85 l / min., H2O, Alarm preparation
VLK-4DA-D	Flow meter 3-17 l / min, H2O, Alarm preparation
VLK-3KA-D	Flow meter 1.5-5.5 l / min, H2O, Alarm preparation
VLK-6HA-D	Flow meter 0.4-2.0 l / min, H2O, Alarm preparation
VLK-3HA-D	Flow meter 0.75-3.25 l / min, H2O, Alarm preparation
See List	The pressure and flow rate information of the seal water required for the slurry pumps in the facility are given in the attached excel file. In order to make this pressure and flow adjustment, it is necessary to use the devices whose information is given in the appendix. The device to be purchased must have manual pressure and flow adjustment, pressure and flow indicator, digital flow switch. In addition, if we can get the pressure and flow value digitally from the device, it will be our priority.
1,17853117854117E+23	
117853/117854/117886/117887	
2851N-8SA-A	
2851R-5CA-AH	
2914-6/VL	
2914D3/VL	
6210-0.3-P-D	
6210-1-NH06-PY	
6210-4-P	
A-2BR	
A-8RA	
BA-5AD-HVO	
C-4CA	
DPA-100P	
E3K-2156	
EK-2MK-D	
EK-3NA	
EK-4AA	
EK-4AR-H	

EK-4BR-HV
HHV 3KC
HRT-4FA
HRV-4EH
KDA-4AR-N
KE2K-4CA
KH-4DA-DN
KH-4EA-D
KLDS-8-M-00A
KLH-4AA-D
LH-4AR
LH-4KR
LH-8SA
LH-WJ13-R
OVAL D-16-P
SLM13
SLM13-EF
SLM13-EKP
SLM13-FGL
SLM13-G
SLM13-GH03-GP
SLM1-F
SLM1-FGP-B3BB
SLM3-EF
SLM3-FG
SLM8-EF
SLM8-FGP-R
SLM8-GH03-FG
SLM8-GH03-GLP
SLM8-GH03-GP

SLM8-GH03-MP	
SLN8-FGP-R	
SR-2,5-8850-S	
SR8-1-MD33-S	
TLFH-4CA	
TLH-4BA-D40	
VDH-3MA-D	
VDH-6HA-D	
VDK-3MA-D	
VDK-3MA-DH	
VDK-BD05	
VE2A-EL48-D	
VEA-4FA-DV	
VEH-3LA-DV	
VEH-4DA-DV	
VEK-3KA-D	
VEK-4DA-DV 4-17 l/min	
VEK-7965	
VLK-7420-D	
ZOVALI/OCARD	
C-3631	
LH-5BA-R	flow meter 0.025-0.325 l/min, H2O,G1/4" connection (new measuring range)
KE2K-4CA-	flow meter 10 - 65 l/min, H2O, G1" connection with quick ejection, 2 measuring tubes
LH-SB11-R	Flow meter 2-19 l/min., air, p= 2.5 bar (g), temperature 30° C, G1/4" connections
VE2K-4FA	
SLM-3	sealing water unit 0.1-3.0L/min, H2O
SLM3-G	alternative position sealing water unit 0.1-3.0 l/min, H2O, Pressure gauge 0-10 bar
SLM8-GH03-GF	

SINGLE SEALS AND PACKINGS LH-SB11R	5-500 Lt/min SEAL WATER FLOW METER AIR FLOW METER 90261081
KEK-4DA	
KK-4DA-D	Flow meter 10-85 l/min, H2O, Alarm preparation
DPP-2K	Manometer 0-2 kPa
VEK-3MA-D	flow meter 2.5-10 l/min, H2O, alarm preparation
KEMI4G	Gauge for KE2K-4CA
SR1-30-B-G-C	Oval gear meter 2-30 l/min., Rear connections G1", Coil sensor, 75.8 pulses/liter
KE2K-4CA--	Flowmeter 10 - 65 l/min, H2O, G1" connection with Quick ejection, 2 Measuring tubes
MP-AR12-W-F	Metal tube flow meter 0 - 65 kg/h, NH4OH, AISI316L tube Display housing Aluminum, EPDM seal, DN15, PN25/40 Flange connections Valve in the outlet
Slm3-Ag	
Vdh-6ha-D Rotameter 0,4-2,0 L/Min,H2o, Alarmvorbereitung	
Slm8-Fgp	
Klh-4da-D Durchflussmesser 10-85l/Min., H2o,Alarmvorbereitung	
Sr-60-Bh51	
Zocupikomi	
Slm8-Epa	
Slm13-Ef Durchflussmesser Wasser Dicht	
Slm8-Ef Sperrwassereinheit0,5-8,0 L/Min, H2o,Manometer 0-25 Bar,Ilk-M18-Fr	
Ve6a-41-D	
6210-0.3-?-D	
Y-M370-E327776	
Sr-30-8850	
6210-1-P-D	
Slm13-Ef Sperrwassereinheit1,0-13,0 L/Min, H2o,Manometer 0-25 Bar,Ilk-M18-Fr	

Ve6a-08-D	
Sr8-2-Af26-S	
Vdk-3ma-D Rotameter 2,5-10 L/Min,H2o, Alarmvorbereitung(Neuerdurchfluss-Bereich)	
C-4ca Flow Metre	
Lh-Wj13-R Visual Indicator	
C-4ca Durchflussmesser 1-10l/Min, H2o	
Slm8	
Slm8-Fgp-R Rotadurchflussmesser Slm8-Fgp-R	
Vlk-7401-D	
2951-2-Akt Durchflussmesser	
Klh-4ea-D	
Sr-10-7844	
Hrk-4fs	
Slm8-Ef Durchflussmesser Wasser Dicht	
A-5ar	
Lh-8sa Rotameter 0,2-2,6 L/Min,H2o, Npt1/4"-Anschluss	
Sr42af26s	FLOW METER
Slm3	
Slm1-F Sperrwassereinheit	
Slm13 Sperrwassereinheit1,0-13,0 L/Min., H2o	
Sr4-2-Af26-S	
Hv-3mc	
Vlk-7403-D	
2951-2-Akt	
Vlk-7401+2914-D/VI	
Hrv-3ms	
Zovali/Ocard	

2950-2-Akt-N
A-8ra Durchflussmesser0,25-3,0 L/Min., H2o
Ve6a-30-D
Slm3-Ef Durchflussmesser Wasserdicht
Vea-Eb75-D
Slm3-Ef Sperrwassereinheit0,1-3,0 L/Min, H2o,Manometer 0-25 Bar,Ilk-M18- Fr
Vlk-7405-D
Sr8-6-Af26-S
Ve2a-EI48d Schwimmermesser
Slm8-Ag
Ve2a-EI48-D Rotadurchflussmesser
F12h-EI35
Ve2a-103-D
Tlfh-4ca-D Rotameter 40-320 L/Min,H2o, Alarmvorbereitung
2851r-5c-A-A-H Rotadurchflussmesser
Eh-9118-D
Tlfh-4ca-D
Sr6-6-Af26-
Kh-Fb11-D
Sr6-2-Af26-S
Tlfh-4ca Rotameter 40-320 L/Min,H2o
Slm3-Fg Sperrwassereinheit0,1-3,0 L/Min, H2o,Ilk-M18-Fr (24v),Manometer 0-10 Bar
Vek-4da-Dv
?-3631 Durchflussmesser
Tlh-4ba-D40 Durchflussmesser 20- 200l/Min., H2o,Sensor-Halterungzilptl40
Ba-5?-D-Hvo Durchflussmesser
Nk-2

Hhv-4ec	
Vdh-3ma-D Rotameter 2,5-10,0 L/Min.,H2o, Alarmvorbereitung	
Ht-4cc	
Kld-8-Ma-C Pulse Modulator Boardpulsmodulatorplatine	
Vlk74052914d2vl Flow Meter Vlk7405-D Kytola Vlk-7405+2914-D/VI With Regulator, G1/2 Connection",	
Ka-4aa-D	
Vea-3ma-D	
Vek-3ka	
Vlk-7405+2914-D/VI	
Ek-4br-Hv Rotameter 2-20 L/Min,Luft, Ventil-Einstellknopf,Viton-Dichtung	
Slm8-Gks	
Kdh-4e-R-Nw	
Sr4-6-Af26-S	
Sr46af26s	FLOW METER