



Lamtec

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Lamtec Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Lamtec Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
650r2030	Lambda probe LS2-K semi-automatic adjustment, immersion depth from flange 500 mm
118305 -	CONTROL MODULE, LAMTEC, BT330 667R1330-1, <230 VAC> - LAMTEC BURNERTRONIC BT330 PRODUCT CODE: 667R1330-1
119258 -	OPERATOR PANEL, MONOCHROME, LAMTEC, UI300 667R0100- BT 330 OPERATOR SCREEN UI300 PRODUCT CODE: 667R0100-1
131655 - Flame	SENSOR (LAMTEC) (FFS 07) - LAMTEC FFS07 FLAME SENSOR, PRODUCT CODE: 659D21
131787 - Flame	SENSOR CONNECTION APPARATUS (LAMTEC) (FH30-10) - LAMTEC FH30-10 PRODUCT CODE: 659S1500
131657 - Flame	MONITORING DEVICE, <LAMTEC> (F152) - LAMTEC F152 FLAME MONITORING DEVICE
118288 - Gas	STEP MOTOR, 24 V DC, IP 54 (LAMTEC) (662R5003-1) - LAMTEC SERVOMOTOR 3NM IP54 PRODUCT CODE: 662R5003-0
118300 - Load	CONTROL MODULE, LAMTEC, LCM100 667R0500-1, <24 VDC> (4-20 MA) - LAMTEC LCM100 LOAD CONTROL MODULE
118277 -	FIELDBUS MODULE, 24 VDC, <LAMTEC> (PBM 100 667R0700 -1) - LAMTEC PBM 100 PROFIBUS MODULE
652R0220	Diaphragm suction pump LONGLIFE 1300 rpm
LAMTEC 650R1000	Lambda probe LS2 Cable length 2m *****
FFS08 659R3001T	
LAMTEC 659D31	Flame sensor FFS08 20 // 3/0/0 / TYPE IR-1 T 1200 ... 2800nm
FS51 : F200 K1 UV1	
CONFIG. NO: A2B11110C90D0020F1K22330	

FMS	
ITEM NO:662R2127OEM	
1005832 - PROBE LAMTEC FFS07 FLAME SENSOR FFS07	
TYP 2 UV-2	Compact flame monitor F200K in the following variant: Configuration: 06/0/0/0/0/0 / TYPE 2 UV-2 UV SPECTRAL RANGE 210 - 380 nm HOUSING STANDARD, SIL3 ACCORDING TO IEC 61508 PART 2 TEMPERATURE RANGE -40 ... + 75 ° C (IR-1 + 60 ° C) MAINS FREQUENCY 50 Hz CURRENT OUTPUT 4 ... 20 mA
662R2111/N	
662R2413 OEM	
SN:00014598	
UI300667R0100-1	
BT.320667R1320-1-LAMTEC 200021010216	
LCM 100 V1.4.0.0 667R0500-1	
Item No:662R5001-1	Torque : 1.2 Nm, Class of Prot : IP54 , Operating range : 90°
No:662R5003-1	3 Nm, Class of Prot : IP54 , Operating range : 90°
652R0220	Diaphragm suction pump LONGLIFE 1300 rpm
650R2030	Lambda probe LS2-K semi-automatic adjustment
662R111-020	662R2111-020 C02 2305 060 090 DPS 5SK0HV154MES2ZS11RSS1B1SS00
30Nm 662R2112	
633R0403MBK/ET	
652R0230	
655R0028	
655R0620	
657P0445	
657P0501	
657P0502	
657R0215F	
657R0790	
657R0792	
657R0831	

[657R0937](#)

[659D31](#)

[659E0102](#)

[659R200](#)

[659R60, 01/Z2/V/0/0/0/0/0/](#)

[659R6112](#)

[659R6114](#)

[660R0015](#)

[660R0016M](#)

[662R2112-030](#)

[662R2122](#)

[662R5001-0](#)

[662r5009-0 OEM!!](#)

[66301-10000SSAP CE 0085 AU](#)
[0207 CE 0036 VIN 115-230V 50](#)
[HZ 50 VA OEM!!](#)

[663O1000](#)

[663R040 \(Konfiguration:](#)
[1PB/ET/\)](#)

[663R040- 5IB ET](#)

[663R0401ETA](#)

[663R040-1PB ET oem](#)

[663R0421N](#)

[663R0935](#)

[663R0935 oem](#)

[663R0935-6442 OEM!!](#)

[663R1-2021D](#)

[667P0515](#)

[670R0](#)

[8 4600 30026](#)

[ETAMATIC OEM](#)

[F200K, Konfiguration:](#)

04/Z2/V/0/0/0/0/0/	
F200K2 IR2	
F200K2-UV2	
FFS 05 UV IP65 659R2001	
FFS 06	
FFS 06 IR OEM!!	
FMS 5	
FPB2500/3500 oem	
gas flap for gas equipment 3236	
LCM-100	
LS2	Lambda O2 Probe
LT2 650R2030	
LT2- WALL MOUNT.CASE	
DB024181	LAMBDA TRANSMITTER LT1 (SIL1) LS1
LAMTEC 659D31	Flame sensor FFS08 20//3/0/0/ IR-1T 1200-2800nm
667R1320-1	Burnertronic BT320, 230VAC, max. 2 drives, interm. operation, 1 fuel
BT330 667R1330-1 230VAC	
663R0935-6442	SOFTWARE: T1U001
FFS08 Type :20/3/0/0	
659D31	Flame sensor FFS08 in the following variant: Configuration: 20//30/0/0/ TYPE IR-1 T SPECTRAL RANGE 1,200...2,800 nm 30m cable standard Customs tariff number: 90275000
T1U001, 663R0935-6442	
659A50	Compact flame monitor F300K in the following variant: Configuration: 04/UI/0/0/ TYPE UV-4 UV SPECTRAL RANGE 215 – 360 nm, EX-II, SIL3 ACCORDING TO IEC 61508, PART 1-7 WITH INTEGRATED F300K USER INTERFACE Zone 2 - Ex nA nC ic IIC T5 (T6) Gc CoC: IECEX IBE 15.0011X WITH UL CERTIFICATION STANDARD CONFIGURATION
662R2127	
F200K 06/Z1 UV/0/0/0/5m/0/	Compact flame monitor F200K in the following variant: Configuration: 06/Z1UV/0/0/0/5m/0/ TYPE 2 UV-2 UV SPECTRAL RANGE 210 – 380 nm HOUSING UV FOR EX-ZONE 1, SIL3 ACCORDING TO IEC 61508, PART 2 Zone 1 - Ex d IIC T6 Gb Zone 21 - Ex tb IIIC T80°C Db BARTEC CoC: IECEX EPS 14.0042 POWER FREQUENCY 50 Hz CURRENT OUTPUT 4...20 mA 5 m CONNECTION CABLE _ Customs tariff number: 90275000 SN:83602479

FSS 06	
662R2111	Actuator 20 Nm in the following variant: Configuration: 020/C02/2305/060/090/DPS/5K/0/HV1/54/ES2/ZS1/1R/S/S/1B/1S/SO0/ ROUND SHAFT 12x30mm WITH KEY 4x4x14mm SUPPLY VOLTAGE 230VAC / 50Hz RUNNING TIME 60 SECONDS / 90° TRAVEL 90° CONTROL THREE-POINT STEP POSITION REPORT POTİ 5 KOHM, POSITIVE, FREE OF PLAY ELECTRICAL MANUAL ADJUSTMENT (BUTTON OPEN/CLOSE) PROTECTION CLASS IP54 2 LIMIT SWITCHES TO LIMIT THE DRIVE 1 PIECE ADDITIONAL SWITCH ROTATION RIGHT (12:00 p.m. to 3:00 a.m.) HOUSING COVER BLUE CABLE GLAND STANDARD 2x M20
652R0220	Diaphragm suction pump LONGLIFE 1300 rpm
659D31	Flame sensor FFS08 in the following variant Configuration: 20//30/0/0/ TYPE IR-1 T SPECTRAL RANGE 1,200...2,800 nm 30m cable standard Customs tariff number: 90275000
PROFIBUS DP \ ETAMATIC V	
MODEL:663R0932V3.0 \ LAMTEC:1385	24VDC
10#.190 Hz \ 4..20mA \ 215 ... 360 NM \	F200K2 UV-6(Ex)
LAMTEC EBM 112 MODULE	
combustion manager lamtec BT 320 667R1320-1	
burn-in manager display lamtec UI300 667R0100-1	
BT 320 667R1320-1	
UI300 667R0100-1	
659R6010	Power pack FN20 230VAC with relay output for F200K
659E0020	Socket for FSB connection, connecting wire 50 cm, including counter nut and cover
659N0512	Silicone connection cable, UL, length 10 m, for F300K
659R60	Compact flame monitor F200K in the following variant: Configuration: 06/0/0/0/0/0/0/0/ TYPE 2 UV-2 UV SPECTRAL RANGE 210 - 380 nm HOUSING STANDARD, SIL3 ACCORDING TO IEC 61508 PART 2 TEMPERATURE RANGE -40...+75°C (IR-1 +60°C) POWER FREQUENCY 50 Hz CURRENT OUTPUT 4...20 mA
657R0833	Display and control unit for LT2
650R1000	Lambda-Sonde LS2 ECO, Kabellänge 2 m
TRANMİSTTER LT2 DISPLAY 657R0833	
O2 LS2 SENSOR 650R1000	

ETAMATIC OEM 66301-1 0 000 S S AP	
652R0220	Diaphragm suction pump LONGLIFE 1300 rpm
Etamatic oem H5.6004 115-230V/50 HZ 50va	
Actuator 40nm (662R2121)	
180nm (662R2125)	
L4a4002	
659D31	659D31 Flame sensor FFS08 in the following variant: Configuration: 20//3/0/0/ TYPE IR-1 T SPECTRAL RANGE 1,200...2,800 nm 3m cable standard
659D31 FFS08 20//3/0/	
ETAMATIC SN:00032207	
659R60	Konfiguration: 06/0/0/0/0/0/0/ (06) TYP 2 UV-2 UV-SPEKTRALBEREICH 210 – 380 nm (0) GEHÄUSE STANDARD, SIL3 NACH IEC 61508 TEIL 2 TEMPERATUR BEREICH -40...+75°C (IR-1 +60°C) (0) NETZFREQUENZ 50 Hz (0) STROMAUSGANG 4...20 mA (0) OHNE
SN: 83601507	
atamatic 66301-10000 ssap	
680R1011	16 ALARM INPUTS, 24 VDC
663R0401-ETA	INTERFACE BUS ADAPTER TYPE PROFIBUS
663R0421N - 2M	LAMTEC COMMUNICATION CABLE
Flame monitor F130I	"Ionisation", SIL3, 230VAC
662R2111	actuator
83500081	
667R0500-1	SN:17310177
ETAMATIC OEM 66301-1 000 S S AP	
667R0500-1	Burnertronic LCM100 667R0500-1 Power regulator module for BT300
667R0600-1	Burnertronic DFM300 667R0600-1 Expansion module
00022452	
LT1 652R0220	Diaphragm suction pump LONGLIFE 1300 RPM
667R0740-1 Fielbusmodul (Profinet) EBM112	

662R211/N 230V/50HZ 20Nm	
662R2413 OEM 230V/50HZ 6Nm	
FFS08 UV 1	
Actuator 140Nm (662R2124-C10)	
F300K UV-4	
LASSTEC F200K 2UV-3	
667R0500-1	Burnertronic LCM100 module/ Power controller for BT300 series
650R2115	Lambda probe LS2-BF BaseFlex, IP65, cable length 2 m, 5-pin
659R60	Compact flame detector F200K
659R60	Compact flame detector F200K Configuration: 06/0/0/0/0/0/0/0/
659R6112	Connection cable, length 3 m, for F200
657R51-20	-LAMBDA TRANSMİTTER \ O2-CO \ 1200 C \ SIL2
57R5940	ANALOG I/O MODUL \ 24 VDC \ 50 MA
656R2010	PROB \ O2+CO \ 1400 C
23032470	
22516039	
EBM112 (667R0740-3)	1638219
CMS UI400 668R0300	1575791
CMS MCC 668R0100	1575765
CMS AEC-TPS 668R0200	1575783
FLUE GAS ONLINE OXYGEN MEASURING DEVICE	PROCESS INFORMATION TO BE USED; The place where the product will be used is explained with a visual. It will be used in the gas channel and the depth of the place where it will be installed is 2150mm. Only oxygen measurement will be made. Point to be used: Biomass Shell Boiler Gas Path After Recuperator Measurement Point Temperature: Normal: 150 C Maximum: 250 C Brands and models that can be offered. Equivalent offers can be sent. Device Brand: ENOTEC Model: OXITEC 500 Serial No: 450512 Voltage: 230V Current: 10 A Device Brand: ABB Type: ZrO2 Oxygen Gas Analysis System Model: AZ 20 Device Brand: LAMTEC Type: Lambda Transmitter Lambda Oxygen Gas Analysis System
EBM112	Feldbusmodul 2 Ports
F 200 K2 UV-2 24DC CE-0085BO0005	
CONNECTOR VE CABLE LAMTEC F200K-659R6	

F200K2	FLAME SCANNER FLAME SCANNER
ETAMATIC OEM 663 O1	
663R0932	terminal
659R60	Compact flame monitor F200K
655R1027	Adapter for LS2 with 5-pin round connector plug
Order No:663r0935	
Ffs08659 D 3120	FOTOSEL FFS08659 D-3120 PHOTOCELL
Lcd Panel 663r0935	Customer Interface ETAOEM Software T1n001 663R0935-4031
663r040-1pb Et	LAMTEC SYSTEM BUS FIELD BUS MODUL 663R040-1PBET Software A9 001
659r60 (Kompaktflammenwã196;Chter F200k)	
F200k Konfiguration: 02/Z2/0/0/0/0/0/	
662r2125/N	
Etamatic V.	
659r60	
66301000	
Bt320-667r1320-1	
662r2127 6nm Ip5	
662r2111 20nm Oem!!	
657r0836	
659r30	
Oem S 66301 10021 Ssap	
662r2127 Oem!!	
657r0791	Ersatzfüllung für Pumpen-Schutzfilter 657R0789 / R790 / R0792 (10-Stück-Packung)
Profibus Dp Fieldbus	
663r040	
659r60 (Without Ex)	
659r6010	

662r2125	
Fpb2500/3500 Mot.	ELEKTRODENZ¼NDUNGSEINHEIT
Order No:663r9000	
662r2127 6nm	
662r2127	
650r1000	
655r0022	
657r0872	SADECE POMPADIR Sample gas pump 12 VDC, nozzle position D, incl. Vibration steamer, for LT1 / LS1 customs tariff no: 90271090
Order No:663o1000	
662r2140	
662r2112	
Etamatic Oem 663o1-10000 Ssap	Software H5.4004 Flame monitoring 50 Hz.
662r2413 6nm	
663r9000	
662r211/N	
66301100	
659s1600	
650r0900	Repair Kit "Critical Nozzle Lambda Sensor LS1"
657r0872-Obsolete!! Replaced With Quot;657r0936quot;	
655r0027	O2 ANALYZER GAS DRAWING ROD (MEV), LENGTH = 1M 80100071023
66301-10000ssap Ce 0085 Au 0207 Ce 0036 Vin 115-230v 50 Hz 50 Va Oem!!	
Fms-4	
657r0936	
Etamatic Oem	
663r0401	
663r0100	
Etamatic Oem 66301-10 000 S	
662r2111	

650R2000	Lambda sensor LS2 Eco
655r0212	Filter attachment 20 µm, incl. Baffle plate, for MEV protection tube up to 700 ° C (standard)