Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Laumas

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Laumas Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Laumas Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Ftp 500	Load cell FTP 500kg - Stainless steel load cell - Combined error <+ / - 0.2% F.S. - Degree of protection IP 67/68 Nominal load 500kg Cable length 5m Stainless Steel AISI 420 Construction - Combined Error <+/- 0.2% F.S. - Protection class IP68 Max 500kg cable length 5m
Wz Cbl 250- 10000 500 Kg	very flat pressure load cell Nominal load: 500 kg 17-4PH stainless steel construction Combined error <+ / - 0.03% (0.02% C3) Protection class IP 68 (on request IPX9K **) ATEX on request
Wz Cbl 250- 10000 2500kg	very flat pressure load cell Nominal load: 2500kg 17-4PH stainless steel construction Combined error <+ / - 0.03% (0.02% C3) Protection class IP 68 (on request IPX9K **) ATEX on request
Wz Ftp 1000	very flat pressure load cell Nominal load: 1000 kg 17-4PH stainless steel construction Combined error <+ / - 0.03% (0.02% C3) Protection class IP 68 (on request IPX9K **) ATEX on request
Wz Cbl 250- 10000	very flat pressure load cell

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Nominal load: 1000 kg 17-4PH stainless steel construction Combined error <+ / - 0.03% (0.02% C3) Protection class IP 68 (on request IPX9K **) ATEX on request
Loadcell Laumas Apl C3 200 Kg	
Wz Apl 100	APL single point load cell Aluminum alloy Max. Faheler 0.02% Maximum load 200kg legal for trade class III
W 200	Weighing indicator DIN housing (96 x 96 x 130 mm, Cabinet cutout 91x91mm) IP54 front protection class. 6-digit red LED semi-alphanumeric display (14 mm h), 7 segment; 8-piece LED. five Key membrane keyboard. Real-time Clock with backup battery. HS code: 90319000
21008-Profinet	TLB Profinet -compact, digital weight transmitter for strain gauge load cells for Suitable for DIN rail mounting, with 6 digit 7 segment LED Status display Serial interface RS 485 and Profinet I / O Country of manufacture: Italy / Italy HS Code: 90319000
Taipan 365	MICROCONTROLLER TAIPAN 365 for continuous dosing of free flowing products and Bulk solids FLOW RATE CONTROLLER FOR CONTINUOUS WEIGHING
AZL-0010	Nominal loads: 10, 15, 20, 30, 50, 100 kg
Single point load cell AZL 50	Combined error ≤ ± 0.02% C3 Max 50kg HS Code: 9031.80.80 Country of origin: Italy

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
TLB 4 485	Multi-channel weighing transmitter TLB 4 Weight transmitter with six-digit red LED display (8 mm high). Space saving compact design. Four buttons for system calibration. Dimensions: 26 x 115 x 120 mm. 4 independent read channels for Load cells (individual Load cell monitoring, display of the Total weight, digital Corner adjustment) RS485 serial port Baud rate: 2400, 4800, 9600, 19200, 38400, 115200 (bit / s)
E0027709	
FCA KG500	22MN WASHERS TENSIONER LOADCELL FCA KG500
NO. 0099942	
TLB485 INDICATOR JOLLYTLB485 S/N (105203197)	
PRC6	Bending beam load cell - Measuring range / type of force: 6kg / pressure force - Accuracy: ± 0.02% of the final value - Sensitivity: 2 mV / V ± 10% - Supply voltage: 10 VDC - Usage / nominal temperature: -20 ° C to + 65 ° C / -10 ° C to + 40 ° C - Electrical connection: cable, length 3 m - Mech. Connection: internal thread M6x1 - Degree of protection: IP67 - Accuracy class: C3 Further specifications according to data sheet Commodity code: 9031 80 80
17-4 PH	
ACN60	
AM60	
ANTIV40	
APL100	
AR 1000	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
AZL100	
AZL20C3	
AZLI50	
BARRIERAMTL7761AC	
C41N	- Input / number of channels: 4/4 - Design / mounting type: plastic housing - Electrical connection: 5 x PG screw connection M12 - Degree of protection: IP67 -Shock protected
CA75/50T	
CBL 250Kg	
CBL 5.000Kg	
CBL10000	
CBL1000L	
CBL250	
CBL2500	load cell - Measuring range / type of force: 2500 kg / compression force - Accuracy: ±0.03% of final value - Sensitivity: 2mV/V ±0.1% - Supply voltage: 10 VDC - Service / nominal temperature: -20°C to +70°C / -10°C to +50°C - Electrical connection: cable, length 5 m - Mech. Connection: pressure initiation button - Degree of protection: IP68
CBL30000	
CBL5000	
CBL7500	
CK2500	
CL10000	
CL20000KG	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
CL500	
CL5000	
CL500KG	
CTL1000	
CTL200	
CTL2500	
CTL300	
CTL500	
CTL5000	
F2007453	
FCAL50	
FCAX 75KG	
FCAX300	
FCAX75	
FTK150	
FTK5000	
FTK75	
FTKL500	
FTP150	
FTP300	
FTP3000	
FTP500	
FTP5000	
JOLLYCLM8	
JOLLYTLBETHERCAT	
JOLLYTLBPROFI	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
JOLLYTLS	
JOLLYTLU	
JOLLYTPS	
JOLLYW100	
N. D256066	
PEC500	
PIEDINOSB2M8	
PRC30	
PS	
PTC100	
PTC75	
P-WS 3 PRODOTTI	
PWS4S	
RS485 TLB	
SIM	
SL200	
SL500	
TF500	
TLB	
TLB4	
TLB485	
TLB4ETHEIP	
TLB4RS485	
TLE	
TLE RS485 + ANALOG OUT-PUT	
TPS	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
W100	Digital display W100 - Design / Mounting type: 48 mm housing x 96 mm / Installation in front panel - Output signal: digital (RS232/RS485) - Supply voltage: 12 - 24 VDC, 5 W - Operating temperature: -20°C to 60°C - Electrical connection: 8 parallel load cells via connection box Further specifications can be found in the datasheet.
1002400	W200-BASE Evaluation electronics with digital display in a DIN housing 96x96x130 mm - Design: Front panel installation - Supply voltage: 12-24 VDC, 5 W - Electrical connection: Spring-loaded terminals - Bridge voltage: 5 VDC - Resolution: 24 bits - Digital display (IP54) - Digital output signal: RS232/RS485 (Modbus RTU) - Operating temperature: -20°C to 60°C Further specifications can be found in the datasheet.
W200BOX-B	
WINOXGMUP	
WL60 3	
WL60 3 PRODOTTI	
WL60 BASE	
CK2500	
WINOXRBP-0PZW1PNETIO68	1007824 LCD display - Design / mounting type: including bracket - Output signal: PROFINET / IO - Supply voltage: 115 / 230 VAC; 50/60Hz; 6VA - Service temperature: -30°C to +80°C - Electrical connection: PG9 6 M16x1.5 cable gland - Degree of protection: IP 68 -More specifications according to data sheet
V10000	mounting kit - for load cells CBL 250 - 12500kg, CBX15000 - Material: stainless steel

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
WINOXR-BP-OPZW1PNETIO68	- Design / mounting type: including bracket - Output signal: PROFINET / IO - Supply voltage: 115 / 230 VAC; 50/60Hz; 6VA - Service temperature: -30°C to +80°C - Electrical connection: PG9 6 M16x1.5 cable gland - Degree of protection: IP 68 -More specifications according to data sheet Statistical goods number: 8543 70 90
FCOL50	shear beam load cell - Measuring range / type of force: 50 kg / weight force - Accuracy: ±0.02% of final value - Sensitivity: 2mV/V ±1% - Supply voltage: maximum 18 VDC - Service / nominal temperature: -35° to +65°C / -10° to +40°C - Electrical connection: cable, 3 m long - Mechanical connection: 3x through-holes Ø8.2 mm - Degree of protection: IP68 Further specifications according to data sheet
CX10000	compression load cell - Measuring range / type of force: 10,000 kg / compression force - Accuracy: ±0.05% of final value - Sensitivity: 2mV/V ±0.1% - Supply voltage: 10 VDC - Service / nominal temperature: -20°C to +60°C / -10°C to +50°C - Electrical connection: cable, length 10 m - Mech. Connection: pressure initiation button - Degree of protection: IP68 Further specifications according to data sheet Statistical goods number: 9031 80 80
W100ANA	- Design / mounting type: housing 48 mm x 96 mm / installation in front panel - Output signal: digital (RS232/RS485), analogue - Supply voltage: 12 - 24 VDC, 5 W - Temperature of use: -20°C to 60°C - Electrical connection: 8 parallel load cells via connection box Further specifications according to data sheet Statistical goods number: 8543 70 90
CTL2500	S-shape load cell - Measuring range / type of force: ±2,500 kg / push and pull force - Accuracy: ±0.02% of final value

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	- Output signal / sensitivity: 2 mV/V - Supply voltage: 10 VDC - Service / nominal temperature: -20°C to +70°C / -10°C to +50°C - Electrical connection: cable, length 10 m - Mechanical connection: Internal thread M20x1.5 on both sides - Degree of protection: IP68 Further specifications according to data sheet
CBL- 2500 C2	
CBL2500	load cell - Measuring range / type of force: 2500 kg / compression force - Accuracy: ±0.03% of final value - Sensitivity: 2mV/V ±0.1% - Supply voltage: 10 VDC - Service / nominal temperature: -20°C to +70°C / -10°C to +50°C - Electrical connection: cable, length 5 m - Mech. Connection: pressure initiation button - Degree of protection: IP68 Further specifications according to data sheet Statistical goods number: 9031 80 80
SA15	1002800 S-shaped load cell - Measuring range / type of force: 15 kg / pulling and pushing force - Accuracy: ±0.02% - Sensitivity: 2mV/V ±10% - Supply voltage: 10 VDC - Service / nominal temperature: -20° to +60°C / -20° to +40°C - Electrical connection: cable, length 3 m - Mechanical connection: internal thread M6x1, on both sides - Degree of protection: IP65 Further specifications according to data sheet
SA30	1006440 S-shaped load cell - Measuring range / type of force: 30 kg / pulling and pushing force - Accuracy: ±0.02% - Sensitivity: 2mV/V ±10% - Supply voltage: 10 VDC - Service / nominal temperature: -20° to +60°C / -20° to +40°C - Electrical connection: cable, length 3 m

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	- Mechanical connection: internal thread M6x1, on both sides - Degree of protection: IP65 Further specifications according to data sheet
SA60	1007304 S-shaped load cell - Measuring range / type of force: 60 kg / pulling and pushing force - Accuracy: ±0.02% - Sensitivity: 2mV/V ±10% - Supply voltage: 10 VDC - Service / nominal temperature: -20° to +60°C / -20° to +40°C - Electrical connection: cable, length 3 m - Mechanical connection: internal thread M6x1, on both sides - Degree of protection: IP65 Further specifications according to data sheet
SL300	1009733 S-shaped force transducer - Measuring range / type of force: 300 kg / push / pull force - Accuracy: ±0.02% FS, C3 - Sensitivity: 2mV/V - Supply voltage: 10VDC - Service / nominal temperature: -35°C to +60°C / -10°C to +40°C - Electrical connection: cable, length 5 m - Mechanical connection: female thread M12x1.75 on both sides - Degree of protection: IP67 Further specifications according to data sheet
CTOL100	1002900 CTOL100 S-shaped load cell - Measuring range / type of force: 100 kg / push and pull force - Accuracy: ±0.03% of final value - Output signal / sensitivity: 2 mV/V - Supply voltage: 10 VDC - Service / nominal temperature: -20°C to +60°C / -10°C to +40°C - Electrical connection: cable, length 10 m - Mechanical connection: Internal thread M12x1.75 on both sides - Degree of protection: IP67 Further specifications according to data sheet

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
CTOL-100KG	
12500kg load cell	
CBL1000	1002848 load cell - Measuring range / type of force: 1000 kg / compression force - Accuracy: ±0.03% of final value - Sensitivity: 2mV/V ±0.1% - Supply voltage: 10 VDC - Service / nominal temperature: -20°C to +70°C / -10°C to +50°C - Electrical connection: cable, length 5 m - Mech. Connection: pressure initiation button - Degree of protection: IP68 Further specifications according to data sheet
CTL2500	S-shape load cell - Measuring range / type of force: ±2,500 kg / push and pull force - Accuracy: ±0.02% of final value - Output signal / sensitivity: 2 mV/V - Supply voltage: 10 VDC - Service / nominal temperature: -20°C to +70°C / -10°C to +50°C - Electrical connection: cable, length 10 m - Mechanical connection: Internal thread M20x1.5 on both sides - Degree of protection: IP68
S/N:133222073	
1002869	AZL30 Bending beam load cell - Measuring range / type of force: 30 kg / push / pull force OIML R60 C3 - Accuracy: ±0.02% of final value - Sensitivity: 2mV/V ±10% - Supply voltage: 10 VDC - Service / nominal temperature: -35°C to +65°C / -10°C to +40°C - Electrical connection: cable, length 6 m - Mechanical connection: M6x1 internal thread - Degree of protection: IP65 Further specifications according to data sheet
1002363	TLB4-ProfinetIO

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Strain gauge evaluation electronics - Input sensitivity / number of channels: ±7 mV/V / 4 - Design / mounting type: Module row housing / DIN rail mounting - Output signal: 2x PROFINET IO connections / RS485 - Supply voltage: 12 - 24 VDC - Temperature of use: -20°C to +60°C - Electrical connection: screw terminals, pluggable - Resolution 16 bits - Bandwidth 600 Hz - Particularities: 6-digit LED digital display, 3 relay outputs, 2 functional inputs Further specifications according to data sheet
1003614	A-DMS-1K Adaptation of a measuring amplifier or a display unit to a strain gauge transducer - Offset check of the strain gauge transducer - Adjustment/programming of the measuring amplifier or the display according to the DMS transducer certificate - Creation of an assignment/configuration Documentation with details of the pin assignment Scaling: XXXXX / XXXX analog output
W 200	
AZS200	Bending beam load cell - Measuring range / type of force: 200 kg / pressure force - Accuracy: ±0.03% of final value - Output signal / sensitivity: 2 mV/V - Supply voltage: 10 VDC - Service / nominal temperature: -20°C to + 60°C / -10°C to +40°C - Electrical connection: cable, length 6 m - Mechanical connection: 6 x M6x1 internal thread - Degree of protection: IP67 Further specifications according to data sheet
26150053	W100 Weight Indicator
APL 100	Bending beam load cell - Measuring range / type of force: 100 kg / pressure force - Accuracy: ±0.02% - Output signal: 2mV/V - Supply voltage: max. 18 V - Usage/nominal temperature: -35°C to +65°C / -10°C to +40°C - Electrical connection: integrated cable, length 3 m

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	- Mechanical connection: M8 screws - Protection class: IP65 Further specifications according to data sheet
1008615	CX10000 Compression load cell - Measuring range / type of force: 10,000 kg / pressure force - Accuracy: ±0.05% of full scale - Sensitivity: 2mV/V ±0.4% - Supply voltage: 10 VDC - Usage/nominal temperature: -20°C to +60°C / -10°C to +50°C - Electrical connection: cable, length 10 m - Mechanical connection: pressure introduction button - Protection class: IP68 Further specifications according to data sheet
1012040	CX30000 Compression load cell - Measuring range / type of force: 30,000 kg / pressure force - Accuracy: ±0.05% of full scale - Sensitivity: 2mV/V ±0.4% - Supply voltage: 10 VDC - Usage/nominal temperature: -20°C to +60°C / -10°C to +50°C - Electrical connection: cable, length 10 m - Mechanical connection: pressure introduction button - Protection class: IP68 Further specifications according to data sheet
1003806	FTP1000 Shear beam load cell - Measuring range / type of force: 1,000 kg / pressure force - Accuracy: ±0.02% of full scale - Output signal / sensitivity: 2 mV/V - Supply voltage: 10 VDC - Usage/nominal temperature: -20°C to +70°C / -10°C to +40°C - Electrical connection: cable, length 5 m - Mechanical connection: 2x through holes 13.5 mm, 1x internal thread M12x1.75 - Protection class: IP68 Further specifications according to data sheet
AZL20	1002871 Bending beam load cell - Measuring range / type of force: 20kg/pressure/pull force OIML R60 C3

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	- Accuracy: ±0.02% of full scale - Sensitivity: 2mV/V ±10% - Supply voltage: 10 VDC - Usage/nominal temperature: -35°C to +65°C / -10°C to +40°C - Electrical connection: cable, length 6 m - Mechanical connection: M6x1 internal thread - Protection class: IP65 Further specifications according to data sheet
TLB4-RS485	1003886 DMS evaluation electronics - Input sensitivity / number of channels: ±7 mV/V / 4 - Design/mounting type: Module row housing / DIN rail mounting - Output signal: RS485 - Supply voltage: 12 - 24 VDC - Operating temperature: -20°C to +60°C - Electrical connection: screw terminals, pluggable - Resolution: 24 bits - Bandwidth: 600 Hz - Particularities: 6-digit LED digital display, 3 relay outputs, 2 function inputs Further specifications according to data sheet
FCOL50	1008388 Shear beam load cell - Measuring range / type of force: 50 kg / weight - Accuracy: ±0.02% of full scale - Sensitivity: 2mV/V ±1% - Supply voltage: maximum 18 VDC - Usage/nominal temperature: -35° to +65°C / -10° to +40°C - Electrical connection: cable, 3 m long - Mechanical connection: 3x through holes Ø8.2 mm - Protection class: IP68 Further specifications according to data sheet
FCOL100	1007233 Shear beam load cell - Measuring range / type of force: 100 kg / weight - Accuracy: ±0.02% of full scale - Sensitivity: 2mV/V ±1% - Supply voltage: maximum 18 VDC - Usage/nominal temperature: -35° to +65°C / -10° to +40°C - Electrical connection: cable, 3 m long - Mechanical connection: 3x through holes Ø8.2 mm - Protection class: IP68

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Further specifications according to data sheet
1002158	W100 Digital display W100 - Design / mounting type: housing 48 mm x 96 mm / installation in front panel - Output signal: digital (RS232/RS485) - Supply voltage: 12 - 24 VDC, 5 W - Operating temperature: -20°C to 60°C - Electrical connection: 8 parallel load cells via connection box Further specifications according to data sheet
1002176	TLB-ProfinetIO DMS evaluation electronics - Input / number of channels: mV/V / 1 channel - Design / mounting type: Modular housing / DIN rail mounting - Output signal: 2x Profinet IO / RS485 - Supply voltage: 12 - 24 VDC - Operating temperature: -20°C to +60°C - Electrical connection: screw terminals, pluggable - Resolution 24 bit - Bandwidth 300 Hz - Special features: 6-digit LED digital display, 3 relay outputs, 2 function inputs Further specifications according to data sheet
1012627	AU3 Bending beam load cell for platforms 250 x 400 mm - Measuring range / force type: 3 kg / pressure force - Accuracy: ±0.02% of the final value - Output signal / sensitivity: 2 mV/V ±10% - Supply voltage: 10 VDC - Operating / nominal temperature: -20°C to + 60°C / -10°C to +40°C - Electrical connection: cable, length 3 m - Mechanical connection: 8 x M4x0.7 internal thread - Protection class: IP65 Further specifications according to data sheet
1002792	PRC30 bending beam load cell - Measuring range / force type: 30 kg / pressure force - Accuracy: ±0.02% of final value - Sensitivity: 2 mV/V ±10% - Supply voltage: 10 VDC - Operating / nominal temperature:

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	-20°C to +65°C / -10°C to +40°C - Electrical connection: cable, length 3 m - Mech. Connection: Internal thread M6x1 - Protection class: IP67 - Accuracy class: C3 Further specifications according to data sheet
TLB-ProfinetIO	002176 strain gauge evaluation electronics - Input / Number of channels: mV/V / 1 channel - Design / mounting type: module row housing / DIN rail mounting - Output signal: 2x Profinet IO / RS485 - Supply voltage: 12 - 24 VDC - Operating temperature: -20°C to +60°C - Electrical connection: screw terminals, pluggable - Resolution 24 bit - Bandwidth 300 Hz - Special features: 6-digit LED digital display, 3 relay outputs, 2 function inputs Further specifications according to data sheet
TLB4-RS485-	Strain gauge evaluation electronics - Input sensitivity / number of channels: ±7 mV/V / 4 - Design / mounting type: Modular housing / DIN rail mounting - Output signal: RS485 - Supply voltage: 12 - 24 VDC - Operating temperature: -20°C to +60°C - Electrical connection: screw terminals, pluggable - Resolution: 24 bit - Bandwidth: 600 Hz - Special features: 6-digit LED digital display, 3 relay outputs, 2 function inputs Further specifications according to data sheet
1009617	FTP75 Shear beam load cell - Measuring range / force type: 75 kg / pressing force - Accuracy: ±0.02% of the final value - Output signal / sensitivity: 2 mV/V - Supply voltage: 10 V DC - Protection rating: IP68 - Operating / nominal temperature: -20°C to +70°C / -10°C to +40°C - Electrical connection: Cable, length 5 m

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	- Mechanical connection: 2x through holes 13.5 mm, 1x internal thread M12x1.75
1006209	LCBPROFINETIO Evaluation electronics with Profinet interface - Entrances: 1 - Design: Stainless steel housing - Output signal: PROFINET I/O - Supply voltage: 12 to 24 VDC - Resolution: 24 bits - Input sensitivity: ±7mV - Bandwidth: 300 Hz Further specifications can be found in the datasheet.
Cbl 5000 Sensor	
Am150 Am 150kg Single-Point Load Cell 400x400mm Aluminum Ip65 Oiml R60 C3	
W100 Anzeigeweight Indicator - 5/4 Outputs (Setpoint) 3/2 I	
Cbl250 Cbl 250kg Compression Load Cell Stainless Steel 17-4 Ph Ip68	
Azl100 Azl 100kg Single-Point Load Cell 400x400mmalluminium Ip65 Oiml R60 C3	
W200 Weight Indicator	
All30 All 30kg Single-Point Load Cell 250x350mmaluminum Ip65 Oiml R60 C3	
Prc50 Single-Point Load Cell For Platforms 350x350 Mm	
Ftp 3000 Sensor	
Am200 Single-Point Load Cells For Platforms 400 X 400 Mm	
Tle Transmitteranalog Weight Transmitter With Rs485	
Pe 75	
Gewichtung A-Wandler Mit. Profinet Tlb Profinet Io	
Cip67	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Ctl500 Tension (Compression) Load Cells	
Am200	
50kg Load Cell	
Tc D09-09.16 Load Cell Nlaa 20a05399	
26689	
Fcal150 Bending Beam Load Cells	
Jollytls Weight Transmitter Model Tls Rs485 + Analogout-Put	
Pf Kg 15 Nã175; 312493 Mv/V 2,0130	
Am150	
Ftp-1000 Shear Beam And Bending Load Cells	
Adpew200ana	
F2010822 Tc D09-09.16	
Tlb C Rs485 Digital-Analog-Wandler	
Ftk500 Ftk 500kg Shear Beam Load Cell Ally Steelip68	
Tf2000z	
Ftk75 Load Cell	
Cbl30000 Sensor	
P-Ws 3 Prodotti Sensor 12 Formule	
F2121520	
Rs485 W100	
Cavo6020s	
8m1160 Strain-Gage Indicator	
Ftkl-C3 Sensor	
W200box-B Basis	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
C3 Cella Di Carico Azli	
Ftk150 Ftk 150kg Bending Beam Load Cell Allysteel Ip67	
B21200 Load Cell Ftk500 Instal. 212b.4	
Cl20000kg Loadcell	
Am150 Single-Point Load Cell For Platforms 400x400 Mm	
Jollytls Gewicht Messumformer Weight Transmitter Model Tls Rs485 + Analogout-Put	
W2003	
Cl10000 Compression / Tension Load Cells	
Sl200 Tension (Compression) Load Cells	
Apl 100 C3 Cella Di Carico Azli	
Ctl200 Tension (Compression) Load Cells	
Ce41atex	
Fcal150	
Lw 30 000r	
Jollyw100ana	
Cl500 Tension Load Cells	
Cbl15000	
Mviv-2 Y-12000 Cella Di Carico Azl C3 Emax-50kg	
B21202 Load Cell Ftk500 Instal. 212b.	
Tlb Profibus Weight Converter (For Large Insulator Line Reactor Equipment)	
Pws4s Weight Indicator Model P-Ws 4 Set	
Cbl500 Cbl 500kg Compression Load Cell Stainless Steel 17-4 Ph Ip68	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Cl5000 Compression / Tension Load Cells	
Jollytls Weight Converter	
Am150 Load Cellsingle-Point Load Cell For Platforms 400x400 Mmip65 Aluminum Oiml R60 C3	
Ftp3000 Ftp 3.000kg Shear Beam Load Cell Stainless Steel Aisi 420 Ip68	
Jollyw100ana Weight Indicator Model W100 + Analog Out-Putenglish Manual	
Sku:W200	
Jollytlbprofinetion Weight Transmitter Model Tlb Rs485 +profinet Io 2 Ports	
B20000 Load Cell Ftk1000 Instal. 200b.4	
Ce41atex Die Steuereinheit	
Ftp1000 Ftp 1.000kg Shear Beam Load Cell Stainless Steel Aisi 420 Ip68 Oiml R60 C3	
Fcax300 Fcax 300kg Bending Beam Load Cell Stainlesssteel Aisi 420 Ip68	
Ftp1000 Ftp 1.000kg Shear Beam Load Cell Stainlesssteel Aisi 420 Ip68 Oiml R60 C3	
192.168.102.106 Weight Controller	
Fun6141t1t	
Cbl 2500 Sensor	
Azl C3 Cert.D09-07.51	
D09-07 46	
Fcal300	
Am150 Am 150kg Single-Point Load Cell 400x400mmaluminum Ip65 Oiml R60 C3	
V10000-275 For Cbl	
Jolly2	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Azl50	
Cbl 15000	
Jollytlu Load Limiting Device Model Tlu Rs485 Rs232	
Jollyw100ana Wiegeindikatorweight Indicator Model W100 + Analog Out-Putenglish Manual	
Jollyw100ana Die Gewichtsanzeigeweight Indicator Model W100 + Analog Out-Putenglish Manual	
Tps420 (Tps420~transmitter, S047, 400kg=20ma)	
Gewichtcontroller Wdosc	
Cbl 5.000kg Sensorcompression Load Cell Stainlesssteel 17-4 Ph Ip68 Oiml R60 C2	
Azli C3 Sensor	
Ftk1000 Ftk 1.000kg Shear Beam Load Cell Allysteel Ip68 Oiml R60 C3	
N. D256066 Tensometrische Sensorfcax Kg 750m V/V 2.0040	
Ftp1000	
Ftk2000	
All3	
Cbl-1000l Sensor	
Wl-60000	
Cbl 2500	
Cbl-15000 Sensor	
Ftk 500	
Jollytls Weight Transmitter Model Tls Rs485 + Analogout-Put	
Prc 50 Stainless Steel Aisi 420	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Constructioncombined Error	
Tle Analog Weight Transmitter With Rs485	
Fcax	
Ctl-2500kg	
Cbl 250 Sensor	
Cbl250 Cbl 250kg Compression Load Cellstainless Steel 17-4 Ph Ip68	
F2007453 Gewichts-Sensor Ftp Cable 5mtemax: 1000 Kg C3tc D09-09.16ftp-Sh 1t	
Cbl 250kg Compression Load Cell Stainlesssteel 17-4 Ph Ip68	
Ctl1000 Sensortension (Compression) Load Cell	
Althen Aosbha-2t Load Cell	
Hl6n	
Ftk 1000	
Fcal50 Fcal 50kg Bending Beam Load Cell Stainlesssteel 17-4 Ph Ip68 Oiml R60 C3	
Fcax150	
Pf15	
Ft-P1000	
Fcax 300 Sensor	
Ftk1000	
Ftk500	
Barrieramtl7761ac Passive Fail-Safe Barriers	
Ftp 1000kg	
Wl60 3 Weighing System	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
B21201 Load Cell Ftk500 Instal. 212b.5	
Ftp3000 Sensor	
Sa15	
Load Cell	
17-4 Ph Bending Beam Load Cell Stainless Steel Ip68 Oiml R60 C3 150kg	
Fcol100	
Ctl300 Ctl 300kg Tension/Compression Load Cell M12stainless Steel 17-4 Ph Ip68	
Clm8 Morsettiera	
Cbl250 Element Gefragt Belastung	
Ar 1000 Single-Point Load Cells For Platforms 800 X 800 Mm	
Fcol50	
Ctl5000 Ctl 5.000kg Tension/Compression Load Cell M24 Stainless Steel 17-4 Ph Ip68 Oiml R60 C3	
Antiv 40	
Model W100	
Cbl 10000 Kg Cbl10000	
B20001 Load Cell Ftk1000 Instal. 200b.5	
Ca75/50t Anchor Load Cellint.Diam. 75mm Ext. 163mm	
Cx 2500 Sensor	
Ftk 150kg Load Cell	
Wl60 3 Prodotti Anzeige	
Cx2500l	
Prc6	
Cbl5000 Cbl 5.000kg Compression Load	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Cell Stainlesssteel 17-4 Ph Ip68 Oiml R60 C2	
Ca75/50t Anchor Load Cell Model Ca75/50tint.Diam. 75mm Ext. 163mm	
Ctl-300 Tension (Compression) Load Cells	
Ftp1000 Shear Beam And Bending Load Cells	
Am100	
Ftp 1000	
Cbl 5.000kg Compression Load Cell Stainlesssteel 17-4 Ph Ip68 Oiml R60 C2	
Sl500 Tension (Compression) Load Cells	
Ctl2500 Sensor	
Simd Digital Weight Load Cell Simulator	
Fcax 500kg	
Am100 Single-Point Load Cells For Platforms 400 X 400 Mm	
W60000 , W100	
Tf-Ps 2000 Series 300 Kg	
Azl50 Single-Point Load Cells For Platforms 400 X 400 Mm	
Ftp-300 Load Cell	
Fcol20	
Fcax 75kg Sensor	
Azl20c3 Single-Point Load Cells For Platforms 400 X 400 Mm	
Fcol20 Bending Beam Load Cells	
??2500 Sensor	
B20002 Load Cell Ftk1000 Instal. 200b.7	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Cbl 250kg Sensorcompression Load Cell Stainlesssteel 17-4 Ph Ip68	
Tls010 Special Fuses	
W100 Anzeigeweight Indicator Model W100 Rs485 + Rs232	
Tps420	
Ft-P1000 Ft-P 1.000kg Shear Beam Load Cell Stainless Steel 17-4 Ph Ip68 Oiml R60 C3	
Fcax75 Bending Beam And Shear Load Cells	
Jollytps Weight Transmitter Model Tps With Analogout-Putenglish Manual	
Fca Kg500 Obsolete, Replaced By Fcax 500kg	
All30	
Cl500kg Power Sensor	
10 398 Tpz	
Cbl1000	
Cbl500	
Prc50	
W100 Weight Indicator - 5/4 Outputs (Setpoint) 3/2 Inputs	
Piedinosb2m8 For Bending Beam And Shear Beam Load Cells	
Lped100	
72819 Load Cell	
Ck2500 Sensor	
Ftp150 Shear Beam And Bending Load Cells	
Cbl250 Cbl 250kg Compression Load Cell Stainlesssteel 17-4 Ph Ip68	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Cella 5000 Kg	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.