

Leuze



Garanti: 12 ay
Bu rne ait Trkiye iĐi kapı teslim fiyat ve teslim sresi iĐeren teklifimizi almak iĐin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iĐin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Leuze** Markası, tedarik sresi iĐin ltfen bizimle iletiŐime geĐiniz.

Firmamız Leuze Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	AĐıklama
GS 61/6.2-S8	50110108 Fork light barrier Physical principle: optical Application: Detection of non-transparent labels Label width, min .: 2 mm Label gap, min .: 2 mm Medium: not transparent Light source: LED, infrared Supply voltage: 10 ... 30 V, DC Digital switching outputs: 1 pc. Switching output 1: transistor, push-pull, switching signal in label gap Switching frequency: 10,000 Hz Connection: round plug, M8, 4-pin Connector outlet: horizontal (parallel to the belt run) Mouth width: 3 mm Mouth depth: 41 mm Dimensions: 11mm x 30mm x 60mm Housing material: plastic Operating elements: Teach button Net weight: 20 g eCl @ ss 9.0: 27270909 Customs tariff number: 85365019 Country of origin: China
50110192	
PRK46C / 4P-M12	Polarized retro-reflective photoelectric sensor
MSI-s / R	safety relay
PRK 96M / R-3420-25	Polarized retro-reflective photoelectric sensor
PRK3CL1.A3/4T-M8	Reflex-Lichtschranke polarisier

HRTR 318M/66-120-S12	Background suppression button
HT46C/4P-M12	Background suppression button
HRT 96M/P-1610-1200-41	
HT3C/4P-M8	
PRK-96K/R-1420-25	Polarized reflex light barrier
LEUZE PRK-96M/R-3420-25	
PRK 96M/P-1361-47	
HRT 46/44-800-S12	
HRTR 46B/66,200-S12	Background suppression button
LEUZE HT46C/4P-M12	Background suppression
LEUZE MLC520-S-14-1020	Safety sensor set 68601102
HT46CI/4P-M12 50127061	HT46CI / 4P-M12 Background suppression button Range limit: 0.005 ... 3 m Light source: LED, infrared Supply voltage: 10 ... 30 V, DC Digital switching outputs: 2 pcs. Switching output 1: transistor, PNP, light switching Switching output 2: transistor, PNP, dark switching Switching frequency: 250 Hz Connection: round plug, M12, plastic, 4-pin Housing design: cubic Dimensions: 20.5mm x 76.3mm x 44mm Housing material: plastic Control elements: multi-turn spindle Ambient temperature, operation: -40 ... 60 ° C Protection class: IP 67, IP 69K Net weight: 60 g; 27270904
PRK 96K/R-1420-25	Polarized retro-reflective photoelectric sensor 50025167
PRK 96M/P-3380-41	olarized retro-reflective photoelectric sensor 50061452
ODS 96B M/C6-600-S12	LEUZE 50106720
LEUZE HT46C/4P-M12	Background suppression button
LEUZE MLC510R14-1800	Safety light curtain receiver
LEUZE MLC500T14-1800	Safety light curtain transmitter
LEUZE MLC520R14-1500	Safety light curtain receiver
LEUZE MLC500T14-1500	Safety light curtain transmitter
LEUZE MLC520R14-1350	
LEUZE MLC500T14-1350	
LEUZE MLC520R14-1650	
LEUZE MLC500T14-1650	
LEUZE MLC520R14-1800	
LEUZE MLC500T14-1800	
HT3C/4P-M8	50129375 Background suppression button
PRK25C.D/4P-12	

LEUZE HRTR 55/66-S8	Background suppression button
HRTL 8/66-350,5000	2701919 Background suppression button
50127024 PRK46C.D/4P-M12	Since the item 777555 on offer is a special purchase, it is dated Exchange and return excluded, except for warranty claims! 50127024 PRK46C.D/4P-M12 polarized reflex light barrier
66537100 MLD510-RT2	Since the item 777555 on offer is a special purchase, it is dated Exchange and return excluded, except for warranty claims! 66537100 MLD510-RT2 multi-beam safety light. transceivers
430410 RS4-clean-Set2	Since the item 777555 on offer is a special purchase, it is dated Exchange and return excluded, except for warranty claims! 430410 RS4-clean-Set2 Cleaning set
PRK 96M/P-1370-42	Reflex light barrier polarized
PRK46C/4P-M12	2144786 Reflex light barrier polarized
BT 46	2828994 fastening part
HT46CL2/48-M12	
50137817	ODS9L2.8/LAK -650-M12
HRT 96K/P-1630-800-41	
LE3CL1.1/6G	One-way photocell receiver
LS3CL1/XX	One-way photocell receiver
50109676	ISS 212MM/4NC-4E0-S12 Inductive sensor Type. Limit range Sn: 4 mm Operating range Sa: 0 ... 3.2 mm Supply voltage: 10 ... 30 V, DC Digital switching outputs: 1 pc. Switching output 1: transistor, PNP, normally closed (NC) Switching frequency: 2,500 Hz Connection: circular connector, M12, 4-pin Housing design: cylindrical Thread size: M12 Dimensions: 12mm x 45mm Installation type: flush Material housing: metal Approvals: c UL US Net Weight: 18g eCl@ss 9.0: 27270101
50025609 PRK 95/44 L.4	
TKA 30X60	50108215
ISS 212MM/4NC-4E0-S12	
IS 112 MM/4NO-4E0-M12	
112 MM/xNx-4E0-M12	
DDL5 200/120.2-10	2850339 Optical data transmission
MSI-m/R	2516680 safety switching device/starting/how the start lock (RES), selectable,
	50146167 Fork light barrier Series 04B Physical principle optical Application detection of small parts MTTF 700.42 years Light source LED, red Wavelength 660 nm Pulsed transmission signal form Repeatability 0.02 mm Minimum object diameter 0.3 mm Protective circuit short circuit protection Reverse polarity protection Supply voltage UB 10 ... 30 V, DC Residual ripple 0 ... 15%, from UB No-load current 0 ... 30 mA Switching hysteresis

GS04B/P.1-80-M8.3	100 µm Number of digital switching outputs 1 piece. Type of digital switching output Voltage type DC Switching current, max. 100 mA Switching voltage high: ≥(UB-2V) low: ≤ 2V Switching element transistor, PNP Switching principle light/dark switchable Switching frequency 5,000 Hz Response time 0.1 ms Readiness delay 150 ms Number of connections 1 piece. Function signal OUT Power supply Type of connection round connector Thread size M8 Type male Material metal Number of poles 3-pole Fork design Jaw width 80 mm Jaw depth 55 mm Dimensions (W x H x L) 10 mm x 100 mm x 80 mm Housing material metal Housing metal zinc die-cast Optical cover material: glass Net weight 118g Housing color black, RAL 9005 Type of fastening Through fastening Type of display LED Number of LEDs 1 piece. Controls 270° potentiometer Function of the control element sensitivity adjustment Light/dark switching Ambient temperature operation -25 ... 60 °C Protection class IP 67 Protection class III Approvals c UL US Valid standards IEC 60947-5-2, DIN EN ISO 1389-1:2016 Annex C,D
HT46CI/4P-M12 50127061	
FRKR 95/44-350 L	
PRK46C.D/4P-M12; 50127024 SENSÖR	
UMS 96 500 26204	
LSS 96M-120W-43	
LSE 96M/P-181W-41	
HRT 96M/P-1640-800-41	
DL1A5A15	
HT46CI/4P-M12	Reflective optical sensor with background suppression by LEUZE, range: 0.005 ... 3 m; light source: infrared; supply voltage: 10-30V DC; output 1: PNP/NO; output 2: PNP/NC; 250 Hz; M12 4-pin connector; dimensions: 20.5 x 76.3 x 44 mm; housing: plastic
HT3CL2.B/4P-M8	Reflective optical sensor with background elimination by LEUZE, range: 0.015 ... 0.55 m; light: laser; error angle: typ.. ± 2°; power supply 10-30V DC; output1: PNP/NO; output2: PNP/NC; 3,000Hz; M8-4pin connector; dimensions: 11.4 x 34.2 x 18.3mm
PRK 46B/6,2-S12	50133045
HRTR 318M/66-120-S12	Reflective optical sensor with background suppression by LEUZE, measuring range, white 90%: 0.001 ... 0.14 m; light: Red; power supply 10-30V DC; output1: PNP/NPN output2: PNP/NPN; 1000Hz; M12-4pin connector; casing cylindrical: M18
ET328.3/4P	LEUZE reflective optical sensor, measuring range, white 90%: 0.001 ... 1 m; light: red; power supply 10-30V DC; output1: PNP/NO; output2: PNP/NC; 500Hz; 2m cable, 4-wire; cylindrical housing: M18; dimensions: 18 x 46 mm
IS 218MM/4NO-8EO	Inductive sensor by LEUZE, diameter M18, sn=8 mm, built-in front, PNP/NO, power supply 10-30 VDC, cable 2 m, 1500Hz, L=52mm
BPS 300i	

MS300	
KD S-M12-8A-P1-050	
PRK3CL1.BA3-LP-M8	
PRK28/4P-M12	Polarized reflective sensor from LEUZE, range: 0.02 ... 6 m; light: red; power supply 10-30V DC; output1: PNP/NO; output2: PNP/NC; 500Hz; M12-4pin connector; dimensions: 15 x 46.5 x 31.8 mm; cylindrical housing: M18; plastic housing
ET318B.3/4P-M12	LEUZE reflective optical sensor, measuring range, white 90%: 0.001 ... 1 m; light: red; power supply 10-30V DC; output1: PNP/NO; output2: PNP/NC; 500Hz; M12-4pin connector; cylindrical housing: M18; dimensions: 18x46mm
KD U-M12-4A-V1-020	Connection cable from LEUZE Electronic
HT46CI/4P-M12	Reflective optical sensor with background elimination by LEUZE, range: 0.005 ... 3 m; light: infrared; power supply 10-30V DC; output1: PNP/NO; output2: PNP/NC; 250Hz; M12-4pin connector; dimensions: 20.5 x 76.3 x 44 mm; case material
118MM/4N0-16N-N12 SENSOR	
M12 4 PIN L SENSOR CABLE 5 MT	
M12 4 PIN SENSOR CABLE 2 MT	
LZ.50127014 PRK46C/4P-200-M12	
RSL420-S/CU416-5 +braket+cable	
SC-1222-50117827	BTP300M-D10
LE5B/4X-M8	One-way light barrier receiver
PRK 18/24 DL.46 50032798	
PRK 25/66.31.03-S12 50112010	
PRK46C.D1/4P-M12 50129753	
PRK 46B/44.01-S12 50104393	
Spare List	
LSSR 2.8	
50080047, HRT 96M/P-1630-800-41	
50137161, PRK3C.B1/6G-M8	
PRK5B/4X-M8	50145252
TKS 100X100	50022816
MSI-EM-IO84-01	Safety relay by LEUZE Electronic
LE25CI.XR1/4P-M12	Receiver for single-beam light barrier, Leuze
LS25CI.XXR/XX-M12	Transmitter for single-beam light barrier, Leuze

HT5B/4X-M8	Optical sensor with background suppression, Leuze
Ddls-200/120.1-20	(50036290) OPTICAL DATA TRANSMISSION
50134413	
Umc-1304	
68003303	
Ls748e	
50036290	(DDLS 200/120.1-20) OPTICAL DATA TRANSMISSION
670096	LIGHT CURTAIN RECEIVER
Rk78/7z142vs	
50109882	
50110784	
Gsu 06	
Cml730i-R40-1570.A/Cv-M12	
Rsl420-S/Cu416-25	
68003927	
68003137	
Cml730i-R10-1760.A/Cv-M12	
426361	
Art.No. 50106547 Hrt 46b/66-S12	
50106085	
549990	
Ws28/2-Se	
SlSr 46b	
Cml730i-R05-1520.A/Cv-M12	
Cpr30-1050-M/T1	(68310430) SAFETY LIGHT CURTAIN RECEIVER
Cml730i-R20-1430.A/Cv-M12	
68000104	
Ac-Cpb-Opt	
670002	
50109707	
68003209	
68003425	
Rsl420-L/Cu416-5	

Kd0955a	
50116465	
68310430	(CPR30-1050-M/T1) SAFETY LIGHT CURTAIN RECEIVER
Cml730i-R10-800.A/Cv-M12	
Ams 348i 120	
Cml730i-R10-960.A/Cv-M12	
68000125	
Set-Ac-Mtx-2s	
Cml730i-R20-630.A/Cv-M12	
50106547	
68000336	
50102613	
50134391	
25 Series	
50132918	
68000319	
Crt 20b	
68003337	
Db 112b	
Pm-2500	
Cml730i-R20-790.A/Cv-M12	
68000913	
68000218	
Rsl410-L/Cu405-2m12	
Dt-814	LIGHT CURTAIN TRANSMITTER 814MM
68003912	
Cml730i-R20-470.A/L-M12	
68003124	
Bar 712	
Les 36	
68000224	
68003216	

Rfm32sl200	
Csl 505	
68003206	
50134409	
68003418	
68000207	
50134394	
Cml730i-R20-2710.A/L-M12	
50040269	
Cml730i-R05-480.A/Cv-M12	
50108999	
68000321	
68003328	
Prk 3b Retro-Reflective Photoelectric Sensors With Polarization Filter	Sens¼r
Ams 200/40-11-H	
Cml730i-R20-1750.A/Cv-M12	
68003333	
50132931	
68003419	
68003125	
8 Series	
50037230	
50132585	
Cml730i-R10-1920.A/L-M12	
50038539	
Bt01	
66556200	
68003907	
580011	
68003312	
Rsl420-XI/Cu416-25	
Cml730i-R10-2240.A/Cv-M12	

68000122	
Cml730i-R40-930.A/L-M12	
50132590	
Lss96m-180w-44	
68000119	
Cml730i-R40-1890.A/L-M12	
426385	(CPSET-M11-ACC) MUTING SENSOR ACCESSORIES
Db 14	
Prk 55	
Art.No. 50115147 Hrtr 25b/44-S12	
Cr30-900-Bh5	LIGHT CURTAIN 24VDC 30MM RES
670002 - , No	
Ddls-170/120.1-2110	DATA TRANSMISSION SYSTEM FREQ ONE 12-30VDC
50038007	(BPS 34 S M 100) BAR CODE POSITIONING SYSTEM
Sls 78/Re-24v	
Cml730i-R05-160.A/Cv-M12	
50134428	
Cml730i-R05-2880.A/Cv-M12	
Krt 55	
50022815	
Kk03/0f3	
50110767 / Gs 61/6.2	
50132929	
LS5B/9X-M8	One-way light barrier transmit
Cml730i-R05-2800.A/Cv-M12	
Cml730i-R10-2080.A/L-M12	
670001	LIGHT CURTAIN CONTROL DEVICE
Cml730i-R05-1680.A/Cv-M12	
68003916	
Rsl410-M/Cu408-M12	
Bt95	
Ddls200200210	(50036281) OPTICAL DATA TRANSMISSION

Krt 20	
68003327	
Sd4t40-1200	
Cml730i-R20-2390.A/L-M12	
Cml730i-R10-640.A/L-M12	
Bps-34-S-M-100	(50038007) BAR CODE POSITIONING SYSTEM
Sls 318	
Cml730i-R20-1270.A/Cv-M12	
Igsu 14	
68000116	
Cml730i-R20-1590.A/L-M12	
Rsl430-L/Cu429-25	
68003116	
68000124	
50131032	
50039599	PHOTOELECTRIC OPTICAL DISTANCE SENSOR
50134400	
Cml730i-R40-2530.A/Cv-M12	
68000128	
50106557	
50040138	
10 Series	
68000907	
Cml730i-R10-1280.A/Cv-M12	
Cml730i-R20-310.A/Cv-M12	
Rsl420-S/Cu416-5	
68000204	
50132591	
Gs754b	
Rsl420-S/Cu411-Rs4	
Rsl430-S/Cu429-10	
Rsm430-XI	

68003406	
50107255	
5 Series	
Cml730i-R20-2550.A/L-M12	
Gf1000/4ls-Ms	
Gs 04	
Cml730i-R05-2560.A/Cv-M12	
68000909	
50030077	
50134397	
Rs4	
Rsl440-M/Cu429-25	
50061406	ULTRASONIC LABEL FORK SENSOR RAN:4MM 10-30VDC 5PIN
Rsl420-S/Cu416-10	
50103082	
Cml730i-R20-150.A/L-M12	
Cml730i-R10-2880.A/Cv-M12	
68000910	
68000416	
Cml730i-R05-240.A/Cv-M12	
68003221	
50128288	
Cml730i-R10-320.A/Cv-M12	
Cml730i-R20-1750.A/L-M12	
Gf1000/1ls-Ms	
68003421	
Is 208	
68000115	
10233682	
Bcl-40-R1-F-100	BARCODE SCANNER
50132915	
68000328	

Ddls-200/120.2-10-M12 68000136	(50106024) OPTICAL DATA TRANSMISSION
547803 Msi201	
68003222	
Ddls-78.1	SENSOR MODULE DATA LINK INFRA-RED PHOTOELECTRIC
Cml730i-R20-310.A/L-M12	
Cml730i-R40-610.A/L-M12	
8x8x40 Ibo90100	SENSOR
Bes516-113-S4-C	
Csl 710	
429393	
68003228	
50125676	
68000409	
Rs4-4	
68003307	
Bps 8	
Bt-2hf	
50132588	
560340 Bt-Set-240bc	
68000134	
50134406	
50132913	
68000219	
50132928	
50131035	
Rk93/4-200-L	
Rsl410-L/Cu411-Rs4	
Cml730i-R05-2640.A/Cv-M12	
Ls72/4e6000	
Art.No.: 50013967 Gs 21/4 G,5000	
50125768	

Sls_518	
68000121	
68003402	
Rsl430-M/Cu429-25	
Rs4-42	
500_03187 - Unknown Model	
50011656	
Cml730i-R20-2230.A/Cv-M12	
50132932	
Cml730i-R05-560.A/Cv-M12	
50029014	BARCODE READER W/ INTEGRATED DECODER 18-36VDC
Ddls-200/120.2-20	(50036291) OPTICAL DATA TRANSMISSION
Rod4-30	
50132927	
540604	
Cml730i-R10-2560.A/L-M12	
Cml730i-R05-1120.A/Cv-M12	
50132920	
Cml730i-R05-320.A/Cv-M12	
68000307	
50080979	
68003336	
50134398	
68003128	
Cml730i-R10-2720.A/L-M12	
Cml730i-R05-1360.A/Cv-M12	
68003334	
Cml730i-R10-1760.A/L-M12	
Bps_300i	
Cml730i-R05-1840.A/Cv-M12	
68000210	
68000137	
68003304	

Cml730i-R20-150.A/Cv-M12	
50132594	
68000310	
68003321	
Cml730i-R20-2070.A/L-M12	
68003204	
68000309	
68000127	
Cml730i-R20-2230.A/L-M12	
68000407	
Cml730i-R10-1120.A/L-M12	
68003401	
68000306	
50131033	
Cml730i-R05-1040.A/Cv-M12	
50132933	
Rsl410-XI/Cu405-2m12	
66533300 Mld510-R4	
50109721	
68003913	
50019925	
430 Series	
68000904	
Cml730i-R20-1590.A/Cv-M12	
Ddls 200/200.1-60	(50040933) OPTICAL DATA TRANSMISSION
2 Ls88-4 Ex	
Mld500-T3I	
Lps 36	
66557100 Mld520-Rt2	
68000230	
68000306 Mic500t30-600	
564307	LIGHT CURTAIN RECEIVER 24VDC 0.3AMP 0/18M RANGE

68000927	
68000315	
Tk100x100	
37u3279-44	
Sd4t40-600	
68000915	
Cml730i-R05-2080.A/Cv-M12	
68003915	
68003130	
Kr25240	
68000921	
68003407	
Is 215	
50134410	
68003422	
Prk 95	
68007115	
Msi-Mx/Rx	SAFETY RELAY 2NO 1NC AOPD MUTING EXTENDED FUNCTION
Rsl440-S/Cu429-25	
68003921	
Mlc 510	
Vsu 12	
68003918	
68003118	
50037498	(BCL 31 S M 100 W) STATIONARY BAR CODE READER
Cml730i-R05-1200.A/Cv-M12	
68000118	
Odsl 30	
68000106	
Rsm420-M	
Cml730i-R10-480.A/Cv-M12	
50132936	

Cml730i-R40-610.A/Cv-M12	
Cml730i-R20-2550.A/Cv-M12	
50039656	
Gf500/4rt-Ms	
Is 205	
426382	CPSET-M03-ACS-MUTING MOUNTING SYSTEMS
Db 12b	
Rk85/4300	
50036291	(DDLS 200/120.2-20) OPTICAL DATA TRANSMISSION
68003310	
Brk-736/4-100	PHOTOELECTRIC 24V
50111158	
50132592	
Ma42is	(50032853)-MODULAR INTERFACING UNIT
Cml730i-R10-2560.A/Cv-M12	
412 Series	
Prk72/2	
50134404	
Bcl-22-Sm-302-X177	(50033533) STATIONARY BAR CODE READER
68003919	
418 Series	
Cml730i-R20-1110.A/Cv-M12	
520019	
Et80-600	
68000406	
68000221	
50111161	
Cprt500/2-MI09/R2	(68900115)-MULTIPLE LIGHT BEAM SAFETY DEVICE TRANSMITTER/RECEIVER
68003306	
68000430	
Art.No. 50013059 Iprk 92/4 S	
Rsl440-XI/Cu429-10	

50105986 Prk 46b/44-S12
68003309
Mld-M003
68003428
68000412
68003315
68000109
Lps36
50104245
50132934
Pm-2500v
50132917
68000922
68000402
50029414
50132919
670005
50132924
Cml730i-R05-2400.A/Cv-M12
Rsl420-M/Cu416-25
50109343
Bcs030ps1cs4
Cml730i-R05-1600.A/Cv-M12
Ams 300i
50134407
Prk 8
50039558
50134392
Rsl410-S/Cu411-Rs4
Rsl410-S/Cu408-M12
68000215
50107243

Rsl420-M/Cu416-10	
Ams200/200-11-H	OPTICAL LASER MEASUREMENT SYSTEM
Mlc 300	
50107229	
68003424	
68000303	
43050022	(SP-EK-CPR-R3/L)-END CAP
Lsis122m6m-R1	STATIONARY 2D-CODE READER 50110307
50134396	
68003230	
Cml730i-R05-640.A/Cv-M12	
Ams304i/120 / 50113678	
Frk 95/44-150 L	
68003201	
50.103.157 Is Not Produced - Alternativ Ams 304i 120	
Prk 18b	
68000139	
66500100 Mid-M002	
Rsl440-L/Cu429-10	
Cml730i-R10-2240.A/L-M12	
Rsl410-XI/Cu408-M12	
Lrt8 Luminescence Scanner	Sens¼r
Art.No. 50033918 Rk 70/4-50, 10000	
Mlc 500	
68003430	
Bcl7-600-100	BAR CODE SCANNER
68003107	
Bcl31-S-L-100-W	(50041799) STATIONARY BAR CODE READER
Cml730i-R40-290.A/Cv-M12	
68003227	
Cml730i-R10-320.A/L-M12	
Cml730i-R10-1120.A/Cv-M12	

Rkr 55	
Rsl420-XI/Cu416-5	
50132593	
Rsl440-XI/Cu429-25	
68000213	
68000401	
Is 212	
Brk712/2	
Rsl440-XI/Cu429-5	
50134401	
Cml730i-R05-720.A/Cv-M12	
Rsl420-L/Cu416-10	
Crt 448	
Rsl430-XI/Cu429-10	
68000325	
50132935	
Ams-384i-40	(50113733) OPTICAL DISTANCE SENSOR
50134412	
50126131	
68000316	
68003115	
68000318	
Cml730i-R10-1440.A/Cv-M12	
Cml730i-R20-2870.A/L-M12	
68003316	
68000112	
Mlc500t90-900	
426384	(CPSET-M12-ACC) MUTING SENSOR ACCESSORIES
Prk 3b/6.22.S8	
68000301	
68000327	

68003103	
68003139	
Gs 754b	
Cml730i-R10-1440.A/L-M12	
Cml730i-R10-1600.A/L-M12	
Rsl420-L/Cu411-Rs4	
68000930	
68003133	
50107493	
E2e-X14md1s	
Cml730i-R05-800.A/Cv-M12	
Cml730i-R10-2720.A/Cv-M12	
50131024	
Brk736/4-180	
68003112	
Cr14-1050	LIGHT CURTAIN RECEIVER 1050MM
68000304	
Cml730i-R10-2880.A/L-M12	
Sd4r40-600e	
50037493	
68000422	
68003134	
68003207	
Mld 500	
68000333	
Msi-Sr-Lc3mr-01	
50132925	
68000427	
Mlc500t20-300	
Ddls-200/200.1-60-M12	(50106037) OPTICAL DATA TRANSMISSION
68000906	
50131030	
68003928	

Cml730i-R40-2210.A/L-M12	
549905	SAFETY RELAY 5AMP 24VDC DIN RAIL MOUNT
Vs32/2	
Rsl440-L/Cu429-5	
50021209	
Prk 96	
68003224	
Rsm430-M	
Cml730i-R40-930.A/Cv-M12	
10146622	
68000919	
Frk85/480011203	
68000418	
50132930	
549856	
68003318	
50134393	
Ddls170/120.2-4110	DATA TRANSMISSION SYSTEM FREQUENCY ONE 12-30VDC
Ddls-7861	OPTICAL DATA TRANSMISSION 50021128
520082	
Cml730i-R20-1910.A/L-M12	
Cml730i-R05-2000.A/Cv-M12	
Ct30-900-Bh3	LIGHT CURTAIN 24VDC 30MM RES
Is 240	
Gsu 14	
50109717	
18 Series	
50134418	
68000201	
Ws28/2-E	
50134395	
68000103	

Cml730i-R10-800.A/L-M12	
Is 204	
Is 206	
Rsm410-M	
Rsl410-M/Cu411-Rs4	
Rk93/260	
68003313	
68003127	
540010	
Rsl 400	
43050012	(SP-EK-CPR-P1/L)-END CAP
68000110	
43050021	(SP-EK-CPR-R3)-END CAP
Rkr 3b	
68003930	
Rsl440-M/Cu429-5	
Cml730i-R20-630.A/L-M12	
68000113	
Cml730i-R05-2320.A/Cv-M12	
68000403	
Cml730i-R40-1570.A/L-M12	
0512d081261	
50132587	
426387	(AC-CPB-IND) ACKNOWLEDGMENT UNIT
50039948	
Cml730i-R05-2480.A/Cv-M12	
Rsl440-M/Cu429-10	
Rsl420-M/Cu416-5	
426383	CPSET-M04-ACS-MUTING MOUNTING SYSTEMS
50117367	
Cml730i-R40-2530.A/L-M12	
Rsl430-L/Cu429-10	

50113678	
Ods 96b	
68003910	
Rsl440-S/Cu429-5	
68000216	
Cml730i-R10-160.A/Cv-M12	
Rsl440-S/Cu429-10	
68003122	
Rsm410-S	
66501200	
429046 Bt-2r1	
Cml730i-R20-1110.A/L-M12	
92 Series	
808023	PC BOARD
68000337	
50109378	
68000424	
50109666	
50109680	
Prk 3b	
Rk03u0374302544	
68003136	
Cml730i-R20-2710.A/Cv-M12	
Rod 4	
Sd4r40-1200e	
Cml730i-R40-2850.A/L-M12	
68000212	
68000413	
Cml730i-R20-950.A/L-M12	
50106546 / Hrt 46b/44-S12	
Ddls-78.2	OPTICAL DATA TRANSMISSION DUPLEX 24VDC
50105763	
Bts56	

50132589	
68003404	
50134402	
549000	
Gs 63	
68000421	
50132583	
Hrtr 3b Standart Diffuse Reflection Light Scanner With Background Suppression	Sens¼r
678061 Cb-M12-10000e-8gf	
Ddls200120210	(50036283) OPTICAL DATA TRANSMISSION
50104179	
68000410	
68003416	
Cml730i-R05-2240.A/Cv-M12	
50110238	
50105417	
50125325	(DDLS 508 40.2 L) OPTICAL DATA TRANSMISSION
68000324	
50114427	
Ods 10	
Odsl 8	
Ams200/40-11	OPTICAL DISTANCE SENSOR
68003427	
68003904	
50040229	
P/N: 50041840 Type: Lrt 8/24.04-50-S12	
426375	CPSET-M17-ACS-MUTING SENSOR ACCESSORIES
Brk 20-101	
Sls 46c	
50104559	
28 Series	

Cml730i-R20-1270.A/L-M12	
50107276	
Ams200/200-11	OPTICAL LASER MEASUREMENT SYSTEM
Ka78037u3343	
Gsu 712	
50108489	
Mlc500t90-1350	
426380	MUTING SENSOR SET
50104365	
68003302	
68000415	
Gsu 710	
50134405	
Rsl430-XI/Cu429-25	
Cml700i	
Cml730i-R40-1250.A/L-M12	
50132923	
Cb-M12-5000e-5gf	
66501300 Mld500-T4	
50132922	
Cml730i-R20-790.A/L-M12	
Mld 300	
43050013	(SP-EK-CPR-P1)-END CAP
Bcl22r1m200	(50061313) STATIONARY BAR CODE READER
50113681	
68000133	
68003202	
Cml730i-R05-1440.A/Cv-M12	
50131027	
Krt 18b	
60040934	
68003219	
50132926	

Krt 21	
68003325	
68000330	
547804 Msi-Em201-8i4io	
96 Series	
Tmc66	
46 Series	
68003339	
68000313	
Ls88-4ex	
68003106	
Cml730i-R20-1430.A/L-M12	
Rsl420-XI/Cu416-10	
2 Series	
Is 288	
Ams 200/40-11 , By (50113677) Ams 304i 40	
Lv463	
68003410	
Mtk5 20x40.1	reflector Type: rectangular Reflection surface: 17 mm x 38 mm Tripple size: 1.2 mm Material: plastic Carrier material: plastic Chemical name Material: PMMA8N Fixing: Passage fastening, adhesive Net weight: 5 g eCI @ ss 9.0: 27273601 Customs tariff number: 90029000 http://leuze.com/specials/redirect-to-catalog.php?q=50104130&c=de&l=de
68000209	
68003412	
68000225	
Cb-M12-10000e-5gf	
Bcl31sf100hw	(50103115) STATIONARY BAR CODE READER
Prk 53	
68000425	
68003210	
68003218	
50132586	

Cml730i-R10-1920.A/Cv-M12	
Cml730i-R20-950.A/Cv-M12	
Odsl-96b-M/C6-200-S12	OPTICAL DISTANCE SENSOR
68000228	
68000918	
68003324	
Bcl-80-0m-100	BARCODE READER W/ INTEGRATED DECODER 18-36VDC
Rsl430-XI/Cu429-5	
Cml730i-R20-2390.A/Cv-M12	
68000202	
68003215	
Msi-Sr4	
68003413	
68000339	
Cml730i-R10-2080.A/Cv-M12	
50037491	
Lrt 8	
68003301	
Mld-Udc	
Sd2t30-750	
Csl 780	
678056 Cb-M12-10000e-5gf	
66537100 Mld510-Rt2	
68003213	
Mldset	
50110793	
Rsl410-S/Cu405-2m12	
Cml730i-R05-2160.A/Cv-M12	
68003101	
Art.:50116934 , Gsu 14c/66d.3-S12 - , By Gsu 14d/66d.3-S12	
3 Series	
	PRK3CL1.A3/4T-M8 Reflex-Lichtschanke polarisiert

Prk3cl1.A3/4t-M8	Sonderausf¼hrung: Autokollimation, Teach-Eingang Grenzreichweite: 0 ... 3 m Lichtquelle: Laser, rot Schutzklasse: 1 Fehlwinkel: typ. ± 2° Versorgungsspannung: 10 ... 30 V, DC Digitale Schaltausg¼nge: 1 St. Schaltausgang 1: Transistor, PNP, hellschaltend Schaltfrequenz: 3.000 Hz Anschluss: Rundstecker, M8, Metall, 4 -polig Bauform Geh¼use: kubisch Abmessungen: 11,4 mm x 34,2 mm x 18,3 mm Werkstoff Geh¼use: Kunststoff Bedienelemente: Teach-Knopf Umgebungstemperatur Betrieb: - 40 ... 55 °C Schutzart: IP 67, IP 69K Nettogewicht: 10 g eCl@ss 9.0: 27270902 Zolltarifnummer: 85365019 http://leuze.com/specials/redirect-to-catalog.php? q=50129411&c=de&l=de
Cml730i-R20-1910.A/Cv-M12	
68000302	
Le5/4p-M8 50117692	
Rsl430-S/Cu429-5	
68003119	
50134438	
68003110	
50132595	
420 Series	
68000428	
Rsl420-M/Cu411-Rs4	
68003330	
Bps34sm100-H	(50038008) BAR CODE POSITIONING SYSTEM
Rsl430-M/Cu429-5	
547935 Msi-Dt30b-01	
540605	
Cml730i-R40-2210.A/Cv-M12	
Cml730i-R40-1890.A/Cv-M12	
50134399	
93 Series	
Sd4r40-1050e	
50104132	
Hrt 96k/R-1690-1200-25	
50106693	
Cml730i-R05-1760.A/Cv-M12	
68003121	

68003113	
SIs 78/2 Se-24v	
DdIs-78.6	OPTICAL DATA TRANSMISSION 50018692
MId 510	
50111325	
MId510-Rt3	
DdIs200200110	(50036280) OPTICAL DATA TRANSMISSION
CmI730i-R10-480.A/L-M12	
CmI730i-R10-640.A/Cv-M12	
50061452 Prk 96m/P-3380-41	
CmI730i-R10-2400.A/Cv-M12	
50134414	
68003403	
671096	LIGHT CURTAIN TRANSMITTER
50036280	(DDLS 200/200.1-10) OPTICAL DATA TRANSMISSION
53 Series	
68000222	
Gs 61	
50125678	
Ac-Scm5-Bt	
68000916	
50132584	
DdIs-78.5	OPTICAL DATA TRANSMISSION 50017928
520021 Bt-La-78m	
Ws75/4e600000668	
50105315 / Bt 46	
50029415	
Rkr 53	
Oms2/120-Is	PHOTOELECTRIC OPTICAL DISTANCE SENSOR
CmI730i-R05-1280.A/Cv-M12	
Ls74se	
50104099	

68003104	
Is 244	
Rsl410-L/Cu408-M12	
68001306 Mlc510r30-600	
Mld 530	
50134408	
Cml730i-R10-1280.A/L-M12	
Cml730i-R05-2720.A/Cv-M12	
Cml730i-R10-1600.A/Cv-M12	
Lv461	
68000227	
95 Series	
426302	(MLD520-R2L-UDC-900-S2) SAFETY SENSOR/RECEIVER SET
50134411	
Lrs 36	
Opsl 775	
Cml730i-R05-960.A/Cv-M12	
68003225	
Rsl440-L/Cu429-25	
68003906	
Rsl420-L/Cu416-25	
Mld530-Rt3m	
68000312	
68000203	
Rsl430-S/Cu429-25	
Rsl430-M/Cu429-10	
50037188	(BPS 37 S M 100) BAR CODE POSITIONING SYSTEM
Cml730i-R05-1920.A/Cv-M12	
Ams-384i-200	(50113735) OPTICAL DISTANCE SENSOR
Mld 520	
Mlc-Udc	
68000334	

Lse4644s12	
50027465 Ls 763/2.8 Se, 2500	
Mlc520r90-1350	
68003203	
Cml730i-R40-290.A/L-M12	
68000322	
Mlc500r14-600	
Cml730i-R20-2070.A/Cv-M12	
68003212	
50039938	
Rsl410-M/Cu405-2m12	
68003319	
50029527	
Rsl430-L/Cu429-5	
Bcl5-150-011	BAR CODE SCANNER
SlSr 25b	
68003909	
Cml730i-R40-1250.A/Cv-M12	
50131036	
50040933	
68000925	
50132914	
50134403	
68000130	
Art.No. 50106560 Hrtl 46b/66-S12	
426377	CPSET-M19-ACS-MUTING SENSOR ACCESSORIES
Ls64/28ses1	
Cml730i-R05-400.A/Cv-M12	
Cml730i-R05-2960.A/Cv-M12	
68003925	
68000928	
Cml730i-R05-880.A/Cv-M12	

50132582	
Krt 3b	
Btu800m	
Mlc520r20-300	
OdsI 9	
Cml730i-R10-2400.A/L-M12	
68003409	
50081294	
Mlc500t14-600	
68006115	
Mlc520r90-900	
50017928	OPTICAL DATA TRANSMISSION
68000419	
50022680	
Is 230	
Lv462	
Cml730i-R20-470.A/Cv-M12	
68000924	
68000206	
55 Series	
50041799	(BCL 31 S L 100 W) STATIONARY BAR CODE READER
DdIs-200/120.1-10-M12	(50106023) OPTICAL DATA TRANSMISSION
50132921	
68003924	
50132916	
50116179	
68003109	
68003922	
50131029	
Cml730i-R20-2870.A/Cv-M12	
68000107	
68000404	
68000912	

[50122268](#)

[68003415](#)

[Is 255](#)