

## Logtag

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Logtag** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Logtag T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">LTI-HID Interface for LogTag® data loggers</a>	LTI-HID
<a href="#">HAXO-8</a>	Humidity and temperature data logger Use: reusable Sensor type: Internal Measuring range: -40 ¼C to +85 ¼C 0% to 100% RH Display: Status LED Data storage: ~ 8,000 readings Self-sufficient PDF report:- Humidity and temperature data logger
<a href="#">TRIX-8</a>	Temperature data logger - EN12830 compliant & WHO pre-qualified Use: Reusable Measuring range: -40 ¼C to +85 ¼C Data storage: ~ 8,000 measured values Sensor type: Internal Display: Status LED Standalone PDF report: -
<a href="#">TRIX-KIT</a>	Battery and front label kit for LogTag- Data logger with permanently soldered battery Suitable for the following models: TRIX-8/-16, TREX-8 consisting of each TRIX-8 FRONT LABELFRONT LABELS 1 piece 244141 CR2450 Lithium Metal Battery with Solder lugs 1 pc.
<a href="#">LTI-HID interface for LogTag data loggers</a>	LTI/HID At least one LTI interface is required to use LogTag data loggers (except data loggers with to configure and read

	the integrated USB connector
<a href="#">TRIX-8</a>	LogTag® TRIX-8 temperature data logger - EN12830 compliant & WHO pre qualified Dimensions : 86mm (H) x 54.5mm (W) x 8.6mm (D) Applications: room surveillance, transport surveillance Recording interval: adjustable from 30 seconds to several hours Readout time : less than 5 seconds Battery replaceable : yes (by technician) Battery life with typical use: 2-3 years Operating temperature : -40 °C to +85 °C Data transfer : LTI/HID interface Display: no Housing material : polycarbonate Weight: 33g Maximum temperature : +80 °C Temperature measuring range: -40 °C to +85 °C Measurements : Temperature Minimum temperature : -40 °C Degree of protection: IP 65 Protection class: IP 65 (jet water) Power supply : 3V LiMnO2 battery Storage capacity : 8,000 events Temperature sensor: internal Temperature data logger
<a href="#">Trid30ã173;7r</a>	
<a href="#">Haxo8</a>	
<a href="#">Trix-8</a>	
<a href="#">Lt/Usb 8</a>	
<a href="#">Logtag Pe</a>	
<a href="#">Sundry Spare</a>	
<a href="#">Trid 30-7f</a>	
<a href="#">Hax0-8</a>	
<a href="#">HAXO-8 humidity and temperature data logger</a>	Data logger HAXO-8 with or without calibration: HAXO-8 without calibration
<a href="#">Utrid16</a>	
<a href="#">Logq82</a>	
<a href="#">Tred30-7r</a>	
<a href="#">Logtag Trid30r Starter Kit3 - Not Available</a>	
<a href="#">Utrix16</a>	
<a href="#">Logtag Usb</a>	
<a href="#">Logtag Wmb</a>	