

Lorenz

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Lorenz Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Lorenz T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



| ¼r¼n | A¼ıklama |
|------------------------------------|--|
| MTW 100BL30040 | Meter MTW QN 10 warm horizontal BL 300 Multi-jet water meter MTWD-M-CC-PTFE for hot water Q3 = 16 (Qn 10) overall length 300mm R 6/4 "G2B Execution: - dry runner - EDC module can be retrofitted (M-Bus, wM-Bus or pulse module) -for horizontal (counter tilted up or to the side) and vertical installation (riser / downpipe) -CopperCan = counter IP68 (flood-proof) -suitable for demineralized water Price includes screw connection, PTFE-coated for meters DN 40, nominal size G2 "/ R1½" Meter is MID-tested |
| D-DR2477/M350-G225 | Rotating torque sensor 50N m 0.25% Data sheet 080894 Supply voltage 12 ... 28VDC Output signal ± 5V Electrical connection 1m, free strands Customs tariff number 90318080 Country of origin non-preferential DE |
| 100432 | |
| 100717 | |
| 101560 | |
| 102931 | |

| | |
|--|---|
| 103562 | |
| 108679 | |
| 112325 | |
| 1203 | |
| 140570DRI / 760014702 | |
| 140570DRI / 760060402 | |
| 277293702 | |
| D-2209 | |
| D-D2452/M220-G21 | |
| D-DR2500/M210-G21 | |
| E-LCV-USB2/U5 | |
| K-K1613/N310-G25 | |
| Option 100% Kontrollsignal | |
| Rheostat for LS 1250 | |
| TYP969 | |
| D-DF30/M310-G21 | torque sensor stat. 10N m 0.1% Data sheet 080852 Supply voltage DMS 2...12VDC Nominal sensitivity 0.5mV/V ±0.1% Electrical connection ES6/A Customs tariff number 90318080 Country of origin non-preferential DE Net weight 0.9kg Our article number 100359 |
| D-DR3000/M310-G21 | 111234 torque sensor rotating 10N·m 0.1% Data sheet 080882 Supply voltage from USB 4...6VDC Output signal torque ±25000 digits Resolution speed 1min-1 Accuracy speed 1% ±1 digit Resolution angle of rotation 0.25° Output signal speed/angle ±32511 digits Electrical connection mini USB-B socket IP68 |
| D-DR3000-P/M310-G21_2643-M20 | 113190 Rotating torque sensor 10N·m 0.1% Data sheet 080882 Supply voltage from USB 4...6VDC Output signal torque ±25000 digits Resolution speed 1min-1 Accuracy speed 1% ±1 digit Resolution angle of rotation 0.25° Output signal speed/angle ±32511 digits Electrical connection mini USB-B socket IP68 |
| D-DR2643/M310-G21 | 112806 Torque sensor rotating 10N·m 0.1% Data sheet 080884 Supply voltage 12...28VDC Output signal ±5V Electrical connection ES12/B |
| D-Option speed/angle measurement | 5V TTL Frequency max. 180kHz Pulses 360 Tracks 2x90° offset Resolution rotation angle 0.25° Output signal 5V TTL Our article number 101560 |
| D-DR2643-P/M310-G21_2643-M30 | 115675 Torque sensor rotating 10N·m 0.1% Data sheet 080884 Supply voltage 12...28VDC Output signal ±5V |

| | |
|--|---|
| | Electrical connection ES12/B |
| D-DR2/M220-G21 | Torque sensor rotating 2N·m 0.1% data sheet 080862 Supply voltage DMS 2...12VDC nominal value 1mV/V ±0.1% Electrical connection ES6/A |
| D-DR3000/M210-G21 | Rotating torque sensor 1N·m 0.1% Data sheet 080882 Power supply from USB 4...6VDC Output signal torque ±25000 digits Resolution: rotational speed 1 min ⁻¹ Rotational speed accuracy: 1% ±1 digit Resolution: Rotation angle 0.25° Output signal speed/angle ±32511 digits Electrical connection: Mini-USB-B socket, IP68 |
| D-DR3000/M150-G21 | Rotating torque sensor 0.5 N·m 0.1% Data sheet 080882 Power supply from USB 4...6VDC Output signal torque ±25000 digits Resolution: rotational speed 1 min ⁻¹ Rotational speed accuracy: 1% ±1 digit Resolution: Rotation angle 0.25° Output signal speed/angle ±32511 digits Electrical connection: Mini-USB-B socket, IP68 |
| D-DR3000/M450-G21 | Rotating torque sensor 500N·m 0.1% Data sheet 080882 Power supply from USB 4...6VDC Output signal torque ±25000 digits Resolution: rotational speed 1 min ⁻¹ Rotational speed accuracy: 1% ±1 digit Resolution: Rotation angle 0.25° Output signal speed/angle ±32511 digits Electrical connection: Mini-USB-B socket, IP68 |
| D-DR12/M416-G21 | Rotating torque sensor 160N·m 0.1% Data sheet 080876 Supply voltage DMS 2...12VDC Nominal value 1mV/V ±0.1% Mechanical connection 1/2" square Supply voltage angle 5VDC Pulses/rotation 360 Track 2 (offset by 90°) Angle signal 5V (TTL) Electrical connection ES12/A |
| 100218 | Option control signal 100% A control resistor is used in the The sensor simulates a signal that the This corresponds to the sensor's 100% characteristic value. This allows you to do this before each measurement The zero point and characteristic value are checked. |
| 140570dri / 760085702 | |
| Dr2-50n | |
| 911210031 | |
| 911210033 | |
| K-K450/N550-G23 1244-M10 | |
| Dr2-200n | |
| 140570dri / 760014702 | |
| Ebd6 2In5-330-0wk | |
| 760936002 | |
| Dr 2212-R Art.Nr.108701 20nm Miniature Rotating Contactless Torque Sensor Range 0-20nm Active Output | |

| |
|--|
| E-Lcv/I4 |
| 100695 |
| K-2283-N470-G31 |
| K-K2624/N650-G25 |
| K-K450/N550-G21 |
| 966gr75 |
| Z-Wkk2-7-D |
| 2-V1-97-440-C354 |
| Ls630cnc |
| 911210037 |
| 911210032 |
| K-K13/N250-G25 |
| 1-06-4138-013-1 |
| X-Kd6/A-Fl-20m/Purs Ip67 |
| 140570dri / 760060402 |
| Dr211230 |
| K-K12/N450-G21 |
| 277293702á; |
| M5-39-681-0-600 |
| 911210043 |
| 921210942 |
| Lvt277230602 |
| 58.415.4702 |
| 7-931-011-3103 |
| Mv04 |
| 9480s(Imd10110) |
| 911210036 |
| Drs404dg1c |
| 911210035 |
| Dr-1988 |



Yursat DıŐ Tic. M¼nendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
+90 224 2400304
info@yursat.com.tr
www.yursat.com.tr

[772515702](#)