



Lutz-Jesco

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Lutz-Jesco Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Lutz-Jesco T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen Özel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
Magdos Lp 2 Pvc/Fpm	10231003 0102P0020CC031A2K2KC1ZC1Z00 Magnetic diaphragm metering pump Product: MAGDOS Type: LP Delivery rate: 1.9 l / h at 16 bar - 2.3 l / h at 8 bar Capacity adjustment: stroke frequency adjustable 0 - 160 strokes / min Material dosing head and valves: PVC Control unit: 110 - 240 V + 5 / -10%, 50/60 Hz Electrical connection: 1.8 m power cord with plug, Europe (at 230 V AC) Suction valve DN4: double ball ceramic / PVDF / FPM (ball / seat / seal) Pressure valve DN4: double ball ceramic / PVDF / FPM (ball / seat / seal) Suction connection material: PVC Suction connection: Hose clamp connection set 4/6, 6/9 and 6/12 Material pressure connection: PVC Pressure connection: hose clamp connection set 4/6, 6/9 and 6/12 Dosing head arrangement: floor mounting Option: without Functions Stroke frequency precisely adjustable with the keyboard
Magdos Lp 05 Pvc/Fpm	0102P0005AC031A2K2KC1ZC1Z00 Magnetic diaphragm metering pump Product: MAGDOS Type: LP Flow rate: 0.36 l / h at 16 bar - 0.54 l / h at 8 bar Capacity adjustment: stroke frequency adjustable 0 - 120 strokes / min Material dosing head and valves: PVC Control unit: 110 - 240 V + 5 / -10%, 50/60 Hz Electrical connection: 1.8 m power cord with plug, Europe (at 230 V AC) Suction valve DN3: double ball ceramic / PVDF / FPM (ball / seat / seal) Pressure valve DN3: double ball ceramic / PVDF / FPM (ball / seat / seal) Suction connection material: PVC Suction connection: Hose clamp connection set 4/6, 6/9 and 6/12 Material pressure connection: PVC Pressure connection: hose clamp connection set 4/6, 6/9 and 6/12 Dosing head arrangement: floor mounting Option: without
	Control cable PVC length 2 m with M12x1 coupling, 4-pin, A-

79113	coded CONTROL CABLE Use for the following functions possible: - external release - pulse output - Analog input - Pulse input - level monitoring Nominal voltage <= 300 V
79112	Control cable PVC length 2 m with coupling M12x1 4-pin B-coded CONTROL CABLE Fault signal relay contacts output Nominal voltage <= 300 V
P-109 A/Y	45GCN20AP010-AP020 Material: PVDF 0,48-13,5m3/h max.1,84g/cm3 0,55Kw 2900rpm 400V AC 50Hz Komplett mit Rohr und befestigungen
P-110 A/Y	45GCN30AP010-AP020 Material: PP 0,48-13,5m3/h max.1,84g/cm3 0,55Kw 2900rpm 400V AC 50Hz Komplett mit Rohr und befestigungen
52897	Shaft protection sleeve with raceway for mechanical seal Ø35 Mathcode:: SHAFT PROTECTION SLEEVE Customs tariff number: 84139100 Weight: 0.196 kg + 59005 Kleber Weicon VA300 - 12 g
0102D0150BC011A2020C1ZC1Z0	
0201-502	
0205-502	
10221305	
10231005	
10241001	
10241002	
10241003	
10241004	
10241019	
10407008	
10417022	
104L15XXX-151	
104P10XXX-140	
10501488	
12201149	
12201177	
12302007	
12335495	
12600052	

[12601001](#)

[12701332](#)

[12701435](#)

[12724321](#)

[13600319](#)

[13600320](#)

[18185](#)

[18186](#)

[18327](#)

[18331](#)

[18353](#)

[18359](#)

[20890](#)

[20891](#)

[22066](#)

[23892](#)

[25087](#)

[25088](#)

[25162](#)

[26845](#)

[27517](#)

[28274](#)

[28300](#)

[28301](#)

[28404](#)

[29312](#)

[29434](#)

[29435](#)

[29746](#)

[29750](#)

29951
29995
32393
32394
32980
33855
33897
34506
37164
38196
39121
40356
40357
42387
44101002
44101004
44102011
50072
50301001
50355
50580
51750
52532
52533
52536
52537
59005
60082
60083
68052
68103

68531	
68706	
68728	
68729	
68772	
69156	
69465	
78509	
80502	
80583	
80584	
80814	
81424	
81463	
81464	
81465	
81627	
81628	
81853	
85099999	
97120	
LP 10 PVDF/FPM	
34877	Membrane flange for membrane Ø52 PP/Ms MEMDOS E/DX 4 - 25 + 83619 Cylinder screw M6x20 DIN 912 A2 + 29462 Membrane insert for membrane Ø52 PPO + 80816 O-ring Ø79x2.5 NBR + 34868 Diaphragm rod M4 1.4305 MEMDOS E/DX - 75 + 80814 Compact seal Ø14/22x5.5 94AU925 + Wiper Ø14/22x7 Type AUASOB Simritan + 81464 Diaphragm Ø52 EPDM/PTFE-coated Base material 70EPDM281 with fabric insert
83619	200121M0602020 Cylinder screw M6x20 DIN 912 A2
	Motor diaphragm dosing pump 0104A0004CF11A2K2KC1FC1F Product: MEMDOS Type: LA Flow rate: 4 l/h at 50/60 Hz against max. 12 bar Material dosing head and valves: PVC Electric drive: 230 V 1ph 50/60 Hz 0.37 kW with motor 0.18 kW Electrical connection: 1.8 m power cable with plug,

<p>MEMDOS LA 4 PVC/FPM</p>	<p>Europe (at 230 V AC) Suction valve: DN4 double ball ceramic/PVDF/FPM (ball/seat/seal) Pressure valve: DN4 double ball ceramic/PVDF/FPM (ball/seat/seal) Material suction connection: PVC Suction connection: hose clamp connection 6/12, short Material pressure connection: PVC Pressure connection: hose clamp connection 6/12, short Functions: Stroke frequency can be adjusted from 0 - 100% using a potentiometer Signal LEDs for status, operation and error display Analogue input 0/4 - 20mA Level input with main alarm Release input for external start/stop Hub feedback output alarm relay output Analogue output 0/4 - 20mA ---- A NOTICE: The successor to the MEMDOS DX type, the MEMDOS LP, is currently not available. We offer another alternative here.</p>
<p>SDL-2 DN10 PVC L=1100</p>	<p>Suction Line 0122N0010C5U1100BP200K0025S Suction lines Product: Suction line Version: Rigid, non-return valve, level control, protection pipe Ø40 Nominal width: DN10 (200 l/h) Material: PVC Suction connection: Threaded spigot G3/4 M Suction line length: 1100 mm Gasket material: FPM + EPDM (both added) Level control: PP float Number of switching points: 2 Material hose: without suction hose Hose length: - Tank connection: with screwing cap K60x6 Special design: without Electrical connection: free cable ends without plug free cable length: approx. 2.5 m Switching function: Contact on rising level Switching voltage: max. < 50 V DC; < 50 V AC Switching current: max. 1 A Switching power: max. 20 VA (protective contact relays at inductive loads)</p>
<p>SDL-2 DN10 PVC L=1100</p>	<p>suction line Match code: 0122N0010C5U1100BP200K0025S suction lines Product: suction line Execution: rigid, non-return valve, level monitoring, protective tube Ø40 Nominal width: DN10 (200 l/h) Material: PVC Suction connection: threaded pin G3/4 outside Suction line length: 1100 mm Gasket material: FPM + EPDM (both included) Level monitoring: PP float Number of switching points: 2 Material hose: without suction hose Hose length: - Tank connection: with screw cap K60x6 Special version: without Electrical connection: free cable ends without plug free cable length: approx. 2.5 m Switching function: normally open when the level rises Electrical load capacity of the float switch Switching voltage: max. < 50 V DC; < 50VAC Switching current: max. 1 A Switching capacity: max. 20 VA (contact protection relay for inductive loads)</p>
<p>68487</p>	<p>Shaft set for bearing bracket A1 Ø35 1.4305/pc</p>
<p>68531</p>	<p>GLRD 35 E Mechanical seal Ø35 eMG1/35-G7 Q7 Q1 EGG independent of direction of rotation complete with split pin</p>
<p>68177</p>	<p>Stud bolt set for BN and N pumps for mechanical seal B2D and B2Q E-steel STUD BOLT SET</p>
<p>50357</p>	<p>Back plate complete for shaft Ø35 PP/1.4305 N/BN pumps</p>
<p>68485</p>	<p>Bearing cap set for bearing bracket A1 N 32/40/50-200, N 50-160</p>
<p>68484</p>	<p>Bearing carrier housing set A1</p>

68059	O-Ring-Satz N/BN 50-160,50-200 EPDM
69000	Suction nozzle DN80 PP/EPDM N/BN 50-160
50289	Impeller cap LH for shaft Ø35 PP/Ms58
50211	Spiral casing for N/BN 50-160 PP
12532008	Pressure holding/overflow valve DN15 PN10 G1/2-G1/2 1.4571/PTFE Q=500 l/h Customs position: 84811019, country/region of origin: DE Net weight: 1.53 kg MATCH CODE 0125D0015SD0010S5ES5E00000A Product: Pressure holding and overflow valve Type: spring loaded Nominal diameter: DN15 Nominal flow rate: 500 l/h at uniform flow (DN15) Housing material: stainless steel Membrane material: EPDM-PTFE coated Material seals: without Nominal pressure: PN10 Material connection input: stainless steel Connection input: threaded connection G1/2 inside Material connection output: stainless steel Connection output: threaded connection G1/2 inside Additional equipment/special design: without Preset blow-off pressure: without Adjustment range: 0.5 - 10 bar
81656	Diaphragm Ø45.5-0.5 x3.2+/-0.3 EPDM-PTFE coated PTFE coated on one side, approx. 0.5 thick
12532006	Pressure holding/overflow valve DN15 PN10 G1/2-G1/2 PVC/PTFE Q=500 l/h MATCH CODE 0125D0015CD0010C5EC5E00000A Product: Pressure holding and overflow valve Type: spring loaded Nominal diameter: DN15 Nominal flow rate: 500 l/h at uniform flow (DN15) Housing material: PVC Membrane material: EPDM-PTFE coated Material seals: without Nominal pressure: PN10 Material connection input: PVC Connection input: threaded connection G1/2 inside Material connection output: PVC Connection output: threaded connection G1/2 inside Additional equipment/special design: without Preset blow-off pressure: without Adjustment range: 0.5 - 10 bar
81656-	Membrane Ø45.5-0.5 x3.2+/-0.3 EPDM-PTFE coated Customs position: 40169300, country/region of origin: DE Net weight: 0.006 kg PTFE coated on one side, approx. 0.5 thick
DIAPHRAGM / PRESSURE RELIEF VALVE / DN15 / EPDM-PTFE	
S-41.813/7818	
21.821-40	Pos3
0205-201	Pump set barrel emptying 19% concentrated acids and alkalis Universal motor MA II 5 / 575 W, 230 V AC/50 Hz, without undervoltage release, protection class IP 54, with 5 m connection cable and Schuko plug. Pump tube made of polyvinylidene fluoride (PVDF) Type PVDF 41 - L - DL, nominal size: 1000 mm, sealless and conditionally dry-run safe, Drive shaft made of Hastelloy C - 4 (2.4610) Special chemical hose DN 19 (3/4"), complete with hose connections and hose

	clamps pre-assembled. Fuel nozzle made of polyvinylidene fluoride (PVDF) with rotating hose connection Viton seal. PP barrel adapter
0030-001	Motor MI 4 - E / 500W 230V AC/50 Hz Customs code: 85012000, Country/region of origin: CH Net weight: 2.905 kg Universal motor with speed controller Power consumption 500 W, 230 V, 50 Hz, with double protective insulation, two-pole Single-pole thermal on/off switch Overcurrent release, protection class IP 24 with 5 m connection cable and plug
0374-482	Special PTFE chemical hose DN 25 (1") Customs position: 40094100, country/region of origin: DE Net weight: 0.775 kg suitable for chemical and mineral oil products as well as almost all solvents for Food and beverages, drinking water, etc. Inner layer made of black, smooth, seamless PTFE non-leaching and non-staining (meets FDA and USP Class VI requirements) Outer rubber made of EPDM electrically conductive, OHM hose according to EN12115. Operating pressure: max. 16 bar Temperature range: -30 to +150 °C (depending on the medium)
0122-205	PVDF 41-L-DL pumping station Nominal size: 1000 mm Customs position: 84137081, country/region of origin: DE Net weight: 1.79 kg Sealless and conditionally dry-running safe Pumping station made of PVDF (natural) Wheel made of ETFE Drive shaft: Hastelloy C - 4 (2.4610) Immersion tube diameter: 41 mm Pressure port: External thread G 1 1/4
0204-422	Hose connection PVDF DN 25 (1")
0300-445	Stepless ear clamp
0204-550	Attach hose, "non-explosive" on both sides
0204-390	PVDF/FPM dispensing nozzle G 1 1/4 AG Customs position: 84818081, country/region of origin: DE Net weight: 0.375 kg Housing and valve tappet made of PVDF Protective bar made of PPN, seal made of FPM (Viton) Operating pressure: max. 3 bar Viscosity: max 760 mPas Flow rate: max 50 l/min (water) Maximum fluid temperature: 80°C Connection: External thread G 1 1/4
11-211-55-05A	BAYONET GEAR-LUTZ--
TR90-PP Flowmeter	
PP-SL 32	19 inch PP
PP-SL 32-	39 inch PP
6060-119	Horizontal centrifugal pump with magnetic coupling TMR-16.15-S-WR-E-R1-BEN-3
6060-021	Horizontal centrifugal pump with magnetic coupling TMR-16.20-P-WR-V-R1-BEN-3
34174	
10499357 /Memdos E160 Pvc	

35043
Magdos Dx 2 Obsolete, Replaced By Magdos Lp 2 Pvc/Fpm
Magdos Lt 6 230v Pvdf 10208322
28400
Adjustment Knob Memdos E/Dx 160...380
99393
10241147
Fedos E-8
Magdos Ld 4 Pvc/Ss/Fpm
79407
39911
Magdos Lb 4 Pvc/Fpm(10211005)
Magdos Dx 40 Pvc
21469
10208381 - Obsolete , Replaced By Magdos Ld 4 Pvc/Ss/Fpm
Minidos A 24 (10301005)
91195
814080-1
80815
Exproof Panel For Memdos Lb
Accessory Kit For Magdos Pvc/Fpm
34173
10407624
Magdos Lt 06 230v Pvdf (Dn3) 10208333 Matchcode: 0102I0006v001a33v1bv1b4