

Mader



Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Mader** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Mader T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
269500	Quick coupling socket shutting off on one side nominal size 7,2 brass design with male thread Type:66 Temperature range:-20 ¼C to +100 ¼C Material of seal:NBR Material of valve body:Brass design Material of valve:Brass design Material of springs, snap rings:Stainless steel 1.4310 Connection: G 1/4 a DN 7,2
KDILX-040-0050-A-PPV-M	standard cylinder - Standard: DIN ISO 15552 - Function: double-acting - Piston diameter: 40 mm - Stroke: 50 mm - Piston rod end: external thread M12 x 1.25 - Type: Piston rod cylinder - Damping: pneumatic, adjustable on both sides - Position detection: for proximity switches - Pneumatic connection: G 1/4 - Ambient temperature: -20 ¼C to +80 ¼C - Operating pressure: 1 – 10 bar
2515414	Stroke length 30mm Maximum load capacity: 30 N
35232	
P/N: 219507 Type: L150.0156	
P/N: 216331 Type: Se-K-6-22	
226926 (L123.1050)	
214996	HE-K-K-6-1-25-75 Robust lifting unit -- with sealed ball guide Impact force 150 - 220 N (at 6 bar) Repeat accuracy ± 0.02 mm
Nsi-R6-60-S-B	
216135(Am00946)	
Lv422054	
P/N: 246844 Type: Rse-K-6-8-R-P	
Me1222	

Se-P2-4-14	
Rse-P1-4-4-R-H(216135)	
Pdi-040-0005-I-P-M-M6k5-Sa	
219599 (L093.6023)	
Nsm-T8-2p-Pnp-5	
215896 (Am00691) Nsi-R6-80-S-B	
216374	SES-K-6-25-H -- Swivel unit size 6 Heavy duty version Driving torque (effective) 6.5 Nm Angle of rotation continuously adjustable 0-190 ° Repeat accuracy ± 0.01 ° hydraulic cushioning external, hardened stop system no loss of the end position screwed proximity switch in the stop sleeve -- double-acting drive cylinder
226952 (L123.4156)	
Am00919	
P/N: 216136 Type: Rse-P1-4-4-L-H	
Pse-4-6-1005	
Mgw-B-64	