



## Madgetech

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Madgetech** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Madgetech Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*

| rn                                 | Aıklama   |
|--------------------------------------|--|
| <a href="#">Hitemp140x2-Td-Fp-12</a> | mt-901913-00 Data logger with rigid probe 508 mm and flexible probe 305 mm, including NIST certificate 30 ° C and 140 ° C Measuring range -60 ° C ... + 260 ° C (probe only), data logger -40 ° C ... + 140 ° C, max. 4 bar (60 PSIA), storage 32,700 Measured values, IP68  |
| <a href="#">mt-900140-00</a>         | HiTemp140-1 data logger with immersion probe 27 mm, incl. NIST certificate at 30 ° C and 140 ° C Measuring range -200 ... + 260°C (probe only), 32,700 Measured values, IP68 HiTemp140 with flexible probe available with various probe lengths, please specify model when ordering  |
| <a href="#">mt-900211-00</a>         | HiTemp140-FP-12 data logger with flexible probe 305 mm, including NIST certificate at 30 ° C and 140 ° C Measuring range -60 ° C ... + 260 ° C (only probe), data logger -40 ° C ... + 140 ° C, max. 4 bar (60 PSIA), memory 32,700 Measured values, IP68 HiTemp140 with flexible probe available with various probe lengths, please specify model when ordering |
| <a href="#">mt-900992-00</a>         | PR140 pressure logger with NPT connection can be used up to 6.9 bar, IP68, 25 mm x 58 mm, food safe for autoclave validation and Steam sterilization   |
| <a href="#">mt-900998-00</a>         | PR140 pressure logger with flush top can be used up to 6.9 bar, IP68, 25 mm x 51 mm, food safe for autoclave validation and Steam  |

|  |  |
|--|--|
|  | sterilization simple interface   |
| <a href="#">mt-900319-00</a>                   | IFC400 USB interface for HiTemp140, PR140 various accessories, consumables, ... for HiTemp140 / Pr140  |
| <a href="#">mt-900097-00</a>                   | Replacement battery ER1425S-HT for HiTemp140 / PR140 Lithium, 3.6 V, 500 mAh, size 1/2 AA up to 150 ° C  |
| <a href="#">mt-900229-00</a>                   | O-ring set for HiTemp140 series  |
| <a href="#">mt-900332-00</a>                   | KEY RING END CAP fastening cap with eyelet for HiTemp140, PR140, RHTemp1000 series (for IS certified loggers only if installed by the manufacturer)  |
| <a href="#">mt-902011-00</a>                   | SVP Secure System - MadgeTech 4 Secure Validation Software Package IQ/OQ/PQ Secure Software Validation Workbook and Software Package, 21 CFR Part 11   |
| <a href="#">mt-900385-00</a>                   | MT-AluCase-18 transport and storage case Internal dimensions 44.45 x 34.04 x 14.99 cm / external dimensions 47.63 x 38.10 x 15.24 cm / foam insert can itself be adjusted RTDTempX data logger with 12 inputs  |
| <a href="#">mt-902173-00</a>                   | RTDTempX12 temperature data logger, Pt100, 12 channels Measuring range -200 °C to +850 °C (depending on sensor) ****RTDTempX data logger with 12 inputs***   |
| <a href="#">Pt100</a>                          | Pt100 probe for "dry heat sterilization / dehydrogenation" Sensor Pt100 4-wire class AA according to DIN IEC 751; probe Sheath 1.4541, diameter 3 mm, probe length: 150 mm, bendable; Transition sleeve stainless steel 6 x 40 mm, encapsulated; Fiberglass cable insulated with steel braiding, length 5 m; Application range up to 350 ° C (dry heat sterilization + dehydrogenation process); Connection free ends; Customs number: 9025 9000 Origin country: Germany |
| <a href="#">RHTemp1000Ex</a>                   | 902154 MadgeTech RHTemp1000Ex data logger Humidity + temperature Measuring range 40°C ... + 80°C / 0 ... 100% RH, memory 16,384 measured values, intrinsically safe, ATEX / IECex specifications see website, incl. traceable NIST certificate   |
| <a href="#">MadgeTech IFC400 USB interface</a> | 900319 for HiTemp140, PR140 and 1000 data loggers  |
| <a href="#">MT-902213-00</a>                   | FM certified (no ATEX approval!) MadgeTech RHTemp1000IS data logger Humidity + temperature (intrinsically safe, Class I, Division 2, Groups A, B, C & D), including NIST traceable Certificate, measuring range 40°C ... + 80°C / 0 ... 100% RH, Memory 16,384 measured values   |
| <a href="#">MT-902154-00</a>                   | ATEX, IECEx, FM 3610 Certified MadgeTech RHTemp1000Ex data logger Humidity + temperature Measuring range 40°C ... + 80°C / 0 ... 100% RH, memory 16,384 measured values, intrinsically safe, ATEX / IECex specifications see website, incl. traceable NIST certificate   |
| <a href="#">Madgetech</a>                      |  |
| <a href="#">Madgetech</a>                      |  |
| <a href="#">MT-902170-00</a>                   | MadgeTech TCTempX4LCD data logger, 4 channels, thermocouple 4 channels for thermocouple (type J, K, T, E, R, S, B, N), with Display, incl. battery and USB Micro B cable, without sensor (please order separately) Origin: US Customs #: 9025 8050   |
| <a href="#">MT-900140-00</a>                   | MadgeTech HiTemp140-1 data logger, probe 27 mm rigid with 27 mm long rigid immersion probe, measuring range -200...+260°C  |

|                                |   |
|--------------------------------|---|
|                                | (probe only), 32,700 readings, IP68, incl. NIST Certificate at 30°C and 140°C Origin: US Customs No.: 9025 1900   |
| <a href="#">HiTemp140</a>      | -40+ -140   |
| <a href="#">MT-902154-00</a>   | MadgeTech RHTemp1000Ex data logger humidity+temperature Measuring range 40°C...+80°C / 0...100%RH, memory 16,384 Measured values, intrinsically safe, ATEX/IECex Specifications see website, incl. traceable NIST certificate   |
| <a href="#">MT-902208-00</a>   | MadgeTech RHTemp1000Ex-KR data logger humidity+temperature with key ring end cap, measuring range 40°C...+80°C / 0...100%RH, memory 16,384 readings, intrinsically safe / Intrinsically Safe, ATEX/IECex specifications see website, incl. traceable NIST certificate   |
| <a href="#">MT-902213-00</a>   | ATTENTION ! The RHTemp1000IS data loggers have no ( ! ) ATEX approval. (intrinsically safe, Class I, Division 2, Groups A, B, C & D), incl. NIST traceable certificate, measuring range 40°C...+80°C / 0... 100%RH, memory 16,384 readings  |
| <a href="#">MT-902218-00</a>   | MadgeTech RHTemp1000IS-KR data logger humidity+temperature Measuring range 40°C...+80°C / 0...100%RH, memory 16,384 Readings, with installed Key-Ring end cap, intrinsically safe / Intrinsically Safe, Class I, Division 2, Groups A, B, C & D, incl. traceable NIST certificate   |
| <a href="#">MT-902214-00</a>   | ATTENTION ! The Temp1000IS data loggers have no ( ! ) ATEX approval. Temp1000IS-1 data logger, probe 25mm Measuring range 40°C...+80°C, memory 65,536 measured values, with 25 mm probe and standard (flush bottom) end cap (intrinsically safe / Intrinsically Safe, Class I, Division 2, Groups A, B, C & D), incl. NIST certificate traceable certificate The Temp1000IS is available with the following probe lengths: 1", 2", 5.25", 7". The Temp1000IS is available in the "Flush |
| <a href="#">MT-900319-00</a>   | for HiTemp140, PR140 and 1000er Datenlogger   |
| <a href="#">MT-900319-00</a>   | MadgeTech IFC400 USB-Interface HiTemp140, PR140 und 1000er Datenlogger  |
| <a href="#">MT-900221-00</a>   | MadgeTech HiTemp140-FR data logger, fast response probe 45mm Measuring range -200...+260°C (probe only), working range logger - 40°C...+140°C, 32,700 measured values, IP68, 32,700 measured values, IP68, including NIST certificate at 30°C and 140°C   |
| <a href="#">MT-901499-00</a>   | MadgeTech RHTemp101A Data Logger Compact logger for humidity and ambient temperature, Measuring range -40°C...80°C, 0...95% RH  |
| <a href="#">MT-901864-00</a>   | WaterBox101A Protective Housing Weatherproof housing for 101A data logger series  |
| <a href="#">Hitemp140-1</a>    | HiTemp140-1 data logger with immersion probe 27 mm, incl. NIST certificate at 30 ° C and 140 ° C Measuring range -200 ... + 260°C (probe only), 32,700 Measured values, IP68  |
| <a href="#">Prhtemp2000</a>    |   |
| <a href="#">Rfprhtemp2000a</a> |   |
| <a href="#">Ew-18010-15</a>    |   |
| <a href="#">Avs140-1</a>       | AUTOCLAVE VALIDATION SYSTEM: INCLUDES (1) HITEMP140 DATA LOGGER WITH NIST CALIBRATION CERTIFICATE, IFC400 INTERFACE CABLE, (1) LICENSE MADGETECHS FDA   |

|  |  |
|--|--|
| <a href="#">Shock101-50-Eb</a>   |  |
| <a href="#">Block Data Loger</a>   |  |
| <a href="#">Ifc200 Usb-Interface F¼r Madgetech Standard</a>                              | Datenlogger Serie u.a. f¼r QuadVolt, OctVolt, QuadTcTemp2000V2, OctTcTemp2000V2, QuadThermoVault, OctThermoVault |
| <a href="#">Level1000</a>  |  |
| <a href="#">Svp-Securesystem</a>   | IQ/OQ/PQ SECURE SOFTWARE VALIDATION WORK BOOK AND SOFTWARE PACKAGE.  |
| <a href="#">Quadthermovault</a>  |  |
| <a href="#">Rhtemp101a - Humidity And Temperature Data Logger / Range -40*C To +80*C</a> |  |
| <a href="#">Pr140</a>  |  |
| <a href="#">Rhtemp101a</a>   |  |
| <a href="#">Pr140-Lvl</a>  |  |
| <a href="#">Hitemp 140-Fr</a>  |  |
| <a href="#">Ifc200 Usb Interface Cable For Standard</a>                                  |  |
| <a href="#">Hightemp 140-1</a>   |  |
| <a href="#">Tc101a</a>   |  |
| <a href="#">Ifc400</a>   |  |
| <a href="#">Oct-Quad-Thermobarrier</a>   | THERMAL BARRIER FOR QUADTEMP AND OCTTEMP   |
| <a href="#">Rhtemp1000is</a>   |  |
| <a href="#">Pr140 Pressure Data Logger</a>   |  |
| <a href="#">Prtemp1000d-100</a>  | 0-100 PSID, DIFFERENTIAL PRESSURE, TEMPERATURE RECORDER  |
| <a href="#">Rfc1000</a>  |  |
| <a href="#">Pr 140 Range : 0 To 5 Bar Pressure Data Loger For High Temperaturs</a>       |  |
| <a href="#">Prtemp1000d-500</a>  | 0-500 PSID, DIFFERENTIAL PRESSURE, TEMPERATURE RECORDER  |
| <a href="#">Pr140 - Pressure Data Logger / Range 0 To 5 Bar</a>                          |  |
| <a href="#">Avs140-6 Autoclave Validation System</a>                                     |  |
| <a href="#">Rfrhtemp2000a</a>  |  |
| <a href="#">Ifc400 Interface</a>   |  |
| <a href="#">Ifc200</a>   |  |
| <a href="#">Prtemp140-Npt</a>  | HIGH TEMPERATURE PRESSURE DATA LOGGER WITH NPT PORT TOP  |
| <a href="#">Hitemp140-1 High Temperatur Presure Data Logger</a>                          |  |
| <a href="#">Hitemp140x2 Dual Probe Data Logger</a>                                       |  |
| <a href="#">Octthermovault</a>   | 8-CHANNEL OVEN TEMPERATURE PROFILER AND AMERICAN POWER   |

SUPPLY

[Hp-1](#)

[Hitemp140x2](#)

[Avs140-6](#)

AUTOCLAVE VALIDATION SYSTEM: INCLUDES (5) HITEMP140 DATA LOGGERS AND (1) PR140 NPT WITH NIST CALIBRATION CERTIFICATES FOR ALL, IFC406 MULTIPLEXER DOCK

[Prtemp1000is-300-Psig](#)