

Masterflex

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Masterflex Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Masterflex T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen Özel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	Aıklama
96400-14	Masterflex L/S® Precision Pump Tubing, Peroxide-Cured Silicone, L/S 14; 25 ft
77600-62	spear parts
Brushless Process Drive with High-Performance Pump	Head for High-Performance Precision Tubing, 33 to 650 rpm; 90 to 260 VAC
07540-06	Masterflex L/S® Fixed-Speed Drive, 6 rpm; 115 VAC
GZ-07015-52	Masterflex L / S® standard pump head for L / S 15 hoses, PPS housing, stainless steel rotor
Master-SIL 2, DN 63, 4 M	DN: 63 Length in meters: 4.00 Customs tariff number: DE 40093100
Master-SIL 2, DN 203, 4 M	DN: 203 Length in meters: 4.00 Customs tariff number: DE 40093100
77112-10	Masterflex B/T® MasterSense™ BioPharma Pump
07519-80	Masterflex L / S® Small cassettes for pump heads 07519-05 and -06
Master-PUR L Trivolution, DN51, 10 M	DN: 51 Length in meters: 10.00 Only flame-retardant (class DIN 4102-B1) at a distance of > 40 mm to the same or others flat building materials. Burning dripping / falling off. microbe-resistant, permanently antistatic, surface resistance RO <10E9 Ohm, flame retardant after DIN 4102 B1 Customs tariff number: DE 39173900
000424	Master SANTO SL, DN 203, 10 M DN: 203 Length in meters: 10.00 Customs tariff number: DE 39173900 Net weight: 16.80

Flamex B se, DN 100, 10 M	DN: 100 Length in meters: 10.00 Only flame retardant (class DIN 4102-B1) at a distance of > 40 mm to the same or others flat building materials. Flaming droplets/particles.
Norprene Tubing LOT 693892	1pcs= 10Meters
Masterflex L/S® Precision Pump Tubing, Versilon™	Masterflex L/S® Precision Pump Tubing, Versilon™ A-60-N, L/S 14; 50 ft Tubing formulation : Versilon A-60-N (Norprene Tubing ID (mm) : 1.6 Wall Thickness (mm) : 1.6 Tubing OD (mm) : 4.8 Length Per Pack (m) : 15.2
Norprene Tubing wall thickness:1.6 Tubing OD (mm)	
MFLX06404-36	Pump hoses, Masterflex®, Tubing int.Ø: 9.70 mm (0.382")
MFLX07528-10-EU	
Mflx77200-60	
MFLX77601-60	I/P® Easy-Load® pump head for Precision tubing, black PPS housing, SS rotor, Masterflex®
VALVE MACHINE AD 8320 MINIFLEX PAINT PUMP HEAD	MASTERFLEX MFLX77200-52 W&H NO: 35023478
MFLX77200-59	REPL.ROTOR ASSEMBLY CRS
MFLX07015-20	
77410+Pharma50 7733	
77410-10+06429-24	
MFLX07522-30-EU	[EN]DRIVE MFLEX L/S 100RPM EUROPEAN 230V + MFLX50001-70 [EN]CORD W/PLUG EUROPEAN 230V 6'/1.82M + MFLX77200-92 Brdelrand
MFLX07555-05	L/S variable speed drive, 20 to 600 rpm; 230 VAC,
000063:32:25,00	Master-PUR H Trivolution PU suction hose / conveyor hose, medium-heavy, good flexibility, permanently antistatic, surface resistance < 10^9 Ohm, microbe-resistant, flame-retardant in accordance with DIN 4102 B1; Spiral: spring steel wire; Wall: pure polyester polyurethane (according to DIN ISO 4649 more abrasion-resistant than comparable polyether polyurethane) DN 32 Length: 25.00 m
000063:160:10,00	Master-PUR H Trivolution PU suction hose / conveyor hose, medium-heavy, good flexibility, permanently antistatic, surface resistance < 10^9 Ohm, microbe-resistant, flame-retardant in accordance with DIN 4102 B1; Spiral: spring steel wire; Wall: pure polyester polyurethane (according to DIN ISO 4649 more abrasion-resistant than comparable polyether polyurethane) DN 160 Length: 10.00 m
07528-20	
000063:80:4,00	Master-PUR H Trivolution PU suction hose / Conveyor hose, medium heavy, good flexibility, permanent antistatic, surface resistance < 10^9 Ohm, microbe-resistant, heavy flammable according to DIN 4102 B1; Spiral: spring steel wire; Wall: pure polyester Polyurethane (according to DIN ISO 4649 more abrasion resistant than comparable polyether polyurethane) DN 80 Length: 4.00 m
FLUE FLOW ACID PUMP HOSE MASTERFLEX	Norprene Tubing LOT # 693892
7518-00	Masterflex L/S Easy Loading peristaltic pump
77601-10	77601-10 East loat 1/P

000063:250	Master-PUR H Trivolution PU suction hose / Medium-heavy-duty delivery hose good flexibility, permanent antistatic Surface resistance < 10 ⁹ Ohm, microbe-resistant, heavy flammable according to DIN 4102 B1; Spiral: spring steel wire; Wall: pure polyester Polyurethane (according to DIN ISO) 4649 more abrasion-resistant than comparable polyether Polyurethane DN 250 Length: 10.00 m
L/S16(96400-16)	Silicone tube
MFLX_06508-18	Hose #18 (7.5 meters/pack)
WZ-07528-10	Flow rate: 0.06-3400 mL/min, Stack 2 or 4 pump heads, Power: 90 to 260 V
WZ-77200-62	Flow rate: 0.034-2900 mL/min
WZ-77200-02	stainless steel mounting hardware for two L/S Easy-Load II pump heads
77200-60	
Ew-07016-21	
210f-150	C
Ew-96400-36	
111-200	CLEAR
117-090-101	
23023620	STAINLESS STEEL CONSOLE
311-120-618	
6404-15 Norprene	
120-050-601	
07569 00	
7549-44 / Ew-77410-10	
110-200	CLEAR
07542-06	
96410-16	
0755271	MOTOR CONTROL
96410-36	
Hv-07569-00	AIR-POWERED DRIVE VARIABLE SPEED 60-600RPM
11730469 Hv-96412-16	
0 7 5 1 9 - 8 0	C A R T R I D G E L / S S M A L L Ursprungsland: UNITED STATES
07036 31	
7553-71	CONTROLLER 115VAC 50/60HZ 3AMP
77521-47 Obsolete/Replacement Ew-07528-10	
=77250-62	
114-120-101 Master-Pur Hx, Dn 120 -Absaug- /Forderschlauch- 1x10m	
07042-85	

110f-100	C
Hv0752445	MODULE
Masterflex Pumpen	Unser Kunde ben¼tigt 2 Pumpen, aber wir wissen leider nicht welche Pumpe geeignet ist, f¼r die Fl¼ssigkeit die verwendet wird. Im anhang finden Sie die documente ¼ber die Fl¼ssigkeiten. (Sika Primer 209 und Sika Primer 506)
311-160-618	
77411 00	
114-200-101	
310-075-601	
Gy-96407-13	
77201-62	
P35 4600 Lot 560579	
77410	
Hm-77495-00	
Ew-07528-10	
620-120-888	
7554-95	
07528 10	
325-063-107	
07019-43	PUMP SHORT SHAFT W/ TUBE
110 040 401	
Ew-77602-10	
07015 52	
1189-5191	
07015-52	
110-040-401	
07540-06	
07542 06	
110f-150	C
111-150	CLEAR
680-120-107	
7760110	
9641082	
77200-52	
662-075-102	
Ew-95612-46	

410-015-118 671-051-107	
532-120-888	
Ew-07519-80	
662-040-102	
Ew-05664-24	
96410 24	
117-070-101	
7742000	DRIVE
7730080	DRIVE
E-3603	
07036-31	
07569-00	
96400-16	
Ew-96241-24	
77200 62	