Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Mc Monitoring



Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Mc Monitoring Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Mc Monitoring Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Lvs-101 M1 (10mtcable)	Linearized vibration velocity Description: Linearized vibration speed sensor Pour cable without connector directly on the sensor. Cable length: 10 m Frequency range: Linearized output: 0.5Hz ... 1.5 kHz (<- 3dB), 0.7Hz ... 900 <-10dB) Sensitivity: 100 mV / mm / s, cross sensitivity: <7%, maximum deflection: 1.8mm PeakPeak Temperature range: -20 ° C - 80 ° C, dimensions [mm]: ø42 x 75, material: stainless steel 1.4301 Weighted: approx. 400g, threaded connection M10x1.5, length 20mm,, integrated linerization electronics Mounting version: HORIZONTAL mounting, supply voltage: +24 VDC (plus 24 VDC) Country of origin: CH, goods tariff number: 9031.8000, weight including packaging 2kg, piece
Lvs-101 M1 (5mt Cable)	
LVS-101 M1 / 10m / -24V DC	Vibration speed sensor -RADIAL Description: Linearized vibration velocity sensor Cable without connector potted directly on the sensor, cable length: 10 m with linearized and non-linearized output Frequency range: Linearized output: 0.5Hz ... 1.5 kHz (<- 3dB), 0.7Hz ... 900 <-10dB) Sensitivity: 100 mV / mm / s, cross-sensitivity: <7% Maximum deflection: 1.8mm peak peak, temperature range: -20 ° C - 80 ° C Dimensions [mm]: ø42 x 75, material: stainless steel 1.4301, weight: approx. 400g Thread connection M10x1.5, length 20mm, Integrated linerization electronics Installation execution: HORIZONTAL installation Supply voltage: -24 VDC (minus 24 VDC)

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Tariff number: 9031.8000, country of origin: CH, packed weight: 2kg
LVS-201 M1 / 10m / -24V DC	Vibration speed sensor - AXIAL Description: Linearized vibration velocity sensor Cable without connector potted directly on the sensor, cable length: 10 m with linearized and non-linearized output Frequency range: Linearized output: 0.5Hz ... 1.5 kHz (<- 3dB), 0.7Hz ... 900 <-10dB) Sensitivity: 100 mV / mm / s, cross-sensitivity: <7% Maximum deflection: 1.8mm peak peak, temperature range: -20 ° C - 80 ° C Dimensions [mm]: ø42 x 75, material: stainless steel 1.4301, weight: approx. 400g Thread connection M10x1.5, length 20mm, Integrated linerization electronics Installation execution: VERTICAL installation Supply voltage: -24 VDC (minus 24 VDC Tariff number: 9031.8000, country of origin: CH, packed weight: 2kg
Mc Monitoring	
LVS-101 M1	10m/+24V/+6V Linearized vibration velocity sensor Specification: Cable without plug cast directly on the sensor. Cable length: 10 m Frequency range: Linearized output: 0.5Hz...1.5 kHz(<-3dB), 0.7Hz...900 <-10dB) Raw signal output: 8Hz ...1.5 kHz (<-3dB) Sensitivity: 100mV/mm/s Cross sensitivity: <7% Maximum deflection: 3mm PeakPeak Temperature range: -20°C - 80°C Dimensions [mm]: ø42 x 84 Material: stainless steel 1.4313 Weight: approx. 500g Thread connection M10x1.5, length 20mm, Integrated linerization electronics Mounting design: HORIZONTAL mounting Supply voltage: +24 VDC (plus 24 VDC) BIAS voltage: +6 VDC (plus 6 VDC)
AGS-550 M3	Triaxial cable 2 meter length MCX coaxial plug 263.5 mm x 38 mm x 3.5 mm (LxWxH)
AGC-550	Measuring range to be specified: 15 to 35 mm (M3)
AGA-550 M2 ADAPTER	8 meter cable with Airgap Adapter

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Sensor=di-V1.3 Mc-Monitoring	
Sensor=kpi-V1.3 Mc-Monitoring	
Sensor=rpi-V1.3 Mc-Monitoring	
Sensor=raw-V1.3 Mc-Monitoring	
Sensor=alo - V1.3 Mc-Monitoring	Detailed images attached to file
Keyphazor Timer=kyt-110 Mc-Monitoring	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.