

## Meclube

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Meclube** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Meclube T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">011-0940-060</a>	
<a href="#">013-1123-000</a>	
<a href="#">013-1138-000</a>	
<a href="#">014-1048-000</a>	
<a href="#">022-1300-000</a>	
<a href="#">023-1964-000</a>	
<a href="#">050-1520-000-01</a>	
<a href="#">053-1537-000</a>	
<a href="#">070-1508-615</a>	
<a href="#">070-2201-315</a>	
	double diaphragm pump housing made of aluminium, pneumatic drive, two-chamber membrane, made of NBR with valve balls made of PTFE, PTFE seals in a pressure ratio of

<a href="#">028-A110-AB3</a>	1:1 with media connections screwed in G 3/4", input and output side, Compressed air connection G 3/8" screw connection Flow rate medium 110 l/min without back pressure, at 0.7 m <sup>3</sup> /min compressed air consumption, Dimensions : 178 x 265 x 245 mm high Weight : 6.0 kg
<a href="#">071-1202-218</a>	Swivel hose reel made of steel, Epoxy resin coated for air/water 20 bar Consisting of: Synthetic black Rubber hose 18 m, G 5/16" DN 8, Viton seals, 90° swivel joint nickel-plated brass, Hose stopper Inlet/outlet: G 3/8" internal thread/G 1/4" external thread Drum Ø 400 mm x 95 mm, weight 18.5 kg
<a href="#">071-2202-218</a>	Hose reel made entirely of stainless steel for water or compressed air up to 20 bar conveyor hose 18 m with 8 mm nominal width inlet G 3/8" internal thread, outlet G 1/4" external thread, drum Ø 400 x 95 mm wide, pivoting wall bracket. Weight 16.6 kg
<a href="#">028-A110-AB1</a>	Double diaphragm pump housing made of aluminum, pneumatic drive, two-chamber membrane, made of NBR with valve balls made of V4A, seals made of NBR in a pressure ratio of 1:1 with media connections screwed in G 3/4", inlet and outlet side, compressed air connection G 3/8" screw connection Delivery capacity medium 110 l/min without back pressure, at 0.7 m <sup>3</sup> /min compressed air consumption, Mafle: 175 x 265 x 245 mm high
<a href="#">028-P700-AB3</a>	Double diaphragm pump for water, antifreeze, Windscreen cleaner and AdBlue Housing made of polypropylene, pneumatic actuator, dual-chamber diaphragm, EX II 3/3 GD h IIB T4 135°C ATEX Zone 2 made of HYTREL+PTFE with valve balls made of PTFE, PTFE seals Print ratio 1:1 with media connections screwed into G 2", inlet and outlet sides, Maximum delivery head 80 m Maximum suction height 5.0 m Compressed air connection G 3/4" connection Medium delivery rate 700 l/min without back pressure, at 1000 NI/min compressed air consumption Dimensions: 595 x 345 x 570 mm high Weight: 37.5 kg
<a href="#">070-1518-615</a>	Rigid steel hose reel, Epoxy resin coated for gasoline 16 bar Explosion protection according to: II 2 G Ex h IIB T4 Gb X and II 2 D Ex h IIIC t4 Db, Synthetic Rubber hose with synthetic textile reinforcement and copper core EN 1761- EN 12115 ATEX (EX Zone) Hose dimensions 15 m, G 1", DN 25, Viton seals, 90° swivel joint, galvanized steel, Hose stopper Inlet/Outlet: G 1" internal thread/G 1" external thread Drum Ø 550 mm x 120 mm, weight 53 kg
<a href="#">014-1089-000</a>	Sliding coupling for 16 mm Ø, for Mounting, M10x1 internal thread
<a href="#">010-1005-000</a>	
<a href="#">079-1772-005</a>	
<a href="#">013-1113-000</a>	
<a href="#">014-1051-030</a>	



Yursat DıŐ Tic. M¼nendislik  
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505  
Osmangazi/BURSA  
+90 224 2400304  
[info@yursat.com.tr](mailto:info@yursat.com.tr)  
[www.yursat.com.tr](http://www.yursat.com.tr)

[014-1062-030](tel:014-1062-030)