Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Meister

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Meister Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Meister Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
FLOW SENSOR DKM-2/3 G 1/2"MS	
FLOW SENSOR DKM-1/24 G 1/2"MS	
52XM1008XG15SI4.0	Flow meter DKM/A-1/8 G 1/2" Measuring range: 2 - 8 l/min Set at flow from bottom to top and 150 cSt Oil - density 900kg/m³ viscosity compensated with flow indicator Version: brass Signal 4.0 Supply voltage: 24V (19..30V) Analog output: 4-20mA and 0-10V Connection: M12 x 1, 5-pin. IP 67, T -20 - 70°C Sensor housing: Al blue anodized Operating pressure max. 250 bar
45XM1001XG15W-VSB	Flow monitor DKG-1/1 G 1/2" Switching range: 0.1 - 0.8 l/min Oil - density 900kg/m³ Viscosity compensated up to 400cSt Version: brass Contact: Changer (COC) 250V 1.5A 50VA, IP 65 Minimum load 3VA lower screw turned out for VSB Operating pressure max. 10 bar Temperature max. 120°C Customs tariff number: 9026 10 81
54XE1024XG25WA	Flow monitor DKM/A-1/24 G 1" Switching range 8 - 24 l/min Oil - density 900kg/m³ viscosity compensated

Ürün	Açıklama
	with flow indicator Execution: 1.4571 Contact: Changer (COC) 250V 1.5A 50VA, IP 65 Minimum load 3VA Operating pressure max. 300 bar Temperature max. 120°C
Compressor MEISTER 700/10/100 D	ELMAG 10032
54XE1024XG25WA	Flow monitor DKM/A-1/24 G 1" Switching range 8 - 24 l/min Oil - density 900kg/m³ viscosity compensated with flow display Version: 1.4571 Contact: Wechsler (COC) 250V 1.5A 50VA, IP 65 Minimum load 3VA Operating pressure max. 300 bar Temperature max. 120°C
64XMA028XG15S	Flow monitor DUM/A-28 G 1/2" Switching range: 1 - 28 l/min water 20°C with flow display Version: brass Contact: normally open (NOC) 250V 3A 100VA, IP 65 Operating pressure max. 200 bar Temperature max. 100°C
52XM1002XG08WA	Flow switch DKM/A-1/2 G 1/4" Switching range: 0.5 - 1.5 l/min Oil density 900kg/m³ viscosity compensated with flow indicator Design: brass Contact: changeover contact (COC) 250V 1.5A 50VA, IP 65 Minimum load 3VA Operating pressure max. 250 bar Temperature max. 120°C
DKM-2/7 Flow	
RVO/U-2	
SG-30S-S-B-STP	switch housing normally open (NOC) 250V 3A 100VA, IP 65 for DKME-1/20

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
FL-110-01-F	1 set of guide rails for including mounting screws
DKG-1/15 G3/4 SS 316Tİ COC	FLOW SWITCH DKG1/15
82AM1020XG15S	Flow switch DKME/A-1/20 G 1/2" Switching range: 1 - 20 l/min Oil - density 900kg/m³ viscosity compensated with flow indicator Finish: Brass Contact: Normally Open (NOC) 250V 3A 100VA, IP65 Operating pressure max. 250 bar Temperature max. 120°C
11XE2020XG15S	Flow monitor RVM/U-2/20 G 1/2" Switching range: 4 - 20 l/min water 20°C Version: 1.4571 Contact: Closer (NOC) 230V 3A 60VA, IP 65 Maximum operating pressure: 350 bar Maximum temperature: 100°C
51XE2007XG15S	Flow monitor DKM-2/7 G 1/2" Flow rate range: 2 - 7 l/min Oil - density 900kg/m³ viscosity-compensated Version: 1.4571 Contact: Closer (NOC) 230V 3A 60VA, IP 65 Maximum operating pressure: 350 bar Maximum temperature: 120°C
FL- 110-01-F	1 set of guide rails for DKM/A-1/45 including mounting screws
SG-30S-W-B-STP	Switch housing changer (COC) 250V 1.5A 50VA, IP 65 Minimum load 3VA for DKM/A-1/45
50XM2003XG15W	Flow monitor DKM-2/3 G 1/2" Flow rate range: 0.8 - 3 l/min Oil - density 900kg/m³ viscosity-compensated Finish: Brass Contact: Wechsler (COC) 250V 1.5A 50VA, IP 65 Minimum load 3VA Maximum operating pressure: 300 bar

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Maximum temperature: 120°C
2XM1004XG15WA	Flow monitor DKM/A-1/4 G 1/2" Flow rate range: 1 - 4 l/min Oil - density 900kg/m³ viscosity-compensated with flow indicator Finish: Brass Contact: Wechsler (COC) 250V 1.5A 50VA, IP 65 Minimum load 3VA Maximum operating pressure: 250 bar Maximum temperature: 120°C
DKM 2/2	FLOW SWITCH/ DKM 2/2
50xm1004xg15w	
Dkm/A-1/4 G 1/2 Ã39;Ã39; Ms	
Dug-14	
Dkm/A-1/45-G1?-Ms	
Chp090027	
Dkm/A-1/4 G 1 Ã39;Ã39; Ms	
Dwm-3	FLOW MONITOR 1/4 BRASS GPH3-47.5
Dkg 1/24 G1/2quot; - 45xm1024xg15w	
Ih9pf40-22	
52xm1110xg25wa	
Dug-4	
Dkm-1/30	
Sg-30x70-1.5a-W	
Dkg-1/8 G 1/2	
Dkg14lpm500	INDICATOR
As213l-M8	
Dkm/A-1/110 G 1quot; 54xe1110xg25wa	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Dwg-18	
Dug-6	
47xe1015xg20w	
Dhtf-Pp (Dhtf-1)	
Dmk/A	
Dkg-1/10g 1/2-Ms-1	
8h180fm-Hi	
45xm1015xg15w	
Seriedkm, 24 L/Min Nã186;308?	
Dug-110	
Dkg-1/15 G3/4 Ss 316ti	DKG-1/15 G3/4 SS 316Tİ COC
Dkme/A-1/40	
41912955 203904	
52xm1002xg08wa Strã246;Mungswõ;Chter Dkm/A-1/2 G 1/4quot;	
Dug-22	
45xm1024xg15w Strã246;Mungswõ;Chter Dkg-1/24 G 1/2quot;	
Rh8pf25-22-Hi	
Dug-8	
50xm1060xg25w	
Dkg-1	
Dkm/A-1/110	
Dkm-1/15 G 1quot;	
Glasrohr Für Dwg-18	
3102-B	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
52xm1110xg25wa (Strã246;Mungswõ;Chter Dkm/A-1/110 G 1quot;)	
Dwg-3	
8h30fm- Hi	
Wa-Jv35mfk	
Rh8pf25-2-Hi	
52XM1024XG25WA	Flow monitor DKM/A-1/24 G 1"; switching range 8 - 24 l/min; oil density 900 kg/m³; viscosity compensated; with flow indicator; brass construction; changeover contact (COC) 250V 1.5A 50VA, IP 65; maximum operating pressure 100 bar; maximum temperature 120°C

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.