

Mesa Electronic



Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için

info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Mesa Electronic Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Mesa Electronic Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
7I52S	
390-0001	
390-0021	
50-A-23466	
520-3511/1	
520-3518	
520-3537	
520-4186	
530-2126	
530-3320	
6I25-LP	
6I25-SP	
7I76	
7I77	
808.623	
820-0170	
900-0920	
CD3S10045480SSR	
EM2020	

JO-3701	
LPS-A 50	
LPS-XA 50 4-20mA	
M3-3100-0200	
M3-3100-0200/9999	
MKM 0.1.0.0.0.0	
MQC-1008 P47	
NTV44G.1012.999.4.9M	
NTV44G.1012.999.4.9M 230V-mG	
SEGMH20-5%WLWA (замена устаревшего TDGMS-H2-0-5%-WA)	
130-6000	
M Gas G4	
130-6010	
Recovery Time Interval (Optional)	- Time interval flushing with storage of the probe value and separate
Rep-6153	
6i25	
C1-3000-0201/9999	
530-3660	
530-3701	
Ntv 44 P	The NTV 44 G was replaced by the NTV 44 P. 520-4185 Power supply NTV 44P for L-probe Type: NTV 44P with housing Device no. : Tariff No .: 90269000 Weight: about 1.5 kg Country of origin: Germany Dimensions: 190 x 120 x 90 mm (LxWxH), protection class IP 65 Input probe: -20 ... 1300 mVDC Heating voltage: max 18 VDC Heating current: max 2.5 A Special features: L-probe output in 4-wire technology Connecting cable about 70 cm long Efficiency typ .:> 80% Auxiliary voltage: 230 V + -10% / 50-60 Hz. Power consumption Max. about 48 VA OR 115 V + -10% / 50-60 Hz. Power consumption. Max. about 48 VA Standard configuration at delivery: L-probe temperature control: NO L probe purging: OFF Mains voltage: 230 V AC or 115 V AC
201930311/1 Lambda Probe L-Sonde ; K1: -3.3; K2: +43	
Factory Test Certificate (Optional)	

Mesa-X33105-0200-1522-000 Regler S2 230v Ac 4-20ma	
Ntv 44p Netzteil	
530-3663	
Zoc--02203	
530-5114	
142fuent0	
Segmh20-5%wlwa (?????? ??????????) Tdgms-H2-0-5%-Wa)	
531-3010	
5310-010	
531-0210	
- Isolated Universal Output (Optional)	- Isolated universal output 0 ... 1300 mV or 0..10 V or 0. ... 20 mA or 4 ... 20 mA
520-6210	
Rep-5310-010	
Mv0600010191	
Carbo-47	
Mqc-1008 P47 Dc - Servoregler Typ Mqc 1008 P47ballastschaltung, 100v 18a	
520-4177 (Ex.520-4167)	
520-4185	
Sg3cbt-72/1600	
6300210	
536-3579	
534-4072	
540-1311	
Rep-Mv22.12.5000	
Agl-14a	
531-0310 Regelzusatz Rz-Rsrz 49.110.211.4.M. Z80-Rs	
130-6012	
531-0310 Regelzusatz Rz-Rsrz	

49.110.211.4.M.Z80-Rs	
Rep-068905303	
Dewchecker 1.1	
Ntv 44 P(Ex.Ntv44g.1012.999.3.9)	
630-0202	
Tcpdem-4ujr-3300	
531-0310	
800-1077	
540-1010	
520-4167	
068905303	
520-3511	
900 0920	
142tubo12	
Rep-Fpg1.0	
24401 (Ex.540-1010)	
Mathematical Function (Optional)	- Mathematical function "% O2" or dew point using 32 vertices in an interval specified with the order
Mdew-F11000	
Ges-1-L Ks10010000ppm	
Mf160.90.200-1100-2f Lambda-Sonde	
28454 (Ex 390-0001)	
Sg3cn-72/1600	
28454	
Em2020 Regelsonde	
24750	