

Mesomatic

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Mesomatic Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Mesomatic Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
31074	
31074-850	
31074-860	
5013.00106	
5013.00133	
5013.00173	
5013.00183	
5013.00220	
5013.00303	
5013.00364	
DK 800/4A/RS485/IN	
DK 910/PDP	
DK710	
DK800	
DK800/2A/PDP/EN	
DK800/2A/RS232/IN	
DK800/2A/PDP/EN	weighing terminal with Profibus DP interface including 1 set of connectors Unsere Art.Nr.: 5013.00043 VERSION APPROVABLE

Ürün	Açıklama
XDK851/4A/PDP	weighing terminal Measuring amplifier and dosing device for load cells - Flush mount housing, front panel mounting - Protection rating on front side IP54 - Operating temperature -15 .. +55°C - Power supply: 24V DC - Display 4.3" full-color touch display, resistive Load cells, measuring amplifiers, industry - max. 8 load cells 350° Digital outputs, 24V DC - 4x HighSide Profibus interface Successor device to the DK800/2A/PDP/IN (5013.00047)
DK800	1-) Weight indicator in DIN box suitable for front panel mounting 2-) 6-digit semi-alphanumeric LED display 3-) 8 signalling LED 4-) 4-key keyboard 5-) IP54 front panel protection rating (IP65 front optional) 6-) Real-time clock/calendar with buffer battery 7-) Removable screw terminal blocks 8-) RS485/RS232 serial ports for communication via protocols ModBus RTU, ASCII continuous one way transmission 9-) Number of load cells : up to 8 (350 Ω) - 4/6 wires 10-) Load cells supply: 5 VDC/120 mA
DK800/2A/PDP/IN weighing terminal	with Profibus-DP interface incl. 1 set of connection plugs
XDK851/4A/PDP/IN	Digital weighing terminal for industrial requirements: - for front panel mounting - Front 150 x 91 mm / Installation depth 81 mm - Front panel cutout 137 x 66 mm - 4.3" full-color touch display resistive - Operating temperature -10 .. +40°C - Protection class front IP54 - 4 digital outputs 24V DC - Profibus DP - Supply voltage 12 .. 24V DC - Power consumption < 5W
Power supply for XDK851	Power supply for DIN rail mounting

Ürün	Açıklama
	- for 1-2 devices XDK851 - Input 88V AC ... 132V AC or 176V AC ... 264V AC switchable - Output 24V DC
Dk910/I	
Dk800/2a/Pdp/En, Art.Nr.: 5013.00496	
Akku Nimh 2,4v	
Dk800/2a/Pdp/In	
Dk910	
Mvd102.2/24vdc Obsolete, Replacement Xmv261/24vdc	
Xmv261/230vdc	
Dk800/2a/Pdp/En/1hz V01.02 Rev. 05	
Xdk911/Pdp	
Mvd102.2 Obsolete, Replacement Xmv261/230vdc Or Xmv261/24vdc (Available In 230v Ac Or 24v Dc)	
Dk710/M/24vdc	
Dk800/230v	
Dk710/M	
Xmv261/24vdc	
Xdk911 - Dk910	
Dk850/2a/Pdp/In/24vdc	
Dk-810 D-71394 S.Nr:040258	
Dk 910/Pdp Obsolete, Replaced By Xdk911/Pdp	