



Metal Work

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Metal Work Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Metal Work T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

| ¼r¼n | A¼ıklama |
|--------------------------------|--|
| 8084601 | |
| 88264K8 | Micro flow regulator Ø10-1 / 4 "special with TP ring piece, EPDM seals, bidirectional freight and packing |
| 1213 5001 75CN | Cylinder ISO 15552 Ø = 50 mm stroke = 170 mm - Series 3, double-acting, - Adjustable end position cushioning - With a magnet - Piston rod = C45 hard chrome plated - Seals = NBR Customs tariff number: 84123100 Country of origin: Italy |
| 1213 3201 25CN | Cylinder ISO 15552 Ø = 32 mm stroke = 125 mm - Series 3, double-acting - Adjustable end position cushioning - With a magnet - piston = technopolymer - Piston rod = C45 hard chrome plated - Seals = NBR |
| 7010 0212 00 | 5/2 way valve, G1 / 8 "type: SOV 25 SOB 00 Connection: 1/8 " electro-pneumatic bistable |
| 7010 0211 00 | 5/2 way valve, G1 / 8 "type: SOV 25 SOS 00, monostable Electropneumatic Spring return Weight: 200g |
| PMA18BAR | 0-12bar |
| 7020 0215 00 | 5/2 way valve 1/4 SOV 35 SES 00 Series 70 valve, electro-pneumatic monostable, external control air 1/8 |
| FR 300 G3/4 | Filter regulator Skillair FR 300 G3 / 4, 8 bar, 20µm RA Art no 4583 0140 00 |
| 0227 3012 01 | Inlet plate HDM 1-25D Ø 10 mm |

| | |
|--|---|
| 1213 3201 25CN | Cylinder ISO 15552 Ø=32 mm Stroke=125 mm 001 1213 3201 25CN - Series 3, double-acting - Adjustable cushioning - With magnet - Piston = Technopolymer - Piston rod = C45 hard chrome plated - Seals = NBR Customs tariff number: 84123100 Country of origin: Italy |
| W095 0000 222 | HALL-Sensor PNP DSM3-N225 30V= LED 2,5 m |
| 7010 0222 00 | 5/3 way valve 1/8 SOV 26 SOS OC electropneumatic Center position vented |
| W021 5000 151 | COIL 22 D8 2W-12VDC 100% ED, IP 65, DIN 40050 |
| W021 5000 101 | COIL 22 Ø8 BA 2W-24VDC W021 5000 101001 Coil temperature 100% ED: 55°C at 20°C ambient temperature Protection class: IP65 DIN 40050 with socket According to Ates 2014/34/EU Directive, Group 2, Category 3 GD |
| W097 0510 01 | Socket 22mm standard black DIN industry standard - form B |
| 7020 0224 00 | 5/3-way solenoid valve, 1/4" SOV 36 SES CC 001 7020 0224 00 5/3-way valve with external control air to also switch in vacuum Technical specifications: 1/4" connections Center position locked. external control air 1/8 Workspace: monostable 2.5 - 10 bar external control air vacuum - 10 bar Temperature range -10° - +60° Nominal diameter 7.5 mm Flow rate 264.26 NI/min Flow rate at 6 bar 0.5 bar 750 NI/min electrical voltage 24 V= Valve is delivered without coil and plug! |
| W097 0510 011 | Socket 22mm standard black DIN industry standard - form B |
| 7020 0102 00 | 3/2-way valve, 1/4" PNV 33 PNS-NC pneumatic normally closed, Control ports = 1/8 (Below for the 2nd item in your picture) |
| Pneumatic regulator 0-10 Bar, Line Input - | - Output ¼" Manometer Output 1/8" |
| Pneumatic Manometer 0-10 Bar , Connection 1/8" | |
| 0227 3012 01 | Inlet plate HDM 1-25D Ø 10 mm |
| 7062 0401 32 | Mach 16 valve, 5/2-way, monostable MSV 25 SMS OO 24VDC electropneumatic - mechanical spring |
| 7062 0403 12 | Center position valve Mach 16, 5/3-way MSV 26 SMS OC 24VDC electro-pneumatic - mid-position exhausted |
| 7062 0401 32 | Valve Mach 16, 5/2 way, MSV 25 SMS OO 24VDC monostable electropneumatic - mechanical spring |
| 7062 0401 33 | Ventil Mach 16 , 5/2-Wege, MSV 25 SMS OO 24VAC monostable electropneumatic - mechanical spring |
| W121 1600 220 | Zylinder ISO 15552 Ø 160 mm Hub 220 mm double-acting, with magnet, adjustable cushioning, Piston rod C45 hard chrome plated, seals NBR |

| | |
|--|---|
| W165 0321 180 | Zylinder Rot. Ø=32 Hub=180 S.R. |
| EB80 8'er 5/2 | |
| 7020021200 | |
| 7020021100 | |
| ISO6432 Ø25 C250 UNIT MW DH 025 CODE W07 | |
| 7020 0204 00 | 3/2-way valve, NO G1/4" SOV 33 SOS NO Electro-pneumatic, normally open |
| 7020 0212 00 | 5/2-way solenoid valve, G1/4", bistable, air spring 9mm el. Electropneumatic Specifications: value Solenoid valve - bistable without coil and socket Working pressure 1 - 10 bar Working pressure electrically with external control air Vacuum up to 10 bar Minimum working pressure 1 bar Temperature range -10 to +60 °C Nominal diameter 7.5 mm Flow capacity C 264.26 NI/min bar Critical factor b 0.27 bar/bar Flow rate at 6 bar and delta P 0.5 bar 750 NI/min Flow rate at 6 bar and delta P 1 bar 1,100 NI/min Response time at 6 bar 21 ms / 21 ms Weight 2.36kg suitable for ATEX Zone 22 |
| 7010021100 VALVOLA SOV 25 SOS 00 | |
| 7072 0305 31 | Ventil HDM I6 2x3/2, NC=5/3 Mitte entlüftet Ø=6 mm |
| 7072 0301 11 | HDM Ventil K6, 5/2-Wege, Ø= 6 mm, bistabil Manual override bistable |
| 7082 03I1 00 | Valve EB 80, 2x 3/2-way NC bistable manual override Works as a 5/3-way valve, center position vents OC |
| MSV25 SOP 00 24VDC-M.Work | selonoid valve |
| 562F40 + 562D10 + 562C10 | Komplett |
| 5624F 4040 00 | Filter Syntesi SY2 1/2 5 RA RA: Condensate drainage with automatic drain, independent of pressure and flow. |
| 5624 D104 00 | Oil filter Syntesi SY2 1/2 5 RMSA RMSA: Condensate draining with manual and automatic draining in a depressurized state. |
| 5624 C104 00 | Activated carbon filter Syntesi SY2 1/2 RMSA RMSA: Condensate draining with manual and automatic draining in a depressurized state. |
| 9900 1010 00 | Manometer M63, 1/4", 0-12 bar |
| 9210 0100 00 | Connection nipple set SY2 |
| 5613 P203 00 | PA 4-way SY1 3/8 compressed air intake |
| 7010 0215 00 | 5/2 way valve 1/8 SOV 25 SES 00 Electro-pneumatic monostable, external control air M5 |
| 9041 0050 00 | Flow regulator RFL U 1/2" can be regulated on one side |

| | |
|---|--|
| 7010 0221 00 | 5/3 way valve 1/8 SOV 26 SOS CC Electric pneumatic Middle position locked |
| 7001 0006 10 | VALVES SERIES 70, MEV 25 URS OO - 5/2 MECHANICALLY ACTUATED Roller lever valve with return |
| SILENCER REDUCED G1/8" BRONZE | W097052003 |
| W097052002 | SILENCER REDUCED G1/4" |
| W097052003 | SILENCER REDUCED G3/8" |
| W360 4000 005 | Logikelement: MEMORY |
| 5422 1181 1200 | Maintenance unit ONE electric, inlet/outlet 3/8 - Filter fineness 20 µm - Control range 0.5 - 8 bar - with filter dirt indicator - Automatic drain - V3V manual - Pressure switch |
| 551 B54 FILTER REGULATOR | 1/4 MM THREAD (5610B460 FR SY1 5 |
| Gasket | ISO 15552 TYPE.A. P.max 10bar No Tube 019763.0220.121A320350 FD BORE.032 STROKE-0350.. |
| 121A A205 00AN | cylinder ISO 15552 Dia=125mm; Stroke 500mm 121A A205 00AN002 Cylinder ISO 15552 Ø 125mm stroke=500 Series A, double-acting, with adjustable end cushioning with magnet, NBR seal hard chrome-plated piston rod |
| 2800320030CP | Compact cylinder LINER Ø=32mm stroke=30mm ISO 21287, Kosta AG, double-acting, with magnet, Kosta = C45 hv, Seals = PU |
| 0227 3012 01 - Input plate HDM 1-25D Ø 10 mm | |
| 0227 3015 00 - Blind end plate 5 - HDM | |
| 0227 3013 02 - Intermediate plate separate supply air 7-HDM | |
| 7073 0301 30 | Valve HDM V8 HHB monostable HDM elpn 5/2 single sol. 8 mm - single sol.man. Ctrl 24 VDC |
| Z329999998 HDM | HDM 3 8 M V8 7 V8 5 1x PLATE 1 hose Ø 10 1x D-Sub 25 pin Manual override monostable 1x 5/2-way monostable Ø8 1x intermediate plate, separate supply air 1x 5/2-way monostable Ø8 1x end plate/blind |
| 371Z 80F6 00H8 | Electric cylinder ISO 15552 Ø80 mm, stroke 600 mm |
| 7072030130- | HDM V6 5/2 way monostable Ø=6 |
| 543511871300 | ONE electric, input/output 1/2 Filter fineness 5 µm Control range 0.5-8 bar with filter dirt indicator manual shut-off valve electric soft start valve Pressure switch (NO/NC), 3-30V AC/DC max. inlet pressure 10 bar Flow rate = 4000 NI/min automatic condensate drain (pressure independent) |
| 0724 371Z80F600H8 | ELKTRO ISO 1552 SINGLE UNIT |

| | |
|---|---|
| 371Z80F600H8 | Electric cylinder ISO 15552 Ø80x600 without a motor |
| 371C50P450682S0S | Electric cylinder ISO 15552 Ø50x450 prepared for an Omron motor |
| W0950001001 | |
| 0090800502 | |
| W0970510011 Stecker 22 Std | |
| 7020021200 | |
| W0970510011 Steckdose 22mm Standard Schwarzdin Industriestandard - Form B | |
| Metal Connector Pin Cable 5mt For Crm2m8 | |
| 7062040102 Mach 16 Msv 25 Smp Oo 24vdc5/2 Ventil-Elektro-Pneumatisch, Anschluss 1/8, Monostabil | |
| Magnetspule 383- 24c Fur Ventile Serie Sovipv | |
| 9002200 | |
| 2I01010 | |
| 7073030130 | |
| Dsl4n | |
| 7010021100 Ventil Sov25 Sos Oo | |
| 5/2 Wegeventil (7020021100) | |
| 121a400075cp Zylinder Iso15552 Dia=40, Hub=75z329999998 | |
| 2f06010 Fitting | |
| Sov 23 Sos Mc 7010020200 Ventil | |
| 7072030111 | |
| 3280001 | |
| 121a400300cp | |
| Pa-300 Fr-300-20 | |
| 1/8 2a No/Nc 2 Mt | |
| 0227301500 5 - Hdm - Blind-Endplatte | |
| 3602004 | |

| | |
|--|--|
| W0351000031 Drehknopf, Sw, 2 Stellungen, Gerastet Bistabil | |
| 121aa11300an | |
| 5521500 | |
| Nsv G5 Ses 00 Ventil | |
| 3402001 | |
| Cyl1213320060cn Zylinder Pneumatische Iso15552 S3 Cyl 32 60 Nbr Chr | |
| Id7051021200 Wegeventil Iso 1 5/2 Elpn Bist | |
| 1213320400xp | |
| Ifm 05h500 05h-Fpkg/Us | |
| 5202003 | |
| 2750230300cn | |
| 4480004 | |
| 0413 Qc24 121a500300cn | |
| 706204010 Solenoidnyj Ventil | |
| 124g50a150av | |
| 5207002 | |
| W0950000453 S. Hall Pnp Dcb3n-24v 5mt Halteklammer | |
| 5521500 Proportionaldruckregler Regtronic 1/8 | |
| 7020021100 Sov 35 Sos Oo5/2-Wege- Magnetventil, 1/4", Ohne Spule | |
| W0215000121 Spule 22 D8 Ba 3va- 110vac 50/60 Hz100% Ed, Ip 65, Din 40050 | |
| 2f05005 Fitting | |
| 7010020200 Pneumatic Valve 10 Bar | |
| 7010020500 Ventil Sov 23 Ses Nc | |
| Plt-10 Iso 15218 | 10mm magnetventil Working pressure 3-7bar, power 0.9W 24VDC NW 0.6mm FKM seal |
| 7010020500 Sov23 Ses Nc | |
| For 1213800250av | |

| | |
|--|--|
| W0970510015 Steckdose 22mm Mit Led + Vdr 24v Din Industriestandard -Form B Transparent | |
| 1200400125cn | |
| W02150000101 Coil + Connector | |
| 2120500025cp | |
| 2I01012 | |
| 2I04004 | |
| 2f01010 Fitting | |
| 7020 0205 00 | 3/2-way valve 1/4 SOV 33 SES NC Electro Pneumatic, normally closed |
| Sov-25-Sob-00 | |
| 2700163200cn Bore: 016 Stroke: 3200 | |
| 707303053 Ventil I8hdm | |
| 0262813032 1580/06 M51 2 8 14x4 X2v6 Z | |
| 2300160025xp | |
| Isv 56 Sos Cc | |
| 2I03005 | |
| 2I02005 | |
| 7069030132 | |
| 9201201 | |
| 121550b800xc | |
| Dsm1-C51k Mwhs | |
| Z320126600 | |
| W0511101101 | |
| 2703250760cp | |
| 0351000050 | |
| 2f06007 Fitting | |
| 9021007c Fitting Mrf N T C 6 1/4 | |
| 7073030130 Hdm V8 Man. Monost. Valve | |
| 0223000701 | |

| | |
|--|--|
| 7073030111 | |
| 90010039 | |
| M5148i8716x4v6x3 | |
| Model: 075 G No:06031859 | |
| 7062040102 Mach 16 5/2 Ventil Msv 25 Smp Oo 24vdc Elektro Pneumatisch Anschluss 1/8, Monos | |
| W0950000222 | |
| 4602002 | |
| 0091250101 | |
| 121z50i040cp | Cylinder ISO 15552 Ø = 50mm, stroke = 40mm single-acting basic position extended Seal for double-acting function installed with magnet, adjustable cushioning, Piston rod = C45 hard chromed, |
| 1120250125xp | |
| 0227301201 Hdm-Eingangsplatte 1 Std 3 - 7 Bar | |
| 1210500050?? Pneumatikzylinder | |
| 4571901 Apr 300 3/4 Solenoid Cnomo Control | |
| 7010011100 Zufuhr Pnv 25 Pns Oo | |
| W0215000101 Spule 22 D8 Ba 2w-24vdc | |
| 7062060132 Valve | |
| 7010022100 | |
| 121aa10150an Zylinder 121aa10150an With 300mm Extended Pistonrod | |
| 7072030130 | |
| 022730 | |
| 5203001 | |
| Sov 33 Sos Nc - 3/2 | |
| 0226960500 | |
| W3501000200 | |
| 2170250010cp | |
| 1130160025cp Pneumatikzylinder | |

| |
|--|
| 2I050004 |
| 7020020200 3/2 Wegeventil 1/4 Sov 33 Sos Ncelektro Pneumatisch Normal Geschlossen |
| 0227300500 Multimach Endplatte, Blind |
| W0950322020 Kopf Der Gabel-Mw Gk M Metalwork Pneumatic M10x1.25 |
| 1211000250ap |
| 1210320025cn |
| 1100250010cp |
| Mav25v1b00 |
| 2f01013 Fitting |
| 7010010200 3/2 Wegeventil 1/8 Pnv 23 Pns Ncpneumatich Normal Geschlossen, Steueran |
| W3501000111 Vme1-11 Nc M5 |
| 2140320040cp |
| Cr22m Sensor |
| 400-517-42 |
| 7062020103 |
| 5111002 Mr Bit Fc 04 1/8" |
| 7010021100 Zufuhr Sov 25-Sos Oo |
| W0952029394 |
| 9065712 |
| W3501001101 |
| Onpp-A-S-0200-N Magnetostriktive Lineare Wandler |
| Z329999998 Ø=40mm, Hub=1300mm |
| 7030020400 |
| 1920.9pl.42 |
| Pr30020 |
| 121a500220cn Pneumatikzylinder |
| 9200701 Haltewinkel R-Fr Sf 1/4 |

| | |
|---|--|
| 7062060132 Mach 16 5/2 Ventil Msv 25 Scs Oo 24vdc | |
| 7062040102 Wegeventil Mit 6-182 | |
| 7062 0301 32 | Mach 16 5/2 valve MSV 25 SES OO 24VDC Electropneumatic, monostable, ext. st |
| 2f01007 Fitting | |
| Id9002200 Pressure Regulator D40 | |
| 4480006 | |
| Cr2m8 W0952028184 Sensor | |
| W 3501000400 | |
| 1130250040cp | |
| 9101201 | |
| W0951602102 | |
| 88261a1 3/2 6mm Mini Valve Block | |
| 1130400720cp | |
| For 7010020200 | |
| 25sos00 | |
| 2500100?050cp | |
| 2f05004 Fitting | |
| 7062040102 Mach 16 5/2 Ventil Msv 25 Smp Oo 24vdc | |
| 2l08002 Fitting | |
| 0240009035 | |
| 2lo2005 | |
| P/N Epr102 | |
| 113u160050cj | |
| W 1201600100 Cylinder | |
| 2220630070cp | |
| 3202001 | |
| 1211000050an | |
| 227301201 | |
| 7073030210 | |
| | |

| |
|---|
| 113016150a Pneumatikzylinder |
| 7070030532 |
| 9232010 |
| 7010010200 3/2 Wegeventil 1/8 Sov 23 Sos Ncelektro Pneumatisch Normal Geschlossen |
| W3501001111 |
| 1130320100cn Cylinder For Plasma Table |
| 7010020200 Ventil3/2 Wegeventil 1/8 Sov 23 Sos Ncelektro Pneumatisch Normal Geschlossen |
| 0950004015 Shock Absorbers Eco S 25 Mc2 Corto + Nut M14 X 1.5 |
| W0950000222 Hall-Sensor Pnp Dsm3- N225 30v= Led 2,5m |
| 2151003 Fitting |
| 1130200050cn |
| 227300200 |
| 1120250100?P |
| W3501000100 Zufuhr Vme 1-01 Nc D4 |
| 2101009 |
| W0950000711 Die Befestigung Des Sensors Zum Zylinder Pneumatic Metalwork |
| W0215000101 Spule 22 D8 Ba 2w-24vcd |
| 7062020103 Wegeventil |
| Z329999998 Z25p4009300003 Conn.Mp1 Cabl Mt3 Led+var 24 |
| 1302002 Regler Newdeal 3/8 8bar |
| W0950000711 Die Befestigung Des Sensors Zum Zylinder |
| 2170320020xp |
| 25bh50b080xp |
| 7062020132 |
| 0240009036 M12 Bus-In Buchse, B- |

| |
|--|
| Kodierung |
| 5612r142 Regler Sy1 1/4 08 |
| 121a500050cn Pneumatikzylinder |
| Cr2m8 Sensor 1725 6w/Va |
| W0950000222 Sensor |
| 1120160030cp |
| 2f04003 Fitting |
| 1210401000ap |
| 0227301500 |
| 7062040102 Mach 16 5/2 Ventil 25 Msv Smp Oo 24vdcelektro Pneumatisch Anschluss 1/8, Monos |
| 722123840101 |
| 1213a11500 Ap Spezialzylinder |
| 517.212 |
| 2008015 |
| W0950000453 S.Hall Pnp Dcb3n-24v 5mt Halteklammer |
| Sov35soboo Pneumatic Valve Max 10bar |
| 9170201 Montage Des Dampf - |
| 9041003 In-Line Durchflussregler Rfl U Ig 1/4 |
| 2006007 |
| 1210320150cp |
| 7063020132 |
| W0950000201 Reed-Sensor Dcb2c-425 Led Stecker=m8 2,5 St 2 17,68 35,36 05.10.20172,5m-Kabel |
| 47100110 |
| W0950802025 Gelenkauge Ga-M M20x1,5 |
| W020021100 Spule |
| W0951602102 Dichtungssatz 160 Hightemp Fkm/Fpm |
| 121a500320cn |

| |
|--|
| 4471900a |
| 7068030132 |
| 0227301500 Blind End-Plate Hdm |
| 0090500101 |
| 2f06009 Fitting |
| 9251720 |
| 120ga10230zp |
| 7062040102 Wegeventil |
| Sov 33 Sos Nc L |
| 9353301 Spares Tf 200 Rmsa |
| 1213?113000?? Spezialzylinder |
| Z329999998 Z52091002300ms51 |
| 4002002 |
| 4488002 |
| 0226007003 Reparatursatz Kit M16 Of Multiple Base Integrategaskets |
| 4589003 |
| 00904060400 |
| 2I01008 |
| 5207003 Regler Mr Bit 1/4 8bar |
| 1213a20090an Iso 15552 Series 3 |
| 121a63d090cn |
| 3202003 |
| 17/12 Rem-Satz Zum Zylinder |
| 9021007c |
| 2130250010cn [hub = 10] |
| 1210630966cp |
| W0210010100 Coil 30 O 8 4w-24vdc |
| 2032011 |
| Ident.-Nr. W0952029394 T-Nut Ce3m8p 3polig M8 300mm |

| | |
|---|--|
| 0273803040 Not Found | |
| 121550b800xc Pneumatikzylinder | |
| 9001003 | |
| 1210320030cn | Cylinder ISO 1552 Ø = 32mm stroke = 30mm double acting, with magnet, adjustable cushioning, Piston rod = C45 hard chromed, Seals = NBR |
| 121aa10150an Pneumatikzylinder | |
| 1210400400cp | |
| 22 D8 Ba 3va-220vac 50/60 Hz | |
| W0950000232 | |
| 2I05004 | |
| 7020021500 Wegeventilsov 35 Ses Oo | |
| 0227301302 | |
| 5/2 Vana 1/8 Sov25sos Oo | |
| 7030020200 Wegeventil 7030020200 Sov 43 Sos Nc | |
| Sov 25 Sos Oo | |
| W0952029394 Hall-Sensor T-Nut Ce3m8p 3polig M8 300mm | |
| 7072030530 Ventil Hdm I6 Monostable | |
| W1212000190 | |
| 1x34 | |
| 2I22003 | |
| 2f04005 Fitting | |
| 2f01012 Fitting | |
| 118z20a015xp | |
| 3602003 | |
| 121340700xp | |
| 2031011 | |
| Fr+I 200 | |
| 0227301230 Hdm - Eingangsplatte 1 Profibus Dp, Std | |
| W0950000201 Reed-Sensor Dsm2-C525 | |

| |
|---|
| Mit 2,5m Kabel |
| 8953700a Getriebe |
| 2110250010cp |
| 0240009036 |
| 227300500 |
| 7072030131 |
| 120za1j500zc |
| Cr22m W0952025390 Sensor |
| W1630222180 |
| Solenoid Bobini 383- 24c |
| Z520910020200m |
| 7062040102 Wegeventil 25 Msv Smp Oo 24vdc; E; 5/2;Monostabiler Mit Fell. Feder |
| 7010010400 |
| 2f05003 Fitting |
| 7073030131 |
| 7010020200 3/2 Wegeventil 1/8 Sov 23 Sos Ncelektro Pneumatisch Normal Geschlossen |
| 227301500 |
| Pneumatikzylinder Auf Die Werkbank Hdtv Supra D |
| W0950000722 Bracket St250 |
| 0090400502 |
| 2f06008 Fitting |
| W0952028184 |
| Verteiler Mav25 Pps Oo |
| 5204008 |
| 706202010 Wegeventil 25 Msv Sop Oo 24vdc. |
| W1212500360 |
| 00904002502 |
| W0950029394 |

| |
|--|
| 7062060132 Wegeventil Mit 6-181 |
| 1211250250ap |
| 4470001 |
| W0950000232 Cylinder Position For Sensor E Hall Npn Sensor Dsm3 M225 |
| 2I04005 |
| Fr+l 1/2 4 012 Rmsa 1/2quot; |
| 1200800030ap Pneumatikzylinderiso 6431-Vdma |
| Cy0006519 |
| 2675400070cp Cylinder |
| 7020022100 5/3 Wegeventil 1/4 Sov 36 Sos Ccelektro Pneumatisch Mittelstellung Gespe |
| 022730030 |
| 9000401 Druckschalter 1/8 2a Wechsler 2mtmit 2m Kabel |
| Hdm-Blind-Endplatte |
| 7062040102 Msv 25 Smp Oo 24vdc |
| Markp40/10 |
| Pa-300 Fr3001/2508 |
| 0227300303 |
| 7020021100 Wegeventil 7020021100 Sov 35 Sos Oo |
| W1430162020 |
| 1213500250cn |
| 7001000910 Mev 25 Lls Oo - 5/2 |
| 1402004 |
| W0970510011 Aufnahmewannesteckdose 22mm Standard Schwarzdin Industriestandard - Form B |
| 4403003 |
| 7020021100 Zufuhr Sov35 Sos Oo |
| 2750250300cn Pneumatikzylinder |

| |
|--|
| Sov 35 Sos 00 |
| 3280002 |
| 1120250020cn |
| 2f04004 Fitting |
| 9000640 |
| W0952025390 Hall-Sensor Dsa-4n Ce32mp 3polig 2,5m |
| 70100102200 |
| 9000401 |
| 121aa10275an Pneumatikzylinder |
| W0970530021 |
| 7010011100 Air-Controlled Valves Max 10 Bar |
| 7020021100 Zufuhr Sov 35 Sos Oo |
| 5207004 |
| 0227301302 Intermediate Blind Hdm |
| 5522500 Proportionaldruckregler Regtronic 1/4 |
| Ce3m8p |
| Pnv 35 Pns |
| 707203013 |
| Ventilinsel |
| 516.501 |
| 47100259 |
| 121aa20160zp |
| 2151001 Fitting |
| 2032010 |
| 1210500045xp |
| 9021008c |
| W0215000111 Die Spule 22 D8 Ba 3,5 Va-24vac 50/60 Hz |
| Ce3m8p Position Sensors 10-30v Dc, Ia |

| |
|--|
| (Current) |
| 235.03-M |
| E3153924vdc |
| Z329999998 Z00w0970550012 Val. Sferamini 1/4 Mf |
| 2005006 |
| 1130160150cp |
| 0091000031 Reparatursatz |
| Hdm V8 - Incomplete Model |
| 0240009035 Stecker M12 / Hdm/Eb80 Profibus Out Dp |
| 235.07-M |
| Nsvg8sesnc70690305 |
| 7020021100 Magnetventil Sov 35 Sos Oo5/2-Wege-Magnetventil, 1/4", Ohne Spule |
| 1213400100xp Druckluftzylinder |
| 9700107 |
| 514.134 |
| W0950402020 |
| 7020011200 |
| 2I14005 Fitting |
| 2I08008 |
| Mav 33 Vlb Oo - 3/2 7020001400 |
| 7073030530 |
| 1210500250zv |
| 2121000020zp Pneumatikzylinder |
| 121a630500cn |
| W0215000111 |
| W0215000101 Spule 22 D8 Ba 2w-24vdc 100% Ed, Ip 65, Din 40050 |
| 121a320160cn |
| 5610r100 Reg Sy1 02 Without |

| |
|--|
| Bushingeinstellbereich=0-2bar, Durchfluss=1.200 |
| 7020021200 5/2 Wegeventil 1/4 Sov 35 Sob Ooelektro Pneumatisch Bistabil |
| W0970520037 Steckdose 30mm Mit Led + Vdr 24 V Transpdin43650 - Form A |
| 7063020132 Mach 18 5/2 Ventil Msv D5 Sos Oo 24vdc |
| 400-514-42 |
| 7020020200 Wegeventil 7020020200 Sov 33 Sos Nc |
| Z32w095000020110 |
| 3.Dm.63010 |
| Z329999998 Ø=40mm, Hub=1250mm |
| 2I05005 |
| Z329999998 |
| 7001000500 |
| 7030021200 |
| 7062020105 Msv 25 Sop Oo 22ovac - 5/2 |
| Sensor W0950029394 Metal Work Pneumatic Hall-Sensor, Mit 300mm Kabel |
| 9700102 |
| 1120320125cn |
| Piriz 22mm Standart Siyah |
| Kom 9237/4 |
| 226180001 |
| Z52021005005ps2 Multiplikatormaximum 8 Bar |
| 2110001 Fitting |
| 9700101 |
| 9151501 |
| 0090800005 |
| 543511881300 |

| |
|--|
| 5610b243 |
| W0215000101 Spule 22 D8 Ba 2w- 24vdc100% Ed, Ip 65, Din 40050 |
| 121a401000ap |
| 707303011 |
| 7020011100 |
| 7021020100 |
| Pepur-10/07 |
| For 800050vp |
| 7062040102 Msv 25 Smp 00, 24vdc |
| 1120250040cp |
| 1425030 |
| 9021112v Druckregler Unter Das D10 |
| Qc0915 W1590320200 Pneumatikzylinder |
| 9011005c |
| 7010021100 Ventil5/2 Wegeventil 1/8 Sov 25-Sos Oo |
| 11036410 |
| Z329999998 1120200225cp |
| 223000301 Platte Cvm -18-03 Serie 70;3 Pneumatischen Oder Elektro- Pneumatischen Verteiler 1/8 |
| 7062040103 Msv 25 Smp Oo 24vac |
| Z329999998 Wegeventlim51 3 8 V6 W6 V6 V4 I4 7 I4 5 |
| 1240400025av |
| 0090500101 Ck .50 |
| 0227301201 |
| 4471900a Apr Pneumatic W/Out End Plates |
| M5148i8716x4v6x5v8 |
| 112 Z 25a400xp |
| 7061020212 Mach 11 5/3 Ventil Msv 16 |

| |
|--|
| Sos Cc 24vdcelektro Pneumatisch Mittelstellung Gespe 2I31014 |
| 121aa10050an Pneumatikzylinder |
| W0952025390 Sensor |
| 113u250500cj |
| 7040021100 Zufuhr Sov C5 Sos Oo |
| Z329999998 Ø=40mm, Hub=750mm |
| Cr2m8 Sensor |
| 2800630025cp |
| 121aa10300an Pneumatikzylinder |
| 5610a700 Ventil Softstart (Ohne Gewinde) |
| 7073030110 |
| 707303013 |
| W 3604000004 |
| W 3501000131 |
| 7020020200 |
| 0090630101 |
| 7020021200 Zufuhr Sov 35 Sob Oo |
| 450.420-M |
| 113u200050cj |
| 1210800340an |
| Kom 1856/4 |
| 7010022100 5/3 Wegeventil 1/8 Sov 26 Pas Cc |
| 1213400450cn |
| 9001003? Fitting |
| W0950322020 Kopf Der Gabel-Mw Gk M M10x1.25 |
| 2152003 |
| Ident.-Nr.6402001 Reg 400 G2 Customs Union |

| |
|--|
| 2f01011 Fitting |
| M3f40- Not Available |
| Msv 05 Sos 00 |
| 0227301253 Hdm Can Open Input 1 |
| Kom 3298/4 |
| 4571906 |
| 7020021100 Wegeventil 5/2 1/4elektro Pneumatisch Monostabil, |
| 9065016 |
| 7030020200 3/2 Wegeventil 1/2 Sov 43 Sos Ncelektro Pneumatisch Normal Geschlossen |
| Hdm 08-5/3-Wege-Ventil, Mittelstellung Gespert, Bistabil |
| 7062040102 Wegeventilmach 16 5/2 Ventil 25 Msv Smp Oo 24vdc Elektro Pneumatisch Anschluss 1/8, Monos |
| 9210003 |
| 2f01008 Fitting |
| 7073030530 Hdm I8 Man. Monost. Valve |
| 7071030530 |
| 7010021200 |
| Sova5sosoo |
| 9041002 In-Line Durchflussregler Rfl U Ig 1/8 |
| 0263905058 Ventilinsel Komplett (Ohne Kabel) |
| W0952029504 Hall-Sensor Pnp, Hs Cr2m8 2-Polig M8 300mm Kabel |
| 5107003 Regler Mr Bit 1/8 8bar |
| 706202010 |
| Cil W121ka30350 |
| W4017004200 |
| 7010021200 5/2 Wegeventil 1/8 Sov 25 Sob Ooelektro Pneumatisch Bistabil |
| Sov 25 Sos Oo - 5/2 |

| | |
|---|--|
| 0262807037 | |
| Ident.-Nr.7020020100 Sov 33 Sob Oo - 3/2 | |
| 2I08006 Fitting | |
| Mr R1/4 | |
| Pneumatic Luft-Block | |
| 457001 | |
| W0950000201 | |
| W120za3g100 4160 Cil.D=160 C=100 Spec.Trasd.Lineare | |
| 121a501400ap | |
| Zufuhr Msv Ds Sos-00 Metal Wovk. Steuerung 01311 Pv 01 Ho 11 N12 24 Vdc 1w 1404 | |
| 7020021100 | |
| 7010001300 | |
| 7072030531 | |
| 9065024 | |
| 0273802000 | |
| 9700103 | |
| 7030 0211 00 | 5/2 way solenoid valve 1/2 SOV 45 S0S 00 Series 70 valve, electropneumatic 1/2", external control air, monostable, spring return |
| 0223000601 | |
| W3501001100 | |
| 2130250015cn - Such Model Is Not Available, You Can Choose Between Hub = 5,10, 25, 30, 40, 50 | |
| Ident.-Nr. W0952022180 | |
| 7020021100 Ventil Magnetventil Sov 35 Sos Oo5/2-Wege-Magnetventil, 1/4", Ohne Spule | |
| W0952022180 Reed-Sensor Tnut Cr22m Dsa2-C 2pol. 2,5m | |
| W3120000021 | |
| W0950502020 Kopf | |

| |
|---|
| 4480003 |
| Cr22m W0952022180 Sensor |
| W4005001150 |
| 2I01021 Fitting |
| 7062020104 |
| 4482008 Filterregler 300 1/2 20 012 Rmsa |
| Nsvg5sesoo70690301 |
| 4480005 |
| W0970530024 Muffler 3/8 Mwse |
| 0090500502 |
| 2170800020ap |
| 1213500400cn |
| Reg 200 1/2" Getriebe |
| Sov 25 Sos 00 Magnetventil |
| W095431 |
| Rubber For 7020001400 - Not Available |
| W3501000100 |
| 121a400500cn |
| Z08ff55pt018050s1 |
| 5520500 M5 Regtronic |
| 7010020500 3/2 Wegeventil 1/8 Sov 23 Ses Nc |
| 7010021200 5/2 Wegeventil 1/8 Sov 25 Sob Oo |
| 7062020102 |
| 121a320075cp Pneumatikzylinder |
| Cy0006519 Solenoid Coil.24vdc3/0.3w0- 13bar |
| 7010021200 Ventil Sov25 Sob Oo |
| 4583004 |
| W0215000001 Spule 22 D8 5w- |

| | |
|--|----------------|
| 24vdc24v= , 5w , 100% Ed Ip 65- Din 40050 | |
| W0952025390 | |
| 9025008? | |
| 7010021100 5/2 Wegeventil 1/8 Sov 25 Sos Oo | |
| 3402003a | |
| 707303011 Ventil K8hdm | |
| 2151005 Fitting | |
| W1800400050 | |
| W0215000101 | 24V DC 2W COIL |
| 7070030132 | |
| 7062040102 | |
| 707303063 | |
| 8825922 | |
| 706903132 Wegeventil V6 | |
| 9000500 | |
| 514.144 | |
| 115q40a550cp | |
| 7010020200 | |
| W1630253180 Drehmodul Mit Flansch +stosdaempfer R3-25 | |
| 0090327001 | |
| W1630222180 Rotary Actuators Series R3, With Flange R3-180 | |
| W0511101101 Rotations-Verbindung Acc.Giunto Rtj-Osg-18-18 | |
| 7010021100 | |
| W0950322020 Gabelkopf Gk-M M10x1,25 | |
| Sensoren Fur Die T-Nut Reed Sensor, M8-Stecker An 300 Mm Kabel | |
| 1210800250ap | |
| W0950000201. | |

| |
|--|
| 9450101 Reparateursatz |
| 9041002 |
| 121a630100cp Reparateursatz Luftkappedurchmesser Zylinder: 63mm Hub: 100mm |
| 7073030110 Hdm K8 Man. Monost. Valve |
| 2I01001 Fitting |
| Kom 3329/4 |
| 7070030112 |
| W0950000222 Elektromagnetische Sensor |
| 543211881300 Air Treatment Unit |