

Mietzsch

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Mietzsch Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Mietzsch Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
KT-02 / KUNSTSTOFFVENTILATOR	Radialer Typ Exakter und säurebeständiger importierter Abluftventilator aus PP Der radiale Ex-Proof-Lüfter aus PP zusammen mit elastischen Anschlüssen am Lufteinlass und -auslass (Exproof and Acidproof ithal fan) Q: 460 m ³ /h - P: 900 Pa / 1Stk Q: 1.700 m ³ /h - P: 900 Pa / 1Stk Q: 2.650 m ³ /h - P: 900 Pa / 1 Stk.
VRE 100 / 734 W 1450 - TS - GD - Z2Z2 - PPsX	Plastic centrifugal fans - Direct drive explosion-proof Series VRE / W Type Nominal size / impeller type W Nominal speed - special design - material Volume flow see m ³ / h Total pressure increase characteristic Pa Temperature of the pumped medium 40 ° C Motor power 0.12 kW Voltage / frequency 400 V 50 Hz Rated motor current 0.52 A. Fan speed 1450 rpm Sound level LA3m 45 dB (A) Weight 10 kg Safety requirements according to VDMA 24 167
Repair switch for VRE100 (optional)	mounted, 3-pole with auxiliary contact, explosion-proof
VRE 160 / 734 W 1450 - TS - GD - Z2Z2 - PPsX	Volume flow see m ³ / h Total pressure increase characteristic Pa Temperature of the pumped medium 40 ° C Motor power 0.25 kW Voltage / frequency 400 V 50 Hz Nominal motor current 0.80 A. Fan speed 1450 rpm Sound level LA3m 52 dB (A) Mass 18 kg

Ürün	Açıklama
Repair switch for VRE160 (optional)	mounted, 3-pole with auxiliary contact, explosion-proof
VRE 200 / 734 W 1450 - TS - GD - Z2Z2 - PPsX	Volume flow see m ³ / h Total pressure increase characteristic Pa Temperature of the pumped medium 40 ° C Motor power 1.1 kW Voltage / frequency 400 V 50 Hz Nominal motor current 2.40 A. Fan speed 1450 rpm Sound level LA3m 60 dB (A) Mass 30 kg
Repair switch for VRE200(Optional)	mounted, 3-pole with auxiliary contact, explosion-proof
VRE 250 / 734 W 1450 - TS - GD - Z2Z2 - PPsX	Volume flow see m ³ / h Total pressure increase characteristic Pa Temperature of the pumped medium 40 ° C Motor power 3.0 kW Voltage / frequency 400 V 50 Hz Nominal motor current 6.0 A. Fan speed 1450 rpm Sound level LA3m 63 dB (A) Mass 42 kg
Repair switch for VRE 250(Optional)	mounted, 3-pole with auxiliary contact, explosion-proof
Vrb 100/721w2900 Pps 400v	
Vre 250/731-L-14-Pps	
Vre 100/731-L-11-Pps	
Dn 90 Mm With Lf 230-S Pps	
Vre200/733w2900	
Vre 315/733w1450	
Impeller Vre 250/731-L-14-Pps	
Siemens B 5 Ip 55	
Motor 0,18 Kw 1060 Siemens B 5 Ip 55 With Fastenig Screws And Cup	
Motor 0,29 Kw 1200 Siemens Exde With Fatening Screws And Cup	
Impeller Vre 100/731-L-11-Pps	
Siemens B5 Ip 55	

Ürün	Açıklama
Vre 250/731-L-19-Pps	
Vre 160 / 734 W 1450	
Impeller Vre 160/731-L-19-Pps-X	
Vre 500/731w1740-Ts-Gds-Ts-090r-Pps/ Cfk	
Dn 75 Mm Manuell Pps	
Motor 0,12 Kw 1740 Siemens B5 Ip55 With Fastening Screw And Cup	
Motor 0,75 Kw 1740 Siemens B5 Ip 55 With Fastening Screws And Cup	
Siemens B5 Ip55	
Impeller Vre 250/731-L-19-Pps	