Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Monitran

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Monitran Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Monitran Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
2285-2p-25	Accelerometer, fully isolated, 4-20mA = 0-25mm/s output, 1/4 - 28UNF female mounting, 2 pin MS connector
Mtn/Ca284	Connection cable from: 2-pin connector on: free ends Cable length: 5 m
MTN/1185C-25,	VIBRATION SENSOR AND QUCK COUPLING STUD
MTN/1100-25 Accelerometer	25mV/g output, 12V nominal bias, 2 Pin MS connector, 1/4" -28UNF female mounting
MTN/MS036	Stainless steel stud 12mm long 1/4"-28 UNF to M6
MTN/8006	Vibration Module Supply: 24 VDC Output signal: 4 - 20mA
MTN/1100C-25	accelerometer Sensitivity: 25 mV/g dynamic range: ±80g Frequency response: ±5% 2 to 10,000 Hz Temperature range: -55 to +140 °C electrical connection: cable, 5 m mech. Connection: 1/4" UNF female Weight: approx. 110 gr. IP protection class: IP67
MTN/8006TC	Temperature input: 10 mV/°C Signal: 4/20mA
MTN/2285C-25-	Range: 0 - 25 mm/s Signal: 4 - 20 mA Mounting: thread 1/4-28 UNF female

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Cable length: 5 m
MTN/1185CM8-25	speed sensor Measuring range: 0 - 25 mm/s rms Supply: 12 - 32 VDC Signal: 4-20mA electrical connection: cable, 5 m mech. Connection: external thread M8
MTN/1185CQ-25	Accelerometer, 4-20mA = 0-25mm/s output, quickfit female mounting, 5 metres o/b ETFE cable.
MTN/2285CM6-20	Measuring range: 0-20mm/s RMS Supply: 12 - 32 VDC Signal: 4-20mA mech. Connection: thread M6 electrical connection: cable, 5 m
MTN/VM330D	Kit including cable MTN/CA476
MTN/1185C-50	speed sensor Measuring range: 0 - 50 mm/s rms Supply: 12 - 32 VDC Signal: 4-20mA electrical connection: cable, 5 m mech. Connection: internal thread 1/4" UNF
MTN/1185C-xx	Measuring range (xx): 10, 20, 25, 50 OR 100 mm/sec RMS Supply: 12 - 32 VDC Signal: 4-20mA electrical connection: cable, 5 m mech. Connection: internal thread 1/4" UNF
MT N / 1185C	
MTN/1185C-25	Measuring range: 0 - 25 mm/s rms Supply: 12 - 32 VDC Signal: 4-20mA electrical connection: cable, 5 m mech. Connection: internal thread 1/4" UNF
MTN/MS067	thread adapter External thread 1/4" UNF on: external thread M8
IEIRGW075	Industrial series LVDT, radial exit, ±75mm stroke, 14-24V input, 4-20mA output (20mA fully in), guided core & extension, M6 stainless steel rod end bearings, rod wiper, IP68, 2 METRES 3 core black PU cable

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
MTN/1185C-25	Measuring range: 0 - 25 mm/s rms Supply: 12 - 32 VDC Signal: 4-20mA electrical connection: cable, 5 m mech. Connection: internal thread 1/4" UNF
MTN/1185ICQ-25	Measuring range: 25mm/sec RMS Supply: 12 - 32 VDC Signal: 4-20mA Electrical connection: PTFE cable, 5 m mech. Connection: Quick-Fit internal thread Weight: about 150 grams
MTN/M2285IC-4P	
MTN/1185CQ-20	piezoel. Speed sensor Power supply: 12 - 32 VDC Signal: 4 - 20mA El. connection: PTFE cable, 5 m mech. Connection: internal thread Quick-Fit
MTN/MS002	Thread adapter from: External thread Quick-Fit on: external thread M8
MTN/1185W-25	Submersible Accelerometer, 4-20mA = 0-25mm/s output, 1/4"-28UNF female mounting, 5 metres waterproof PU cable
MTN/MS002	External thread Quick Fit External thread M8
MTN/8006	Vibration modul iinput 24VDC 4-20ma
0020108237	EO00200255 SENSING; VIBRATION; MERCURY CONTACT
MTN/1185CQ-25	Measuring range: 25 mm/sec RMS Power supply: 12 - 32 VDC Signal: 4 - 20mA El. connection: PTFE cable, 5 m mech. Connection: internal thread Quick-Fit
MTN/1185C-25/309	speed sensor Measuring range: 0 - 25 mm/s rms Power supply: 12 - 32 VDC Signal: 4 - 20mA El. connection: cable, 5 m mech. Connection: internal thread 1/4" UNF fully isolated can titreşim sensörü Titreşim sensörü (M8 Saplaması ile birlikte)

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
MTN/1185C-25.	Accelerometer, 4-20mA = 0-25mm/s output, 1/4" - 28UNF female mounting, o/b ETFE cable. 5 METRES
MTN/1185-25	Accelerometer, 4-20mA = 0-25mm/s output, 1/4" - 28UNF female mounting, 3 pin 62GB connector
MTN/CA137-1185	Cable Assembly for use with 1185 connector version accelerometers, o/b twin core ETFE cable, 3 Pin 62GB socket to free ends, 5 METRES
MTN/CA137	Connection cable for: MTN/1185 Cable length: 5 m
1185C-25/309	Vibration sensor Measuring range: 0 - 10 mm/s rms Power supply: 12 - 32 VDC Signal: 4 - 20 mA Electrical connection: Cable, 5 m Mechanical connection: 1/4" UNF internal thread fully isolated can
MTN/1185C-xx	Measuring range (xx): 10, 20, 25, 50 OR 100 mm/sec RMS Power supply: 12 - 32 VDC Signal: 4 - 20 mA El. connection: PTFE cable, 5 m Mechanical connection: Internal thread 1/4" UNF
MTN/1185C-25	Measuring range: 0 - 25 mm/s rms Power supply: 12 - 32 VDC Signal: 4 - 20 mA El. connection: Cable, 5 m Mech. connection: Internal thread 1/4" UNF
MTN/1185CQ-50	Measuring range: 50 mm/sec RMS Power supply: 12 - 32 VDC Signal: 4 - 20 mA El. connection: PTFE cable, 5 m Mechanical connection: Quick-Fit internal thread Tariff number: 9031 8080 (Not dual use)
MTN/1185-25 With socket	
MTN/1185-3P-25	Accelerometer, 4-20mA = 0-25mm/s output, 1/4" - 28UNF female mounting, 3 pin 62GB connector.
MTN/MH008 62GB	connector 3 pin socket
MTN/1185C-25/309.	WITH VIBRATION SENSOR AND M8 STUD
1185C-25 SN:686800	Vibration Sensor

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
MTN/1185IC-25	Measuring range: 25 mm/sec RMS Power supply: 12 - 32 VDC Signal: 4 - 20 mA Electrical connection: PTFE cable, 5 m mechanical connection: internal thread ¼” UNF Weight (nom): 150 grams
MTN/2285I-2PM8-10	Measuring range: 0 - 10 mm/s rms Power supply: 12 - 32 VDC Signal: 4 - 20 mA Electrical connection: MS connector 2-pin mechanical connection: external thread M8
MTN/2285-2P-??	Accelerometer, fully isolated, 4-20mA = 0-??mm/s output, 1/4" -28UNF female mounting, 2 pin MS connector. Made in Stainless Steel SS303.
MTN/1185ICM-40	ATEX & IECEx Certified Group II Intrinsically Safe Accelerometer to Ex ia IIC T6, 0-40mm/s = 4-20mA output, M10 male mounting, o/b twin core ETFE cable. 5 metres
MTN/1185IC-25	Piezoelectric speed sensor Measuring range: 25 mm/sec RMS Power supply: 12 - 32 VDC Signal: 4 - 20 mA Electrical connection: PTFE cable, 5 m Mechanical connection: ¼” UNF internal thread Weight (nominal): 150 grams
MTN/1185CM8 4-20MA 0-25MM/S	Turbo blower vibration sensor
MTN/2285STC-50	Measuring range: 50 mm/s RMS Cable length: 5 m
MTN/1100C-xx	Sensitivity: xx mV/g Dynamic range: ±80 g Frequency response: ±5% 2 to 10,000 Hz Temperature range: -55 to +140 °C Electrical connection: Cable, 5 m Mechanical connection: 1/4" UNF Female Weight: approx. 110 g. IP protection class: IP67
MTN/1185IC-50	Piezoelectric speed sensor Measuring range: 50 mm/sec RMS Power supply: 12 - 32 VDC Signal: 4 - 20 mA Electrical connection: PTFE cable, 5 m Mechanical connection: ¼” UNF internal thread Weight (nominal): 150 grams

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
MTN/1185IC-25	Piezoelectric speed sensor Measuring range: 25 mm/sec RMS Power supply: 12 - 32 VDC Signal: 4 - 20 mA Electrical connection: PTFE cable, 5 m Mechanical connection: ¼” UNF internal thread Weight (nominal): 150 grams
Mtn/2285c-25	
Mtn/2287ic	
Mtn/1181c	
Mtn/2200s-2p	
Mtn/2287i-4p	
Mtn/2287iw	
Mtn/1185c (5m) Sensors	Accelerometer, 4-20mA = 0-25mm/s output, 1/4" - 28UNF female mounting, o/b ETFE cable 5 metres.
Mtn/3014	
Mtn/2287c	
Mtn/1186c	
Mp050a321-161	
Mtn/3016	
Mtn/Ms062	
Mtn/9004-Hd	
Ms002 M8 Male	
Mtn/3025	
Mtn/1188w	
Mtn/He1-581061	
Mtn/2285tc	
Mtn/Mh001	
Id/Mtn-1185-50	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Mtn/2285itc	
Mtn/2285iw	
Mtn/1100c	
Mtn/3040	
Mtn/2285-2p	
Mtn/2200-2p	
Mtn/2200itc	
Mtn/3010	
Mtn/Vm110-581001	
Mtn/2285s-2p	
Kit	
Mtn/1185hcq-10	
Mtn/Ms 067	
Mtn/9006-Hd	
Mtn/2287s-2p	
Mtn/Mm1-581042	
Mtn/3018	
Mtn/Ca476	Cable Assembly 4 pin cable only suitable for MTN/2100-HP probe
Mtn/1100stw	
Mtn/3004	
Mtn/1186q-10	
Mtn/2200is-2p	
Vm110	VIBRATION METER, VELOCITY RATE:2000MM/S, DISPLACEMENT MAX:2000 M, ACCURACY %:1.5%, SVHC:NO SVHC (19-DEC-2011)
Mtn/9007-Hd	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Mtn/9008-Hd	
Mtn/9005-Hd	
Mtn/3012	
1120ihcf1/4	
Mtn/2287s	
Mtn/1185-50	
Mtn/3064	
Mtn/2285i-4p	
Mtn/2285ic	
Mtn/2287w	
Mtn/8066	
Mtn/3006	
Mtn/2200i-2p	
Mtn/2287-2p	
Mtn/Ms003	
Mtn/2200it-4p	
Mtn/9010-Hd	
Mtn/9011-Hd	
Mtn 8066	
Mtn/9003-Hd	
MTN/2285STC	cable length 5m
Mtn/2287sc	
Mtn/2287i	
Mtn/2285s-4p	
Mtn/2285sc	
Mtn/Ms067	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Mtn/2287	
Mtn/2285i-2p	
Mtn/Ms001	
Mtn/2287-4p	
Mtn/Ps2-581052	
Mtn/1188	
Mtn/2285c	
Mtn/Ms006	
Mtn/9002-Hd	
Mtn/3008	
Mtn/9009-Hd	
Mtn/1188c	
Mtn/2287s-4p	
83640	
Mtn/1186w	
Mtn/1188q-1	
Mtn/2100-581031	
Mtn/2285w	
Mtn/2285-4p	
Mtn/Vm110	VIBRATION METER LCD 31/2DIGIT 5-20KHZ 200MVAC/DC
Mtn/2287i-2p	
Mtn/3020	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.