

Monitran



Garanti: 12 ay
 Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Monitran** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Monitran T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
2285-2p-25	Accelerometer, fully isolated, 4- 20mA = 0-25mm/s output, 1/4 - 28UNF female mounting, 2 pin MS connector
Mtn/Ca284	Connection cable from: 2-pin connector on: free ends Cable length: 5 m
MTN/1185C-25.	VIBRATION SENSOR AND QUICK COUPLING STUD
MTN/1100-25 Accelerometer	25mV/g output, 12V nominal bias, 2 Pin MS connector, 1/4" -28UNF female mounting
MTN/MS036	Stainless steel stud 12mm long 1/4"-28 UNF to M6
MTN/8006	Vibration Module Supply: 24 VDC Output signal: 4 - 20mA
MTN/1100C-25	accelerometer Sensitivity: 25 mV/g dynamic range: ±80g Frequency response: ±5% 2 to 10,000 Hz Temperature range: -55 to +140 ¼C electrical connection: cable, 5 m mech. Connection: 1/4" UNF female Weight: approx. 110 gr. IP protection class: IP67
MTN/8006TC	Temperature input: 10 mV/¼C Signal: 4/20mA
MTN/2285C-25	Accelerometer, Fully isolated, 4-20mA = 0-25mm/s output, 1/4 -28 UNF female mounting, Frequency response 2Hz- 1KHz, 5 metres o/b ETFE cable
MTN/1185CM8-25	speed sensor Measuring range: 0 - 25 mm/s rms Supply: 12 - 32 VDC Signal: 4-20mA electrical connection: cable, 5 m mech. Connection: external thread M8
MTN/1185CQ-25	Accelerometer, 4-20mA = 0-25mm/s output, quickfit female mounting, 5

	metres o/b ETFE cable.
MTN/2285CM6-20	Measuring range: 0-20mm/s RMS Supply: 12 - 32 VDC Signal: 4-20mA mech. Connection: thread M6 electrical connection: cable, 5 m
MTN/VM330D	Kit including cable MTN/CA476
MTN/1185C-50	speed sensor Measuring range: 0 - 50 mm/s rms Supply: 12 - 32 VDC Signal: 4-20mA electrical connection: cable, 5 m mech. Connection: internal thread 1/4" UNF
MTN/1185C-xx	Measuring range (xx): 10, 20, 25, 50 OR 100 mm/sec RMS Supply: 12 - 32 VDC Signal: 4-20mA electrical connection: cable, 5 m mech. Connection: internal thread 1/4" UNF
MT N / 1185C	
MTN/1185C-25	Measuring range: 0 - 25 mm/s rms Supply: 12 - 32 VDC Signal: 4-20mA electrical connection: cable, 5 m mech. Connection: internal thread 1/4" UNF
MTN/MS067	thread adapter External thread 1/4" UNF on: external thread M8
IEIRGW075	Industrial series LVDT, radial exit, ±75mm stroke, 14-24V input, 4-20mA output (20mA fully in), guided core & extension, M6 stainless steel rod end bearings, rod wiper, IP68, 2 METRES 3 core black PU cable
MTN/1185C-25	Measuring range: 0 - 25 mm/s rms Supply: 12 - 32 VDC Signal: 4-20mA electrical connection: cable, 5 m mech. Connection: internal thread 1/4" UNF
MTN/1185ICQ-25	Measuring range: 25mm/sec RMS Supply: 12 - 32 VDC Signal: 4-20mA Electrical connection: PTFE cable, 5 m mech. Connection: Quick-Fit internal thread Weight: about 150 grams
MTN/M2285IC-4P	
MTN/1185CQ-20	piezoel. Speed sensor Power supply: 12 - 32 VDC Signal: 4 - 20mA El. connection: PTFE cable, 5 m mech. Connection: internal thread Quick-Fit
MTN/MS002	Thread adapter from: External thread Quick-Fit on: external thread M8
MTN/1185W-25	Submersible Accelerometer, 4-20mA = 0-25mm/s output, 1/4"-28UNF female mounting, 5 metres waterproof PU cable
MTN/MS002	External thread Quick Fit External thread M8
MTN/8006	Vibration modul iinput 24VDC 4-20ma
0020108237	EO00200255 SENSING; VIBRATION; MERCURY CONTACT
MTN/1185CQ-25	Measuring range: 25 mm/sec RMS Power supply: 12 - 32 VDC Signal: 4 - 20mA El. connection: PTFE cable, 5 m mech. Connection: internal thread Quick-Fit
MTN/1185C-25/309	speed sensor Measuring range: 0 - 25 mm/s rms Power supply: 12 - 32 VDC Signal: 4 - 20mA El. connection: cable, 5 m mech. Connection: internal thread 1/4" UNF fully isolated can titreŐim sensr
MTN/1185C-25.	Accelerometer, 4-20mA = 0-25mm/s output, 1/4" - 28UNF female mounting, o/b ETFE cable. 5 METRES
MTN/1185-25	Accelerometer, 4-20mA = 0-25mm/s output, 1/4" - 28UNF female mounting, 3 pin 62GB connector
MTN/CA137-1185	Cable Assembly for use with 1185 connector version accelerometers, o/b twin core ETFE cable, 3 Pin 62GB socket to free ends, 5 METRES
MTN/CA137	Connection cable for: MTN/1185 Cable length: 5 m
1185C-25/309	

MTN/1185C-xx	Measuring range (xx): 10, 20, 25, 50 OR 100 mm/sec RMS Power supply: 12 - 32 VDC Signal: 4 - 20 mA El. connection: PTFE cable, 5 m Mechanical connection: Internal thread 1/4" UNF
MTN/1185C-25	Measuring range: 0 - 25 mm/s rms Power supply: 12 - 32 VDC Signal: 4 - 20 mA El. connection: Cable, 5 m Mech. connection: Internal thread 1/4" UNF
MTN/1185CQ-50	Measuring range: 50 mm/sec RMS Power supply: 12 - 32 VDC Signal: 4 - 20 mA El. connection: PTFE cable, 5 m Mechanical connection: Quick-Fit internal thread Tariff number: 9031 8080 (Not dual use)
MTN/1185-25 With socket	
MTN/1185-3P-25	Accelerometer, 4-20mA = 0-25mm/s output, 1/4" - 28UNF female mounting, 3 pin 62GB connector.
MTN/MH008 62GB	connector 3 pin socket
MTN/1185C-25/309.	WITH VIBRATION SENSOR AND M8 STUD
1185C-25 SN:686800	Vibration Sensor
MTN/1185IC-25	Measuring range: 25 mm/sec RMS Power supply: 12 - 32 VDC Signal: 4 - 20 mA Electrical connection: PTFE cable, 5 m mechanical connection: internal thread 1/4" UNF Weight (nom): 150 grams
MTN/2285I-2PM8-10	Measuring range: 0 - 10 mm/s rms Power supply: 12 - 32 VDC Signal: 4 - 20 mA Electrical connection: MS connector 2-pin mechanical connection: external thread M8
MTN/2285-2P-??	Accelerometer, fully isolated, 4-20mA = 0-??mm/s output, 1/4" -28UNF female mounting, 2 pin MS connector. Made in Stainless Steel SS303.
MTN/1185ICM-40	ATEX & IECEx Certified Group II Intrinsically Safe Accelerometer to Ex ia IIC T6, 0-40mm/s = 4-20mA output, M10 male mounting, o/b twin core ETFE cable. 5 metres
MTN/1185IC-25	Piezoelectric speed sensor Measuring range: 25 mm/sec RMS Power supply: 12 - 32 VDC Signal: 4 - 20 mA Electrical connection: PTFE cable, 5 m Mechanical connection: 1/4" UNF internal thread Weight (nominal): 150 grams
MTN/1185CM8 4-20MA 0-25MM/S	Turbo blower vibration sensor
MTN/2285STC-50	Measuring range: 50 mm/s RMS Cable length: 5 m
MTN/1100C-xx	Sensitivity: xx mV/g Dynamic range: ±80 g Frequency response: ±5% 2 to 10,000 Hz Temperature range: -55 to +140 °C Electrical connection: Cable, 5 m Mechanical connection: 1/4" UNF Female Weight: approx. 110 g. IP protection class: IP67
MTN/1185IC-50	Piezoelectric speed sensor Measuring range: 50 mm/sec RMS Power supply: 12 - 32 VDC Signal: 4 - 20 mA Electrical connection: PTFE cable, 5 m Mechanical connection: 1/4" UNF internal thread Weight (nominal): 150 grams
MTN/1185IC-25	Piezoelectric speed sensor Measuring range: 25 mm/sec RMS Power supply: 12 - 32 VDC Signal: 4 - 20 mA Electrical connection: PTFE cable, 5 m Mechanical connection: 1/4" UNF internal thread Weight (nominal): 150 grams
Mtn/2285c-25	
Mtn/2287ic	
Mtn/1181c	
Mtn/2200s-2p	

Mtn/2287i-4p	
Mtn/2287iw	
Mtn/1185c (5m) Sensors	Accelerometer, 4-20mA = 0-25mm/s output, 1/4" - 28UNF female mounting, o/b ETFE cable 5 metres.
Mtn/3014	
Mtn/2287c	
Mtn/1186c	
Mp050a321-161	
Mtn/3016	
Mtn/Ms062	
Mtn/9004-Hd	
Ms002 M8 Male	
Mtn/3025	
Mtn/1188w	
Mtn/He1-581061	
Mtn/2285tc	
Mtn/Mh001	
Id/Mtn-1185-50	
Mtn/2285itc	
Mtn/2285iw	
Mtn/1100c	
Mtn/3040	
Mtn/2285-2p	
Mtn/2200-2p	
Mtn/2200itc	
Mtn/3010	
Mtn/Vm110-581001	
Mtn/2285s-2p	
Kit	
Mtn/1185hcq-10	
Mtn/Ms 067	
Mtn/9006-Hd	
Mtn/2287s-2p	
Mtn/Mm1-581042	
Mtn/3018	
Mtn/Ca476	Cable Assembly 4 pin cable only suitable for MTN/2100-HP probe

Mtn/1100stw	
Mtn/3004	
Mtn/1186q-10	
Mtn/2200is-2p	
Vm110	VIBRATION METER, VELOCITY RATE:2000MM/S, DISPLACEMENT MAX:2000 M, ACCURACY %:1.5%, SVHC:NO SVHC (19-DEC-2011)
Mtn/9007-Hd	
Mtn/9008-Hd	
Mtn/9005-Hd	
Mtn/3012	
1120ihcf1/4	
Mtn/2287s	
Mtn/1185-50	
Mtn/3064	
Mtn/2285i-4p	
Mtn/2285ic	
Mtn/2287w	
Mtn/8066	
Mtn/3006	
Mtn/2200i-2p	
Mtn/2287-2p	
Mtn/Ms003	
Mtn/2200it-4p	
Mtn/9010-Hd	
Mtn/9011-Hd	
Mtn 8066	
Mtn/9003-Hd	
MTN/2285STC	cable length 5m
Mtn/2287sc	
Mtn/2287i	
Mtn/2285s-4p	
Mtn/2285sc	
Mtn/Ms067	
Mtn/2287	
Mtn/2285i-2p	
Mtn/Ms001	

Mtn/2287-4p	
Mtn/Ps2-581052	
Mtn/1188	
Mtn/2285c	
Mtn/Ms006	
Mtn/9002-Hd	
Mtn/3008	
Mtn/9009-Hd	
Mtn/1188c	
Mtn/2287s-4p	
83640	
Mtn/1186w	
Mtn/1188q-1	
Mtn/2100-581031	
Mtn/2285w	
Mtn/2285-4p	
Mtn/Vm110	VIBRATION METER LCD 31/2DIGIT 5-20KHZ 200MVAC/DC
Mtn/2287i-2p	
Mtn/3020	