

Mors Smitt



Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Mors Smitt** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Mors Smitt T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
D-U201-Lw013	
D-U201-Lw022	
Tddb-U201 3...30s	TIMING RELAY
V29 Socket	V29 socket: spring clamp terminal, wall / rail mount
D-U201-L	Relay D-U200: 24 VDC, 4CO, 250V/10A, LED coil indicator
Tdb4-U201 0-120 Min	Timing relay: Delay-on, 24V DC, 10 A, 4 C/O
Tdbe4-U201 0 - 30 Min / 0 - 30 Min	Timing relay: Delay-on/off, 24V DC, 10 A, 1NC 3 C/O
Mtdv4-U201	Timing relay voltage monitoring: Delay-on/off, 24V DC, 10 A, 4 C/O

1806st	1.1. The overcurrent relay will be suitable for use inside the locomotive. 1.2. The nominal voltage of the primary circuit will be 1500 VAC, 50 Hz (maximum 1800 VAC). 1.3. The nominal current value of the primary circuit will be 800 A, 50 Hz. 1.4. The maximum current value will be 4000 A (100 ms). 1.5. Message receiving time will be less than 300 ms at 1200 A. 1.6. Receiving messages 1000 A ($\pm 10\%$) 1.7. The drop will be less than 700 A. 1.8. There will be 1 NC (normally closed) and 1 NO (normally open) contact. 1.9. The rated voltage of the contacts will be 110 VDC (77 VDC - 137.5 VDC). 1:10. Contact values will be 0.3 ADC, 90 VDC and L / R = 40 ms.
D-U204L	
V23 socket	
type KDN	Relay, type KDN (coil voltage to be specified) Part number: to be confirmed
BISTABLE RELAY	KDN relays, latching, 8 C/O, 10A 110VDC 24 VDC = 270 piece 125 VDC = 270 piece 220 VDC = 250 piece IP20 Socket
Typ KDN 110VDC	
Typ KDN 125VDC	
D-BR4 110VDC	330214191
D-B 110VDC	330219806
D 220-230V 50Hz	330219757
ERT-S	
V93	socket V93. Rail Din for KDN.
see List	
D-BR4 110VDC	330214191
D-B 110VDC	330219806
V23 socket - Screw terminal	338000580
D 220-230V 50Hz	330219757
KDN-U201-DE 24VDC	617560006
RMS4M200-09	RMS TEST SOCKET 4M200-09
330213818 D-U201-L 24VDC	
D-U203-CL, 72B, 8A	
V29-D	
CU-U203-B, 72B, 8A	
V17-D	
CU-U201-B, 24B, 8A	

B 400 115 EG S V F X8 + EA103-BFD	
SPO 1M4-8L110S4	(Brand Faiveley) Changeover Switch
1806 ST Relay	
330213811 D-U204-L 110VDC	
TA/VA400/T1	
TDDB-U201-C	0.1-1s 24 VDC
631900355 MCB GR1-610-14-B-A1-2-1-22-2	
D-U200	
330213811 D-U204-L 110VDC	
338000580 V23 socket - Screw terminal	
330213812 D-U201-LT 24VDC	
D-U204	+ with socket (110VDC)
D-U204N-Lr	
V23 socket	
V23BR	338000402 screw base rail D
617500004 CU-U201-G 24VDC	
617500003 CU-U206-G 12VDC	
338001501 V16-D socket	
TDE4N-UN	IT WILL BE 24VDC 16AMP SINGLE CONTACT PIN SOCKET WILL BE INCLUDED
Q43PF0059	N.S1-L-24-12.0.8
Q43ARC002	N.S1-PFC-12-C
617500027 CP-U201-G 24VDC	
KDN-U201	Redundancy Change over Relay (L+R) with base: on-board
DU-201	on-board Safety-Relais
D-U303	on-board Safety-Relais
Redundancy Change over Relay (L+R)	with base: KDN-U201
330214027 D-U204-W013 110VDC code AV	
338000418 V23 code AV	
380V - 40A IEC 60077-4 RMT3	

110V - 6A IEC 60077-4 RMT3	
110V - 10A IEC 60077-4 RMT3	
110V - 16A IEC 60077-4 RMT3	
110V - 2.5A IEC 60077-4 RMT3	
D-204L 110VDC 10A	
Relay CU-U204-B	
Relay D-U204-Q	
Relay B400 115 EG SVF	
Relay D-U307-KLC	
Timer relay TDE4-U204-C 1-10S	
Timer relay TDB4-U204-C 1-10S	
Voltage relay MTDV4-U204-KC	
Timer relay TDE4-U204-C 10-100S	
CR3-620, CR3-610, CR3-660	
71.14.006.0013	1806 ST
Faiveley SPO 1M4-8L110S4	
B400-115-EG-SVF-X8	
EA103-BFD	
D U204-L 110VDC	10A
V23BR-	
1806 ST	
CU-U203-B, 72B, 8A	
CU-U201-B, 24B, 8A	
Faiveley – SPO 1M4-8L110S4	
FAIVELEY	SPO 1M4-8L110S4
CU-U206-G	
V16-D	
TTBCA 400 72 AG F 1	RELAY MKNK 4C/O 72VDC TDL MST WELD-NT
D-U307-Ekl	
24v Dc	
338000610 V29	

338001401 V170d
1431
D3v144s-B2I
626 005 032
D3v144s-B
631900105 Gr2-620-12-B-S1-2-1-2a-2/ 20a Short
603.020.321
D-U204-QI 110 Vdc
Umd-81-Mtdv4-U204-Kc 0,5s/05s 84/90 Vdc
330213788
C0361104b
631900092 Gr2-420-56-B-S1-2-1-2a-2/ 2a Long
617560004
338 001 401 Type:V17-D 228111892
330213897 D-U204 Ck
338000610 Type V29
I1-L-U024r
330219873
326001016
338000580
V21 - 338000200
603.020.017 Type:D3v96s
L2-L-D125
338001402
000906642
338 000 610 Type:V29 228111304
330219802
326001011
Cu-U204-B 110 Vdc
Ea-111-Af

5633 934-12
338000610as
631900101 Gr2-440-12-B-S1-2-1-2a-2/ 4a Short
Ddh96s Esc. 60-0-500
Vm-3r
1491 St
V29-W013
Ea103egbfd
V23(Soket)
Acd-U204 Dmrc,V23
631900100 Gr2-420-12-B-S1-2-1-2a-2/ 2a Short
330 213 751
326001015
626000303 228110048 Erta1 4,5mtr Black
Ar1-420-14-Bs1-0-1-1-2
Ar1-410-14-B-S-1-0-1-1-2
892870 (Tf-21 8a)
D3v96s (603.011.126)
D8--U204-Lq (110 Vdc)
330214133 D-U201-Ckl W022
626000304 228110049 Erta2 4,5mtr Green
626000593 Ni L204
D-Ra-125vdc
326001010
631900103 Gr2-610-12-B-S1-2-1-2a-2/ 10a Short
330214127 D-U201 Ck
338000610av
631900102 Gr2-460-12-B-S1-2-1-2a-2/ 6a Short

D-U201-Lm-W013	
Tdb4-U204 1-10s	
626000306 228110051 Erta4 20mtr Blue	
631900096 Gr2-616-56-B-S1-2-1-2a-2/ 16a Long	
20 Slot Female Connector For Relays	
D-U204-Cw013	
617.500.026	
Cu-U201-Ge 24vdc	
Ert-S	
626000348 Ert-S Nieaf-Smitt/Eng	
338001400	
Mors Smith Sc 044 110 5 G With Socket (Cor Nj X*)	SC RELAY: SC 044 110 5 G(4 N/C+4 N/O 110 VDC double coil latching relay) with socket (Alkyde compound)with locking spring (153879) COR NJ X* (Latching set reset relay (4NO+4NC) with double 110v dc coils complete with relay socket) with locking spring,SCHNEIDER
Am 400 24 Agz Sc	
631900095 Gr2-610-56-B-S1-2-1-2a-2/ 10a Long	
338001401	
631900094 Gr2-460-56-B-S1-2-1-2a-2/ 6a Long	
V610-Bjbc-105/121-Bd2	
D-U204-Q 110 Vdc	
B-400-115egsvf1	
330213746	
626000257	
A-400-110-Sv-Scv	
Bd-U204c	
626000305 228110050 Erta3 15mtr Red	
Vm-4r 321000519	