



Motortronics

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Motortronics Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Motortronics Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Motortronics	
Motortronics	
Vmx-S-112-Cx-1d	VMX-C SHUNT RATED WITH DEADFRONT, 208 V, 112 A, 30 HP
11-191-301	
Xld-414-N-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 414A, CONTROL POWER: 240V, NEMA 1
Vmx-S-450-Cb-4	VMX-S (CONFIGURED), NEMA 12/4, 480V, 350HP, 450A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Me2201m1f	
Xld-862-E-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 862A, CONTROL POWER: 240V, NEMA 12
Vmx-S-480-Cx-2d	VMX-C SHUNT RATED WITH DEADFRONT, 230 V, 480 A, 200 HP

Dxt-92-600-N	
Vmx-S-450-Cb-5d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 400HP, 450A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Me2-101-M-Din	
Vmx-H-800-Cb-5	VMX-H (CONFIGURED), NEMA 12/4, 575V, 600HP, 800A, 1200A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 92H X 36W X 30D
Dxt-476-600-E	
Vmx-H-600-Cb-1d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 208V, 150HP, 600A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Vmx-S-550-Cx-4d	VMX-C SHUNT RATED WITH DEADFRONT, 460 V, 550 A, 450 HP
Xld-862-N	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 862A, CONTROL POWER: 120V, NEMA 1
Xld-550-600-N-240	600 V, NEMA 1, 550 A, 240 VAC CONTROL POWER
Mvc3-110600-E-Swg	
Vmx-S-361-Cb-1	VMX-S (CONFIGURED), NEMA 12/4, 208V, 125HP, 361A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Vmx-S-92-Cb-1d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 208V, 30HP, 92A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
Vmx-S-900-Cx2	VMX-C SHUNT RATED, 230 V, 900 A, 350 HP
11-8-RI-801	
52002500600c	
Ptg5-2-110-602cc	
Xld-550-N	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 550A, CONTROL POWER: 120V, NEMA 1
Bxld-360-E-240	
Abc-10-480-P	
11-197-202	
Vmx-S-480-Cb-1	VMX-S (CONFIGURED), NEMA 12/4, 208V, 150HP, 480A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
11-7sft-101	

Xld-1150-N	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1150A, CONTROL POWER: 120V, NEMA 1
Vmx-H-800-Cb-1	VMX-H (CONFIGURED), NEMA 12/4, 208V, 800A, 1200A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 92H X 36W X 30D
Xld-1006-N-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1006A, CONTROL POWER: 240V, NEMA 1
Csd-401-N	
34-630-3-7200c	
Vmx-Kp-Cpu-112	
Vmx-S-92-Cx5	
Vmx-H-80-Cx-2d	
11-780-601	
Vmx-S-550-Cx2	VMX-C SHUNT RATED, 230 V, 550 A, 200 HP
Vmx-S-361-Cb-2	VMX-S (CONFIGURED), NEMA 12/4, 240V, 125HP, 361A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Bxld-414-E	
Vmx-S-150-Cx1	VMX-C SHUNT RATED, 208 V, 150 A, 40 HP
344003712000	
Vmx-S-210-Cb-1d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 208V, 60HP, 210A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSI
Vmx-H-45-Cb-1d	VMX-C FULL RATED WITH DEADFRONT, CIRCUIT BREAKER, 208 V, 45 A, 10 HP
Vmx-H-156-Cb-5d	
Bxld-78-600-N-240	
11-2drl-750	
PtW3-1-60-482	
Xld-414-E-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 414A, CONTROL POWER: 240V, NEMA 12
Mwh-50-P-575	
Cpt3-60-2-4800-6	
Vmx-H-125-Cx1	
Vmx-H-68-Cx-4d	VMX-C FULL RATED WITH DEADFRONT, 460 V, 68 A, 50 HP

Mvc3-Stk41600p	
Dxt-718-460-E	
Xld-288-P	288A STARTER
Bxld-550-N	
Xld-862-600-N-240	600 V, NEMA 1, 862 A, 240 VAC CONTROL POWER
Vmx-S-450-Cx4	VMX-C SHUNT RATED, 460 V, 450 A, 350 HP
11-7asft-750	
Xld-150-N	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 150A, CONTROL POWER: 120V, NEMA 1
Kp1-430-E	
Vmx-S-160-Cb-2d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 240V, 60HP, 160A, 225A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSI
Ptw5-1-110-722	
Bdxt-862-230-N	
Vmx-H-21-Fs-4	
Lcb3003lcl3003	
Xld-718-N-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 718A, CONTROL POWER: 240V, NEMA 1
Xld-1250-600-N	600 V, NEMA 1, 1250 A, 120 VAC CONTROL POWER
Vmx-H-690-Cb-1	VMX-H (CONFIGURED), NEMA 12/4, 208V, 250HP, 690A, 1200A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 92H X 36W X 30D
Vmx-S-305-Cb-2d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 240V, 125HP, 305A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
25-0400-6500-23	
Vmx-H-480-Cx5	VMX-C FULL RATED, 575 V, 480 A, 350-500 HP
Vmx-112-Bp-E	
Vmx-S-150-Cb-1	VMX-S (CONFIGURED), NEMA 12/4, 208V, 40HP, 150A, 225A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 37H X 1
Vmx-S-480-Cb-5d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 500HP, 480A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED),

	DIMENS
Vmx-S-275-Cb-1	VMX-S (CONFIGURED), NEMA 12/4, 208V, 75HP, 275A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X 3
Lcb10024	
Vmx-S-862-Cx4	VMX-C SHUNT RATED, 460 V, 862 A, 600 HP
Xld-1250-600-P	600 V, PANEL, 1250 A, 120 VAC CONTROL POWER
Bdxt-62-600-E	
11-76rl-401	
Xld-48-E	
Vmx-H-45-Cb5	
Ss1-48025-Pb	
Vmx-S-112-Cx4	VMX-C SHUNT RATED, 460 V, 112 A, 75 HP
Xld-288-600-N-240	600 V, NEMA 1, 288 A, 240 VAC CONTROL POWER
Xld-39-600-P-240	
Ls4-48300-P	SOFT START CONTROLLER
Vmx-H-156-Cb-1d	
Abc-100-400-E	
Vmx-H-800-Cx1	VMX-C FULL RATED, 208 V, 800 A, 250 HP
Vmx-H-125-Cx-1d	
11-197-801	
Mvc	
11-6rl-751	
Vmx-S-210-Cb-2d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 240V, 75HP, 210A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSI
Vmx-H-800-Cb-2	VMX-H (CONFIGURED), NEMA 12/4, 240V, 300HP, 800A, 1200A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 92H X 36W X 30D
Vmx-S-78-Cb-5	VMX-S (CONFIGURED), NEMA 12/4, 575V, 75HP, 78A, 100A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 37H X 15
11-66-500	
Vcm-485-Kit	

Bdxt-78-600-E	
11-7sht-162	
Vmx-S-480-Cb-5	VMX-S (CONFIGURED), NEMA 12/4, 575V, 500HP, 480A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Vmx-H-80-Cb-5d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 50HP, 80A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
Dxt-476-208-E	
Dxt-1006-460-N	
11-7asht-801	
Vmx-H-400-Cb-5	VMX-H (CONFIGURED), NEMA 12/4, 575V, 300HP, 400A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 48H X 33W X 16D
Xld-220-600-E	600 V, NEMA 12, 220 A, 120 VAC CONTROL POWER
Vmx-S-160-Cb-4d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 50HP, 78A, 100A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
Xld-180-E-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 92A, CONTROL POWER: 120V, NEMA 12
PtW3-1-60-662f	
Vmx-S-62-Cb-4	
Fdxt-39-230-E	
Vmx-S-862-Cb-2	VMX-S (CONFIGURED), NEMA 12/4, 240V, 300HP, 862A, 1200A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 92H X
Vmx-S-112-Cb-2d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 240V, 40HP, 112A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSI
Xld-1200-600-E	600 V, NEMA 12, 1200 A, 120 VAC CONTROL POWER
Vmx-H-96-Cx-2d	VMX-C FULL RATED WITH DEADFRONT, 230 V, 96 A, 30 HP
Bdxt-180-460-N	
Vmx-H-96-Cb-4	VMX-H (CONFIGURED), NEMA 12/4, 480V, 75HP, 96A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 37H X 15W X 12D
Vmx-H-800-Cx5	VMX-C FULL RATED, 575 V, 800 A, 600 HP
PtW3-1-60-552cs	

Vmx-H-480-Cx1	VMX-C FULL RATED, 208 V, 480 A, 150 HP
Xld-1006-600-P-240	600 V, PANEL, 1006 A, 240 VAC CONTROL POWER
Mvc3-41600-E	
Xld-220-600-N-240	600 V, NEMA 1, 220 A, 240 VAC CONTROL POWER
10-0081	
Vmx-H-55-Cb-4d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 30HP, 40A, 60A FS, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSION
Ptw5-2-110-1382	
11-5rl-301	
Vmx-S-39-Cb1	
Vmx-H-80-Cb-2	VMX-H (CONFIGURED), NEMA 12/4, 240V, 30HP, 80A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 37H X 15W X 12D
11-300-801	
Vmx-H-68-Cx-5d	VMX-C FULL RATED WITH DEADFRONT, 575 V, 68 A, 50 HP
Vmx-H-600-Cx2	VMX-C FULL RATED, 230 V, 600 A, 250 HP
Vmx-S-600-Cb-2d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 240V, 250HP, 600A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Vmx-H-55-Cb-2d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 240V, 25HP, 55A, 100A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
Abc-24-400-P	
11-785-151	
Xld-414-600-E-240	600 V, NEMA 12, 414 A, 240 VAC CONTROL POWER
Ptg3-1-60-332cs	
Vmx-S-305-Cx5	VMX-C SHUNT RATED, 575 V, 305 A, 300 HP
Bxld-150-600-E-240	
Xld-862-600-P-240	600 V, PANEL, 862 A, 240 VAC CONTROL POWER
Vmx-S-112-Cb-4	VMX-S (CONFIGURED), NEMA 12/4, 480V, 75HP, 112A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 37H X 1
Mt-Vw3a9202	
Bxld-62-600-E-240	

Vmx-S-361-Cx-5d	VMX-C SHUNT RATED WITH DEADFRONT, 575 V, 361 A, 350 HP
11-2-Sft-301	
Vmx-S-550-Cb-5d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 500HP, 550A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Xld-414-P-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 414A, CONTROL POWER: 240V, PANEL
Vmx-S-160-Cb-1	VMX-S (CONFIGURED), NEMA 12/4, 208V, 50HP, 160A, 225A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 37H X 1
11-194-401	
Vmx-S-361-Cx4	VMX-C SHUNT RATED, 460 V, 361 A, 300 HP
11-76sht-151	
PtW3-2-60-442	
Xld-180-600-E	600 V, NEMA 12, 180 A, 120 VAC CONTROL POWER
Xld-220-N	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 220A, CONTROL POWER: 120V, NEMA 1
Vmx-S-361-Cx2	VMX-C SHUNT RATED, 230 V, 361 A, 125 HP
Xld-1006-P	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1006A, CONTROL POWER: 120V, PANEL
Xld-288-N	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 288A, CONTROL POWER: 120V, NEMA 1
Xld-550-E	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 39A, CONTROL POWER: 240V, NEMA 12
11-785-301	
Xld-550-600-P-240	600 V, PANEL, 550 A, 240 VAC CONTROL POWER
Xld-1006-P-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1006A, CONTROL POWER: 240V, PANEL
Xld-718-600-E-240	600 V, NEMA 12, 718 A, 240 VAC CONTROL POWER
Vmx-H-312-Cx-2d	VMX-C FULL RATED WITH DEADFRONT, 230 V, 312 A, 125 HP
Xld-288-600-E-240	600 V, NEMA 12, 288 A, 240 VAC CONTROL POWER
Vmx-S-480-Cx-1d	VMX-C SHUNT RATED WITH DEADFRONT, 208 V, 480 A, 150 HP
Vmx-S-275-Cb-2d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 240V, 100HP, 275A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED),

	DIMENS
Xld-1200-E	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 120A, CONTROL POWER: 240V, NEMA 12
Vmx-H-600-Cb-1	VMX-H (CONFIGURED), NEMA 12/4, 208V, 200HP, 600A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 48H X 33W X 16D
Vmx-H-400-Cb-1	VMX-H (CONFIGURED), NEMA 12/4, 208V, 125HP, 400A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 48H X 33W X 16D
Mvc3-33500-E-Swg	
Vmx-78-Bp-N	
Xld-92-P	
Dxt-180-208-N	
36-0239	
Xld-476-600-N	600 V, NEMA 1, 476 A, 120 VAC CONTROL POWER
PtW5-2-110-722	
Vmx-S-450-Cx-2d	VMX-C SHUNT RATED WITH DEADFRONT, 230 V, 450 A, 150 HP
Vmx-H-690-Cx2	VMX-C FULL RATED, 230 V, 690 A, 250 HP
Vmx-S-450-Cx-4d	VMX-C SHUNT RATED WITH DEADFRONT, 460 V, 450 A, 350 HP
11-6sht-152	
11-19rl-601	
Vmx-S-305-Cx2	VMX-C SHUNT RATED, 230 V, 305 A, 125 HP
Vmx-H-68-Cb-1d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 208V, 25HP, 68A, 100A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
467-480	
11-7asft-801	
Xld-1250-N	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1250A, CONTROL POWER: 120V, NEMA 1
533e15500	
Vcm-203	
Vmx-S-62-Cb-5d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 50-60HP, 62A, 100A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMEN
11-76rl-801	

Vmx-H-68-Cb-5	VMX-H (CONFIGURED), NEMA 12/4, 575V, 50HP, 68A, 100A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 37H X 15W X 12D
52-18r-2400	
Vmx-H-248-Cx-2d	
Dxt-1200-460-P	
Vmx-H-690-Cx1	VMX-C FULL RATED, 208 V, 690 A, 250 HP
Vmx-H-960-Cx5	VMX-C FULL RATED, 575 V, 960 A, 700-900 HP
Vmx-Kp-Cpu-48	
Vmx-S-450-Cb-2	VMX-S (CONFIGURED), NEMA 12/4, 240V, 150HP, 450A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Mvc4-721000-E-Swg	
Xld-288-E	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1006A, CONTROL POWER: 120V, NEMA 12
Xld-1006-N	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1006A, CONTROL POWER: 120V, NEMA 1
Vmx-S-600-Cb-5d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 600HP, 600A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Mvc3-72400-E-Swg	
Jnbrn2-401	
Dxt-862	
Bxld-414-N-240	
Vmx-S-450-Cx-1d	VMX-C SHUNT RATED WITH DEADFRONT, 208 V, 450 A, 150 HP
Mvc3-Dvdt-150	
11-194-251	
Vmx-S-480-Cb-1d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 208V, 150HP, 480A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Vmx-S-112-Cx5	VMX-C SHUNT RATED, 575 V, 112 A, 100 HP
Xld-1006-E	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 78A, CONTROL POWER: 240V, NEMA 12
11-300-202	

Vmx-H-40-Cb1	
Vmx-S-112-Cb-4d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 30HP, 48A, 60A FS, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSION
Ptg3-2-60-552ff	
Dxt-288-460-N	
Vmx-H-220-Cb-5	
Vmx-H-96-Cb-5d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 60HP, 96A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
Csd-407-N4	
Xld-288-600-E	600 V, NEMA 12, 288 A, 120 VAC CONTROL POWER
Vmx-H-40-Cx2	
Vmx-S-550-Cx-1d	VMX-C SHUNT RATED WITH DEADFRONT, 208 V, 550 A, 150 HP
Vmx-S-361-Cx1	VMX-C SHUNT RATED, 208 V, 361 A, 125 HP
Dxt-1150-600-N	
Vmx-S-862-Cx2	VMX-C SHUNT RATED, 230 V, 862 A, 300 HP
Vmx-S-210-Cb-1	VMX-S (CONFIGURED), NEMA 12/4, 208V, 60HP, 210A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X 3
11-10sft-151	
Xld-1250-E	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 150A, CONTROL POWER: 240V, NEMA 12
Xld-220-600-E-240	600 V, NEMA 12, 220 A, 240 VAC CONTROL POWER
11-180sht-102	
11-5drl-122	
2vt469-600	
5200070250	
Dxt-120-208-P	
Vmx-S-48-Fs-1	
Vmx-H-27-Cb4	
Bxld-1150-N	
Mt-4200-P	

Pc3157a	
Xld-120-E-240	
Vmx-S-305-Cb-5d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 300HP, 305A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
121410	
Mvc3-Stk33200-*	
Bdxt-78-460-E	
Vmx-H-480-Cx-5d	VMX-C FULL RATED WITH DEADFRONT, 575 V, 480 A, 350-500 HP
Bdxt-220-208-E	
Vmx-S-480-Cx5	VMX-C SHUNT RATED, 575 V, 480 A, 500 HP
Xld-476-P-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 476A, CONTROL POWER: 240V, PANEL
Vmx-H-960-Cx2	VMX-C FULL RATED, 230 V, 960 A, 350-400 HP
Vmx-H-96-Cx-4d	VMX-C FULL RATED WITH DEADFRONT, 460 V, 96 A, 60 HP
Bdxt-550-460-N	
Vmx-S-39-Cx-4d	
Vmx-92-Bp-N	
Vmx-S-112-Cx-4d	VMX-C SHUNT RATED WITH DEADFRONT, 460 V, 112 A, 75 HP
11-5drl-201	
Vmx-H-45-Cx2	
11-120-152	
Xld-288-N-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 288A, CONTROL POWER: 240V, NEMA 1
Mt-Vw3a1104r10	
11-192-301	
Vmx-H-55-Cb-2	
Vmx-H-21-Cx-1d	
Vmx-S-275-Cx1	VMX-C SHUNT RATED, 208 V, 275 A, 75 HP
Dxt-48-460-N	
Mwh-50-P-380	
Ptw3-1-60-692cs	

11-170-501	
Vmx-Kp-Cpu-900	
Me2-101-M	
36-0411	
11-5sht-102	
11-780-201	
Vmx-S-150-Cb-4	VMX-S (CONFIGURED), NEMA 12/4, 480V, 100HP, 150A, 225A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 37H X
467-069	
11-2sht-101	
11-66-151	
Vmx-S-150-Cx2	VMX-C SHUNT RATED, 230 V, 150 A, 50 HP
Vmx-H-27-Fs-5d	
Vmx-H-96-Cx-5d	VMX-C FULL RATED WITH DEADFRONT, 575 V, 96 A, 60 HP
Vmx-S-39-Cx1	
Vcm205p	
Xld-718-N	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 718A, CONTROL POWER: 120V, NEMA 1
11-170-301	
Mwh-50-P-415	
Xld-62-600-P	
Vmx-S-18-Fs-1	
Xld-78-E-240	
Vmx-H-400-Cx-4d	VMX-C FULL RATED WITH DEADFRONT, 460 V, 400 A, 300 HP
11-56-Sft-102	
Dxt-62-600-N	
Vmx-H-480-Cb-2d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 240V, 200HP, 480A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Vmx-H-96-Cb-2	VMX-H (CONFIGURED), NEMA 12/4, 240V, 30HP, 96A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 37H X 15W X 12D

Bdxt-62-208-E	
001-480-118	
Dxt-476-460-P	
11-5darl-401	
Bxld-62-E-240	
Bdxt-92-600-N	
Vmx-H-68-Cx2	
Vmx-S-600-Cx-4d	VMX-C SHUNT RATED WITH DEADFRONT, 460 V, 600 A, 500 HP
Vmx-S-862-Cb-5	VMX-S (CONFIGURED), NEMA 12/4, 575V, 700HP, 862A, 1200A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 92H X
11-2-RI-201	
10708017322v	TRANSDUCER
Dxt-718-230-N	
Xld-1200-600-E-240	600 V, NEMA 12, 1200 A, 240 VAC CONTROL POWER
Vmx-S-305-Cx1	VMX-C SHUNT RATED, 208 V, 305 A, 100 HP
PtW3-2-60-662ff	
Vmx-S-160-Cx-2d	VMX-C SHUNT RATED WITH DEADFRONT, 230 V, 160 A, 60 HP
Vcm-415-P	
Csd-205-N4	
34-800-3-7200cj	
Bdxt-476-600-E	
Xld-48-N	
34-400-3-7200cj	
Mvc3-41400-E-Dol	
Dxt-1006-208-E	
Bdxt-62-460-N	
PtW5-1-110-842f	
11-2drl-401	
Mvc3-Stk-130300	
Xld-62-600-N4	

Bxld-862-E	
Ptg3-1-60-422f	
Bdxt-78-208-N	
460-480	
Vcm-201-P	
Csd-410-N	
11-7sft-102	
Xld-550-E-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 550A, CONTROL POWER: 240V, NEMA 12
Vmx-S-305-Cx4	VMX-C SHUNT RATED, 460 V, 305 A, 250 HP
Vmx-H-600-Cx-5d	VMX-C FULL RATED WITH DEADFRONT, 575 V, 600 A, 600 HP
Vmx-S-275-Cx5	VMX-C SHUNT RATED, 575 V, 275 A, 250 HP
Vmx-H-600-Cb-2	VMX-H (CONFIGURED), NEMA 12/4, 240V, 200HP, 600A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 48H X 33W X 16D
Vmx-S-361-Cb-5	VMX-S (CONFIGURED), NEMA 12/4, 575V, 350HP, 361A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Xld-150-600-P-240	
11-8-Sht-102	
Ms148125n	
11-2drl-601	
Vmx-S-275-Cb-5	VMX-S (CONFIGURED), NEMA 12/4, 575V, 250HP, 275A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Dxt-550-600-N	
Vmx-S-305-Cb-4d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 100HP, 150A, 225A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Abc-1000-400-P	
64-Vs7008	
Dxt-718-460-P	
11-180sht-750	
Xld-414-600-N	600 V, NEMA 1, 414 A, 120 VAC CONTROL POWER

Xld-1200-600-P-240	600 V, PANEL, 1200 A, 240 VAC CONTROL POWER
11-140-301	
Vmx-S-92-Cb-5	VMX-S (CONFIGURED), NEMA 12/4, 575V, 75HP, 92A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 37H X 15
Dxt-288-208-P	
Vcm-205	
Vmx-H-80-Cx5	
Xld-862-600-E	600 V, NEMA 12, 862 A, 120 VAC CONTROL POWER
Vmx-S-112-Cb-1	VMX-S (CONFIGURED), NEMA 12/4, 208V, 30HP, 112A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 37H X 1
Xld-476-P	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 476A, CONTROL POWER: 120V, PANEL
Vmx-H-960-Cx4	VMX-C FULL RATED, 460 V, 960 A, 700-800 HP
Xld-476-600-E	600 V, NEMA 12, 476 A, 120 VAC CONTROL POWER
11-7sft-151	
Cpt3-60-2-6900-5	
Vmx-S-150-Cb-2	VMX-S (CONFIGURED), NEMA 12/4, 240V, 50HP, 150A, 225A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 37H X 1
Ptg3-2-60-242	
Bxld-62-N	
Cpt3-60-2-5500-6	
Csd-405-4n	
Dxt-360-230-N	
Vmx-H-400-Cb-4	VMX-H (CONFIGURED), NEMA 12/4, 480V, 300HP, 400A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 48H X 33W X 16D
Vmx-S-78-Cb-4d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 15-20HP, 28A, 60A FS, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Vmx-S-550-Cb-1	VMX-S (CONFIGURED), NEMA 12/4, 208V, 200HP, 550A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Dxt-78-230-E	
Vmx-H-400-Cx-2d	VMX-C FULL RATED WITH DEADFRONT, 230 V, 400 A, 150 HP

Bdxt-288-460-E	
Vmx-H-45-Cx-5d	
Vmx-S-275-Cb-4d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 75HP, 112A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSI
Vmx-H-480-Cb-5	VMX-H (CONFIGURED), NEMA 12/4, 575V, 500HP, 480A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 48H X 33W X 16D
Mvc3-66100-E-Swg	
Ptg5-1-110-842f	
Mvc3-Gdfp	
Lcb1002-Cc-22	
Abc-200-400-P	
Abc-800-480-P	
Dxt-288-600-N	
Vmx-S-600-Cb-1d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 208V, 200HP, 600A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Bdxt-550-230-N	
Ptg5-1-110-1442f	
Dxt-150-460-E	
Mt-Vw3a9213	
Abc-10-400-P	
Mt-Vw3a9509	
Vmx-S-112-Cx2	VMX-C SHUNT RATED, 230 V, 112 A, 40 HP
Xld-39-E-240	
Xld-48-600-E	
Xld-1150-600-N-240	600 V, NEMA 1, 1150 A, 240 VAC CONTROL POWER
11-170-102	
Dxt-48-208-N	
11-8-Sht-122	
Xld-Kp12-Kit-1	

Xld-288	SOFT START 288A 208/240/480/600V 75/100/200/250HP
11-5arl-751	
11-5arl-251	
11-56-Sft-122	
Vmx-S-92-Cb-4	VMX-S (CONFIGURED), NEMA 12/4, 480V, 60HP, 92A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 37H X 15
Csd-430-N	
Mvc3-41600-E-Swg	
Vmx-S-160-Cx-4d	VMX-C SHUNT RATED WITH DEADFRONT, 460 V, 160 A, 125 HP
Ptw3-2-60-692	
Vmx-S-160-Cx-1d	VMX-C SHUNT RATED WITH DEADFRONT, 208 V, 160 A, 50 HP
Vmx-H-600-Cx5	VMX-C FULL RATED, 575 V, 600 A, 600 HP
11-785-251	
Vmx-S-160-Cx-5d	VMX-C SHUNT RATED WITH DEADFRONT, 575 V, 160 A, 150 HP
Vmx-S-862-Cb-1	VMX-S (CONFIGURED), NEMA 12/4, 208V, 250HP, 862A, 1200A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 92H X
Bdxt-414-230-N	
Kp1-210-N	
11-170-162	
Xld-862-N-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 862A, CONTROL POWER: 240V, NEMA 1
11-785-101	
11-2sht-301	
Xld-414-600-N-240	600 V, NEMA 1, 414 A, 240 VAC CONTROL POWER
Xld-150-N-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 150A, CONTROL POWER: 240V, NEMA 1
Dxt-414	
Xld-1250-P	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1250A, CONTROL POWER: 120V, PANEL
Vmx-H-45-Cx1	
Xld-1006-600-N	600 V, NEMA 1, 1006 A, 120 VAC CONTROL POWER

11-6rl-301	
11-6arl-401	
Vmx-S-210-Cb-2	VMX-S (CONFIGURED), NEMA 12/4, 240V, 75HP, 210A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X 3
11-5arl-501	
Vmx-H-45-Cb-2d	VMX-C FULL RATED WITH DEADFRONT, CIRCUIT BREAKER, 230 V, 45 A, 15 HP
Vmx-S-210-Cb-5	VMX-S (CONFIGURED), NEMA 12/4, 575V, 200HP, 210A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Vmx-H-480-Cb-1	VMX-H (CONFIGURED), NEMA 12/4, 208V, 150HP, 480A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 48H X 33W X 16D
Mt-Vw3a3202	
Vmx-H-55-Cb-1d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 208V, 20HP, 55A, 100A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
Dxt-1150-460-E	
Cpt3-60-2-4800-5	
Xld-476-600-E-240	600 V, NEMA 12, 476 A, 240 VAC CONTROL POWER
Ls4-48125-Nx2	
Mt-Vw3a9211	
11-6asht-401	
Vmx-S-62-Cb-1d	
11-5sft-151	
Dxt-39-600-E	
Vmx-S-550-Cb-2d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 240V, 200HP, 550A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Bdxt-92-208-E	
Mvc3-Stk33630-45-*	
Mvc3-33400-E	
Xld-220-N-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 220A, CONTROL POWER: 240V, NEMA 1

Mvc4-Mb/Cpu-Kit	
Vmx-S-275-Cx-5d	VMX-C SHUNT RATED WITH DEADFRONT, 575 V, 275 A, 250 HP
11-125-202	
11-100-201	
Vmx-S-150-Cx-2d	VMX-C SHUNT RATED WITH DEADFRONT, 230 V, 150 A, 50 HP
Vmx-H-68-Cx-1d	VMX-C FULL RATED WITH DEADFRONT, 208 V, 68 A, 20 HP
Bxld-550-E	
Vmx-S-450-Cb-5	VMX-S (CONFIGURED), NEMA 12/4, 575V, 400HP, 450A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Vmx-S-18-Fs-4d	
Ptw5-1-110-1382c	
Vmx-H-55-Cb-5	VMX-H (CONFIGURED), NEMA 12/4, 575V, 40HP, 55A, 100A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 37H X 15W X 12D
11-5sht-101	
Lcb1002241	
11-7sht-501	
Xld-1250-E-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1250A, CONTROL POWER: 240V, NEMA 12
Vmx-H-45-Fs-5d	
Cpt3-30-2-6000-5	
Xld-288-600-P	600 V, PANEL, 288 A, 120 VAC CONTROL POWER
Vmx-H-312-Cb-4d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 300HP, 312A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Dxt-120-600-P	
Xld-92-600-P	
Xld-1150-600-N	600 V, NEMA 1, 1150 A, 120 VAC CONTROL POWER
11-1b-151	
11-56-Sft-751	
Vmx-S-92-Cb-2	VMX-S (CONFIGURED), NEMA 12/4, 240V, 30HP, 92A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 37H X 15

Xld-180-600-N	600 V, NEMA 1, 180 A, 120 VAC CONTROL POWER
Vmx-S-28-Fs-5d	
Vmx-S-480-Cb-4d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 200HP, 275A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Xld-360-E	360A STARTER
Vmx-S-210-Cx1	VMX-C SHUNT RATED, 208 V, 210 A, 60 HP
Vmx-H-1080-Cb2	
Dxt-550-600-P	
Lcb1002-2-4-Aa	
Bdxt-150-230-E	
Vmx-1250-Bp	
Mt-Vw3a1104r30	
Vmx-H-480-Cx-1d	VMX-C FULL RATED WITH DEADFRONT, 208 V, 480 A, 150 HP
Xld-180-N	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 180A, CONTROL POWER: 120V, NEMA 1
Xld-39-P	
Dxt-62-208-E	
Vmx-S-450-Cb-2d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 240V, 150HP, 450A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
11-5arl-101	
11-56-Sft-101	
Xld-476-N	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 476A, CONTROL POWER: 120V, NEMA 1
Vmx-S-48-Cb-1d	
11-8-Sht-152	
Abc-50-240-E	
Dxt-862-208-E	
Vmx-H-480-Cx4	VMX-C FULL RATED, 460 V, 480 A, 400 HP
Vmx-S-900-Cx5	VMX-C SHUNT RATED, 575 V, 900 A, 800-900 HP
64-Vs7072	
	VMX-H (CONFIGURED), NEMA 12/4, 240V, 200HP, 480A, 600A

Vmx-H-480-Cb-2	CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 48H X 33W X 16D
Mvc3-Stk72500	
Vmx-H-68-Cb-4	VMX-H (CONFIGURED), NEMA 12/4, 480V, 60HP, 68A, 100A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 37H X 15W X 12D
Abc-400-600-E	
Abc-400-400-P	
64-Vs008	
Ptg5-1-110-722f	
Vmx-H-21-Cb-5d	
Xld-360-P	360A STARTER
11-1b-500	
Abc-550-240-E	
Vmx-S-550-Cb-5	VMX-S (CONFIGURED), NEMA 12/4, 575V, 500HP, 550A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Vmx-S-28-Fs-4	
Vmx-S-39-Cb-2d	
Xld-1006-E-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1006A, CONTROL POWER: 240V, NEMA 12
Vmx-H-600-Cx4	VMX-C FULL RATED, 460 V, 600 A, 500 HP
Vmx-S-361-Cx-4d	VMX-C SHUNT RATED WITH DEADFRONT, 460 V, 361 A, 300 HP
25-0400-6500-72	
Xld-414-E	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1200A, CONTROL POWER: 120V, NEMA 12
Xld-718-P-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 718A, CONTROL POWER: 240V, PANEL
Vmx-S-92-Cx1	
Vmx-H-600-Cx-1d	VMX-C FULL RATED WITH DEADFRONT, 208 V, 600 A, 200 HP
Ptg5-2-110-113	
Vmx-S-862-Cb-4	VMX-S (CONFIGURED), NEMA 12/4, 480V, 600HP, 862A, 1200A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 92H X
Bxld-288-N	

Vmx-H-800-Cx2	VMX-C FULL RATED, 230 V, 800 A, 300 HP
Vmx-H-600-Cx-4d	VMX-C FULL RATED WITH DEADFRONT, 460 V, 600 A, 500 HP
Ss1-3-Ex1	
Vmx-H-68-Cb-4d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 40HP, 45A, 60A FS, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSION
11-7asht-152	
11-194-601	
Vmx-Kp-Cpu-210	
Dxt-1200	
Bdxt-360-230-E	
Vmx-Kp-Cpu-18	
34-400-3-7200c	
Vmx-S-275-Cx-4d	VMX-C SHUNT RATED WITH DEADFRONT, 460 V, 275 A, 200 HP
Mvc3-23100-E-Swg	
Xld-1250-600-E	600 V, NEMA 12, 1250 A, 120 VAC CONTROL POWER
11-5asht-751	
Xld-1200-P-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1200A, CONTROL POWER: 240V, PANEL
Vmx-S-361-Cx-1d	VMX-C SHUNT RATED WITH DEADFRONT, 208 V, 361 A, 125 HP
11-64-301	
Abc-200-480-E	
Xld-48-P	
Bdxt-288-208-E	
Ptg5-2-110-1322ff	
Vmx-H-400-Cx4	VMX-C FULL RATED, 460 V, 400 A, 300 HP
Vmx-S-600-Cb-5	VMX-S (CONFIGURED), NEMA 12/4, 575V, 600HP, 600A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Vmx-H-690-Cb-5	VMX-H (CONFIGURED), NEMA 12/4, 575V, 600HP, 690A, 1200A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 92H X 36W X 30D
11-8-Sht-251	

Vmx-S-450-Cx-5d	VMX-C SHUNT RATED WITH DEADFRONT, 575 V, 450 A, 450 HP
Vmx-H-68-Cb-2d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 240V, 30HP, 68A, 100A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
Vmx-S-450-Cx2	VMX-C SHUNT RATED, 230 V, 450 A, 150 HP
Vmx-S-39-Cb2	
Xld-220-600-P-240	600 V, PANEL, 220 A, 240 VAC CONTROL POWER
Vmx-S-92-Cx-1d	VMX-C SHUNT RATED WITH DEADFRONT, 208 V, 92 A, 25 HP
Xld-360-600-P-240	600 V, PANEL, 360 A, 240 VAC CONTROL POWER
11-180sht-601	
Vmx-H-27-Cb-4d	
Vmx-H-400-Cb-4d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 300HP, 400A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Dxt-360-230-P	
468-069	
Vmx-H-400-Cx-1d	VMX-C FULL RATED WITH DEADFRONT, 208 V, 400 A, 125 HP
Vmx-S-92-Cb-4d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 25HP, 39A, 60A FS, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSION
Vmx-S-361-Cb-2d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 240V, 125HP, 361A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Xld-1250-N-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1250A, CONTROL POWER: 240V, NEMA 1
Bdxt-550-600-N	
Vmx-H-312-Cb-2	VMX-H (CONFIGURED), NEMA 12/4, 240V, 150HP, 312A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 48H X 33W X 16D
Abc-400-240-P	
Ptg3-2-60-692ccs	
Vmx-S-275-Cb-1d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 208V, 75HP, 275A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSI

Jnbrn2-207	
Vmx-H-68-Cb-2	VMX-H (CONFIGURED), NEMA 12/4, 240V, 30HP, 68A, 100A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 37H X 15W X 12D
K3-201-P	
Dxt-550-208-N	
Vmx-S-275-Cx4	VMX-C SHUNT RATED, 460 V, 275 A, 200 HP
Xld-180-N-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 180A, CONTROL POWER: 240V, NEMA 1
Vmx-S-92-Cx-4d	VMX-C SHUNT RATED WITH DEADFRONT, 460 V, 92 A, 60 HP
11-56-Sft-801	
Vmx-H-960-Cb-5	VMX-H (CONFIGURED), NEMA 12/4, 575V, 900HP, 960A, 1200A / 1600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 92H X 36W X 30D
Xld-718-600-N-240	600 V, NEMA 1, 718 A, 240 VAC CONTROL POWER
2darl	
Vmx-S-210-Cx-2d	VMX-C SHUNT RATED WITH DEADFRONT, 230 V, 210 A, 75 HP
Vmx-S-150-Cb-5	VMX-S (CONFIGURED), NEMA 12/4, 575V, 125HP, 150A, 225A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 37H X
Vmx-H-55-Cb-5d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 40HP, 55A, 100A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
Xld-550-600-N	600 V, NEMA 1, 550 A, 120 VAC CONTROL POWER
11-6arl-102	
Xld-718-P	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 718A, CONTROL POWER: 120V, PANEL
Vmx-H-96-Cb-1	VMX-H (CONFIGURED), NEMA 12/4, 208V, 30HP, 96A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 37H X 15W X 12D
Xld-220-P-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 220A, CONTROL POWER: 240V, PANEL
Lcb1002-2-4	
Xld-220-600-N	600 V, NEMA 1, 220 A, 120 VAC CONTROL POWER
Xld-120-P	
Dxt-92-230-P	
Jnbrn2-203	

11-8-RI-401	
Vmx-H-480-Cx-4d	VMX-C FULL RATED WITH DEADFRONT, 460 V, 480 A, 400 HP
11-14-101	
Es400	
Xld-1150-600-P-240	600 V, PANEL, 1150 A, 240 VAC CONTROL POWER
Xld-476-600-P	600 V, PANEL, 476 A, 120 VAC CONTROL POWER
Abc-10-480-E	
Xld-862-600-P	600 V, PANEL, 862 A, 120 VAC CONTROL POWER
11-8-RI-251	
Bxld-718-600-E-240	
Vmx-S-210-Cx2	VMX-C SHUNT RATED, 230 V, 210 A, 75 HP
Vmx-S-480-Cb-4	VMX-S (CONFIGURED), NEMA 12/4, 480V, 400HP, 480A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Vmx-H-600-Cb-2d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 240V, 200HP, 600A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Vmx-S-62-Cx-1d	
52-18r-4800	
Vmx-H-600-Cx-2d	VMX-C FULL RATED WITH DEADFRONT, 230 V, 600 A, 250 HP
Ps1-57200-P	DRIVE 200HP
Vmx-H-400-Cb-1d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 208V, 125HP, 400A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
11-180sht-152	
Xld-1200-N-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1200A, CONTROL POWER: 240V, NEMA 1
Xld-550-600-E	600 V, NEMA 12, 550 A, 120 VAC CONTROL POWER
Dxt-62	
Vmx-H-600-Cb-4	VMX-H (CONFIGURED), NEMA 12/4, 480V, 500HP, 600A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 48H X 33W X 16D
Jnbn2-403	
Vmx-S-600-Cx1	VMX-C SHUNT RATED, 208 V, 600 A, 200 HP

Bxld-48-N-240	
Dxt-862-208-N	
Dxt-476-208-P	
Ptg3-1-60-692f	
Vcm-475	
Vmx-S-480-Cx4	VMX-C SHUNT RATED, 460 V, 480 A, 400 HP
Bdxt-120-230-E	
Vmx-S-600-Cx-2d	VMX-C SHUNT RATED WITH DEADFRONT, 230 V, 600 A, 250 HP
Vmx-S-150-Cb-4d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 40HP, 62A, 100A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
Vmx1003-Pwr	
Vmx-S-600-Cb-1	VMX-S (CONFIGURED), NEMA 12/4, 208V, 200HP, 600A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Vmx-S-600-Cb-4	VMX-S (CONFIGURED), NEMA 12/4, 480V, 500HP, 600A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Dxt-39-460-E	
Vmx-S-900-Cb1	VMX-C SHUNT RATED, CIRCUIT BREAKER, 208 V, 900 A, 300 HP
10708.041	
11-125-801	
Vmx-S-361-Cb-4d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 125HP, 160A, 225A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Xld-360-600-N	600 V, NEMA 1, 360 A, 120 VAC CONTROL POWER
3pt3-60-122fff	
Vmx-H-312-Cb-1d	
Vmx-H-690-Cb-2	VMX-H (CONFIGURED), NEMA 12/4, 240V, 300HP, 690A, 1200A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 92H X 36W X 30D
Vmx-H-96-Cb-1d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 208V, 30HP, 96A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO

Vmx-H-690-Cb-4	VMX-H (CONFIGURED), NEMA 12/4, 480V, 500HP, 690A, 1200A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 92H X 36W X 30D
Ptg5-2-110-1442	
Ptg5-1-110-332c	
PtW3-1-60-422f	
Vmx-S-150-Cx-1d	VMX-C SHUNT RATED WITH DEADFRONT, 208 V, 150 A, 40 HP
Vmx-H-480-Cb-1d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 208V, 150HP, 480A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Vmx-S-600-Cx4	VMX-C SHUNT RATED, 460 V, 600 A, 500 HP
Xld-476-N-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 476A, CONTROL POWER: 240V, NEMA 1
Bdxt-92-230-N	
Dxt-414-230-N	
Vmx-S-600-Cx5	VMX-C SHUNT RATED, 575 V, 600 A, 600 HP
Lc1-4-575-E	
Dxt-1250-600-E	
Hv1-42-P	
11-19sht-301	
Vmx-S-600-Cx-5d	VMX-C SHUNT RATED WITH DEADFRONT, 575 V, 600 A, 600 HP
Vcm-415	
11-5rbt-750	
Csd-202-N	
Vmx-S-305-Cb-5	VMX-S (CONFIGURED), NEMA 12/4, 575V, 300HP, 305A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Xld-1006-600-E-240	600 V, NEMA 12, 1006 A, 240 VAC CONTROL POWER
Bxld-718-E	
Bdxt-150-600-N	
Vmx-S-305-Cx-4d	VMX-C SHUNT RATED WITH DEADFRONT, 460 V, 305 A, 250 HP
Xld-288-600-N	600 V, NEMA 1, 288 A, 120 VAC CONTROL POWER
Vmx-S-78-Cx-4d	

Xld-718-600-N	600 V, NEMA 1, 718 A, 120 VAC CONTROL POWER
11-197-601	
Vmx-S-210-Cx-5d	VMX-C SHUNT RATED WITH DEADFRONT, 575 V, 210 A, 200 HP
Xld-1250-600-P-240	600 V, PANEL, 1250 A, 240 VAC CONTROL POWER
Mwh-10-P-575	
Xld-220-600-P	600 V, PANEL, 220 A, 120 VAC CONTROL POWER
Vmx-S-600-Cb-4d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 300HP, 361A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Vmx-H-45-Cx4	
Vmx-S-48-Cx1	
Vmx-H-96-Cb-2d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 240V, 30HP, 96A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
Mvc4-41800-E-Swg	
Vmx-S-112-Cb-5	VMX-S (CONFIGURED), NEMA 12/4, 575V, 100HP, 112A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 37H X
Xld-414-N	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 414A, CONTROL POWER: 120V, NEMA 1
Bxld-476-600-N-240	
11-170-202	
Mt-4100-P	
Vmx-H-68-Cx-2d	VMX-C FULL RATED WITH DEADFRONT, 230 V, 68 A, 25 HP
Xld-718-600-E	600 V, NEMA 12, 718 A, 120 VAC CONTROL POWER
Xld-1250-600-N-240	600 V, NEMA 1, 1250 A, 240 VAC CONTROL POWER
Vmx-S-150-Cb-2d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 240V, 50HP, 150A, 225A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSI
467-346	
Vmx-H-45-Cb-5d	VMX-C FULL RATED WITH DEADFRONT, CIRCUIT BREAKER, 575 V, 45 A, 30 HP
Vmx-S-78-Cb-2d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 240V, 25HP, 78A, 100A CB, OVERLOAD CAPACITY 500% FOR 60SEC,

CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO	
11-19sht-152	
Mt-Vw3a3407	
11-126-801	
Dxt-120	
Vmx-S-78-Cx-5d	
Xld-39-600-N4	
Vmx-H-600-Cx1	VMX-C FULL RATED, 208 V, 600 A, 200 HP
25-0100-6500-41	
Mvc3-Mb/Cpu-Kit(Note1)	
Xld-1200-600-N	600 V, NEMA 1, 1200 A, 120 VAC CONTROL POWER
Xld-1150-600-P	600 V, PANEL, 1150 A, 120 VAC CONTROL POWER
11-5asht-801	
11-6sht-122	
11-7asft-122	
Vmx-H-400-Cx-5d	VMX-C FULL RATED WITH DEADFRONT, 575 V, 400 A, 300 HP
Bdxt-180-600-N	
Xld-48-600-N-240	
Vcm-410	
Dxt-92	
Vmx-S-550-Cb-1d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 208V, 200HP, 550A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
11-76rl-202	
Dxt-1250-600-N	
Vmx-H-220-Cb-4d	
Vmx-S-600-Cb-2	VMX-S (CONFIGURED), NEMA 12/4, 240V, 250HP, 600A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Vmx-H-248-Cb-1	
Vmx-H-690-Cx4	VMX-C FULL RATED, 460 V, 690 A, 500 HP
Vmx-S-210-Cx-1d	VMX-C SHUNT RATED WITH DEADFRONT, 208 V, 210 A, 60 HP

Vmx-H-80-Cb-4	VMX-H (CONFIGURED), NEMA 12/4, 480V, 75HP, 80A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 37H X 15W X 12D
Mvc3-69100-E-Swg	
Xld-550-N-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 550A, CONTROL POWER: 240V, NEMA 1
100003a	
Vmx-H-96-Cb-5	VMX-H (CONFIGURED), NEMA 12/4, 575V, 60HP, 96A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 37H X 15W X 12D
Vmx-H-55-Cx-2d	
Ptg5-1-110-113	
11-5rl-201	
11-7arl-801	
Vmx-H-480-Cx-2d	VMX-C FULL RATED WITH DEADFRONT, 230 V, 480 A, 200 HP
Vmx-Kp-Cpu-600	
Bdxt-476-460-N	
11-5darl-201	
Abc-200-240-Px1	
Ptg3-2-60-455ff	
11-6sht-401	
Vmx-H-80-Cb-1d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 208V, 30HP, 80A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
Vmx-H-55-Cx-4d	
11-14-500	
11-56-750	
Bdxt-1250-600-N	
Vmx-S-28-Cx1	
Bxld-180-E-240	
11-64-251	
Bdxt-220-600-E	
Vmx-H-400-Cb-5d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 300HP, 400A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS

Vmx-H-220-Cx2	
Vmx-S-480-Cx-4d	VMX-C SHUNT RATED WITH DEADFRONT, 460 V, 480 A, 400 HP
PtW3-2-60-450ccs	
Vmx-S-305-Cx-1d	VMX-C SHUNT RATED WITH DEADFRONT, 208 V, 305 A, 100 HP
Ls548075p	
Vmx-H-68-Cb-5d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 50HP, 68A, 100A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
Mvc3-Stk-130200	
Vmx-210-Bp-690	
BxId-1006-E	
Vmx-S-112-Cx-5d	VMX-C SHUNT RATED WITH DEADFRONT, 575 V, 112 A, 100 HP
PtW3-2-60-442ccs	
Vmx-S-480-Cb-2	VMX-S (CONFIGURED), NEMA 12/4, 240V, 200HP, 480A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Vmx-S-900-Cb5	VMX-C SHUNT RATED, CIRCUIT BREAKER, 575 V, 900 A, 800-900 HP
Vmx-H-125-Cx5	
Vmx-S-275-Cb-4	VMX-S (CONFIGURED), NEMA 12/4, 480V, 200HP, 275A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
XId-180-E	180A SOFTSTART
Dxt-150-600-E	
Vmx-S-210-Cx-4d	VMX-C SHUNT RATED WITH DEADFRONT, 460 V, 210 A, 150 HP
11-5rbt-401	
Vmx-S-550-Cx4	VMX-C SHUNT RATED, 460 V, 550 A, 450 HP
BxId-550-E-240	
Kp1-401-N	
Abc-10-400-E	
11-192-101	
Ls44800	

11-6arl-751	
Vmx-S-160-Cx5	VMX-C SHUNT RATED, 575 V, 160 A, 150 HP
Xld-414-600-E	600 V, NEMA 12, 414 A, 120 VAC CONTROL POWER
Vmx-S-550-Cx-2d	VMX-C SHUNT RATED WITH DEADFRONT, 230 V, 550 A, 200 HP
Vmx-S-600-Cx2	VMX-C SHUNT RATED, 230 V, 600 A, 250 HP
Vmx-S-450-Cx1	VMX-C SHUNT RATED, 208 V, 450 A, 150 HP
34-630-3-7200cj	
Vmx-S-210-Cx5	VMX-C SHUNT RATED, 575 V, 210 A, 200 HP
Mt-220-P	
11-191-401	
11-5arl-201	
Vmx-S-305-Cb-1	VMX-S (CONFIGURED), NEMA 12/4, 208V, 100HP, 305A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Mvc3-41100-E-Swg	
11-191-251	
Vmx-H-400-Cx1	VMX-C FULL RATED, 208 V, 400 A, 125 HP
Vmx-S-275-Cx-1d	VMX-C SHUNT RATED WITH DEADFRONT, 208 V, 275 A, 75 HP
Mt-4500-P	
Mvc3-Stk23200-*	
Vmx-H-400-Cx5	VMX-C FULL RATED, 575 V, 400 A, 300 HP
Me2-402-M-Din	
Mvc3-72600-E	
Vcm-210	
11-76rl-301	
2rl	
Vmx-S-112-Cb-2	VMX-S (CONFIGURED), NEMA 12/4, 240V, 40HP, 112A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 37H X 1
Dxt-150-230-N	
Xld-1150-N-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1150A, CONTROL POWER: 240V, NEMA 1

Vmx-900-Bp-690	
Vmx-S-112-Cx1	VMX-C SHUNT RATED, 208 V, 112 A, 30 HP
Dxt-1200-208-N	
Vmx-S-900-Cb2	VMX-C SHUNT RATED, CIRCUIT BREAKER, 230 V, 900 A, 350 HP
Dxt-550-460-E	
Mvc3-Stk66200p	
PtW5-1-110-1382	
Abc-400-400-E	
Xld-476-E	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1250A, CONTROL POWER: 120V, NEMA 12
Bxld-718-N	
Vmx-H-40-Fs-4	
Vmx-S-450-Cb-1	VMX-S (CONFIGURED), NEMA 12/4, 208V, 150HP, 450A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
PtW5-2-110-722cc	
Cpt3-60-2-6600-5	
Vmx-S-361-Cb-1d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 208V, 125HP, 361A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Xld-1150-E	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 92A, CONTROL POWER: 240V, NEMA 12
Xld-120-600-N-240	
Vmx-H-312-Cb-5d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 250HP, 312A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
11-135-500	
Vcm-201-1-P	
Vmx-H-400-Cx2	VMX-C FULL RATED, 230 V, 400 A, 150 HP
11-6sht-501	
Xld-220-P	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 220A, CONTROL POWER: 120V, PANEL
11-5rbt-122	

11-5sft-801	
Vmx-H-600-Cb-5	VMX-H (CONFIGURED), NEMA 12/4, 575V, 600HP, 600A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 48H X 33W X 16D
Vmx-H-220-Cx-5d	
Vmx-H-480-Cx2	VMX-C FULL RATED, 230 V, 480 A, 200 HP
Vmx-S-160-Cx4	VMX-C SHUNT RATED, 460 V, 160 A, 125 HP
Bxld-414-N	
Bxld-550-600-N	
Vmx-S-862-Cx1	VMX-C SHUNT RATED, 208 V, 862 A, 250 HP
Mt-4700-P	
Xld-48-N4	
Bdxt-78-230-N	
Ptg3-2-60-552ccs	
Vmx-H-400-Cb-2	VMX-H (CONFIGURED), NEMA 12/4, 240V, 200HP, 400A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 48H X 33W X 16D
Xld-360-600-P	600 V, PANEL, 360 A, 120 VAC CONTROL POWER
Vmx-H-21-Cb4	
11-5asft-101	
Xld-78-600-P-240	
11-19sht-801	
PtW5-1-110-113	
Vmx-S-305-Cx-2d	VMX-C SHUNT RATED WITH DEADFRONT, 230 V, 305 A, 125 HP
Xld-180-600-P	
10a2193	
64-Ab7007	
Vmx-S-361-Cx-2d	VMX-C SHUNT RATED WITH DEADFRONT, 230 V, 361 A, 125 HP
11-64-401	
100127	
11-5asft-750	
XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS:	

Xld-150-E-240	78A, CONTROL POWER: 120V, NEMA 12
11-7rl-401	
Xld-48-P-240	
Mt-Vw3a3406	
Xld-150-E	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 550A, CONTROL POWER: 120V, NEMA 12
Vmx-H-800-Cx4	VMX-C FULL RATED, 460 V, 800 A, 600 HP
76sft	
11-7asft-751	
Dxt-78-600-N	
Vmx-H-312-Cx-4d	VMX-C FULL RATED WITH DEADFRONT, 460 V, 312 A, 250 HP
Vmx-S-305-Cb-4	VMX-S (CONFIGURED), NEMA 12/4, 480V, 250HP, 305A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Bdxt-476-208-N	
Xld-360-E-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 360A, CONTROL POWER: 240V, NEMA 12
Vmx-H-68-Cb-1	VMX-H (CONFIGURED), NEMA 12/4, 208V, 25HP, 68A, 100A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 37H X 15W X 12D
Vmx-S-112-Cb-5d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 100HP, 112A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Bdxt-1200-230-N	
Xld-476-600-P-240	600 V, PANEL, 476 A, 240 VAC CONTROL POWER
Vmx-S-550-Cx5	VMX-C SHUNT RATED, 575 V, 550 A, 500 HP
Vmx-S-160-Cx1	VMX-C SHUNT RATED, 208 V, 160 A, 50 HP
Xld-1006-600-P	600 V, PANEL, 1006 A, 120 VAC CONTROL POWER
Xld-Keypad	
Mt-Vw3a9210	
Vmx-S-39-Fs-2	
Vmx-H-21-Cx2	
Mvc4-41200-E-Swg	
11-2darl-251	

Vcm-203-P	
11-780-301	
Dxt-862-460-E	
71-0251	
Vmx-H-68-Cx4	
Bxld-414-E-240	
Vmx-H-220-Cb-1	
Cpt3-60-2-5500-5	
Xld-718-600-P	600 V, PANEL, 718 A, 120 VAC CONTROL POWER
11-6sft-251	
Vmx-S-480-Cb-2d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 240V, 200HP, 480A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Vmx-S-18-Cx5	
Csd-203-N	
Vmx-H-312-Cx1	VMX-C FULL RATED, 208 V, 312 A, 100 HP
34-630-3-12000	
Xld-150-600-N	600 V, NEMA 1, 150 A, 120 VAC CONTROL POWER
Xld-550-P	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 550A, CONTROL POWER: 120V, PANEL
Xld-360-N	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 360A, CONTROL POWER: 120V, NEMA 1
Xld-120-N	
Vmx-H-96-Cx-1d	VMX-C FULL RATED WITH DEADFRONT, 208 V, 96 A, 30 HP
25-0200-6500-72	
Xld-1150-600-E-240	600 V, NEMA 12, 1150 A, 240 VAC CONTROL POWER
Dxt-476-600-P	
2511301600	
Vmx-S-92-Cb-2d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 240V, 30HP, 92A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
Vmx-S-92-Cb-1	VMX-S (CONFIGURED), NEMA 12/4, 208V, 30HP, 92A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 37H X 15

Vmx-S-900-Cb4	VMX-C SHUNT RATED, CIRCUIT BREAKER, 460 V, 900 A, 700 HP
Ptg3-2-60-552	
11-135-501	
Dxt-550-208-P	
Xld-476-600-N-240	600 V, NEMA 1, 476 A, 240 VAC CONTROL POWER
Vmx-S-275-Cb-2	VMX-S (CONFIGURED), NEMA 12/4, 240V, 100HP, 275A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Mvc4-72400-E-Swg	
Vmx-H-45-Cb-4d	VMX-C FULL RATED WITH DEADFRONT, CIRCUIT BREAKER, 460 V, 45 A, 30 HP
Vmx-S-150-Cx5	VMX-C SHUNT RATED, 575 V, 150 A, 125 HP
Vmx-S-900-Cx4	VMX-C SHUNT RATED, 460 V, 900 A, 700 HP
Mvc4stk41200	
Vmx-H-312-Cx2	VMX-C FULL RATED, 230 V, 312 A, 125 HP
34-200-3-7200	
Vmx-S-862-Cx5	VMX-C SHUNT RATED, 575 V, 862 A, 700 HP
Mvc4-411000-E-Swg	
Vmx-S-361-Cb-4	VMX-S (CONFIGURED), NEMA 12/4, 480V, 300HP, 361A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Vmx-H-312-Cb-4	
Vmx-S-450-Cb-4d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 150HP, 210A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Xld-Rs485-Kit-1	
Vmx-S-112-Cb-1d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 208V, 30HP, 112A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSI
Vmx-H-960-Cb-1	VMX-H (CONFIGURED), NEMA 12/4, 208V, 300HP, 960A, 1200A / 1600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 92H X 36W X 30D
Lc2-1-Pd	
Abc-400-240-E	

Mvc4-72100-E-Swg	
PtW3-1-60-482f	
Xld-414-600-P-240	600 V, PANEL, 414 A, 240 VAC CONTROL POWER
Dxt-150-208-E	
Xld-862-P	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 862A, CONTROL POWER: 120V, PANEL
Xld-288-600-P-240	600 V, PANEL, 288 A, 240 VAC CONTROL POWER
11-126-152	
Dxt-414-600-P	
11-65-301	
Xld-180-600-E-240	600 V, NEMA 12, 180 A, 240 VAC CONTROL POWER
Vmx-S-210-Cb-5d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 200HP, 210A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
11-8-RI-601	
Xld-862-600-N	600 V, NEMA 1, 862 A, 120 VAC CONTROL POWER
Xld-414-600-P	600 V, PANEL, 414 A, 120 VAC CONTROL POWER
Ptg5-1-110-552c	
11-6asht-601	
Vmx-S-210-Cx4	VMX-C SHUNT RATED, 460 V, 210 A, 150 HP
Vmx-S-210-Cb-4	VMX-S (CONFIGURED), NEMA 12/4, 480V, 150HP, 210A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Lc5-6-P	
Xld-288-P-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 288A, CONTROL POWER: 240V, PANEL
Vmx-S-450-Cx5	VMX-C SHUNT RATED, 575 V, 450 A, 400-450 HP
34-72-4-C-B-F1-0-12	
Me2-2p5-M	
11-15sft-151	
11-7asft-201	
Mvc3-Stk66200-*	
Xld-862-E	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 62A, CONTROL POWER: 240V, NEMA 12

11-10sft-301	
Vmx-H-125-Cx-2d	
Ptg3-1-60-442cs	
Vmx-H-400-Cb-2d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 240V, 200HP, 400A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
11-6rl-151	
Vmx-S-18-Cx1	
11-7rl-122	
Ptg5-1-110-502c	
Vmx-S-160-Cb-2	VMX-S (CONFIGURED), NEMA 12/4, 240V, 60HP, 160A, 225A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 37H X 1
Xld-1200-N	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1200A, CONTROL POWER: 120V, NEMA 1
Bxld-288-600-E	
Vmx-S-78-Cb-5d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 75HP, 78A, 100A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
6sht	
Vmx-S-112-Cx-2d	VMX-C SHUNT RATED WITH DEADFRONT, 230 V, 112 A, 40 HP
Abc-24-240-E	
Xld-360-600-N-240	600 V, NEMA 1, 360 A, 240 VAC CONTROL POWER
Vmx-H-96-Cx4	
11-6sht-102	
Xld-150-600-E	600 V, NEMA 12, 150 A, 120 VAC CONTROL POWER
Xld-360-P-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 360A, CONTROL POWER: 240V, PANEL
3pt3-60-602ccc	
11-5rl-750	
Vcm210p	
Vmx-S-48-Cx4	
11-100-102	

Vmx-S-150-Cx-5d	VMX-C SHUNT RATED WITH DEADFRONT, 575 V, 150 A, 125 HP
10708.008	
Vmx-H-960-Cb-4	VMX-H (CONFIGURED), NEMA 12/4, 480V, 800HP, 960A, 1200A / 1600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 92H X 36W X 30D
Dxt-48-208-P	
Xld-1006-600-N-240	600 V, NEMA 1, 1006 A, 240 VAC CONTROL POWER
50nv95k304t1c	
Vmx-H-80-Cb-2d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 240V, 30HP, 80A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
Xld-120	120A STARTER
Vmx-S-92-Cx-5d	VMX-C SHUNT RATED WITH DEADFRONT, 575 V, 92 A, 75 HP
11-195-601	
Mvc3-33100-E	
11-2rl-401	
Vmx-S-305-Cb-2	VMX-S (CONFIGURED), NEMA 12/4, 240V, 125HP, 305A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Vmx-H-480-Cb-5d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 500HP, 480A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Hv1-43-Pd	
64-Vs7001	
Vmx-S-28-Fs-1	
Vmx-S-275-Cx-2d	VMX-C SHUNT RATED WITH DEADFRONT, 230 V, 275 A, 100 HP
Xld-1250-P-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1250A, CONTROL POWER: 240V, PANEL
Mwh-50-P	
Vmx-S-160-Cb-5	VMX-S (CONFIGURED), NEMA 12/4, 575V, 150HP, 160A, 225A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 37H X
Vmx-S-18-Cb-2d	
64-Mlink-01k	

11-300-151	
Vmx-S-361-Cx5	VMX-C SHUNT RATED, 575 V, 361 A, 350 HP
Dxt-718-230-E	
Kp1-403	
11-5darl-500	
Ptw3-1-60-332cs	
Bxld-180-600-E	
Vmx-S-210-Cb-4d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 60HP, 92A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
Lcb1002-575-1	
Mvc4-1381000-E-Swg	
Xld-220-E-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 120A, CONTROL POWER: 120V, NEMA 12
11-7arl-101	
Csd-415-N	
Xlc4e	
Vmx-S-600-Cx-1d	VMX-C SHUNT RATED WITH DEADFRONT, 208 V, 600 A, 200 HP
Vmx-S-39-Cx2	
Xld-220-E	220A STARTER
Ptg3-2-60-242ff	
Xld-180-600-N-240	600 V, NEMA 1, 180 A, 240 VAC CONTROL POWER
Bxld-39-600-E-240	
Vmx-S-92-Cb-5d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 75HP, 92A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
Xld-1150-P-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1150A, CONTROL POWER: 240V, PANEL
11-6sft-201	
008-120-13s	
Bxld-39-E-240	
Vmx-H-27-Cb2	
	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V,

Vmx-S-160-Cb-5d	150HP, 160A, 225A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
11-126-102	
Xld-1150-600-E	600 V, NEMA 12, 1150 A, 120 VAC CONTROL POWER
PtW5-1-110-1382f	
11-5arl-801	
Mvc3-23600-E-Dol	
Xld-718-E	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 48A, CONTROL POWER: 240V, NEMA 12
Xld-550-600-P	600 V, PANEL, 550 A, 120 VAC CONTROL POWER
Xld-550-P-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 550A, CONTROL POWER: 240V, PANEL
Mvc3-Stk41200p	
11-56-201	
Vcm-2p5-1	
Bxld-1200-600-N-240	
Vmx-H-125-Cb-2d	
Abc-550-480-E	
Bdxt-92-460-N	
Vmx-H-312-Cb-5	VMX-H (CONFIGURED), NEMA 12/4, 575V, 250HP, 312A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 48H X 33W X 16D
Vmx-S-78-Cb-1d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 208V, 25HP, 78A, 100A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
Vmx-S-900-Cx1	VMX-C SHUNT RATED, 208 V, 900 A, 300 HP
11-56-401	
Wms-4170a	
Xld-550-600-E-240	600 V, NEMA 12, 550 A, 240 VAC CONTROL POWER
Dxt-220-208-E	
52-9r-7200	
K32120	
Xld-62-P-240	
	VMX-C SHUNT RATED WITH DEADFRONT, 575 V, 305 A, 300

Vmx-S-305-Cx-5d	HP
11-6asft-101	
Dxt-150-230-E	
11-5sht-601	
Vmx-S-160-Cx2	VMX-C SHUNT RATED, 230 V, 160 A, 60 HP
Csd202nx1	
Dxt-180	
Vmx-H-80-Cb-5	VMX-H (CONFIGURED), NEMA 12/4, 575V, 50HP, 80A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 37H X 15W X 12D
11-5sft-500	
Bxld-360-E	
11-785-801	
11-66-501	
11-191-101	
11-180sht-751	
Vmx-H-480-Cb-4	VMX-H (CONFIGURED), NEMA 12/4, 480V, 400HP, 480A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 48H X 33W X 16D
Vmx-S-275-Cx2	VMX-C SHUNT RATED, 230 V, 275 A, 100 HP
11-76sht-101	
Mvc4-69100-E-Swg	
Xld-1250-600-E-240	600 V, NEMA 12, 1250 A, 240 VAC CONTROL POWER
Vmx-H-960-Cb-2	VMX-H (CONFIGURED), NEMA 12/4, 240V, 400HP, 960A, 1200A / 1600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 92H X 36W X 30D
8sht	
11-140-251	
Vmx-H-27-Cx4	
11-19sht-501	
Xld-1006-600-E	600 V, NEMA 12, 1006 A, 120 VAC CONTROL POWER
Vmx-H-156-Cx2	
Xld-862-600-E-240	600 V, NEMA 12, 862 A, 240 VAC CONTROL POWER
Abc-550-400-E	

11-6sht-301	
11-5drl-750	
460-240	
11-780-251	
Bxld-862-600-N	
Vmx-S-18-Fs-5d	
Xld-862-P-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 862A, CONTROL POWER: 240V, PANEL
Vmx-Kp-Cpu-275	
Vmx-H-480-Cb-4d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 400HP, 480A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Vmx-S-48-Cb4	
11-180sht-201	
PtW3-1-60-602f	
Bdxt-862-208-N	
135mr	
Bxld-92-E	
PtW3-2-60-482ccs	
2sht	
Vmx-S-550-Cb-4	VMX-S (CONFIGURED), NEMA 12/4, 480V, 450HP, 550A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Bdxt-1006-208-N	
11-64-201	
Vmx-S-160-Cb-1d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 208V, 50HP, 160A, 225A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSI
11-56-Sft-750	
Kp1-210	
Vmx-S-550-Cb-4d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 250HP, 305A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS

Jnbrn2-202	
Dxt-39-208-N	
11-56-RI-201	
11-300-500	
468-480	
Vmx-S-450-Cb-1d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 208V, 150HP, 450A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Xld-360-600-E	600 V, NEMA 12, 360 A, 120 VAC CONTROL POWER
Xld-48-N-240	
Vmx-S-39-Cb4	
Xld-476-E-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 476A, CONTROL POWER: 240V, NEMA 12
11-6asht-751	
Bxld-62-600-E	
Dxt-78-208-N	
11-2-Sft-500	
Xld-120-600-E	
Dxt-862-230-N	
Bdxt-718-208-N	
Mvc4-69200-E-Swg	
Vmx-H-80-Cb-1	VMX-H (CONFIGURED), NEMA 12/4, 208V, 30HP, 80A, 150A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 37H X 15W X 12D
Bdxt-120-230-N	
Xld-360-600-E-240	600 V, NEMA 12, 360 A, 240 VAC CONTROL POWER
Vmx-S-275-Cb-5d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 250HP, 275A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Fdxt-39-600-N	
2vt469-069	
Xld-62-600-N4-240	
	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS:

Xld-1150-P	1150A, CONTROL POWER: 120V, PANEL
Vmx-H-690-Cx5	VMX-C FULL RATED, 575 V, 690 A, 600 HP
11-785-401	
Mvc3-Stk41100-*	
Vmx-S-480-Cx2	VMX-C SHUNT RATED, 230 V, 480 A, 200 HP
Xld-360-N-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 360A, CONTROL POWER: 240V, NEMA 1
11-5rbt-301	
Xld-718-E-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 718A, CONTROL POWER: 240V, NEMA 12
Xld-288-E-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 150A, CONTROL POWER: 120V, NEMA 12
11-19sht-401	
Vmx-H-600-Cb-5d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 600HP, 600A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Vmx-S-92-Cx-2d	VMX-C SHUNT RATED WITH DEADFRONT, 230 V, 92 A, 30 HP
Vmx-H-156-Cb-2	
Vmx-H-96-Cb-4d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 60HP, 68A, 100A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
Vmx-S-550-Cx-5d	VMX-C SHUNT RATED WITH DEADFRONT, 575 V, 550 A, 500 HP
Xld-1200-E-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1200A, CONTROL POWER: 240V, NEMA 12
Vcm-475-N	
Ptw5-2-110-1442cc	
Xld-48-E-240	
Xld-1200-P	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1200A, CONTROL POWER: 120V, PANEL
Abc-800-600-P	
Abc-1000-480-E	
Vmx-Kp-Cpu-361	
Ptw3-2-60-602	
	VMX-H (CONFIGURED), NEMA 12/4, 480V, 600HP, 800A,

Vmx-H-800-Cb-4	1200A CB, OVERLOAD CAPACITY 500% FOR 60SEC, DIMENSIONS: 92H X 36W X 30D
11-6asht-251	
11-76sht-301	
Vmx-28-Bp-E	
Lc2-3-N	
1b	
11-6rl-152	
Vmx-S-550-Cb-2	VMX-S (CONFIGURED), NEMA 12/4, 240V, 200HP, 550A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 48H X
Bxld-862-E-240	
Vmx-H-600-Cb-4d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 500HP, 600A, 800A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
11-5sft-501	
Vmx-160-Bp	
11-19rl-301	
Cpt3-60-2-4160-5	
Vmx-H-312-Cx-1d	VMX-C FULL RATED WITH DEADFRONT, 208 V, 312 A, 100 HP
Vmx-S-480-Cx-5d	VMX-C SHUNT RATED WITH DEADFRONT, 575 V, 480 A, 500 HP
Mvc3 41650-Ge-6 Oem	
Xld-718-600-P-240	600 V, PANEL, 718 A, 240 VAC CONTROL POWER
Vmx-S-150-Cb-1d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 208V, 40HP, 150A, 225A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSI
Vcm-215	
Vmx-H-40-Cb4	
Bdxt-476-230-E	
Vmx-92-Bp-E	
Vmx-H-80-Cb-4d	VMX-H (CONFIGURED W/ DEADFRONT), NEMA 12/4, 480V, 50HP, 55A, 100A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIO
Vmx-H-312-Cx-5d	

Xld-1200-600-P	600 V, PANEL, 1200 A, 120 VAC CONTROL POWER
Mvc3-69600-E	
Ptw3-1-60-242cs	
11-5sft-601	
Bxld-39-E	
Vmx-H-27-Fs-5	
Ptg3-2-60-469ccs	
Mvc3-23500-E-Swg	
Vmx-S-305-Cb-1d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 208V, 100HP, 305A, 400A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Mvc3-72400-E	
Bdxt-220-600-N	
Vmx-361-Bp	SOFT STARTER
BI54-48-300	SOFT START CONTROL WITH CB 300HP 3-PHASE 480V
Xld-92-N-240	
Vmx-S-150-Cx-4d	VMX-C SHUNT RATED WITH DEADFRONT, 460 V, 150 A, 100 HP
Ptg5-2-110-722ff	
Cpt3-60-2-6900-6	
Mvc3-Stk23500	
11-195-122	
71-0230	
Xld-Kpn1-Kit-3	
2sft	
Vmx-S-150-Cb-5d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 125HP, 150A, 225A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Vmx-S-160-Cb-4	VMX-S (CONFIGURED), NEMA 12/4, 480V, 125HP, 160A, 225A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENSIONS: 37H X
Vmx-S-150-Cx4	VMX-C SHUNT RATED, 460 V, 150 A, 100 HP
Vmx-H-312-Cx4	VMX-C FULL RATED, 460 V, 312 A, 250 HP

Vmx-S-480-Cx1	VMX-C SHUNT RATED, 208 V, 480 A, 150 HP
Bxld-48-600-N	
Xld-1200-600-N-240	600 V, NEMA 1, 1200 A, 240 VAC CONTROL POWER
Spcsd-410-N4xmpp	
11-5sht-301	
11-140-750	
11-56-301	
Xld-150-600-N-240	600 V, NEMA 1, 150 A, 240 VAC CONTROL POWER
Xld-150-600-E-240	600 V, NEMA 12, 150 A, 240 VAC CONTROL POWER
Vmx-39-Bp-N	
Vmx-H-960-Cx1	VMX-C FULL RATED, 208 V, 960 A, 300 HP
Vmx-S-550-Cx1	VMX-C SHUNT RATED, 208 V, 550 A, 150 HP
Mt-Vw3a3101	
11-300-601	
Vmx-S-48-Cx-2d	
11-126-401	
11-180sht-122	
PtW3-1-60-242	
Vcm-402-P	
11-785-751	
Vcm-425-N	
Vmx-H-40-Fs-4d	
3pt3-60-662fff	
Mvc3-Dvdt	
Vmx-S-361-Cb-5d	VMX-S (CONFIGURED W/ DEADFRONT), NEMA 12/4, 575V, 350HP, 361A, 600A CB, OVERLOAD CAPACITY 500% FOR 60SEC, CONTROL POWER TRANSFORMER (INCLUDED), DIMENS
Ptg5-2-110-123ff	
11-6asft-801	
Xld-1150-E-240	XLD DIGITAL SOFT STARTER SERIES, 208-480V, MAX AMPS: 1150A, CONTROL POWER: 240V, NEMA 12

11-6rl-801	
Vmx-H-80-Cx4	
Mvc3-Stk23100-*	
Ps148300p	PREMIUM STARTER 300HP 480V 3PH 50/60HZ DIM. REF#5
Ptg3-1-60-502	
Kp1-207	
Dxt-476-208-N	
11-7sft-152	
Xld-180-600-P-240	