



Munters

Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Munters Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Munters T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
90780010	Celdek 7060-15; 72"x12"x12"
90780010	Celdek 7060-15; 60"x12"x12"
150-020508-001	Electric Motor Reducer Type : ACE72T Serial number : 1083446 Hz : 50 / 60 V : 400 +10% / 480 +10% A : 0.13 / 0.13 W : 19 / 23 IP : 65 i : 2563 rpm rpm : 1.1 / 1.3 Nm: 30 / 30 The electric motor will be coupled.
150-020508-001	Gear motor ACE72T B3 (380-480V 50/60Hz, 30Nm)
150-018087-001 PLC, HMI, POL871.71/STD, CLIM	
150-039702-001 SENSOR, HUMIDITY&TEMP 4-20MA, DUCT	
19081259 Actuator SCC61	
1901500968-01 Thermostat ML2 175+-8grC fast	
190101143-166 Thermostat TR2 160°C 250V 15A	
150-014921-001 PLC, POL955.00/STD CLIMATIX	
150-014920-001 PLC, POL638.00/STD CLIMATIX	
ACE72T- 150-025445-006	
	190300 Dehumidifier M 120, 230V/50-60Hz Sorption dehumidifier in a compact, ready-to-use version with: <input type="checkbox"/> Housing made of corrosion-resistant die-cast aluminum, painted, with hose connection nozzle and side opening for optical rotor rotation control as well as recessed handles for easier transport <input type="checkbox"/> Titanium silica gel sorption rotor with abrasion-resistant sorbent, including gear ring for direct drive <input type="checkbox"/> Gear motor with pinion for direct rotor drive <input type="checkbox"/> Filter mats,

M120	grade EU3, in the process and regeneration air inlet □ Radial fans for the process and regeneration air flow with a common internal drive motor □ Electric heater for heating the regeneration air □ MAN/AUTO selector switch for optional operation with an external humidity meter □ Hygrostat socket for easy connection of an external control hygrostat □ Control system with all necessary switching, safety and control functions including maximum thermostat in accordance with the relevant Manufactured to EC standards and wired ready for connection with connection cable including plug □ Rotor material, flame retardant, certified according to DIN 4102-1 (BAM) Technical data: Process air Air volume, free blowing 180 m ³ /h Air volume, nominal 120 m ³ /h Pressure, externally available, nominal, Pst. approx.: 200 Pa Regeneration air Air volume, nominal: 35 m ³ /h Pressure, externally available, nominal, Pst. approx. 100 Pa Dehumidification performance Inlet condition of the process air 20°C, 60% r. F. approx.: 20.0 l/24h Energy requirement Electrical connection 1 x 230V, 50Hz, 1.28 kW Dimensions and weight: Height: 425 mm Width: 425 mm Depth: 481 mm Weight: 26.0 kg
150 020508 001	
MK35 NX	Dehumidifier
MK55 NX	Dehumidifier
1901500968-01 Thermostat ML2 175+-8grCfast	
190101143-166 Thermostat TR2160C 250V 15A,	
Heater rod 700W 254/440V	
GA95lp	
GN95	
1- 2608250EU	Housing - Fan ED30HE MP 0.5PS O, 3~400V 50Hz
1- 2604014EU	Housing - Fan ED30HE PMP 0.5PS O, 3~400V 50Hz
ED 30HE fan	
170- 028190 - 003	M ROTOR R HPS 0564 400
1502226 - 01	Cog Belt Q800 H075
8010109	DH2125 1800Wx1500H ALU AIMgSI0.5 Materials: Frame & Flanges: seawater aluminum resistant (AIMg0.5). Profiles: seawater-resistant aluminum (AIMgSI0.5). Flanges: mounting possible on both sides (top and bottom, front, bottom, back) Drainage: possible on both sides (front and back, center) Specification & Performance Parameter Default Operational Value Speed m/s 4 m/s 3.9 m/s Max. pressure loss 40 Pa 39.96 Pa Limit droplet 20 µ 20.4 µ Volume flow rate 32900 m ³ /h Please note that the specified parameters determine the volume flow rate. of 32,900 m ³ /h.

DV 270	
Vduse-1/2vx28-1002-100;	
Ccx 1.5	
Fca5	
20220018	
4312506	SEAL KIT
Ccx 2,5 20870094	
Munters-Type-Vd3;Se-12quot;-100;-Pp-28ltr2bar-Pack-40-Pcs-Istanbul-Turkiye	
Rh98-Wall Mounted Control Unit And Room Sensor 43154	
13x2240li A88 V Belt	
1679201000	
Mb-954-2a	
Gv1-M01-0,1-0,16a	
Mx2 95	
Mlt1400	
3x16-220v-50/60hz	
M2ta090s-490540041-B No:17599 400v Star 1640 R/Min 1,5hp 1.1kw 2,6 A	
160oc	
Md300	
Drive Motor Kit - 19043350	
0-600 Min 220v	
Zb2-Bz105+zb2-Bd3	
3x9-220v-50/60hz	
Zb2-Bs844+zb2-Bz104	
RotoI MI 1100/1350	
150-020508-001	DRIVE MOTOR 30NM, 50/60HZ, REP:190101467-1
Mx2 95 / 170-013059	
170-190500-001	
Gv1-Mo8-2,5-4.0a	

Fca515	
Fan For Ga 125 Lp	
Fca15	
Ccx 2.5	
Xb2-Bv75-D=22mm	
190101467-1	ML420 GEAR MOTOR
Motor For Ga 125 Lp	
Vduse-1/2quot;-100;	
MI 690	
Ccx 1,5 20870093	
M120	
150oc	
Jdw5 5kpa / Basiñ Sivici Jdw5 5kpa Alre Krs.	
103710716	
Dve - 1504145	