



## Nabtesco

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Nabtesco** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Nabtesco Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*

rn	Aıklama
<a href="#">217158-01 valf</a>	
<a href="#">EGCS-314M-2. 09A</a>	73794212-01 3 way valve. POS 31, x 1pc complete.
<a href="#">NPS -2 check chock valve complete Nabtesco. POS 32</a>	
<a href="#">Coil Nabtesco DC24V AIW 0,32 ϕ 20c Ω</a>	
<a href="#">NABTESCO RV080E-101-B-B</a>	
<a href="#">RV080E INPUT GEAR KIT</a>	
<a href="#">Repair kit 3/2 way valve</a>	see list
<a href="#">CS05A-00</a>	37-24-2 MSP96055
<a href="#">4-way Pnmatik valf</a>	
<a href="#">P55E015F00 / RV-160E-171-B-B (STD)</a>	transmission Country of origin: Japan Gross weight: 29,040KG Net Weight: 26,400KG Gear Type : Precision Gear Kit Transmission Series : RV-E Gear Size : 160E Main bearing, standard input sprocket Your advantages: integrated main storage Hysteresis loss : <1 arcmin Reduction : 1:171.0 Rated torque : 1,568 Nm Acceleration torque : 3,920 Nm Emergency stop torque : 7,840 Nm Torsional stiffness : 392 Nm/arcmin Rocking stiffness : 2,940 Nm/arcmin permitted tilting moment: 3,920 Nm Max. torque (static) : 7,840 Nm Max. speed 100% duty cycle: 25.0 rpm Max. speed 40% duty cycle: 45.0 rpm Radial load : 18,594 N Axial load : 14,700 N Weight : 26.4 kg Lubrication : RV_Grease

	**The gear component is delivered without lubrication. The customer has before use for a professional to provide lubrication.**
<a href="#">P45E013B00 / RV-80E-101-A-B (STD)</a>	transmission Country of origin: Japan Gross Weight: 15,000KG Net Weight: 15,000KG Gear Type : Precision Gear - Installation Kit Gear series : RV-E, with solid shaft Gear size : 80E Includes : main bearing, standard input sprocket Your advantages: integrated main storage Technical specifications Hysteresis loss : <1 arcmin Reduction : 1:101.0 Rated torque : 784 Nm Acceleration torque : 1,960 Nm Emergency stop torque : 3,920 Nm Torsional stiffness : 196 Nm/arcmin Rocking stiffness : 1,176 Nm/arcmin permitted tilting moment: 2,156 Nm Max. torque (static) : 4,312 Nm Max. speed 100% duty cycle: 40.0 rpm Max. speed 40% duty cycle: 70.0 rpm Radial load : 12,979 N Axial load : 7,840 N Weight : 13.1 kg Lubrication : RV_Grease **The gear component is delivered without lubrication. The customer has before use for a professional to provide lubrication.**
<a href="#">Felt set</a>	Gear box code: RV-320ES-241 Example Product Code: 15Z 245 273 15 80 Rotary shaft seal code
<a href="#">RV 100N 161</a>	
<a href="#">RV-450E-257 (A97L-0218-0266#450E-257 RV J2/J3)</a>	
<a href="#">A97L-0118-0949/70C36 RV 100C-36.75</a>	
<a href="#">A97L-0218-0806/120C36 RV 120C-36.75</a>	
<a href="#">A97L-0218-0265/450C-37 RV-450C-37.34</a>	
<a href="#">A97L-0218-0348/550F-253 RV-550F-253.9</a>	
<a href="#">PF30V00004F5</a>	
<a href="#">NAB RV450E-192.4-B-B</a>	
<a href="#">RV80N-101</a>	
<a href="#">RV160N-102,81</a>	
<a href="#">RV160N-125</a>	
<a href="#">RV-700F-269.21</a>	
<a href="#">P25E016F00 / RV-20E-161-B-B (STD)</a>	Gearbox type: Precision gearbox - installation kit Gearbox series: RV-E, with solid shaft Gearbox size: 20E Includes: Main bearing, customer-specific. Input pinion Your advantages: integrated main bearing +++ highest precision +++ hysteresis loss <1 arc minute Technical data Hysteresis loss: <1 arcmin Reduction ratio: 1:161.0 Nominal torque: 167 Nm Acceleration torque: 412 Nm Emergency stop torque: 833 Nm Torsional rigidity: 49 Nm/arcmin Tilt-down rigidity: 372 Nm/arcmin Permitted tilting torque: 882 Nm Max. torque (static): 1,764 Nm Max. speed 100% duty cycle: 40.0 rpm Max. speed 40% duty cycle: 75.0 rpm Radial load: 7,786 N Axial load: 3,920 N Weight: 4.7 kg Lubrication: RV_Grease
<a href="#">P35E014F00 / RV-40E-121-B-B (STD)</a>	Gearbox type: Precision gearbox - installation kit Gearbox series: RV-E, with solid shaft Gearbox size: 40E Includes: Main bearing, customer-specific. Input pinion Your advantages: integrated main bearing +++ highest precision +++ hysteresis loss <1 arc minute Technical data Hysteresis loss: <1 arcmin Reduction ratio: 1:121.0 Nominal torque: 412 Nm Acceleration torque: 1,029 Nm Emergency stop torque: 2,058 Nm Torsional rigidity: 108 Nm/arcmin Tilt-down rigidity: 931 Nm/arcmin Permitted tilt-down torque: 1,666 Nm Max. torque (static): 3,332 Nm Max. speed 100% duty cycle: 40.0 rpm Max. speed 40% duty cycle: 70.0 rpm Radial load: 11,588 N Axial load: 5,194 N Weight: 9.3 kg Lubrication: RV_Grease

<a href="#">P45E014F00 / RV-80E-121-B-B (STD)</a>	Gearbox type: Precision gearbox - installation kit Gearbox series: RV-E, with solid shaft Gearbox size: 80E Includes: Main bearing, customer-specific. Input pinion Your advantages: integrated main bearing +++ highest precision +++ hysteresis loss <1 arc minute Technical data Hysteresis loss: <1 arcmin Reduction ratio: 1:121.0 Nominal torque: 784 Nm Acceleration torque: 1,960 Nm Emergency stop torque: 3,920 Nm Torsional rigidity: 196 Nm/arcmin Tilt-down rigidity: 1,176 Nm/arcmin Permitted tilt-down torque: 2,156 Nm Max. torque (static): 4,312 Nm Max. speed 100% duty cycle: 40.0 rpm Max. speed 40% duty cycle: 70.0 rpm Radial load: 12,979 N Axial load: 7,840 N Weight : 13.1 kg Lubrication: RV_Grease
<a href="#">RV-320E B type shaft input and 141 bond</a>	
<a href="#">RC-20E A type spindle input and 121 bond</a>	
<a href="#">H349025595 / H811D4100-00-S</a>	(Only the valve cover is required, not as a complete set.)
<a href="#">PSC-38-P</a>	SUPER SPOOL, PNEUMATIC DIRECTIONAL VALVE
<a href="#">NT-0664R</a>	Repair Kit EGCS-322M-3
<a href="#">MSP99190B</a>	SWING MOTOR ASSY
<a href="#">RV-320E-118.5</a>	
<a href="#">Gm21va-A-48/83-1</a>	
<a href="#">Cs04-Rb-35-26-1 S/N: 9z001</a>	
<a href="#">309,310a,B,C,D</a>	
<a href="#">M4v290e/Rg6.5 S8x0011 Ksa10220</a>	
<a href="#">Rv-410f053-0</a>	
<a href="#">Gm21va-A-48/26-3</a>	
<a href="#">Rv-110 E-111-A-B</a>	
<a href="#">Rv-80e-57-A-B</a>	
<a href="#">Sn: 06500528, Msp 00139c, Gm09vn-E-21/33-3</a>	
<a href="#">Rv-40e-105</a>	GEAR REDUCER SIZE 40 105:0 RATIO RV-E SERIES
<a href="#">7sh59621-00 ,Axial Vibration Monitor Control Box Nabco Pc No 73758407-01 Code No 727, 36 87001-06581</a>	
<a href="#">S/N: 10b09547 Cs04-Rb-35-26-1 Msp99190a</a>	
<a href="#">Nmt-Ca10.</a>	
<a href="#">0669799UA</a>	Contents: 0781 221 UA – Motor Assy 0669 901 UA – Reduction Assy 0785 608 UA – Valve Assy
<a href="#">Cs09m-Bb-53-35-1 Msp99169</a>	
<a href="#">Rv-Ge-31-Fa</a>	
<a href="#">Gh-7-11-D-A-P</a>	
<a href="#">Rv-110-E-111-A-B</a>	
<a href="#">Spare Parts As Rotor/Plate And Pressure Pins</a>	
<a href="#">P76e056-00</a>	GEAR REDUCER SIZE 450 KGM 171:1 RATIO RV-E SERIES
<a href="#">Moly White 16kg Pai</a>	

<a href="#">Gh 7-11 2</a>	
<a href="#">Ball Bearing- Dimensions :179 Mmx 151 Mm Width:14 Mmm- (For Cso4-Rb-35-27 Msp02141 S/N:13202746 Hydr</a>	
<a href="#">P55e012d00</a>	GEAR REDUCER SIZE 160 81:1 RATIO RV-E SERIES
<a href="#">6526-2102446-20 Pms-33e(Dc24v 11w)</a>	
<a href="#">A97l-0218-266ã450e-257 ()</a>	
<a href="#">E01x2.E02</a>	
<a href="#">Gm21va-A-42-7</a>	
<a href="#">74y49011-10</a>	
<a href="#">Molywhite Grease (1- Can=2 Kgs)</a>	
<a href="#">Ch S/N S1203a0</a>	
<a href="#">Model Md 404m</a>	
<a href="#">Vigogrease/Molywhite</a>	
<a href="#">Seal Kit For Cs04-Rb-35-27-1</a>	
<a href="#">Gm23vl-C.56/94-6</a>	
<a href="#">M4v290z-Rg10 Motor Unit</a>	
<a href="#">Vico Grease Re0 16 Kgs</a>	
<a href="#">74y59337-10</a>	
<a href="#">Rd-80e-101</a>	GEAR REDUCER CYCLOIDAL SIZE 80 KGM 101:1 RATIO
<a href="#">Repaire Kit For Pump Nabtesco ( Piston ,Rotor , Svec Plate , Brake Lining ,Brake Piston Orings ,</a>	
<a href="#">Cs 04-Rb-35-26-1</a>	
<a href="#">Rv-450e-171-Z-B</a>	GEAR REDUCER SIZE 450 KGM 171:1 RATIO RV-E SERIES
<a href="#">Cs04-Rb-35-27-1 Msp02141 S/N 411s-00-Aab</a>	
<a href="#">Gumruk Ve Nakliye Masraflari.</a>	
<a href="#">Gm21va-A-42/72</a>	
<a href="#">Dr-42 P/N:412 000 54150</a>	
<a href="#">P/N: 74758457-01</a>	
<a href="#">Vigo Grease Re No 0 (Dose 2 Kg)</a>	
<a href="#">M4v290/170e A790064</a>	
<a href="#">74y59309-10</a>	
<a href="#">Seriel No:13202746 For Cs04-Rb-35-27 ? Msp02141</a>	
<a href="#">Cs04-Rb-35-27-1 Msp02141 S/N 03b00881</a>	
<a href="#">74796025-01</a>	
<a href="#">74y49003-19</a>	
<a href="#">M4v290 170f</a>	

<a href="#">M4v290erg6.5 S790143 Ksa10220</a>	
<a href="#">M4v245/1400z</a>	
<a href="#">Mcg 402-06</a>	
<a href="#">M4v290-Rg6.5</a>	
<a href="#">S/N Sk16025055 , Type Mbd-Fiva I-45 Paert Nr. 241</a>	
<a href="#">E06</a>	
<a href="#">Rd-040e-153</a>	GEARHEAD RD SERIES 153:1 RATIO
<a href="#">E04</a>	
<a href="#">74y49041-09</a>	
<a href="#">Rv-700f-269.21</a>	
<a href="#">6526?2084965-40</a>	
<a href="#">0401-1000500-00</a>	
<a href="#">Molywhite ? 2.0kg Can</a>	
<a href="#">Hm18l-J-56-2</a>	
<a href="#">06941</a>	
<a href="#">Gh40-11</a>	
<a href="#">P35e013b00</a>	GEAR REDUCER SIZE 40 105:0 RATIO RV-E SERIES
<a href="#">Gm10va-C-33/54-3</a>	
<a href="#">Repair Kit For Cs04-Rb-35-27-1</a>	
<a href="#">73754849-01</a>	
<a href="#">M4v24j/140z</a>	
<a href="#">Gm10va</a>	
<a href="#">M4v290/170z</a>	
<a href="#">Rv-160e-81-Z-B</a>	GEAR REDUCER SIZE 160 81:1 RATIO RV-E SERIES
<a href="#">Gm09m - L - 40 - 3 Msp96004a 05710425</a>	
<a href="#">P70j107dc0</a>	GEAR REDUCER SIZE 450 KGM 171:1 RATIO RV-E SERIES
<a href="#">Gm09m-E-40-1</a>	
<a href="#">Rv-70f-79.84</a>	