

Nieruf

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Nieruf Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Nieruf Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Lug Dn 200 Pn16	VALVE
KP01000110	Compensator DN80 type KP01 steel galvanized NBR Medium: liquid and harmless gaseous media (no steam) Flange material: galvanized steel Sleeve: NBR -10°C to +80°C Nominal diameter: DN80 Connection: Flange DIN EN 1092-1
KP01000010	Compensator DN80 type KP01 steel galvanized EPDM Medium: liquid and harmless gaseous media (no steam) Flange material: galvanized steel Sleeve: EPDM -10°C to +100°C Nominal diameter: DN80 Connection: Flange DIN EN 1092-1
SZ05000004	Fine sieve strainer 3/4" inch Stainless steel type SZ05 Design: Y-design with sealing plug Medium: liquid media Housing: stainless steel 1.4408 Cap: stainless steel 1.4408 Seal: PTFE Nominal width: 3/4" inch Internal thread BSP horizontal or vertical installation removable stainless steel filter
UV02020004	Corner overflow valve 3/4" inch IG UV02 Red brass/brass 2 - 12 bar Medium: liquid and gaseous media Material: Red brass/brass Seal: PTFE -60°C to +225°C Nominal diameter: 3/4" inch IG Internal thread BSP-P Setting range: 2.0 - 12.0 bar

Ürün	Açıklama
	Adjustable under operating conditions Corner overflow valve 3/4" inch Red brass/brass 2 - 12 bar
EV06340004	Solenoid valve DN20 G 3/4" inch NBR 110V stainless steel 1.4308 steering Switching function: NC - normally closed Medium: liquid & gaseous media Material: stainless steel 1.4308 Connection voltage: 110V Seal: NBR -10°C to +90°C Pressure range: 0.0 - 8 bar Connection: internal thread G 3/4" inch DN20 Flow rate: KV value 6.5 m³/h
Axial Expansion Joint DN200 PN25	Axial Expansion DN200 PN25 mod. AF.25.200
Angular Expansion Joint DN200 PN25	Angular Expansion DN200 PN25 mod. AGM-12C.25.200
Axial Expansion Joint DN200 PN40	Axial Expansion DN200

Ürün	Açıklama
	PN40 mod. AF.40.200
Angular Expansion Joint DN200 PN40	Angular Expansion DN200 PN40 mod. AGM -12C.40.200,
Axial Expansion Joint DN250 PN16	Axial Expansion DN250 PN16 mod. AF.16.250
Angular Expansion Joint DN250 PN16	Angular Expansion DN250 PN16 mod. AGM-12C.16.250,