



Niezgodka

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Niezgodka Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Niezgodka Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
NPS "1"	
NPS "2"	
NPS "3"	
81.2	Back pressure regulator without CE mark according to PED (Art. 4/3) F038517 Valve type: 81.2 Size: I Material: 1.4301 / 1.4571 Piston plate: ø 64 mm Process connection: flanges according to DIN 2635 Inlet: DN 25 PN 40 form C Outlet: DN 25 PN 40 form C Cone seal: PTFE other seals: EPDM Spring No .: 307 Options: - Code: 80-I-K064-F307-PTFE / EPDM Kvs value: 3.5 m ³ / h Inlet pressure P1: 3.0 bar (g) Pressure level: PN 40 Medium: not specified Temperature: 20 ° C Throughput: not specified Customs tariff number: 8481 80 59 Country of origin: DE
Typ 70.2-SKS-025.CL	Pressure reducer Typ 70.2-SKS DN025 PN16 Tri Clamp Inlet Body: 1.4301 / 1.4571 PN16 connections: DN025 / 025 1 "x1" Tri Clamp ASME-BPE Inlet body: 1.4301 Wet surfaces: 1.4571 Disc sealing: EPDM (PDA) Other seals: EPDM (PDA) / PTFE (PDA) There are 2 1/4 "manometer connections on the body. Inner surface quality Ra: 2,6Mm (std.) Suitable for sterilization with 140C steam SETTING RANGE: IT WILL BE 1,5-3 BAR. Inlet pressure: 4,0 Bar Outlet pressure: 2.0 Bar
70.2 Model Series SKS-CL	F071281 Stainless steel pressure reducing valve without CE mark according to PED (Art. 4/3) Valve type: 70.2 SKS-CL series Size: I Material: 1.4301 / 1.4571 Piston plate: ø 64 mm Process connection: clamp socket DIN 32676, for pipes according to DIN 11866, row C Entry: DN / OD 1 Outlet: DN / OD 1 Cone seal: EPDM (FDA) other seals: EPDM (FDA) / PTFE (FDA) Spring No .: 306 Options: - Code: I-K064-F306-EPDM (FDA) Kvs value: 3.2 m ³ / h Pre-pressure P1: 4.0 bar (g) Downstream pressure P2: 2.0 bar (g) (spring range: 1.5 - 3.0 barg) Pressure level: PN 16 Medium: not specified Throughput: not specified Temperature: 20 ° C Clamping socket Dk: 50.5 mm Clamping connector Di: 22.1 mm Pressure reducing valve closes at 0 consumption, inner

	surfaces in contact with the product with Ra = 2.6 µm (standard), max.damping temperature 140 ° C, housing with 2 pressure gauge connection holes G 1/4 Customs tariff number: 8481 10 19 Country of origin: DE
F082337	Stainless steel pressure reducing valve with CE mark according to PED Valve type: 70.2 SKS-CL series Size: II Material: 1.4301 / 1.4571 Piston plate: ø 84 mm Process connection: Clamping socket DIN 32676, for pipes according to DIN 11866, row A Entry: DN 32 Outlet: DN 32 Cone seal: EPDM (FDA) other seals: EPDM (FDA) / PTFE (FDA) Spring No.: 306 Options: - Code: II-K084-F306-EPDM (FDA) Kvs value: 6.5 m³ / h Pre-pressure P1: 3.5 bar (g) Downstream pressure P2: 1.0 bar (g) Pressure level: PN 16 Medium: water Throughput: not specified Temperature: not specified Clamping socket Dk: 50.5 mm Clamping connector Di: 32.0 mm Net weight: approx. 5.8 kg / pc Pressure reducing valve closes at zero consumption, inner surfaces in contact with the product with Ra = 2.6 µm (standard), max.damping temperature 140 ° C, housing with 2 pressure gauge connection holes G 1/4 Customs tariff number: 8481 10 19 Country of origin: DE
Typ 10.1	
08212	
0-K064-PTFE/EPDM (FDA)	
10.1	
11-878	
30.1	
66.3	
A100454	
A100456	
A100472	
A100474	
A100477	
A100495	
A100496	
A100561	
A100563	
A100584	
A100588	
A100590	

A3000273
A3000273 Test 2.2
A3001738
A3003213
A3006023
A3007638
A3007639
A3011512
DIN 11866
DN50 F064257
E0000005
E0000013
E0000134
E0000146
E0000551
E0600376
E0600406
F 03760
F001978
F002368
F002832 + A3011535
F008661
F015223
F015273
F015328
F015339
F015339 (Ventilnummer Y05531)
F015877
F017261
F017262

F017698
F017843
F019658
F020188
F020410
F020659
F022342
F023057
F023994
F024433
F026220
F028889
F029750 (Ventiltyp: 10.2)
F031913
F031947
F032267
F034110
F034175
F035212
F036061
F036661
F044035
F044454
F046832
F051579
F052782 (Ventilnummer A04473)
F053301
F059961
F066709
F067618

F067709
F071568
F073441
F078576
F078577
F078580
F079662
F082286
F082288
F082315
F082317
F082830
Gleitmo 591
I-K064-F306-PTFE/AF/EPDM
Model 24.2, Size 1" x 1"
PRC125
SKS-DRE-88 , Typ DM-GA , DN 25
TUV-SV-04-847
TUV-SV-04-847-12.5
TUV-SV-04-847-d0-12.5
TUV-SV-09-847 do 10
TUV-SV-10-658-22.5
TUV-SV-11-713-12.5
TUV-SV-16-713
TUV-SV-99-847-DO-12
Typ 5.2 (1.4581 / 1.4571)
Typ 91.2 (Referenz Nummer D20345)
Typ: 30.1
Typ: 1.2 A
Typ: 30.2
TYP: 71

Ventiltyp: 10.2	
Ventiltyp: 110.1	
Ventiltyp: 32.2	
Ventiltyp: 71.2	
Ventiltyp:18.2 (F064744)	
F085588	pre-pressure controller without CE mark according to PED (Art. 4/3) piece Valve type: 81.2 Size: I Material: 1.4301 / 1.4571 Butt plate: ø 27 mm Process connection: Flanges according to DIN 2635 Inlet: DN 25 PN 40 form C Outlet: DN 25 PN 40 form C Cone seal: PTFE other seals: FPM Spring No.: 307 Options: - Code: 80-I-K027-F307-PTFE/FPM Kvs value: 3.5 m ³ /h Inlet pressure P1: 30.0 bar(g) Pressure level: PN 40 Medium: not specified Temperature: 20°C Throughput: not specified
70.2 series SKS-CL	F082337 Stainless steel pressure reducing valve with CE mark according to PED Valve type: 70.2 series SKS-CL Size: II Material: 1.4301 / 1.4571 Butt plate: ø 84 mm Process connection: clamp socket DIN 32676, for pipes according to DIN 11866, series A Entry: DN 32 Outlet: DN 32 Cone seal: EPDM (FDA) other seals: EPDM (FDA) / PTFE (FDA) Spring No.: 305 Options: - Code: II-K084-F305-EPDM (FDA) Kvs value: 6.5 m ³ /h Inlet pressure P1: 3.5 bar(g) Low pressure P2: 1.0 bar(g) Pressure level: PN 16 Medium: water Throughput: not specified Temperature: 20°C Clamp socket Dk: 50.5 mm Clamp socket Di: 32.0 mm Pressure reducing valve closing at 0 consumption, inner surfaces in contact with the product with Ra = 2.6 µm (standard), max. steaming temperature 140°C, housing with 2 pressure gauge connection bores G 1/4 Customs tariff number: 8481 10 19 Country of origin: DE
F035325 70.2 SKS-CL series	Stainless steel pressure reducing valve with CE mark according to PED Valve type: 70.2 series SKS-CL Size: II Material: 1.4301 / 1.4571 Butt plate: ø 84 mm Process connection: clamp socket DIN 32676, for pipes according to DIN 11850 Entry: DN 32 Outlet: DN 32 Cone seal: EPDM (FDA) other seals: EPDM (FDA) / PTFE (FDA) Spring No.: 307 Options: - Code: II-K084-F307-EPDM (FDA) Kvs value: 6.5 m ³ /h Inlet pressure P1: 3.5 bar(g) Downstream pressure P2: 1.2 - 2.4 bar(g) Pressure level: PN 16 Medium: water Throughput: not specified Temperature: 20°C Clamp liner Dc: 50.5 mm Clamp liner Di: 32.0 mm Pressure reducing valve closing at 0 consumption, inner surfaces in contact with the product with Ra = 2.6 µm (standard), max. steaming temperature 140°C, housing with 2 pressure gauge connection bores G 1/4 Note: Valve in accordance with valve number L14568
	Stainless steel pressure reducing valve with CE mark according to PED Valve type: 70.2 series SKS-CL Size: II Material: 1.4301 / 1.4571 Butt plate: ø 84 mm Process connection: clamp socket DIN 32676, for pipes according to DIN 11866, series A Entry: DN 32 complete connection

F088650 70.2 SKS-CL series	Outlet: DN 32 complete connection Cone seal: EPDM (FDA) other seals: EPDM (FDA) / PTFE (FDA) Spring No.: 307 Options: - Code: II-K084-F307-EPDM (FDA) Kvs value: 6.5 m ³ /h Inlet pressure P1: 3.5 bar(g) Downstream pressure P2: 1.2 - 2.4 bar(g) Pressure level: PN 16 Medium: water Throughput: not mentioned Temperature: 20°C Clamp liner Dc: 50.5 mm Clamp liner Di: 32.0 mm Pressure reducing valve closing at 0 consumption, inner surfaces in contact with the product with Ra = 2.6 µm (standard), max. steaming temperature 140°C, housing with 2 pressure gauge connection bores G 1/4 Remark: Valve design same as valve number L14568 Customs tariff number: 8481 10 19 Country of origin: DE
A3011535	A3011535 (depending on version and connections) Inspection certificate 3.1 material according to EN 10204 (material/media-wetted parts) complete sentence
A3001694	FDA certification for wetted seals 1x cone seal (EPDM or FEPM or PTFE) 1x O-rings (EPDM) 1x O-rings (FEPM) 1x sealing rings (PTFE) Other certificates and manometers on request for an additional charge. The indicated prices apply before delivery. Subsequent certificates will be charged with an additional surcharge of 50%.
F090569	Safety valve with component identification and CE mark according to PED Valve type: 35.2 Size: I Material: 1.4404 / 1.4404 do / seat ø: 16 mm Process connection: Clamp fitting DIN 32676, for pipes according to DIN 11866 series A Admission: DN 25 Outlet: DN 25 Valve head: C Cone seal: 1.4404 / PTFE (FDA) other seals: EPDM (FDA) Spring No.: 115 Options:- Setting overpressure: 1.7 bar(g) Pressure rating: PN 16 Medium: not specified Temperature: 20°C Throughput: not specified Clamping socket Dk: 50.5mm Clamping socket Di: 26.0 mm SE: 100.0mm SA: 100.0mm
F090705	Valve type: 70.2 SKG-CL series Size: IV Material: 1.4571 / 1.4571 Piston plate: ø 99 mm Process connection: Clamp fitting DIN 32676, for pipes according to DIN 11866, series C Entry: DN/OD 4 Outlet: DN/OD 4 Cone seal: PTFE (FDA) other seals: FEPM (FDA) / EPDM (FDA) / PTFE (FDA) Spring No.: 357 Options: GG Code: IV-S-K099-F357-PTFE/FEPM/EPDM (FDA) Kvs value: 53.0 m ³ /h Pre-pressure P1: 4.75 -7.0 bar(g) Reduced pressure P2: 3.0 bar(g) Pressure rating: PN 10 Medium: Steam Throughput: not specified GG: Surfaces in contact with media with surface quality Ra = 0.6µm Temperature: max 200°C Clamping socket Dk: 119.0 mm Clamping socket Di: 97.4 mm Pressure reducing valve closes at 0 consumption, inner surfaces in contact with product with Ra = 2.6 µm (standard), max. damping temperature 200°C, housing with 2 pressure gauge connection holes G 1/4 Note: Version like valve number F03619, but with adapted text Process connections according to standard as well as items 350 and 351 made of FEPM, which are used should be over 4 bar for steam applications.
	Sizes: 3/8", 1/2", 3/4", 1", 1.1/4", 1.1/2, 2" Connections: Screwed BSPP or NPT Materials: Inlet Nozzle: Stainless Steel / Body & Bonnet: S.G Iron (1.1) or Stainless Steel (1.2 & 1.7)

Type 1 Relief Valve	Disk: Metal, Viton, Nylon, PEEK or Vespel Joints & Seals: NBR, FPM, EPDM (depending upon model) Medium: Steam, Gases and Liquids Set Pressure: 0.05 to 500 Barg (depending upon size) Temperature: (1.1) -10 to 280 degC, (1.2) -60 to 280 degC, (1.7) -200 to 280 degC
F024566	Pressure Reducing Valve with CE-marking acc. to PED Valve type: 71.2 Size: III Material: 1.4571 / 1.4571 Piston plate: ø 48 mm Process connection: flanges acc. to DIN 2635 Inlet: DN 65 PN 40 form C Outlet: DN 65 PN 40 form C Disc sealing: FPM Other sealings: FPM / PTFE Spring no.: 329 Options: - Code: III-K048-F329-FPM Kvs-value: 13.5 m ³ /h Inlet pressure P1: 30.0 bar(g) Outlet pressure P2: 10.0 bar(g) Nominal pressure: PN 40 Fluid: not specified Temperature: 20°C (presumed) Flow: not specified Pressure-reducing valve in case of 0-throughput shut tightly, body with 2 manometer connections G 1/4
F040465	Pressure Reducing Valve without CE-mark acc. to PED (Art. 4/3) Valvetype: 71.2 Size: I Material: 1.4301 / 1.4571 Piston plate: ø 38 mm Process connection: flanges acc. to DIN 2635 Inlet: DN 25 PN 40 form C Outlet: DN 25 PN 40 form C Disc sealing: FPM Other sealings: FPM / PTFE Spring no.: 307 Options: - Code: I-K038-F307-FPM Kvs-value: 3,5 m ³ /h Inletpressure P1: 30,0 bar(g) Outletpressure P2: 10,0 bar(g) Nominal pressure: PN 40 Fluid: not specified Temperature: 20°C (presumed) Flow: not specified Pressure-reducing valve in case of 0-throughput shut tightly, body with 2 manometer connections G 1/4 Remark: Valvespecification according to valvenumber H23803
F002104	Pressure Reducing Valve with CE-marking acc. to PED Valvetype: 71.2 Size: III Material: 1.4571 / 1.4571 Piston plate: ø 48 mm Process connection: flanges acc. to DIN 2635 Inlet: DN 50 PN 40 form C Outlet: DN 50 PN 40 form C Disc sealing: FPM Other sealings: FPM / PTFE Spring no.: 329 Options: - Code: III-K048-F329-FPM Kvs-value: 13,0 m ³ /h Inletpressure P1: 20,0 bar(g) Outletpressure P2: 10,0 bar(g) Nominal pressure: PN 40 Fluid: not specified Temperature: 20°C (presumed) Flow: not specified Pressure-reducing valve in case of 0-throughput shut tightly, body with 2 manometer connections G 1/4 Remark: Valvespecification according to valvenumber H23802
A3000290	degreased single packed in PE-bag
TÜV-SV-04-847	G 3/4" \ 6 BAR \ TYPE: 10.1 BGI
Type 10.1	SAFETY VALVE, (TYP:10.1)-(D/G:0,42)-(F:0,29)-(d0:8)-(Ts:10)-(p:150 BAR(g))
F054899	Stainless steel pressure reducing valve with CE marking according to PED Valve type: 70.2 Series SKS-CL Size: III Material: 1.4435 / 1.4404 Piston plate: ø 84 mm Process connection: TRI-CLAMP® clamping fitting, for pipes according to ASME-BPE Admission: NPS 2 Exit: NPS 2 Conical seal: PTFE (FDA) Other seals: EPDM (FDA) / PTFE (FDA) Spring No.: 327 Options: GC Code: III-K084-F327-PTFE/EPDM (FDA) Kvs value: 13 m ³ /h Pre-charge pressure P1: 3.5 bar(g) Reduced

	pressure P2: 2.2 - 2.5 bar(g) Pressure rating: PN 16 Medium: not specified Throughput: not specified GC: Media-contacting surfaces with surface quality Ra = 0.8µm Clamping sleeve Dk: 64.0 mm Clamping sleeve Di: 47.5 mm Temperature: 20°C (assumed) Pressure reducing valve closing at 0 consumption, max. damping temperature 150°C, housing with 2 Pressure gauge connection bores G 1/4 The design corresponds to valve number E09703.
type10.2	Niezgodka, Model: type10.2 330 bar PRV inlet G1/2"A, Outlet sortie G3/4 The inlet should be 1/2" and the outlet can be 1/2 or 3/4".
Druckminderventil Typ 70.2g1 1/2 Pn401.4301/1.4571	
A3007906 Rohrfeder-Manometer - Klasse 1,6 - Ng 630 - 2,5 Bar	
A3000273 Test Report 2.2	
F034892	
A3000276 Tã220;V-Inspection Certificate 3.1 A	
F042274	
A3007906	
F022155	
F017877	
F018965	
F020477	
0-K027-F101-Ptfe/Epdm (Fda)	
F019312	
F038299	
Typ: 30.2 Tã220;V-Sv-11-713	
F044958	
10.1 F002995	
F040515	
Type 10.7	
F002369	
A3000274 Sammelzeugnis 3.1 Ventil	
Valvetype: 10.2 (F024728)	

F002021
30.1-Bgiii-2in-CI150 Valve,Relief
F047817 Pressure Reducing Valve Without Ce Marking According To Ped (Art. 3/3)
I-K064-Epdm (Fda)
A3011536
F028889 Type 70.2
F021780
A3000276
F003995
F040431
70.2 Npt F060334 Pressure Reducing Valve
70.2 Baureihe Sks-F(As)
F023957
E0000003
F026035 Code: I-K027-F308-Ptfe/Fpm
F036503 Sicherheitsventil
F002348
A3007483
70.2 Series Skk-F Druckminderer
F017871
Typ 1.1 C Ventild 12.538 Bar
F011148
F066405
F035692
F036661 Druckminderventil Skk-Ga Typ 70.2 Din 11851, Dn 15, Pn 16
A3000274
Typ 35
F023674 (315 Bar)
F050767

F053501
Ventiltyp: 5.2 (F018198)
F054769
F041366
652mfk
F042093
Valvetype: 10.1 (F030406)
Ii-M235-Epdm (Fda)
F071181
Tä220;V-Sv-11-713 D0 12.5
Valvetype: 10.7 (F031771)
F002349
Typ 70-75 - Bg Ii
90.2
F063987
A3007420
Niezgodka-A3000274- Abnahmepr3;Fzeugnis-31-Ventil- Istanbul-Turkiye
F023674 (300 Bar)
F002025
F034151
E0000329
F040518
2090814400201
F019866
F019866 Vakuum-Ventil Dn25 0,18 Bar Mit Dichtungen Aus Gummi Mit Ptfе Umflechtung
F023674 (230 Bar)
E0000146 Dichtsatz - Typ 1, 10, 14, 18, 140 - Bg I
Iii-K064-Epdm (Fda)

F076431
A3007638 Rohrfeder-Manometer - Klasse 1,6 - Ng 630 - 6 Bar
A3002211
Druckregelventil Ii-K084-F307-Epdm
F018965 Druckminderventil Aus Edelstahl
F040658
F009657
A3011534
F024078
F026627
Druckregelventil Ii-K084-F306-Epdm
F009217
10.1 F024433
F007327
F017813
A3001694
F015345
F060397
Typ 1.1 C Ventild 1638 Bar
F002369 Druckminderventil.Ausgangsdruck Von 0.25 Bar Bis 1 Bar
F048245
A3000273 Werkszeugnis 2.2nach En 10204
F015223 Sicherheitsventil Mit Bauteilkennzeichenund Ce-Kennzeichen Nach Ped
F057382
F036503
A3000275